



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Product code : 873338

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands
+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact
your local emergency telephone number at 112

Product Information

+31 (0)78 654 3500 (in the Netherlands), or
contact your local CSR contact person

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard,
Category 3

H412: Harmful to aquatic life with long lasting
effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412

Harmful to aquatic life with long lasting
effects.

Supplemental Hazard : EUH066

Repeated exposure may cause skin



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Statements

dryness or cracking.

Precautionary statements

: **Prevention:**

P273

Avoid release to the environment.

Disposal:

P501

Dispose of contents/ container to an approved waste disposal plant.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 01-2119484627-25-xxxx	Asp. Tox.1; H304	>= 5,00 - < 10,00
bis(nonylphenyl)amine	36878-20-3 253-249-4 01-2119488911-28-xxxx	Aquatic Chronic4; H413	>= 2,50 - < 5,00
Phosphorodithioic acid, mixed O,O-bis(1,3- dimethylbutyl and iso- Pr) esters, zinc salts	84605-29-8 283-392-8 01-2119493626-26-xxxx	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic2; H411	>= 1,00 - < 2,50
2,6-di-tert-Butyl-p- cresol	128-37-0 204-881-4 01-2119565113-46-xxxx	Aquatic Acute1; H400 Aquatic Chronic1; H410	>= 0,10 - < 0,25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

4.1 Description of first aid measures

- General advice : No hazards which require special first aid measures.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash contaminated clothing before re-use.
If on skin, rinse well with water.
Remove contaminated clothing. If irritation develops, get medical attention.
- In case of eye contact : If eye irritation persists, consult a specialist.
Protect unharmed eye.
Remove contact lenses.
Flush eyes with water as a precaution.
- If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.
- Risks : Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing : High volume water jet



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

media

5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Hazardous combustion products : Nitrogen oxides (NOx)
carbon dioxide and carbon monoxide

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Use personal protective equipment.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
Prevent further leakage or spillage if safe to do so.
Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Dispose of rinse water in accordance with local and national regulations.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Avoid contact with skin and eyes.
- Advice on protection against fire and explosion : Normal measures for preventive fire protection.
- Hygiene measures : When using do not smoke. When using do not eat or drink.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place.
- Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

- Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2,6-di-tert-Butyl-p-cresol	128-37-0	TWA	10 mg/m ³	GB EH40

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

effects.

Personal protective equipment

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Hand protection

Remarks : Nitrile rubber butyl-rubber

The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Choose body protection according to the amount and concentration of the dangerous substance at the work place.
Safety shoes
Impervious clothing
Wear as appropriate:

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily

Odour Threshold : No data available

pH : Not applicable

Pour point : < -33 °C

Boiling point/boiling range : > 225 °C

Flash point : 236 °C
Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Upper explosion limit / Upper flammability limit	: No data available
Lower explosion limit / Lower flammability limit	: No data available
Vapour pressure	: 0,00004 hPa Calculated Vapor Pressure
Relative vapour density	: No data available
Relative density	: ca. 0,866 (15,6 °C)
Density	: ca. 0,867 g/cm3 (15,6 °C)
Solubility(ies)	
Water solubility	: insoluble
Solubility in other solvents	: No data available
Partition coefficient: n-octanol/water	: No data available
Decomposition temperature	: No data available
Viscosity	
Viscosity, dynamic	: No data available
Viscosity, kinematic	: ca. 149 mm2/s (40 °C)
Oxidizing properties	: No data available

9.2 Other information

Self-ignition	: No data available
---------------	---------------------

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Hazardous reactions : Product will not undergo hazardous polymerization.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Oxidizing agents
alkalis
Acids
Acid chlorides

10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

HEAVY PARAFFINIC DISTILLATE:

Acute oral toxicity : LD50 (Rat): > 15 g/kg
Acute dermal toxicity : LD50 (Rabbit): > 5 g/kg

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Remarks: No mortality observed at this dose.
Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by dermal absorption under GHS.
Remarks: Information given is based on data obtained from similar substances.



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Components:

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Acute oral toxicity	: LD50 (Rat): 3.100 mg/kg
Acute inhalation toxicity	: LC50 (Rat): > 2,3 mg/l Exposure time: 4 h Test atmosphere: vapour Assessment: No adverse effect has been observed in acute inhalation toxicity tests.
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: No adverse effect has been observed in acute dermal toxicity tests.

Components:

BUTYLATED HYDROXY TOLUENE:

Acute oral toxicity	: LD50 (Rat): > 6.000 mg/kg Method: OECD Test Guideline 401 GLP: yes
Acute dermal toxicity	: LD50 (Rat): > 2.000 mg/kg Assessment: Not classified as acutely toxic by dermal absorption under GHS. Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: Slight, transient irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit
Result: Mild skin irritation
Remarks: Information given is based on data obtained from similar substances.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species: Rabbit



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Result: Irritating to skin.

BUTYLATED HYDROXY TOLUENE:

Species: Rabbit

Method: OECD Test Guideline 404

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result: Slight, transient irritation

Remarks: Expected based on components.

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

HEAVY PARAFFINIC DISTILLATE:

Result: No eye irritation

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Rabbit

Result: Slight, transient irritation

Remarks: Information given is based on data obtained from similar substances.

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Species: Rabbit

Result: Corrosive

BUTYLATED HYDROXY TOLUENE:

Species: Rabbit

Method: OECD Test Guideline 405

Result: Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Method: OECD Test Guideline 406

Remarks: Information given is based on data obtained from similar substances.



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Test Type: **Buehler Test**
Species: **Guinea pig**
Assessment: **Does not cause skin sensitisation.**
Method: **OECD Test Guideline 406**

BUTYLATED HYDROXY TOLUENE:

Assessment: **Does not cause skin sensitisation.**

Germ cell mutagenicity

Not classified based on available information.

Components:

REACTION PROD. OF BENZENEAMINE, N-PHENYL- W/ NONENE (BRANCHED):

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

PHOSPHORODITHIOIC ACID, MIXED O,O-BIS(1,3-DIMETHYLBUTYL AND ISO-PR) ESTERS, ZINC SALTS:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

BUTYLATED HYDROXY TOLUENE:

Genotoxicity in vitro : Test Type: **Ames test**
Test species: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Components:

HEAVY PARAFFINIC DISTILLATE:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

SECTION 12: Ecological information

12.1 Toxicity

Components:

Distillates (petroleum), hydrotreated heavy paraffinic

Toxicity to fish : LL50 (Fish): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EL50 (Aquatic invertebrates): > 10.000 mg/l
Exposure time: 48 h

Toxicity to algae : EL50 (Algae, algal mat (Algae)): > 100 mg/l
Exposure time: 72 h

Toxicity to fish (Chronic toxicity) : NOEC: 10 mg/l
Species: Fish

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Species: Aquatic invertebrates

bis(nonylphenyl)amine

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: Information given is based on data obtained from similar substances.

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Test substance: WAF

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout)): 4,5 mg/l**
Exposure time: **96 h**
Test Type: **semi-static test**
Test substance: **WAF**
Method: **OECD Test Guideline 203**

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea)): 23 mg/l**
Exposure time: **48 h**
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 202**

Toxicity to algae : **EL50 (Desmodesmus subspicatus (green algae)): 24 mg/l**
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 201**

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOEC: 0,4 mg/l**
Exposure time: **28 d**
End point: **Reproduction Test**
Species: **Daphnia magna (Water flea)**
Test substance: **WAF**
Method: **OECD Test Guideline 211**

2,6-di-tert-Butyl-p-cresol

Toxicity to fish : **LC50 (Fish): estimated 0,199 mg/l**
Exposure time: **96 h**
Remarks: **QSAR**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea)): 0,48 mg/l**
Exposure time: **48 h**
Test Type: **static test**
Method: **OECD Test Guideline 202**

M-Factor (Short-term (acute) aquatic hazard) : **1**

Toxicity to fish (Chronic toxicity) : **NOEC: 0,053 mg/l**
Exposure time: **42 d**
Species: **Oryzias latipes (Orange-red killifish)**
Test Type: **flow-through test**



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

M-Factor (Long-term
(chronic) aquatic hazard) : 1

12.2 Persistence and degradability

Components:

bis(nonylphenyl)amine

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 0 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 1,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2,6-di-tert-Butyl-p-cresol

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 4,5 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Physico-chemical
removability : Remarks: The product can be degraded by abiotic (e.g.
chemical or photolytic) processes.

12.3 Bioaccumulative potential

Components:

bis(nonylphenyl)amine

Partition coefficient: n-
octanol/water : log Pow: > 7,5

Phosphorodithioic acid, mixed O,O-bis(1,3-dimethylbutyl and iso-Pr) esters, zinc salts

Partition coefficient: n-
octanol/water : log Pow: 0,56

2,6-di-tert-Butyl-p-cresol

Partition coefficient: n-
octanol/water : log Pow: 4,17 (21 °C)

12.4 Mobility in soil

No data available



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects., An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Send to a licensed waste management company.
Do not contaminate ponds, waterways or ditches with chemical or used container.
The product should not be allowed to enter drains, water courses or the soil.

Contaminated packaging : Do not re-use empty containers.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Dispose of as unused product.
Empty remaining contents.

SECTION 14: Transport information

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:
DISTILLATES (PETROLEUM),
HYDROTREATED HEAVY
PARAFFINIC (Number on list 28)

(Number on list 28)



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Directive 96/82/EC does not apply

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Not applicable

The components of this product are reported in the following inventories:

DSL	: All components of this product are on the Canadian DSL
AICS	: On the inventory, or in compliance with the inventory
ENCS	: Contact your sales representative for additional information.
KECI	: On the inventory, or in compliance with the inventory
PICCS	: On the inventory, or in compliance with the inventory
IECSC	: On the inventory, or in compliance with the inventory
TCSI	: On the inventory, or in compliance with the inventory
TSCA	: On TSCA Inventory

Inventories

AICS (Australia), AIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Internal information : R0517747



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Full text of H-Statements

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H318	Causes serious eye damage.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet

Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS : Chemical Abstracts Service (Division of the American Chemical Society).

CMR : Carcinogenic, Mutagenic or Toxic for Reproduction

FG : Food grade

GHS : Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement : Hazard Statement

IATA : International Air Transport Association.

IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization

ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"

IMDG : International Maritime Code for Dangerous Goods

ISO : International Organization for Standardization

logPow : octanol-water partition coefficient

LCxx : Lethal Concentration, for xx percent of test population

LDxx : Lethal Dose, for xx percent of test population.

ICxx : Inhibitory Concentration for xx of a substance



SAFETY DATA SHEET

Valvoline™ VR1 RACING SAE 10W-60
Synthetic Blend Motor Oil

Version: 5.0

Revision Date: 06.04.2021

Print Date: 20/09/2022

Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrase : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrase: Safety phrase
WGK : German Water Hazard Class