according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 1 of 12

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Cartechnic 5W-40 Pumpe-Düse

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

engine oil

Uses advised against

none

1.3. Details of the supplier of the safety data sheet

Company name: Auto-Teile-Ring GmbH Street: Marie-Curie-Strasse 3 Place: D-73770 Denkendorf Telephone: +49 0711 918979-99 Info@cartechnic.de

1.4. Emergency telephone Poison Information Center Mainz, Germany, Tel: +49(0)6131/19240

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GB CLP Regulation

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

GB CLP Regulation

Special labelling of certain mixtures

EUH208 Contains maleic anhydride. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3. Other hazards

This product contains no substances of very high concern (SVHC) (>0,1%) which are included in the Candidate List according to Article 59 of REACH.

For information or further instructions, see also section 11 or 12.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (GB CLP Regulation)			
64742-54-7	Distillates (petroleum), hydrotreated	d heavy paraffinic; Baseoil - unspecifi	ied	30 - < 35 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304			
	Mineral Oil* (64742-54-7, 64742-65	5-0, 64742-55-8, 64742-56-9)		5 - < 7 %
	Asp. Tox. 1; H304			
	Calcium branched alkyl phenate sulphide			1 - < 3 %
	Aquatic Chronic 4; H413			
108-31-6	maleic anhydride			< 0.1 %

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse Revision date: 02.03.2023 Product code: Page 2 of 12

203-571-6	607-096-00-9	01-2119472428-31	
Acute Tox. 4, Skin Corr. 1B, Eye Da	Acute Tox. 4, Skin Corr. 1B, Eye Dam. 1, Resp. Sens. 1, Skin Sens. 1A, STOT RE 1; H302 H314		
H318 H334 H317 H372 EUH071	H318 H334 H317 H372 EUH071		

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity	
	Specific Conc. L	imits, M-factors and ATE		
64742-54-7	265-157-1	tillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified 30 - < 35		
	dermal: LD50 =	LD50 = >2000 mg/kg; oral: LD50 = >5000 mg/kg		
108-31-6	203-571-6	I-6 maleic anhydride <0		
	dermal: LD50 = 2620 mg/kg; oral: LD50 = 1090 mg/kg Skin Sens. 1A; H317: >= 0,001 - 100			

Further Information

Note L: The harmonised classification as a carcinogen applies unless it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions – Dimethyl sulphoxide extraction refractive index method" Institute of Petroleum, London).

*The mineral oil can be described by one or more EINECS numbers. 265-157-1, 265-169-7, 265-158-7, 265-159-2, (REACH-no.: 01-2119484627-25, 01-2119471299-27, 01-2119487077-29, 01-2119480132-48)

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After inhalation

In case of accident by inhalation: remove casualty to fresh air and keep at rest. In case of allergic symptoms, especially in the breathing area, seek medical advice immediately.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off immediately all contaminated clothing. In case of skin irritation, seek medical treatment.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water. In case of troubles or persistent symptoms, consult an ophthalmologist.

After ingestion

Do NOT induce vomiting. Rinse mouth thoroughly with water. Let water be drunken in little sips (dilution effect). Never give anything by mouth to an unconscious person or a person with cramps. When in doubt or if symptoms are observed, get medical advice.

4.2. Most important symptoms and effects, both acute and delayed

If swallowed or in the event of vomiting, risk of entering the lungs.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Sand. Foam. Carbon dioxide (CO2). Extinguishing powder. In case of major fire and large quantities: Water spray jet. Water mist.

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 3 of 12

Unsuitable extinguishing media

High power water jet.

5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke.

Can be released in case of fire: Carbon monoxide Carbon dioxide (CO2) Sulphur dioxide (SO2) Nitrogen oxides (NOx) Phosphorus oxides

5.3. Advice for firefighters

In case of fire and/or explosion do not breathe fumes. In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

Co-ordinate fire-fighting measures to the fire surroundings.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Ventilate affected area.

Special danger of slipping by leaking/spilling product.

For non-emergency personnel

Wear personal protection equipment (refer to section 8).

For emergency responders

No special precautionary measures are necessary.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Prevent spread over a wide area (e.g. by containment or oil barriers). Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Absorb with liquid-binding material (e.g. sand, diatomaceous earth, acid- or universal binding agents).

Treat the recovered material as prescribed in the section on waste disposal.

For cleaning up

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

No information available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

Wear suitable protective clothing. (See section 8.)

Avoid formation of oil dust.

Advice on protection against fire and explosion

Usual measures for fire prevention. Keep away from sources of ignition - No smoking.

Fire class B

Advice on general occupational hygiene

Clean skin thoroughly after working.

Do not put any product-impregnated cleaning rags into your trouser pockets.

Contaminated work clothing should not be allowed out of the workplace.

Wash contaminated clothing before reuse.

Further information on handling

Do not breathe vapour/aerosol.

Avoid contact with eyes and skin.

General protection and hygiene measures: See section 8.

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 4 of 12

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep container tightly closed in a cool, well-ventilated place. Only use containers specifically approved for the substance/product.

Hints on joint storage

Do not store together with: Gas. Explosives. Oxidizing solids. Oxidizing liquids. Radioactive substances. Infectious substances

Further information on storage conditions

Temperature control required. Protect from light. Keep container tightly closed. Do not allow contact with air.

7.3. Specific end use(s)

See section 1.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
108-31-6	Maleic anhydride	-	1		TWA (8 h)	WEL
		-	3		STEL (15 min)	WEL

DNEL/DMEL values

CAS No	Substance				
DNEL type		Exposure route	Effect	Value	
108-31-6	maleic anhydride				
Worker DNEL, long-term		inhalation	systemic	0,081 mg/m³	
Worker DNEL, acute		inhalation	systemic	0,2 mg/m³	
Worker DNEL, long-term		inhalation	local	0,081 mg/m³	
Worker DNEL, acute		inhalation	local	0,2 mg/m³	

PNEC values

CAS No	Substance				
Environmental	compartment	Value			
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
Secondary poi	soning	9,33 mg/kg			
108-31-6	maleic anhydride				
Freshwater 0,038 mg		0,038 mg/l			
Freshwater (intermittent releases) 0,379 mg		0,379 mg/l			
Marine water 0,004 mg/		0,004 mg/l			
Freshwater sediment 0,296 mg		0,296 mg/kg			
Marine sediment 0,03 m		0,03 mg/kg			
Micro-organisms in sewage treatment plants (STP) 44,6 mg/l		44,6 mg/l			
Soil 0,037 mg		0,037 mg/kg			

Additional advice on limit values

Air limit values:

Possibility of exposure to Aerosol (Mineral oil)

Limit value (TLV-TWA) = 5 mg/m3 - Source: ACGIH

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 5 of 12

Limit value (TLV-STEL) = 10 mg/m3 - Source: ACGIH

STEL: short-term exposure limits TLV: Threshold Limiting Value TWA: time weighted average

ACGIH: American Conference of Governmental Industrial Hygienists

8.2. Exposure controls





Appropriate engineering controls

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

Eye/face protection

Safety goggles with side protection. In case of increased risk add protective face shield. BS/EN 166

Hand protection

Use safety gloves of following materials: NBR (nitrile) / neopren / viton (permeationslevel 5 - 6), Cat. II according to norm EN 374/EN 388.

The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances.

For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Gloves must be periodically inspected and changed in case of wear, perforations or contaminations.

In the case of wanting to use the gloves again, clean them before taking off and air them well.

Skin protection

Oil-resistant and hardly inflammable protective clothing.

Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500 (D).

Respiratory protection

With correct and proper use, and under normal conditions, breathing protection is not required.

Respiratory protection necessary at:

- -aerosol or mist formation
- -Exceeding exposure limit values

Suitable respiratory protection apparatus: Respiratory equipment in case of nebulosity or aerosol: Use a mask with a filter type A2, A2/P2 or ABEK.

The filter class must be suitable for the maximum contaminant concentration (gas/vapour/aerosol/particulates) that may arise when handling the product. If the concentration is exceeded, self-contained breathing apparatus must be used.

Thermal hazards

Wear protective clothing for operations with hot material: heat resistant coveralls (with trousers legs over boots and sleeves over cuffs of gloves), heat resistant heavy duty antiskid boots (e. g. leather).

Environmental exposure controls

No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: liquid Colour: clear

Odour: characteristic

Test method

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 6 of 12

Melting point/freezing point:

Boiling point or initial boiling point and

No information available.

No information available.

boiling range:

Flammability: No information available.

Lower explosion limits: No information available.

Upper explosion limits: No information available.

Flash point: 236 °C DIN ISO 2592

Auto-ignition temperature:

Decomposition temperature:

No information available.

PH-Value:

No information available.

No information available.

Viscosity / kinematic: 75,1 mm²/s DIN EN ISO 3104

(at 40 °C)

Water solubility: Immiscible

Solubility in other solvents

No information available.

Partition coefficient n-octanol/water:

Vapour pressure:

No information available.

No information available.

(at 20 °C)

Vapour pressure: No information available.

(at 50 °C)

Density (at 15 °C): 0,853 g/cm³ DIN 51757

Bulk density:

Relative vapour density:

No information available.

No information available.

No information available.

9.2. Other information

Information with regard to physical hazard classes

Explosive properties

none

Sustaining combustion: No data available

Self-ignition temperature

Solid: No information available.
Gas: No information available.

Oxidizing properties

none

Other safety characteristics

Evaporation rate:

Solvent separation test:

No information available.

Pour point: -39 °C ISO 3016

Viscosity / dynamic:

Flow time:

No information available.

No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

The product is chemically stable under recommended conditions of storage, use and temperature.

10.3. Possibility of hazardous reactions

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 7 of 12

No hazardous reactions known.

Refer to chapter 10.5.

10.4. Conditions to avoid

No information available.

10.5. Incompatible materials

Oxidising agent, strong

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in GB CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
64742-54-7	Distillates (petroleum), hy	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified				
	oral	LD50 mg/kg	>5000	Rat	ECHA Dossier	OECD 401
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA Dossier	OECD 402
108-31-6	reference of the maleic anhydride					
	oral	LD50 mg/kg	1090	Rat	SIDS Initial Assessment Report for SIAM	OECD Guideline 401
	dermal	LD50 mg/kg	2620	Rabbit	Toxicol. Appl. Pharmacol. 42, 417-424 (1	Smyth et al.

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains maleic anhydride. May produce an allergic reaction.

May cause sensitisation especially in sensitive humans.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified:

In vitro mutagenicity/genotoxicity:

Method

- OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)

Result: negative.; Literature information: ECHA dossier

Carcinogenicity:

Method: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Species: Mouse.

Results: Non-carcinogenic if DMSO extract as measured by IP346 is less than 3% w/w.; Literature information:

ECHA dossier Reproductive toxicity:

Species: Rat (Sprague-Dawley)

Method: OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 8 of 12

Results: NOAEL > 1000 mg/kg; Literature information: ECHA dossier

Developmental toxicity/teratogenicity: Species: Rat (Sprague-Dawley)

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)
Results: NOAEL >= 2000 mg/kg; Literature information: ECHA dossier

maleic anhydride:

In-vitro mutagenicity:

Method:

-OECD Guideline 471 (Bacterial Reverse Mutation Assay)

-OECD Guideline 476 (In Vitro Mammalian Cell Gene Mutation Test)

Result: negative.)

Literature information: ECHA dossier

In-vitro mutagenicity: Method: EU Method B.18

Result: negative.

Literature information: ECHA dossier

Reproductive toxicity:

Method: OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

Species: Rat

Result: NOAEL (P0, P1) = 55 mg/kg; NOAEL (F1) = 55 mg/kg

Literature information: ECHA dossier

Developmental toxicity/teratogenicity:

Method: OECD Guideline 414 (Prenatal Developmental Toxicity Study)

Species: Rat

Result: NOAEL (fetus) >= 140 mg/kg

Result: NOAEL (Maternal toxicity) >= 140 mg/kg

Literature information: ECHA dossier

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified:

Subacute inhalative toxicity:

Method: -

Exposure time: 28d; Species: Rat

Results: NOAEL >980 mg/m3; Literature information: ECHA dossier

Subacute dermal toxicity:

Method: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

Exposure time: 28d; Species: Rabbit

Results: 1000 mg/kg; Literature information: ECHA dossier

maleic anhydride:

Subchronic oral toxicity:

Method: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents).

Species: Rat.

Result: LOAEL= 250 mg/kg.

Literature information: ECHA dossier

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 9 of 12

Endocrine disrupting properties

No information available.

Other information

Frequent contact specially if dried out may cause skin and eye irritations.

SECTION 12: Ecological information

12.1. Toxicity

If this product contains phenol, dodecyl, branched (EC No. 310-154-3), this product is not to be classified as dangerous for the environment (H410, H411, H412). Raw materials containing this substance have not been classified by our suppliers as hazardous to the environment (H410, H411) on the basis of test data, expert judgement or analogy assessments.

CAS No	Chemical name	Chemical name					
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
64742-54-7	Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	Crustacea toxicity	NOEC	10 mg/l		Daphnia magna (OECD 211)	ECHA Dossier	
108-31-6	maleic anhydride						
	Acute algae toxicity	ErC50 mg/l	74,35	I . — · ·	Pseudokirchneriella subcapitata	ECHA Dossier	OECD Guideline 201
	Acute crustacea toxicity	EC50 mg/l	42,81	48 h	Daphnia magna	ECHA Dossier	OECD Guideline 202

12.2. Persistence and degradability

The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

CAS No	Chemical name					
	Method	Value	d	Source		
	Evaluation					
64742-54-7 Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil - unspecified						
	OECD 301F / ISO 9408 / EEC 92/69 annex V, C.4-D 31% 28 ECHA Dossier					
	Not easily bio-degradable (according to OECD-criteria).					
	OECD 301B / ISO 9439 / EEC 92/69 annex V, C.4-C 2-4% 28 ECHA Dossier					
	Not easily bio-degradable (according to OECD-criteria).					
108-31-6	maleic anhydride					
	OECD Guideline 301 B >90% 28 ECHA Dossier					
	Easily biodegradable (concerning to the criteria of the OECD)					

12.3. Bioaccumulative potential

No indication of bioaccumulation potential.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
108-31-6	maleic anhydride	-2,61

12.4. Mobility in soil

No information available.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1

12.6. Endocrine disrupting properties

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 10 of 12

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

The aforementioned statement applies to substances contained in the product with a minimum content of 0.1 %

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Dispose of waste according to applicable legislation. Consult the appropriate local waste disposal expert about waste disposal. Non-contaminated packages may be recycled. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND

PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by

hazardous substances; hazardous waste

Contaminated packaging

Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Inland waterways transport (ADN)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Marine transport (IMDG)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number:	No dangerous good in sense of this transport regulation.
14.2. UN proper shipping name:	No dangerous good in sense of this transport regulation.
14.3. Transport hazard class(es):	No dangerous good in sense of this transport regulation.
14.4. Packing group:	No dangerous good in sense of this transport regulation.

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Informations for safe handling see chapter 7.

Informations for personal protective equipment see chapter 8.

14.7. Maritime transport in bulk according to IMO instruments

not relevant

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 11 of 12

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulatory information

Restrictions on use (REACH, annex XVII):

Entry 75

2010/75/EU (VOC): No information available. 2004/42/EC (VOC): No information available.

Information according to 2012/18/EU

(SEVESO III):

Not subject to 2012/18/EU (SEVESO III)

Additional information

Safety Data Sheet according to UK-REACH Regulation

This mixture is classified as not hazardous according to GHS (GB CLP).

UK REACH Appendix XVII, No (mixture): not relevant

Observe in addition any national regulations!

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

Additional information

Regulation (EC) No 649/2012 of the European Parliament and of the Council concerning the export and import of dangerous chemicals: not relevant

15.2 Chemical Safety Assessment

not applicable.

SECTION 16: Other information

Changes

Rev.: 1,0 - 24.04.2015 Rev.: 1,1 - 29.04.2016 Rev.: 2,0 - 30.05.2017 Rev.: 3,0 - 27.06.2018 Rev.: 4.0 - 25.06.2019

Rev.: 5,0 - 25.06.2020; Changes in chapter: 3.2, 16

Rev.: 6.0 - 15.06.2021; Changes in chapter: 3.2, 6.1, 6.3, 11.2, 12.6, 12.7, 15.1, 16

Rev.: 6,1 - 11.03.2022, Changes in chapter: 2.2, 2.3, 3.2, 8.1, 8.2, 11.1, 11.2, 12.1, 12.2, 12.3, 12.5, 12.6,

15.1, 16

Rev.: 7,0 - 02.03.2023, Changes in chapter: 9.1, 16

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement

concerning the International Carriage of Dangerous Goods by Road)

CAS: Chemical Abstracts Service DNEL: Derived No Effect Level

IARC: INTERNATIONAL AGENCY FOR RESEARCH ON CANCER

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

GefStoffV: Gefahrstoffverordnung (Ordinance on Hazardous Substances, Germany)

LOAEL: Lowest observed adverse effect level

LOAEC: Lowest observed adverse effect concentration

according to UK REACH Regulation

Cartechnic 5W-40 Pumpe-Düse

Revision date: 02.03.2023 Product code: Page 12 of 12

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

NOAEL: No observed adverse effect level

NOAEC: No observed adverse effect concentration

NTP: National Toxicology Program

N/A: not applicable

PNEC: predicted no effect concentration PBT: Persistent bioaccumulative toxic

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de

fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

SVHC: substance of very high concern TRGS Technische Regeln fuerGefahrstoffe TSCA: Toxic Substances Control Act VOC: Volatile Organic Compounds

Relevant H and EUH statements (number and full text)

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H372	Causes damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains maleic anhydride. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

Classification according to GHS [GB CLP] - Classification procedure:

Health hazards: Calculation method. Environmental hazards: Calculation method. Physical hazards: On basis of test data

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)