



SAFETY DATA SHEET

Professional Rubber Based Paintable Undershield aerosol

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name	Professional Rubber Based Paintable Undershield aerosol
Product number	RF00826C
UFI	UFI: 6K18-T25F-W67P-PV5H
REACH registration notes	This is a MIXTURE; no registration information contained in this document . Holts are classed as Downstream User.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Car maintenance product. Body sealing material.
------------------------	---

1.3. Details of the supplier of the safety data sheet

Supplier	A Holts Car Care Product Holt Lloyd International Ltd Barton Dock Road Stretford Manchester M32 0YQ - England, UK +44 (0) 161 866 4800 FAX +44 (0) 161 866 4854 www.holtsauto.com
Contact person	Contact Email address: info@holtsauto.com

1.4. Emergency telephone number

Emergency telephone	UK - 00 44 (0) 161 866 4800 Office hrs = 0900 - 1700 hrs
----------------------------	--

National emergency telephone number	National Poisons Information Service City Hospital, Birmingham B187QH, United Kingdom Telephone: +44 121 507 4123 Email: allistervale@npis.org, sallybradberry@npis.org www.npis.org
--	--

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical hazards	Aerosol 1 - H222, H229
Health hazards	Eye Irrit. 2 - H319 Skin Sens. 1 - H317 STOT SE 3 - H336
Environmental hazards	Aquatic Chronic 3 - H412

2.2. Label elements

Professional Rubber Based Paintable Undershield aerosol

Hazard pictograms



Signal word

Danger

Hazard statements

H222 Extremely flammable aerosol.
 H229 Pressurised container: may burst if heated.
 H319 Causes serious eye irritation.
 H317 May cause an allergic skin reaction.
 H336 May cause drowsiness or dizziness.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
 P102 Keep out of reach of children.
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P211 Do not spray on an open flame or other ignition source.
 P251 Do not pierce or burn, even after use.
 P261 Avoid breathing vapour/ spray.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see medical advice on this label).
 P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
 P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

EUH066 Repeated exposure may cause skin dryness or cracking.

UFI

UFI: 6K18-T25F-W67P-PV5H

Contains

BUTYL ACETATE -norm, ACETONE, ETHYL ACETATE, ROSIN, Hydrocarbons, C9, aromatics, Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Supplementary precautionary statements

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P264 Wash contaminated skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P308+P313 IF exposed or concerned: Get medical advice/ attention.
 P312 Call a POISON CENTRE/doctor if you feel unwell.
 P333+P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P337+P313 If eye irritation persists: Get medical advice/ attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.

2.3. Other hazards

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Professional Rubber Based Paintable Undershield aerosol

BUTYL ACETATE -norm			10-30%
CAS number: 123-86-4	EC number: 204-658-1	REACH registration number: 01-2119485493-29-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H336			
PROPANE			10-30%
CAS number: 74-98-6	EC number: 200-827-9	REACH registration number: 01-2119486944-21-XXXX	
Classification Flam. Gas 1 - H220			
ACETONE			5-10%
CAS number: 67-64-1	EC number: 200-662-2	REACH registration number: 01-2119471330-49-XXXX	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
ISOBUTANE			5-10%
CAS number: 75-28-5	EC number: 200-857-2	REACH registration number: 01-2119486944-21-XXXX	
Classification Flam. Gas 1 - H220 Press. Gas			
ETHYL ACETATE			5-10%
CAS number: 141-78-6	EC number: 205-500-4	REACH registration number: 01-2119475103-46-XXXX	
Classification Flam. Liq. 2 - H225 Eye Irrit. 2 - H319 STOT SE 3 - H336			
BUTANE			5-10%
CAS number: 106-97-8	EC number: 203-448-7	REACH registration number: 01-2119474691-32-XXXX	
Classification Flam. Gas 1 - H220 Press. Gas			

Professional Rubber Based Paintable Undershield aerosol

Hydrocarbons, C9, aromatics			1-5%
CAS number: —	EC number: 918-668-5	REACH registration number: 01-2119455851-35-XXXX	
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335, H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
ROSIN			1-5%
CAS number: 8050-09-7	EC number: 232-475-7	REACH registration number: 01-2119480418-32-XXXX	
Classification Skin Sens. 1 - H317			
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics			1-5%
CAS number: —	EC number: 920-750-0	REACH registration number: 01-2119473851-33-XXXX	
Classification Flam. Liq. 2 - H225 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411			
XYLENE			1-5%
CAS number: 1330-20-7	EC number: 215-535-7	REACH registration number: 01-2119488216-32-XXXX	
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Skin Irrit. 2 - H315			

The full text for all hazard statements is displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	Move affected person to fresh air at once. Get medical attention if any discomfort continues.
Inhalation	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention if any discomfort continues.
Ingestion	Do not induce vomiting. Rinse mouth thoroughly with water. Get medical attention.
Skin contact	Remove affected person from source of contamination. Remove contaminated clothing. Wash skin thoroughly with soap and water. Get medical attention if any discomfort continues.

Professional Rubber Based Paintable Undershield aerosol

Eye contact Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information Treat symptomatically.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Extinguish with foam, carbon dioxide, dry powder or water fog.

5.2. Special hazards arising from the substance or mixture

Specific hazards Extremely flammable. May explode when heated or when exposed to flames or sparks. Containers can burst violently or explode when heated, due to excessive pressure build-up.

Hazardous combustion products Toxic gases or vapours.

5.3. Advice for firefighters

Protective actions during firefighting Containers close to fire should be removed or cooled with water. Use water to keep fire exposed containers cool and disperse vapours.

Special protective equipment for firefighters Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Wear protective gloves, eye and face protection. Keep unnecessary and unprotected personnel away from the spillage.

6.2. Environmental precautions

Environmental precautions Avoid release to the environment. Inform the relevant authorities if environmental pollution occurs (sewers, waterways, soil or air).

6.3. Methods and material for containment and cleaning up

Methods for cleaning up Provide adequate ventilation. Wear suitable protective equipment, including gloves, goggles/face shield, respirator, boots, clothing or apron, as appropriate. Absorb in vermiculite, dry sand or earth and place into containers.

6.4. Reference to other sections

Reference to other sections For personal protection, see Section 8. For waste disposal, see Section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions Avoid spilling. Avoid contact with skin and eyes. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Persons susceptible to allergic reactions should not handle this product.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions Store in tightly-closed, original container in a dry, cool and well-ventilated place. Keep only in the original container. Keep away from food, drink and animal feeding stuffs.

Professional Rubber Based Paintable Undershield aerosol

Storage class Flammable compressed gas storage. Aerosol containers and lighters

7.3. Specific end use(s)

Specific end use(s) The identified uses for this product are detailed in Section 1.2.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ACETONE

Long-term exposure limit (8-hour TWA): WEL 500 ppm 1210 mg/m³

Short-term exposure limit (15-minute): WEL 1500 ppm 3620 mg/m³

ISOBUTANE

Long-term exposure limit (8-hour TWA): OES 800 ppm

Short-term exposure limit (15-minute): OES 800 ppm

ETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 200 ppm

Short-term exposure limit (15-minute): WEL 400 ppm

BUTANE

Long-term exposure limit (8-hour TWA): WEL 600 ppm 1450 mg/m³

Short-term exposure limit (15-minute): WEL 750 ppm 1810 mg/m³

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm 220 mg/m³

Short-term exposure limit (15-minute): WEL 100 ppm 441 mg/m³

Sk

WEL = Workplace Exposure Limit.

Sk = Can be absorbed through the skin.

Ingredient comments WEL = Workplace Exposure Limits

BUTYL ACETATE -norm (CAS: 123-86-4)

DNEL

Workers - Inhalation; Long term systemic effects: 300 mg/m³

Workers - Inhalation; Short term systemic effects: 600 mg/m³

Workers - Inhalation; Long term local effects: 300 mg/m³

Workers - Inhalation; Short term local effects: 600 mg/m³

Workers - Dermal; Long term systemic effects: 11 mg/kg bw/day

Workers - Dermal; Short term systemic effects: 11 mg/kg bw/day

General population - Inhalation; Long term systemic effects: 35.7 mg/m³

General population - Inhalation; Short term systemic effects: 300 mg/m³

General population - Inhalation; Long term local effects: 35.7 mg/m³

General population - Inhalation; Short term local effects: 300 mg/m³

General population - Dermal; Long term systemic effects: 6 mg/kg bw/day

General population - Dermal; Short term systemic effects: 6 mg/kg bw/day

General population - Oral; Long term systemic effects: 2 mg/kg bw/day

General population - Oral; Short term systemic effects: 6 mg/kg bw/day

Professional Rubber Based Paintable Undershield aerosol

PNEC

Fresh water; 0.18 mg/l
marine water; 0.018 mg/l
STP; 35.6 mg/l
Sediment (Freshwater); 0.981 mg/kg sediment dw
Sediment (Marinewater); 0.098 mg/kg sediment dw
Soil; 0.09 mg/kg soil dw

ACETONE (CAS: 67-64-1)

DNEL

Consumer - Oral; Long term systemic effects: 62 mg/kg/day
Workers - Dermal; Long term systemic effects: 186 mg/kg/day
Consumer - Dermal; Long term systemic effects: 62 mg/kg/day
Workers - Inhalation; Short term local effects: 2420 mg/m³
Workers - Inhalation; Long term systemic effects: 1210 mg/m³
Consumer - Inhalation; Long term systemic effects: 200 mg/m³

PNEC

Fresh water; 10.6 mg/l
marine water; 1.06 mg/l
Intermittent release; 21 mg/l
Sediment (Freshwater); 30.4 mg/kg
Sediment (Marinewater); 3.04 mg/kg
Soil; 29.5 mg/kg
STP; 100 mg/l

ETHYL ACETATE (CAS: 141-78-6)

DNEL

Workers - Inhalation; Long term systemic effects: 734 mg/m³
Workers - Inhalation; Short term systemic effects: 1468 mg/m³
Workers - Inhalation; Long term local effects: 734 mg/m³
Workers - Inhalation; Short term local effects: 1468 mg/m³
Workers - Dermal; Long term systemic effects: 63 mg/kg bw/day
General population - Inhalation; Long term systemic effects: 367 mg/m³
General population - Inhalation; Short term systemic effects: 734 mg/m³
General population - Inhalation; Long term local effects: 367 mg/m³
General population - Inhalation; Short term local effects: 734 mg/m³
General population - Dermal; Long term systemic effects: 37 mg/kg bw/day
General population - Oral; Long term systemic effects: 4.5 mg/kg bw/day

PNEC

Fresh water; 0.24 mg/l
marine water; 0.024 mg/l
STP; 650 mg/l
Sediment (Freshwater); 1.15 mg/kg sediment dw
Sediment (Marinewater); 0.115 mg/kg sediment dw
Soil; 0.148 mg/kg soil dw

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

DNEL

Workers - Inhalation; Long term systemic effects: 2035 mg/m³
Workers - Dermal; Long term systemic effects: 773 mg/kg/day
General population - Inhalation; Long term systemic effects: 608 mg/m³
General population - Dermal; Long term systemic effects: 699 mg/kg/day
General population - Oral; Long term systemic effects: 699 mg/kg/day

Hydrocarbons, C9, aromatics

Professional Rubber Based Paintable Undershield aerosol

DNEL	Workers - Inhalation; Long term systemic effects: 150 mg/m ³ Workers - Dermal; Long term systemic effects: 25 mg/kg/day General population - Inhalation; Long term systemic effects: 32 mg/m ³ General population - Dermal; Long term systemic effects: 11 mg/kg/day General population - Oral; Long term systemic effects: 11 mg/kg/day
-------------	--

ROSIN (CAS: 8050-09-7)

DNEL	Workers - Inhalation; Long term local effects: 10 mg/m ³ Workers - Dermal; Long term systemic effects: 2.131 mg/kg bw/day General population - Dermal; Long term systemic effects: 1.065 mg/kg bw/day General population - Oral; Long term systemic effects: 1.065 mg/kg bw/day
PNEC	Fresh water; 0.002 mg/l marine water; 0.0002 mg/l STP; 1000 mg/l Sediment (Freshwater); 0.007 mg/kg sediment dw Sediment (Marinewater); 0.001 mg/kg sediment dw

XYLENE (CAS: 1330-20-7)

DNEL	Consumer - Dermal; Long term systemic effects: 108 mg/kg/day Workers - Dermal; Long term systemic effects: 180 mg/kg/day Consumer - Inhalation; Short term local effects: 174 mg/m ³ Consumer - Inhalation; Short term systemic effects: 174 mg/m ³ Workers - Inhalation; Short term systemic effects: 289 mg/m ³ Workers - Inhalation; Short term local effects: 289 mg/m ³ Consumer - Inhalation; Long term systemic effects: 14.8 mg/m ³ Workers - Inhalation; Long term systemic effects: 77 mg/m ³
-------------	--

8.2. Exposure controls

Protective equipment



Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. The following protection should be worn: Chemical splash goggles or face shield.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. Wear protective gloves made of the following material: Butyl rubber. Protective gloves should have a minimum thickness of 0.4 mm mm. To protect hands from chemicals, gloves should comply with European Standard EN374.

Other skin and body protection

Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures

Do not smoke in work area. Wash at the end of each work shift and before eating, smoking and using the toilet. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Do not eat, drink or smoke when using this product.

Professional Rubber Based Paintable Undershield aerosol

Respiratory protection	No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.
-------------------------------	---

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Aerosol.
Colour	Black.
Odour	Characteristic. Organic solvents.
pH	Not determined.
Melting point	Not determined.
Initial boiling point and range	Not applicable.
Flash point	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 1.2% Upper flammable/explosive limit: 10.9%
Vapour pressure	3500 hPa @ 20°C
Relative density	~0.8 @ 20°C
Solubility(ies)	Immiscible with water.
Partition coefficient	Not determined.
Auto-ignition temperature	365°C 689°F
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	Not determined.

9.2. Other information

Volatility	62.9%
Volatile organic compound	This product contains a maximum VOC content of 579.1 g/litre.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No test data specifically related to reactivity available for this product or its ingredients.
-------------------	--

10.2. Chemical stability

Stability	Stable at normal ambient temperatures.
------------------	--

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	None known.
---	-------------

10.4. Conditions to avoid

Conditions to avoid	Avoid excessive heat for prolonged periods of time.
----------------------------	---

10.5. Incompatible materials

Materials to avoid	None known.
---------------------------	-------------

Professional Rubber Based Paintable Undershield aerosol

10.6. Hazardous decomposition products

Hazardous decomposition products Heating may generate the following products: Toxic gases/vapours/fumes of: Carbon dioxide (CO₂). Carbon monoxide (CO).

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects No information available.

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

ATE dermal (mg/kg) 111,111.11

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Skin corrosion/irritation Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation May cause an allergic skin reaction.

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity - development Does not contain any substances known to be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Central and/or peripheral nervous system damage.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Not relevant.

Inhalation May cause drowsiness or dizziness. May cause discomfort.

Ingestion May cause discomfort if swallowed.

Professional Rubber Based Paintable Undershield aerosol

Skin contact May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Route of exposure Inhalation Skin and/or eye contact

Toxicological information on ingredients.

PROPANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

ACETONE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,800.0

Species Rat

ATE oral (mg/kg) 5,800.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 7,400.0

Species Rabbit

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 76.0

Species Rat

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

ISOBUTANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Species Rat

ATE oral (mg/kg) 5,000.0

BUTANE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,000.0

Professional Rubber Based Paintable Undershield aerosol

Species Rat

Hydrocarbons, C9, aromatics

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,592.0

Species Rat

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,160.0

Species Rabbit

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Acute toxicity - oral

Notes (oral LD₅₀) LD₅₀ > 5840 mg/kg, Oral, Rat

Acute toxicity - dermal

Notes (dermal LD₅₀) LD₅₀ > 2800-3100 mg/kg, Dermal, Rat

Acute toxicity - inhalation

Notes (inhalation LC₅₀) LC₅₀ > 23.3 mg/l, Inhalation, Rat

Skin corrosion/irritation

Skin corrosion/irritation Not irritating.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation No information available.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Central and/or peripheral nervous system damage.

Specific target organ toxicity - repeated exposure

Professional Rubber Based Paintable Undershield aerosol

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

XYLENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 3,523.0

Species Rat

ATE oral (mg/kg) 3,523.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 2,000.0

Species Rabbit

ATE dermal (mg/kg) 2,000.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 29,000.0

Species Rat

Species Human

ATE inhalation (vapours mg/l) 29,000.0

Skin corrosion/irritation

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/irritation

Serious eye damage/irritation Causes serious eye irritation.

Carcinogenicity

IARC carcinogenicity IARC Group 3 Not classifiable as to its carcinogenicity to humans.

Aspiration hazard

Aspiration hazard May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

Ecotoxicity Dangerous for the environment. Harmful to aquatic life with long lasting effects.

12.1. Toxicity

Acute aquatic toxicity

Acute toxicity - fish No information available.

Acute toxicity - aquatic invertebrates Not available.

Acute toxicity - aquatic plants Not available.

Professional Rubber Based Paintable Undershield aerosol

Acute toxicity - microorganisms Not available.

Acute toxicity - terrestrial Not available.

Chronic aquatic toxicity

Chronic toxicity - fish early life stage Not available.

Short term toxicity - embryo and sac fry stages Not available.

Chronic toxicity - aquatic invertebrates Not available.

Ecological information on ingredients.

ACETONE

Acute aquatic toxicity

Acute toxicity - fish LC₅₀, 96 hours: 5540 mg/l, Oncorhynchus mykiss (Rainbow trout)
LC₅₀, 96 hours: 11000 mg/l, Marinewater fish
LC₅₀, 96 hours: 8300 mg/l, Lepomis macrochirus (Bluegill)

Acute toxicity - aquatic invertebrates EC₅₀, 48 hours: 8800 mg/l, Freshwater invertebrates

Acute toxicity - aquatic plants EC₅₀, 96 hours: 7200 mg/l, Algae
NOEC, 96 hours: 430 mg/l, Algae

Hydrocarbons, C9, aromatics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 9.2 hours: 96 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EC₅₀, 2.9 hours: 48 mg/l, Daphnia magna

Acute toxicity - aquatic plants IC₅₀, 2.9 hours: 72 mg/l, Pseudokirchneriella subcapitata
NOEC, 1 hours: 72 mg/l, Pseudokirchneriella subcapitata

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Acute aquatic toxicity

Acute toxicity - fish LL₅₀, 96 hours: 3-10 mg/l, Oncorhynchus mykiss (Rainbow trout)
NOEC, 96 hours: 3 mg/l, Oncorhynchus mykiss (Rainbow trout)

Acute toxicity - aquatic invertebrates EL50, 48 hours: 4.6-10 mg/l, Daphnia magna

Acute toxicity - aquatic plants EL50, 72 hours: 10-30 mg/l, Raphidocelis subcapitata
NOELR, 72 hours: 6.3 mg/l, Raphidocelis subcapitata
NOEL, 72 hours: < 1 mg/l, Raphidocelis subcapitata

Chronic aquatic toxicity

Chronic toxicity - fish early life stage NOELR, 28 days: 0.574 mg/l,

Chronic toxicity - aquatic invertebrates NOELR, 21 days: 1 mg/l, Daphnia magna

Professional Rubber Based Paintable Undershield aerosol

XYLENE

Acute aquatic toxicity

Acute toxicity - fish	LC ₅₀ , 13.5 hours: 96 mg/l, Fish
Acute toxicity - aquatic invertebrates	EC ₅₀ , 7.4 hours: 48 mg/l, Daphnia magna
Acute toxicity - aquatic plants	IC ₅₀ , 72 hours: 1-10 mg/l, Algae

12.2. Persistence and degradability

Persistence and degradability Expected to be readily biodegradable.

Ecological information on ingredients.

ACETONE

Persistence and degradability	90 +/- 2.2%; 28 days
-------------------------------	----------------------

Hydrocarbons, C9, aromatics

Persistence and degradability	The product is readily biodegradable.
-------------------------------	---------------------------------------

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Stability (hydrolysis)	Not applicable.
Biodegradation	Rapidly degradable

XYLENE

Biodegradation	The substance is readily biodegradable.
----------------	---

12.3. Bioaccumulative potential

Bioaccumulative potential No information available.

Partition coefficient Not determined.

Ecological information on ingredients.

ACETONE

Bioaccumulative potential	Bioaccumulation is unlikely.
---------------------------	------------------------------

Hydrocarbons, C9, aromatics

Bioaccumulative potential	The product is not bioaccumulating.
---------------------------	-------------------------------------

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Bioaccumulative potential	Not applicable.
---------------------------	-----------------

12.4. Mobility in soil

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Professional Rubber Based Paintable Undershield aerosol

Mobility Not considered mobile.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment Not relevant.

Ecological information on ingredients.

Hydrocarbons, C9, aromatics

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Results of PBT and vPvB assessment This substance is not classified as PBT or vPvB according to current EU criteria.

12.6. Other adverse effects

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority.

Waste class WGK : 2 (Germany)

SECTION 14: Transport information

General Refer to the Dangerous Goods List for information on any Special Provisions 190, 327, 344, 625.

14.1. UN number

UN No. (ADR/RID) 1950

UN No. (IMDG) 1950

UN No. (ICAO) 1950

UN No. (ADN) 1950

14.2. UN proper shipping name

Proper shipping name (ADR/RID) AEROSOLS

Proper shipping name (IMDG) AEROSOLS

Proper shipping name (ICAO) AEROSOLS

Proper shipping name (ADN) AEROSOLS

14.3. Transport hazard class(es)

ADR/RID class 2.1

ADR/RID classification code 5F

ADR/RID label 2.1

IMDG class 2.1

ICAO class/division 2.1

Professional Rubber Based Paintable Undershield aerosol

ADN class 2.1

Transport labels



14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS F-D, S-U

ADR transport category 2

Tunnel restriction code (D)

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not applicable.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Commission Regulation (EU) No 2015/830 of 28 May 2015.

Council Directive of 20 May 1975 on the approximation of the laws of the Member States relating to aerosol dispensers (75/324/EEC) (as amended).

15.2. Chemical safety assessment

SECTION 16: Other information

Professional Rubber Based Paintable Undershield aerosol

Abbreviations and acronyms used in the safety data sheet

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.
 ATE: Acute Toxicity Estimate.
 CAS: Chemical Abstracts Service.
 DNEL: Derived No Effect Level.
 EC₅₀: 50% of maximal Effective Concentration.
 GHS: Globally Harmonized System.
 IATA: International Air Transport Association.
 IBC: International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk (International Bulk Chemical Code).
 ICAO: Technical Instructions for the Safe Transport of Dangerous Goods by Air.
 IMDG: International Maritime Dangerous Goods.
 LC₅₀: Lethal Concentration to 50 % of a test population.
 LD₅₀: Lethal Dose to 50% of a test population (Median Lethal Dose).
 NOAEL: No Observed Adverse Effect Level.
 PBT: Persistent, Bioaccumulative and Toxic substance.
 PNEC: Predicted No Effect Concentration.
 REACH: Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
 SVHC: Substances of Very High Concern.
 vPvB: Very Persistent and Very Bioaccumulative.

Revision date 08/08/2020

Revision 2

Supersedes date 24/09/2015

SDS number 14290

Hazard statements in full

H220 Extremely flammable gas.
 H222 Extremely flammable aerosol.
 H225 Highly flammable liquid and vapour.
 H226 Flammable liquid and vapour.
 H229 Pressurised container: may burst if heated.
 H304 May be fatal if swallowed and enters airways.
 H312 Harmful in contact with skin.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.