



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

**1.1 Product identifier:** LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK LACQUER 650°C - SPRAY

**1.2 Relevant identified uses of the substance or mixture and uses advised against:**

Relevant uses: Aerosol thermal varnish.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Details of the supplier of the safety data sheet:**

Agencja Handlowa "BOLL" Wojciech Dalewski Spółka Jawna  
ul. Chemiczna 3  
65-713 Zielona Góra - Polska  
Phone.: 68 451 99 99 - Fax: 68 451 99 00  
technolog@boll.pl

**1.4 Emergency telephone number:**

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

**CLP Regulation (EC) No 1272/2008:**

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aerosol 1: Flammable aerosols, Category 1, H222

Aerosol 1: Pressurised container: May burst if heated., H229

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Eye Irrit. 2: Eye irritation, Category 2, H319

STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335

STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

**2.2 Label elements:**

**CLP Regulation (EC) No 1272/2008:**

**Danger**



**Hazard statements:**

H222 - Extremely flammable aerosol

H229 - Pressurised container: May burst if heated

H319 - Causes serious eye irritation

H335 - May cause respiratory irritation

H336 - May cause drowsiness or dizziness

H412 - Harmful to aquatic life with long lasting effects

**Precautionary statements:**

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211: Do not spray on an open flame or other ignition source

P251: Do not pierce or burn, even after use

P260: Do not breathe spray

P271: Use only outdoors or in a well-ventilated area

P273: Avoid release to the environment

P280: Wear protective gloves/eye protection

P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P312: Call a POISON CENTER/doctor if you feel unwell

P403: Store in a well-ventilated place

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

**Supplementary information:**

EUH066: Repeated exposure may cause skin dryness or cracking

**2.3 Other hazards:**

Product fails to meet PBT/vPvB criteria

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substance:**

Non-applicable

**3.2 Mixture:**

**Chemical description:** active ingredient mixture with a propellant. Propellant: propane - butane

**Components:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

| Identification                                                                            | Chemical name/Classification                                                             |                                                                                                                                                    | Concentration         |
|-------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| CAS: 67-64-1<br>EC: 200-662-2<br>Index: 606-001-00-8<br>REACH: 01-2119471330-49-XXXX      | <b>Acetone<sup>(1)</sup></b> ATP CLP00                                                   |                                                                                                                                                    | <b>10 - &lt;25 %</b>  |
|                                                                                           | Regulation 1272/2008                                                                     | Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger                                                                           |                       |
| CAS: 106-97-8<br>EC: 203-448-7<br>Index: 601-004-00-0<br>REACH: 01-2119474691-32-XXXX     | <b>Butane<sup>(1)</sup></b> ATP CLP00                                                    |                                                                                                                                                    | <b>10 - &lt;25 %</b>  |
|                                                                                           | Regulation 1272/2008                                                                     | Flam. Gas 1A: H220; Press. Gas: H280 - Danger                                                                                                      |                       |
| CAS: 74-98-6<br>EC: 200-827-9<br>Index: 601-003-00-5<br>REACH: 01-2119486944-21-XXXX      | <b>Propane<sup>(1)</sup></b> ATP CLP00                                                   |                                                                                                                                                    | <b>10 - &lt;25 %</b>  |
|                                                                                           | Regulation 1272/2008                                                                     | Flam. Gas 1A: H220; Press. Gas: H280 - Danger                                                                                                      |                       |
| CAS: 108-10-1<br>EC: 203-550-1<br>Index: 606-004-00-4<br>REACH: 01-2119473980-30-XXXX     | <b>4-methylpentan-2-one<sup>(1)</sup></b> ATP CLP00                                      |                                                                                                                                                    | <b>10 - &lt;25 %</b>  |
|                                                                                           | Regulation 1272/2008                                                                     | Acute Tox. 4: H332; Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H335; EUH066 - Danger                                                       |                       |
| CAS: 64742-95-6<br>EC: 918-668-5<br>Index: Non-applicable<br>REACH: 01-2119455851-35-XXXX | <b>Hydrocarbons, C9, aromatics (EC 200-753-7 &lt;0,1%)<sup>(1)</sup></b> Self-classified |                                                                                                                                                    | <b>2,5 - &lt;10 %</b> |
|                                                                                           | Regulation 1272/2008                                                                     | Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335; STOT SE 3: H336; EUH066 - Danger                                  |                       |
| CAS: 1330-20-7<br>EC: 215-535-7<br>Index: 601-022-00-9<br>REACH: 01-2119488216-32-XXXX    | <b>Xylene<sup>(1)</sup></b> Self-classified                                              |                                                                                                                                                    | <b>1 - &lt;2,5 %</b>  |
|                                                                                           | Regulation 1272/2008                                                                     | Acute Tox. 4: H312+H332; Asp. Tox. 1: H304; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H335 - Danger |                       |
| CAS: 95-63-6<br>EC: 202-436-9<br>Index: 601-043-00-3<br>REACH: 01-2119472135-42-XXXX      | <b>1,2,4-trimethylbenzene<sup>(1)</sup></b> ATP CLP00                                    |                                                                                                                                                    | <b>1 - &lt;2,5 %</b>  |
|                                                                                           | Regulation 1272/2008                                                                     | Acute Tox. 4: H332; Aquatic Chronic 2: H411; Eye Irrit. 2: H319; Flam. Liq. 3: H226; Skin Irrit. 2: H315; STOT SE 3: H335 - Warning                |                       |
| CAS: 108-67-8<br>EC: 203-604-4<br>Index: 601-025-00-5<br>REACH: 01-2120738996-34-XXXX     | <b>Mesitylene<sup>(1)</sup></b> ATP CLP00                                                |                                                                                                                                                    | <b>&lt;1 %</b>        |
|                                                                                           | Regulation 1272/2008                                                                     | Aquatic Chronic 2: H411; Flam. Liq. 3: H226; STOT SE 3: H335 - Warning                                                                             |                       |
| CAS: 100-41-4<br>EC: 202-849-4<br>Index: 601-023-00-4<br>REACH: 01-2119489370-35-XXXX     | <b>Ethylbenzene<sup>(1)</sup></b> ATP ATP06                                              |                                                                                                                                                    | <b>&lt;1 %</b>        |
|                                                                                           | Regulation 1272/2008                                                                     | Acute Tox. 4: H332; Asp. Tox. 1: H304; Flam. Liq. 2: H225; STOT RE 2: H373 - Danger                                                                |                       |
| CAS: 98-82-8<br>EC: 202-704-5<br>Index: 601-024-00-X<br>REACH: 01-2119473983-24-XXXX      | <b>Cumene<sup>(1)</sup></b> ATP CLP00                                                    |                                                                                                                                                    | <b>&lt;1 %</b>        |
|                                                                                           | Regulation 1272/2008                                                                     | Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT SE 3: H335 - Danger                                                           |                       |

<sup>(1)</sup> Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

**Other information:**

| Identification                               | Specific concentration limit   |
|----------------------------------------------|--------------------------------|
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4 | % (w/w) >=25: STOT SE 3 - H335 |

SECTION 4: FIRST AID MEASURES

**4.1 Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, both acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of any immediate medical attention and special treatment needed:**

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

**5.1 Extinguishing media:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO<sub>2</sub>). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Special hazards arising from the substance or mixture:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Advice for firefighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions:**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Methods and material for containment and cleaning up:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Avoid splashes and pulverizations. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

Minimum Temp.: 10 °C

Maximum Temp.: 20 °C

Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Control parameters:**

Substances whose occupational exposure limits have to be monitored in the workplace

| Identification | Environmental limits |         |
|----------------|----------------------|---------|
|                | IOELV (8h)           | 500 ppm |
| IOELV (STEL)   |                      |         |

Acetone  
CAS: 67-64-1 EC: 200-662-2

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK**  
**LACQUER 650°C - SPRAY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Identification                                       | Environmental limits |         |                       |
|------------------------------------------------------|----------------------|---------|-----------------------|
|                                                      | IOELV (8h)           | 20 ppm  | 83 mg/m <sup>3</sup>  |
| 4-methylpentan-2-one<br>CAS: 108-10-1 EC: 203-550-1  | IOELV (STEL)         | 50 ppm  | 208 mg/m <sup>3</sup> |
| Xylene<br>CAS: 1330-20-7 EC: 215-535-7               | IOELV (8h)           | 50 ppm  | 221 mg/m <sup>3</sup> |
|                                                      | IOELV (STEL)         | 100 ppm | 442 mg/m <sup>3</sup> |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6 EC: 202-436-9 | IOELV (8h)           | 20 ppm  | 100 mg/m <sup>3</sup> |
|                                                      | IOELV (STEL)         |         |                       |
| Mesitylene<br>CAS: 108-67-8 EC: 203-604-4            | IOELV (8h)           | 20 ppm  | 100 mg/m <sup>3</sup> |
|                                                      | IOELV (STEL)         |         |                       |
| Ethylbenzene<br>CAS: 100-41-4 EC: 202-849-4          | IOELV (8h)           | 100 ppm | 442 mg/m <sup>3</sup> |
|                                                      | IOELV (STEL)         | 200 ppm | 884 mg/m <sup>3</sup> |
| Cumene<br>CAS: 98-82-8 EC: 202-704-5                 | IOELV (8h)           | 20 ppm  | 100 mg/m <sup>3</sup> |
|                                                      | IOELV (STEL)         | 50 ppm  | 250 mg/m <sup>3</sup> |

**DNEL (Workers):**

| Identification                                                                       |            | Short exposure        |                        | Long exposure          |                       |
|--------------------------------------------------------------------------------------|------------|-----------------------|------------------------|------------------------|-----------------------|
|                                                                                      |            | Systemic              | Local                  | Systemic               | Local                 |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2                                             | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 186 mg/kg              | Non-applicable        |
|                                                                                      | Inhalation | Non-applicable        | 2420 mg/m <sup>3</sup> | 1210 mg/m <sup>3</sup> | Non-applicable        |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1                               | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 11,8 mg/kg             | Non-applicable        |
|                                                                                      | Inhalation | 208 mg/m <sup>3</sup> | 208 mg/m <sup>3</sup>  | 83 mg/m <sup>3</sup>   | 83 mg/m <sup>3</sup>  |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 25 mg/kg               | Non-applicable        |
|                                                                                      | Inhalation | Non-applicable        | Non-applicable         | 150 mg/m <sup>3</sup>  | Non-applicable        |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                                            | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 180 mg/kg              | Non-applicable        |
|                                                                                      | Inhalation | 289 mg/m <sup>3</sup> | 289 mg/m <sup>3</sup>  | 77 mg/m <sup>3</sup>   | Non-applicable        |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9                              | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 16171 mg/kg            | Non-applicable        |
|                                                                                      | Inhalation | 100 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup> |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                                         | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 16171 mg/kg            | Non-applicable        |
|                                                                                      | Inhalation | 100 mg/m <sup>3</sup> | 100 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup> |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                       | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 180 mg/kg              | Non-applicable        |
|                                                                                      | Inhalation | Non-applicable        | 293 mg/m <sup>3</sup>  | 77 mg/m <sup>3</sup>   | Non-applicable        |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5                                              | Oral       | Non-applicable        | Non-applicable         | Non-applicable         | Non-applicable        |
|                                                                                      | Dermal     | Non-applicable        | Non-applicable         | 15,4 mg/kg             | Non-applicable        |
|                                                                                      | Inhalation | Non-applicable        | 250 mg/m <sup>3</sup>  | 100 mg/m <sup>3</sup>  | Non-applicable        |

**DNEL (General population):**

| Identification                                         |            | Short exposure |                | Long exposure          |                |
|--------------------------------------------------------|------------|----------------|----------------|------------------------|----------------|
|                                                        |            | Systemic       | Local          | Systemic               | Local          |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2               | Oral       | Non-applicable | Non-applicable | 62 mg/kg               | Non-applicable |
|                                                        | Dermal     | Non-applicable | Non-applicable | 62 mg/kg               | Non-applicable |
|                                                        | Inhalation | Non-applicable | Non-applicable | 200 mg/m <sup>3</sup>  | Non-applicable |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1 | Oral       | Non-applicable | Non-applicable | 4,2 mg/kg              | Non-applicable |
|                                                        | Dermal     | Non-applicable | Non-applicable | 4,2 mg/kg              | Non-applicable |
|                                                        | Inhalation | Non-applicable | Non-applicable | 14,7 mg/m <sup>3</sup> | Non-applicable |

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK**  
**LACQUER 650°C - SPRAY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

| Identification                                                                       |            | Short exposure         |                        | Long exposure          |                        |
|--------------------------------------------------------------------------------------|------------|------------------------|------------------------|------------------------|------------------------|
|                                                                                      |            | Systemic               | Local                  | Systemic               | Local                  |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | Oral       | Non-applicable         | Non-applicable         | 11 mg/kg               | Non-applicable         |
|                                                                                      | Dermal     | Non-applicable         | Non-applicable         | 11 mg/kg               | Non-applicable         |
|                                                                                      | Inhalation | Non-applicable         | Non-applicable         | 32 mg/m <sup>3</sup>   | Non-applicable         |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                                            | Oral       | Non-applicable         | Non-applicable         | 1,6 mg/kg              | Non-applicable         |
|                                                                                      | Dermal     | Non-applicable         | Non-applicable         | 108 mg/kg              | Non-applicable         |
|                                                                                      | Inhalation | Non-applicable         | Non-applicable         | 14,8 mg/m <sup>3</sup> | Non-applicable         |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9                              | Oral       | Non-applicable         | Non-applicable         | 15 mg/kg               | Non-applicable         |
|                                                                                      | Dermal     | Non-applicable         | Non-applicable         | 9512 mg/kg             | Non-applicable         |
|                                                                                      | Inhalation | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                                         | Oral       | Non-applicable         | Non-applicable         | 15 mg/kg               | Non-applicable         |
|                                                                                      | Dermal     | Non-applicable         | Non-applicable         | 9512 mg/kg             | Non-applicable         |
|                                                                                      | Inhalation | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> | 29,4 mg/m <sup>3</sup> |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                       | Oral       | Non-applicable         | Non-applicable         | 1,6 mg/kg              | Non-applicable         |
|                                                                                      | Dermal     | Non-applicable         | Non-applicable         | Non-applicable         | Non-applicable         |
|                                                                                      | Inhalation | Non-applicable         | Non-applicable         | 15 mg/m <sup>3</sup>   | Non-applicable         |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5                                              | Oral       | Non-applicable         | Non-applicable         | 5 mg/kg                | Non-applicable         |
|                                                                                      | Dermal     | Non-applicable         | Non-applicable         | 1,2 mg/kg              | Non-applicable         |
|                                                                                      | Inhalation | Non-applicable         | Non-applicable         | 16,6 mg/m <sup>3</sup> | Non-applicable         |

**PNEC:**

| Identification                                          |              |                |                         |             |
|---------------------------------------------------------|--------------|----------------|-------------------------|-------------|
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2                | STP          | 100 mg/L       | Fresh water             | 10,6 mg/L   |
|                                                         | Soil         | 29,5 mg/kg     | Marine water            | 1,06 mg/L   |
|                                                         | Intermittent | 21 mg/L        | Sediment (Fresh water)  | 30,4 mg/kg  |
|                                                         | Oral         | Non-applicable | Sediment (Marine water) | 3,04 mg/kg  |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1  | STP          | 27,5 mg/L      | Fresh water             | 0,6 mg/L    |
|                                                         | Soil         | 1,3 mg/kg      | Marine water            | 0,06 mg/L   |
|                                                         | Intermittent | 1,5 mg/L       | Sediment (Fresh water)  | 8,27 mg/kg  |
|                                                         | Oral         | Non-applicable | Sediment (Marine water) | 0,83 mg/kg  |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7               | STP          | 6,58 mg/L      | Fresh water             | 0,327 mg/L  |
|                                                         | Soil         | 2,31 mg/kg     | Marine water            | 0,327 mg/L  |
|                                                         | Intermittent | 0,327 mg/L     | Sediment (Fresh water)  | 12,46 mg/kg |
|                                                         | Oral         | Non-applicable | Sediment (Marine water) | 12,46 mg/kg |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9 | STP          | 2,41 mg/L      | Fresh water             | 0,12 mg/L   |
|                                                         | Soil         | 2,34 mg/kg     | Marine water            | 0,12 mg/L   |
|                                                         | Intermittent | 0,12 mg/L      | Sediment (Fresh water)  | 13,56 mg/kg |
|                                                         | Oral         | Non-applicable | Sediment (Marine water) | 13,56 mg/kg |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4            | STP          | 2,02 mg/L      | Fresh water             | 0,101 mg/L  |
|                                                         | Soil         | 1,34 mg/kg     | Marine water            | 0,101 mg/L  |
|                                                         | Intermittent | 0,101 mg/L     | Sediment (Fresh water)  | 7,86 mg/kg  |
|                                                         | Oral         | Non-applicable | Sediment (Marine water) | 7,86 mg/kg  |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4          | STP          | 9,6 mg/L       | Fresh water             | 0,1 mg/L    |
|                                                         | Soil         | 2,68 mg/kg     | Marine water            | 0,01 mg/L   |
|                                                         | Intermittent | 0,1 mg/L       | Sediment (Fresh water)  | 13,7 mg/kg  |
|                                                         | Oral         | 20 g/kg        | Sediment (Marine water) | 1,37 mg/kg  |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5                 | STP          | 200 mg/L       | Fresh water             | 0,035 mg/L  |
|                                                         | Soil         | 0,624 mg/kg    | Marine water            | 0,0035 mg/L |
|                                                         | Intermittent | 0,012 mg/L     | Sediment (Fresh water)  | 3,22 mg/kg  |
|                                                         | Oral         | Non-applicable | Sediment (Marine water) | 0,322 mg/kg |

**8.2 Exposure controls:**

A.- General security and hygiene measures in the work place

- CONTINUED ON NEXT PAGE -

**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Directive 89/686/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

**B.- Respiratory protection**

| Pictogram                                                                                                                   | PPE                                          | Labelling                                                                                    | CEN Standard                               | Remarks                                                                                                                 |
|-----------------------------------------------------------------------------------------------------------------------------|----------------------------------------------|----------------------------------------------------------------------------------------------|--------------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory respiratory tract protection | Filter mask for gases, vapours and particles | <br>CAT III | EN 149:2001+A1:2009<br>EN 405:2001+A1:2009 | Replace when an increase in resistance to breathing is observed and/or a smell or taste of the contaminant is detected. |

**C.- Specific protection for the hands**

| Pictogram                                                                                                      | PPE                                       | Labelling                                                                                    | CEN Standard                                                | Remarks                                                                                                                                                                                            |
|----------------------------------------------------------------------------------------------------------------|-------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory hand protection | NON-disposable chemical protective gloves | <br>CAT III | EN ISO 374-1:2016<br>EN 16523-1:2015<br>EN 420:2003+A1:2009 | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

"As the product is a mixture of several substances, the resistance of the glove material can not be predicted in advance with total reliability and has therefore to be checked prior to the application"

**D.- Ocular and facial protection**

| Pictogram                                                                                                        | PPE         | Labelling                                                                                     | CEN Standard                                                  | Remarks                                                                                                                   |
|------------------------------------------------------------------------------------------------------------------|-------------|-----------------------------------------------------------------------------------------------|---------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| <br>Mandatory face protection | Face shield | <br>CAT II | EN 166:2001<br>EN 167:2001<br>EN 168:2001<br>EN ISO 4007:2018 | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

**E.- Body protection**

| Pictogram                                                                                                                 | PPE                                                                                                 | Labelling                                                                                      | CEN Standard                                                                                                                                      | Remarks                                                                                     |
|---------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------|
| <br>Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | <br>CAT III | EN 1149-1,2,3<br>EN 13034:2005+A1:2009<br>EN ISO 13982-1:2004/A1:2010<br>EN ISO 6529:2013<br>EN ISO 6530:2005<br>EN ISO 13688:2013<br>EN 464:1994 | For professional use only. Clean periodically according to the manufacturer's instructions. |
| <br>Mandatory foot protection          | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | <br>CAT III | EN ISO 13287:2012<br>EN ISO 20345:2011<br>EN 13832-1:2019                                                                                         | Replace boots at any sign of deterioration.                                                 |

**F.- Additional emergency measures**

| Emergency measure                                                                                       | Standards                                       | Emergency measure                                                                                        | Standards                                      |
|---------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------------------------------------------------------------------------------|------------------------------------------------|
| <br>Emergency shower | ANSI Z358-1<br>ISO 3864-1:2011, ISO 3864-4:2011 | <br>Eyewash stations | DIN 12 899<br>ISO 3864-1:2011, ISO 3864-4:2011 |

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**Volatile organic compounds:**

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 100 % weight

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

|                           |                                     |
|---------------------------|-------------------------------------|
| V.O.C. density at 20 °C:  | 630,5 kg/m <sup>3</sup> (630,5 g/L) |
| Average carbon number:    | 5,71                                |
| Average molecular weight: | 89,47 g/mol                         |

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

|                          |                                                                                         |
|--------------------------|-----------------------------------------------------------------------------------------|
| Physical state at 20 °C: | Aerosol                                                                                 |
| Appearance:              | Fluid                                                                                   |
| Colour:                  |  Black |
| Odour:                   | Characteristic                                                                          |
| Odour threshold:         | Non-applicable *                                                                        |

**Volatility:**

|                                        |                     |
|----------------------------------------|---------------------|
| Boiling point at atmospheric pressure: | -44 °C (Propellant) |
| Vapour pressure at 20 °C:              | 830000 Pa           |
| Vapour pressure at 50 °C:              | Non-applicable *    |
| Evaporation rate at 20 °C:             | Non-applicable *    |

**Product description:**

|                                              |                       |
|----------------------------------------------|-----------------------|
| Density at 20 °C:                            | 0,8 kg/m <sup>3</sup> |
| Relative density at 20 °C:                   | 0,77                  |
| Dynamic viscosity at 20 °C:                  | Non-applicable *      |
| Kinematic viscosity at 20 °C:                | Non-applicable *      |
| Kinematic viscosity at 40 °C:                | Non-applicable *      |
| Concentration:                               | Non-applicable *      |
| pH:                                          | Non-applicable *      |
| Vapour density at 20 °C:                     | Non-applicable *      |
| Partition coefficient n-octanol/water 20 °C: | Non-applicable *      |
| Solubility in water at 20 °C:                | Non-applicable *      |
| Solubility properties:                       | Insoluble in water    |
| Decomposition temperature:                   | Non-applicable *      |
| Melting point/freezing point:                | Non-applicable *      |
| Recipient pressure:                          | Non-applicable *      |
| Explosive properties:                        | Non-applicable *      |
| Oxidising properties:                        | Non-applicable *      |

**Flammability:**

|                            |                     |
|----------------------------|---------------------|
| Flash Point:               | -97 °C (Propellant) |
| Flammability (solid, gas): | Non-applicable *    |
| Autoignition temperature:  | Non-applicable *    |
| Lower flammability limit:  | 0,7 % Volume        |
| Upper flammability limit:  | 13 % Volume         |

**Explosive:**

|                        |                  |
|------------------------|------------------|
| Lower explosive limit: | Non-applicable * |
|------------------------|------------------|

\*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Upper explosive limit: Non-applicable \*

**9.2 Other information:**

Surface tension at 20 °C: Non-applicable \*

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

**10.4 Conditions to avoid:**

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight            | Humidity       |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable     | Not applicable   | Risk of combustion      | Avoid direct impact | Not applicable |

**10.5 Incompatible materials:**

| Acids              | Water          | Oxidising materials | Combustible materials | Others                        |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable        | Avoid alkalis or strong bases |

**10.6 Hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
- Contact with the eyes: Produces eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK**  
**LACQUER 650°C - SPRAY**

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: 4-methylpentan-2-one (2B); Xylene (3); Ethylbenzene (2B); Cumene (2B)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
- Skin: Repeated exposure may cause skin dryness or cracking

H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

| Identification                                                                       | Acute toxicity  |                      | Genus  |
|--------------------------------------------------------------------------------------|-----------------|----------------------|--------|
|                                                                                      |                 |                      |        |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2                                             | LD50 oral       | 5800 mg/kg           | Rat    |
|                                                                                      | LD50 dermal     | 7426 mg/kg           | Rabbit |
|                                                                                      | LC50 inhalation | 76 mg/L (4 h)        | Rat    |
| Butane<br>CAS: 106-97-8<br>EC: 203-448-7                                             | LD50 oral       | >2000 mg/kg          |        |
|                                                                                      | LD50 dermal     | >2000 mg/kg          |        |
|                                                                                      | LC50 inhalation | 658 mg/L (4 h)       | Rat    |
| Propane<br>CAS: 74-98-6<br>EC: 200-827-9                                             | LD50 oral       | >2000 mg/kg          |        |
|                                                                                      | LD50 dermal     | >2000 mg/kg          |        |
|                                                                                      | LC50 inhalation | >5 mg/L (4 h)        |        |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1                               | LD50 oral       | 2080 mg/kg           |        |
|                                                                                      | LD50 dermal     | >2000 mg/kg          |        |
|                                                                                      | LC50 inhalation | 11 mg/L (4 h) (ATEi) |        |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | LD50 oral       | >2000 mg/kg          |        |
|                                                                                      | LD50 dermal     | >2000 mg/kg          |        |
|                                                                                      | LC50 inhalation | >20 mg/L (4 h)       |        |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                                            | LD50 oral       | 2100 mg/kg           | Rat    |
|                                                                                      | LD50 dermal     | 1100 mg/kg (ATEi)    | Rat    |
|                                                                                      | LC50 inhalation | 11 mg/L (4 h) (ATEi) |        |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9                              | LD50 oral       | 3400 mg/kg           | Rat    |
|                                                                                      | LD50 dermal     | 3160 mg/kg           | Rabbit |
|                                                                                      | LC50 inhalation | 11 mg/L (4 h)        | Rat    |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                                         | LD50 oral       | 6000 mg/kg           | Rat    |
|                                                                                      | LD50 dermal     | >2000 mg/kg          |        |
|                                                                                      | LC50 inhalation | >20 mg/L             |        |

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK**  
**LACQUER 650°C - SPRAY**

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

| Identification                                 | Acute toxicity  |             | Genus |
|------------------------------------------------|-----------------|-------------|-------|
|                                                | LD50 oral       | LD50 dermal |       |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4 | 3500 mg/kg      | 15354 mg/kg | Rat   |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5        | 17,2 mg/L (4 h) |             | Rat   |
|                                                | 2700 mg/kg      |             |       |
|                                                | >2000 mg/kg     |             |       |
|                                                | >20 mg/L        |             |       |

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Toxicity:**

| Identification                                                                       | Acute toxicity     |      | Species                   | Genus      |
|--------------------------------------------------------------------------------------|--------------------|------|---------------------------|------------|
|                                                                                      | LC50               | EC50 |                           |            |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2                                             | 5540 mg/L (96 h)   |      | Oncorhynchus mykiss       | Fish       |
|                                                                                      | 23.5 mg/L (48 h)   |      | Daphnia magna             | Crustacean |
|                                                                                      | 3400 mg/L (48 h)   |      | Chlorella pyrenoidosa     | Algae      |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1                               | 900 mg/L (48 h)    |      | Leuciscus idus            | Fish       |
|                                                                                      | 862 mg/L (24 h)    |      | Daphnia magna             | Crustacean |
|                                                                                      | 980 mg/L (48 h)    |      | Scenedesmus subspicatus   | Algae      |
| Hydrocarbons, C9, aromatics (EC 200-753-7 <0,1%)<br>CAS: 64742-95-6<br>EC: 918-668-5 | 1 - 10 mg/L (96 h) |      |                           | Fish       |
|                                                                                      | 1 - 10 mg/L        |      |                           | Crustacean |
|                                                                                      | 1 - 10 mg/L        |      |                           | Algae      |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7                                            | 13.5 mg/L (96 h)   |      | Oncorhynchus mykiss       | Fish       |
|                                                                                      | 3.4 mg/L (48 h)    |      | Ceriodaphnia dubia        | Crustacean |
|                                                                                      | 10 mg/L (72 h)     |      | Skeletonema costatum      | Algae      |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9                              | 7.72 mg/L (96 h)   |      | Pimephales promelas       | Fish       |
|                                                                                      | 6.14 mg/L (48 h)   |      | Daphnia magna             | Crustacean |
|                                                                                      | Non-applicable     |      |                           |            |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4                                         | 12.5 mg/L (96 h)   |      | Carassius auratus         | Fish       |
|                                                                                      | 50 mg/L (24 h)     |      | Daphnia magna             | Crustacean |
|                                                                                      | 53 mg/L (48 h)     |      | Scenedesmus subspicatus   | Algae      |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4                                       | 42.3 mg/L (96 h)   |      | Pimephales promelas       | Fish       |
|                                                                                      | 75 mg/L (48 h)     |      | Daphnia magna             | Crustacean |
|                                                                                      | 63 mg/L (3 h)      |      | Chlorella vulgaris        | Algae      |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5                                              | 2.7 mg/L (96 h)    |      | Salmo gairdneri           | Fish       |
|                                                                                      | 10.8 mg/L (48 h)   |      | Daphnia magna             | Crustacean |
|                                                                                      | 2.6 mg/L (72 h)    |      | Selenastrum capricornutum | Algae      |

**12.2 Persistence and degradability:**

| Identification                                          | Degradability  |     | Biodegradability |         |
|---------------------------------------------------------|----------------|-----|------------------|---------|
|                                                         | BOD5           | COD | Concentration    | Period  |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2                | Non-applicable |     | 100 mg/L         | 28 days |
|                                                         | Non-applicable |     | 28 days          | 96 %    |
|                                                         | 0.96           |     | % Biodegradable  |         |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1  | 2.06 g O2/g    |     | 100 mg/L         | 14 days |
|                                                         | 2.16 g O2/g    |     | 14 days          | 84 %    |
|                                                         | 0.95           |     | % Biodegradable  |         |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7               | Non-applicable |     | Non-applicable   | 28 days |
|                                                         | Non-applicable |     | 28 days          | 88 %    |
|                                                         | Non-applicable |     | % Biodegradable  |         |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9 | Non-applicable |     | 100 mg/L         | 28 days |
|                                                         | Non-applicable |     | 28 days          | 18 %    |
|                                                         | 0.43           |     | % Biodegradable  |         |

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK**  
**LACQUER 650°C - SPRAY**

SECTION 12: ECOLOGICAL INFORMATION (continued)

| Identification                                 | Degradability |                | Biodegradability |          |
|------------------------------------------------|---------------|----------------|------------------|----------|
|                                                | Parameter     | Value          | Parameter        | Value    |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4   | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|                                                | COD           | Non-applicable | Period           | 14 days  |
|                                                | BOD5/COD      | Non-applicable | % Biodegradable  | 0 %      |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4 | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|                                                | COD           | Non-applicable | Period           | 14 days  |
|                                                | BOD5/COD      | Non-applicable | % Biodegradable  | 90 %     |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5        | BOD5          | Non-applicable | Concentration    | 100 mg/L |
|                                                | COD           | Non-applicable | Period           | 14 days  |
|                                                | BOD5/COD      | Non-applicable | % Biodegradable  | 40 %     |

**12.3 Bioaccumulative potential:**

| Identification                                          | Bioaccumulation potential |          |
|---------------------------------------------------------|---------------------------|----------|
|                                                         | Parameter                 | Value    |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2                | BCF                       | 1        |
|                                                         | Pow Log                   | -0.24    |
|                                                         | Potential                 | Low      |
| Butane<br>CAS: 106-97-8<br>EC: 203-448-7                | BCF                       | 33       |
|                                                         | Pow Log                   | 2.89     |
|                                                         | Potential                 | Moderate |
| Propane<br>CAS: 74-98-6<br>EC: 200-827-9                | BCF                       | 13       |
|                                                         | Pow Log                   | 2.86     |
|                                                         | Potential                 | Low      |
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1  | BCF                       | 2        |
|                                                         | Pow Log                   | 1.31     |
|                                                         | Potential                 | Low      |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7               | BCF                       | 9        |
|                                                         | Pow Log                   | 2.77     |
|                                                         | Potential                 | Low      |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9 | BCF                       | 154      |
|                                                         | Pow Log                   | 3.78     |
|                                                         | Potential                 | High     |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4            | BCF                       | 182      |
|                                                         | Pow Log                   | 3.42     |
|                                                         | Potential                 | High     |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4          | BCF                       | 1        |
|                                                         | Pow Log                   | 3.15     |
|                                                         | Potential                 | Low      |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5                 | BCF                       | 120      |
|                                                         | Pow Log                   | 3.66     |
|                                                         | Potential                 | High     |

**12.4 Mobility in soil:**

| Identification                           | Absorption/desorption |                      | Volatility |                                 |
|------------------------------------------|-----------------------|----------------------|------------|---------------------------------|
|                                          | Parameter             | Value                | Parameter  | Value                           |
| Acetone<br>CAS: 67-64-1<br>EC: 200-662-2 | Koc                   | 1                    | Henry      | 2,93 Pa·m <sup>3</sup> /mol     |
|                                          | Conclusion            | Very High            | Dry soil   | Yes                             |
|                                          | Surface tension       | 2,304E-2 N/m (25 °C) | Moist soil | Yes                             |
| Butane<br>CAS: 106-97-8<br>EC: 203-448-7 | Koc                   | 900                  | Henry      | 96258,75 Pa·m <sup>3</sup> /mol |
|                                          | Conclusion            | Low                  | Dry soil   | Yes                             |
|                                          | Surface tension       | 1,187E-2 N/m (25 °C) | Moist soil | Yes                             |
| Propane<br>CAS: 74-98-6<br>EC: 200-827-9 | Koc                   | 460                  | Henry      | 71636,78 Pa·m <sup>3</sup> /mol |
|                                          | Conclusion            | Moderate             | Dry soil   | Yes                             |
|                                          | Surface tension       | 7,02E-3 N/m (25 °C)  | Moist soil | Yes                             |

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

| Identification                                          | Absorption/desorption |                      | Volatility |                               |
|---------------------------------------------------------|-----------------------|----------------------|------------|-------------------------------|
| 4-methylpentan-2-one<br>CAS: 108-10-1<br>EC: 203-550-1  | Koc                   | Non-applicable       | Henry      | Non-applicable                |
|                                                         | Conclusion            | Non-applicable       | Dry soil   | Non-applicable                |
|                                                         | Surface tension       | 2,35E-2 N/m (25 °C)  | Moist soil | Non-applicable                |
| Xylene<br>CAS: 1330-20-7<br>EC: 215-535-7               | Koc                   | 202                  | Henry      | 524,86 Pa·m <sup>3</sup> /mol |
|                                                         | Conclusion            | Moderate             | Dry soil   | Yes                           |
|                                                         | Surface tension       | Non-applicable       | Moist soil | Yes                           |
| 1,2,4-trimethylbenzene<br>CAS: 95-63-6<br>EC: 202-436-9 | Koc                   | 537                  | Henry      | 624,16 Pa·m <sup>3</sup> /mol |
|                                                         | Conclusion            | Low                  | Dry soil   | Yes                           |
|                                                         | Surface tension       | 2,919E-2 N/m (25 °C) | Moist soil | Yes                           |
| Mesitylene<br>CAS: 108-67-8<br>EC: 203-604-4            | Koc                   | 1445                 | Henry      | 888,62 Pa·m <sup>3</sup> /mol |
|                                                         | Conclusion            | Low                  | Dry soil   | Yes                           |
|                                                         | Surface tension       | 2,805E-2 N/m (25 °C) | Moist soil | Yes                           |
| Ethylbenzene<br>CAS: 100-41-4<br>EC: 202-849-4          | Koc                   | 520                  | Henry      | 798,44 Pa·m <sup>3</sup> /mol |
|                                                         | Conclusion            | Moderate             | Dry soil   | Yes                           |
|                                                         | Surface tension       | 2,859E-2 N/m (25 °C) | Moist soil | Yes                           |
| Cumene<br>CAS: 98-82-8<br>EC: 202-704-5                 | Koc                   | Non-applicable       | Henry      | Non-applicable                |
|                                                         | Conclusion            | Non-applicable       | Dry soil   | Non-applicable                |
|                                                         | Surface tension       | 2,769E-2 N/m (25 °C) | Moist soil | Non-applicable                |

**12.5 Results of PBT and vPvB assessment:**

Product fails to meet PBT/vPvB criteria

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Waste treatment methods:**

| Code      | Description                                                                     | Waste class (Regulation (EU) No 1357/2014) |
|-----------|---------------------------------------------------------------------------------|--------------------------------------------|
| 16 05 04* | gases in pressure containers (including halons) containing hazardous substances | Dangerous                                  |

**Type of waste (Regulation (EU) No 1357/2014):**

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP4 Irritant — skin irritation and eye damage

**Waste management (disposal and evaluation):**

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommend disposal down the drain. See paragraph 6.2.

**Regulations related to waste management:**

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to ADR 2019 and RID 2019:

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

SECTION 14: TRANSPORT INFORMATION (continued)



- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
Special regulations: 190, 327, 344, 625  
Tunnel restriction code: D  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 38-16:



- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
Special regulations: 190, 277, 327, 344, 63, 959  
EmS Codes: F-D, S-U  
Physico-Chemical properties: see section 9  
Limited quantities: 1 L  
Segregation group: Non-applicable  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

With regard to IATA/ICAO 2019:



- 14.1 UN number:** UN1950  
**14.2 UN proper shipping name:** AEROSOLS, flammable  
**14.3 Transport hazard class(es):** 2  
Labels: 2.1  
**14.4 Packing group:** N/A  
**14.5 Environmental hazards:** No  
**14.6 Special precautions for user**  
Physico-Chemical properties: see section 9  
**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:**

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable  
Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable  
Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable  
Article 95, REGULATION (EU) No 528/2012: Non-applicable  
REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

**SECTION 15: REGULATORY INFORMATION (continued)**

**Seveso III:**

| Section | Description | Lower-tier requirements | Upper-tier requirements |
|---------|-------------|-------------------------|-------------------------|
| P3a     |             | 150                     | 500                     |

**Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):**

Regulation (EU) No 98/2013 of the European Parliament and of the Council of 15 January 2013 on the marketing and use of explosives precursors: Contains Acetone. Product under the provisions of Article 9

Shall not be used in:

- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- tricks and jokes,
- games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

**Other legislation:**

The product could be affected by sectorial legislation

**15.2 Chemical safety assessment:**

The supplier has not carried out evaluation of chemical safety.

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830)

**Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:**

Non-applicable

**Texts of the legislative phrases mentioned in section 2:**

- H222: Extremely flammable aerosol
- H319: Causes serious eye irritation
- H335: May cause respiratory irritation
- H336: May cause drowsiness or dizziness
- H412: Harmful to aquatic life with long lasting effects
- H229: Pressurised container: May burst if heated

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**CLP Regulation (EC) No 1272/2008:**

- Acute Tox. 4: H312+H332 - Harmful in contact with skin or if inhaled
- Acute Tox. 4: H332 - Harmful if inhaled
- Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects
- Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways
- Eye Irrit. 2: H319 - Causes serious eye irritation
- Flam. Gas 1A: H220 - Extremely flammable gas
- Flam. Liq. 2: H225 - Highly flammable liquid and vapour
- Flam. Liq. 3: H226 - Flammable liquid and vapour
- Press. Gas: H280 - Contains gas under pressure, may explode if heated
- Skin Irrit. 2: H315 - Causes skin irritation
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure
- STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
- STOT SE 3: H335 - May cause respiratory irritation
- STOT SE 3: H336 - May cause drowsiness or dizziness

**Classification procedure:**

- CONTINUED ON NEXT PAGE -



**LAKIER TERMICZNY CZARNY - SPRAY - THERMAL BLACK  
LACQUER 650°C - SPRAY**

SECTION 16: OTHER INFORMATION (continued)

Aerosol 1: Calculation method  
Eye Irrit. 2: Calculation method  
STOT SE 3: Calculation method  
STOT SE 3: Calculation method  
Aquatic Chronic 3: Calculation method  
Aerosol 1: Calculation method

**Advice related to training:**

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<http://echa.europa.eu>  
<http://eur-lex.europa.eu>

**Abbreviations and acronyms:**

ADR: European agreement concerning the international carriage of dangerous goods by road  
IMDG: International maritime dangerous goods code  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organisation  
COD: Chemical Oxygen Demand  
BOD5: 5-day biochemical oxygen demand  
BCF: Bioconcentration factor  
LD50: Lethal Dose 50  
LC50: Lethal Concentration 50  
EC50: Effective concentration 50  
Log-POW: Octanol-water partition coefficient  
Koc: Partition coefficient of organic carbon

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -