

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 24

SDS No.: 205861

V014.0 Revision: 07.04.2025

printing date: 12.05.2025

Replaces version from: 21.11.2024

LOCTITE EA 3430 B

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

LOCTITE EA 3430 B

UFI: HNEF-S0EJ-200V-PAAG

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use: Epoxy Hardener

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website www.mysds.henkel.com or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Acute toxicity Category 4

H302 Harmful if swallowed. Route of Exposure: Oral

Skin corrosion Sub-category 1A

H314 Causes severe skin burns and eye damage.

Serious eye damage Category 1

H318 Causes serious eye damage.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

LOCTITE EA 3430 B SDS No.: 205861 Page 2 of 24

V014.0

Hazard pictogram:



Contains 2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol)

3,3'-Oxybis(ethyleneoxy)bis(propylamine)

N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

Signal word: Danger

Hazard statement: H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage. H317 May cause an allergic skin reaction. H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: "***" ***For consumer use only: P101 If medical advice is needed, have product

container or label at hand. P102 Keep out of reach of children. P501 Dispose of

contents/container in accordance with national regulation.***

Precautionary statement: P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection. Prevention

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. **Precautionary statement:** Response

Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P310 Immediately call a POISON CENTER or doctor.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration ≥ the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration ≥ the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

SDS No.: 205861 LOCTITE EA 3430 B Page 3 of 24

V014.0

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg. No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
2,2'-[1,2- ethanediylbis(oxy)]bis(ethanethio 1) 14970-87-7 239-044-2 01-2120768482-47	10- < 20 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410 Acute Tox. 3, Oral, H301 Acute Tox. 4, Inhalation, H332	M acute = 1 M chronic = 1	
3,3'- Oxybis(ethyleneoxy)bis(propyla mine) 4246-51-9 224-207-2 01-2119963377-26	5-< 10 %	Skin Corr. 1B, H314 Eye Dam. 1, H318 Skin Sens. 1, H317	dermal:ATE = 2.500 mg/kg	
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8 234-148-4 01-2119970376-29	5-< 10 %	Acute Tox. 4, Oral, H302 Skin Corr. 1A, H314 Skin Sens. 1B, H317 Acute Tox. 4, Dermal, H312 Eye Dam. 1, H318		
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]bisoxir ane 1675-54-3 216-823-5 01-2119456619-26	1- < 5 %	Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Skin Sens. 1, H317 Skin Irrit. 2, H315	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	
Benzyldimethylamine 103-83-3 203-149-1 01-2119529232-48	0,1-< 1 %	Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Flam. Liq. 3, H226 Aquatic Chronic 2, H411 Acute Tox. 4, Oral, H302 Acute Tox. 3, Inhalation, H331		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

SDS No.: 205861 LOCTITE EA 3430 B Page 4 of 24

V014.0

4.2. Most important symptoms and effects, both acute and delayed

SKIN: Rash, Urticaria.

INGESTION: Nausea, vomiting, diarrhea, abdominal pain.

Causes burns.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

water, carbon dioxide, foam, powder

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO2) and nitrogen oxides (NOx) can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Additional information:

In case of fire, keep containers cool with water spray.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid skin and eye contact.

See advice in section 8

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

SDS No.: 205861 LOCTITE EA 3430 B Page 5 of 24

V014.0

7.2. Conditions for safe storage, including any incompatibilities

Store in sealed original container. Ensure good ventilation/extraction. Store in a cool, well-ventilated place. Refer to Technical Data Sheet.

7.3. Specific end use(s)

Epoxy Hardener

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

None

Occupational Exposure Limits

Valid for

Ireland

None

SDS No.: 205861 LOCTITE EA 3430 B Page 6 of 24

V014.0

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value			Remarks	
		F	mg/l	ppm	mg/kg	others	
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	aqua (freshwater)		0,00076 mg/l				
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	aqua (marine water)		0,000076 mg/l				
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	sewage treatment plant (STP)		6,74 mg/l				
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	sediment (freshwater)				0,0047 mg/kg		
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	sediment (marine water)				0,00047 mg/kg		
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Soil				0,0005 mg/kg		
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	aqua (intermittent releases)		0,0076 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (freshwater)		0,22 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (marine water)		0,022 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	aqua (intermittent releases)		2,2 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sewage treatment plant (STP)		125 mg/l				
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (freshwater)				1,1 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	sediment (marine water)				0,11 mg/kg		
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Soil				0,091 mg/kg		
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	aqua (freshwater)		9,2 μg/l				
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	aqua (marine water)		0,92 μg/l				
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	aqua (intermittent releases)		92 μg/l				
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	Sewage treatment plant		18,1 mg/l				
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	sediment (freshwater)				0,0336 mg/kg		
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	sediment (marine water)				0,00336 mg/kg		
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	Soil				0,00132 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (freshwater)		0,006 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Freshwater - intermittent		0,018 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700	aqua (marine water)		0,001 mg/l				

SDS No.: 205861 LOCTITE EA 3430 B Page 7 of 24

V014.0

1675-54-3				
4,4-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Marine water - intermittent	0,002 mg/l		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sewage treatment plant (STP)	10 mg/l		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (freshwater)		0,341 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (marine water)		0,034 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Soil		0,065 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	oral		11 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Air			no hazard identified
Benzyldimethylamine 103-83-3 Benzyldimethylamine	aqua (freshwater) Freshwater -	0,005 mg/l		
103-83-3 Benzyldimethylamine	intermittent aqua (marine	0 mg/l		
103-83-3	water)			
Benzyldimethylamine 103-83-3	sewage treatment plant (STP)	534 mg/l		
Benzyldimethylamine 103-83-3	sediment (freshwater)		0,071 mg/kg	
Benzyldimethylamine 103-83-3	sediment (marine water)		0,007 mg/kg	
Benzyldimethylamine 103-83-3	Soil		0,011 mg/kg	

SDS No.: 205861 LOCTITE EA 3430 B Page 8 of 24

V014.0

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7		inhalation	Long term exposure - systemic effects		1,23 mg/m3	
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Workers	dermal	Long term exposure - systemic effects		1,75 mg/kg	
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	General population	inhalation	Long term exposure - systemic effects		0,22 mg/m3	
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	General population	oral	Long term exposure - systemic effects		0,125 mg/kg	
2,2'-[1,2-Ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	General population	dermal	Long term exposure - systemic effects		0,625 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - systemic effects		59 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Acute/short term exposure - systemic effects		176 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	inhalation	Long term exposure - local effects		13 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Workers	dermal	Long term exposure - systemic effects		8,3 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - systemic effects		17 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - systemic effects		52 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Long term exposure - local effects		0,5 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	inhalation	Acute/short term exposure - local effects		6,5 mg/m3	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	dermal	Long term exposure - systemic effects		5 mg/kg	
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	General population	oral	Long term exposure - systemic effects		5 mg/kg	
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	Workers	inhalation	Long term exposure - systemic effects		0,35 mg/m3	
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	Workers	dermal	Long term exposure - systemic effects		0,05 mg/kg	
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	General population	inhalation	Long term exposure - systemic effects		0,65 mg/m3	
N'-(3-Aminopropyl)-N,N-dimethylpropane- 1,3-diamine 10563-29-8	General population	oral	Long term exposure - systemic effects		0,2 mg/kg	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric	General	inhalation	Long term		0,87 mg/m3	no hazard identified

SDS No.: 205861 LOCTITE EA 3430 B Page 9 of 24

V014.0

reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight \leq 700	population		exposure - systemic effects		
1675-54-3 4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-	General population	dermal	Long term exposure -	0,0893 mg/kg	no hazard identified
epoxypropane, number average molecular weight ≤ 700 1675-54-3			systemic effects		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	oral	Long term exposure - systemic effects	0,5 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Long term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	inhalation	Acute/short term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Long term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Workers	dermal	Acute/short term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Long term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	inhalation	Acute/short term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Long term exposure - local effects		no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	General population	dermal	Acute/short term exposure - local effects		no hazard identified
Benzyldimethylamine 103-83-3	Workers	inhalation	Long term exposure - systemic effects	7,4 mg/m3	
Benzyldimethylamine 103-83-3	Workers	inhalation	Acute/short term exposure - systemic effects	14,8 mg/m3	
Benzyldimethylamine 103-83-3	Workers	inhalation	Long term exposure - local effects		
Benzyldimethylamine 103-83-3	Workers	inhalation	Acute/short term exposure - local effects		
Benzyldimethylamine 103-83-3	Workers	dermal	Long term exposure - systemic effects	1,05 mg/kg	
Benzyldimethylamine 103-83-3	Workers	dermal	Acute/short term exposure - systemic effects	2,1 mg/kg	
Benzyldimethylamine 103-83-3	Workers	dermal	Long term exposure - local		

SDS No.: 205861 LOCTITE EA 3430 B Page 10 of 24

V014.0

	1	1	effects	1	1
Benzyldimethylamine 103-83-3	Workers	dermal	Acute/short term exposure - local effects		
Benzyldimethylamine 103-83-3	General population	inhalation	Long term exposure - systemic effects	1,3 mg/m3	
Benzyldimethylamine 103-83-3	General population	inhalation	Acute/short term exposure - systemic effects	2,6 mg/m3	
Benzyldimethylamine 103-83-3	General population	inhalation	Long term exposure - local effects		
Benzyldimethylamine 103-83-3	General population	inhalation	Acute/short term exposure - local effects		
Benzyldimethylamine 103-83-3	General population	dermal	Long term exposure - systemic effects	0,4 mg/kg	
Benzyldimethylamine 103-83-3	General population	dermal	Acute/short term exposure - systemic effects	0,8 mg/kg	
Benzyldimethylamine 103-83-3	General population	dermal	Long term exposure - local effects		
Benzyldimethylamine 103-83-3	General population	dermal	Acute/short term exposure - local effects		
Benzyldimethylamine 103-83-3	General population	oral	Long term exposure - systemic effects	0,4 mg/kg	
Benzyldimethylamine 103-83-3	General population	oral	Acute/short term exposure - systemic effects	0,8 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing. Protective eye equipment should conform to EN166.

SDS No.: 205861 LOCTITE EA 3430 B Page 11 of 24

V014.0

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form liquid
Colour Clear
Odor characteristic
Physical state liquid

Melting point Not applicable, Product is a liquid

Solidification temperature < 5 °C (< 41 °F)

Initial boiling point > 230 °C (> 446 °F)no method / method unknown

Flammability The product is not flammable.

Explosive limits Not applicable, The product is not flammable. Flash point > 100,0 °C (> 212 °F); no method / method unknown

Auto-ignition temperature > 224 °C (> 435.2 °F)

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

I 9,1

(25 °C (77 °F); Conc.: 100 g/l; Solvent: Water)

Viscosity (kinematic) 20.000 mm2/s

(25 °C (77 °F);)

Viscosity, dynamic 19.000 - 26.000 mPa.s LCT STM 740; cone & plate viscosity

(Cone and plate; 25 °C (77 °F); Shear gradient: 10

s-1)

Solubility (qualitative) Soluble

(Solvent: Acetone)

Solubility (qualitative) Partially soluble

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable Mixture

Vapour pressure < 700 mbar;no method / method unknown

(21 °C (69.8 °F))

Density 1,1 g/cm3 None

(25 °C (77 °F))

Relative vapour density: > 1

(20 °C)

Particle characteristics Not applicable Product is a liquid

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reaction with strong acids.

Strong bases.

10.2. Chemical stability

Stable under recommended storage conditions.

SDS No.: 205861 LOCTITE EA 3430 B Page 12 of 24

V014.0

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

Stable under normal conditions of storage and use.

10.5. Incompatible materials

See section reactivity.

10.6. Hazardous decomposition products

carbon oxides.

Rapid polymerisation may generate excessive heat and pressure.

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
2,2'-[1,2- ethanediylbis(oxy)]bis(eth anethiol) 14970-87-7	LD50	> 50 - 300 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	LD50	3.160 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	LD50	1.669 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Benzyldimethylamine 103-83-3	LD50	353 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)

SDS No.: 205861 LOCTITE EA 3430 B Page 13 of 24

V014.0

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
2,2'-[1,2-	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
ethanediylbis(oxy)]bis(eth				
anethiol)				
14970-87-7				
3,3'-	Acute	2.500 mg/kg		Expert judgement
Oxybis(ethyleneoxy)bis(p	toxicity			
ropylamine)	estimate			
4246-51-9	(ATE)			
3,3'-	LD50	> 2.150 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute
Oxybis(ethyleneoxy)bis(p				Dermal Toxicity)
ropylamine)				
4246-51-9				
N'-(3-Aminopropyl)-N,N-	LD50	1.310 mg/kg	rat	not specified
dimethylpropane-1,3-				
diamine				
10563-29-8				
2,2'-[(1-	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
methylethylidene)bis(4,1-				
phenyleneoxymethylene)]				
bisoxirane				
1675-54-3				
Benzyldimethylamine	LD50	1.477 mg/kg	rabbit	not specified
103-83-3				

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
2,2'-[1,2-	LC50	1,34 mg/l	dust/mist	4 h	rat	not specified
ethanediylbis(oxy)]bis(eth						_
anethiol)						
14970-87-7						
Benzyldimethylamine	LC50	2,052 mg/l	vapour	4 h	rat	not specified
103-83-3		-				_

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	Sub-Category 1B (corrosive)		rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	irritating			Weight of evidence

SDS No.: 205861 LOCTITE EA 3430 B Page 14 of 24

V014.0

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	irritating			Weight of evidence

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2,2'-[1,2- ethanediylbis(oxy)]bis(eth anethiol) 14970-87-7	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)

SDS No.: 205861 LOCTITE EA 3430 B Page 15 of 24

V014.0

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
3,3'- Oxybis(ethyleneoxy)bis(p ropylamine) 4246-51-9	NOAEL P 600 mg/kg	screening	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)] bisoxirane 1675-54-3	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two- Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Based on available data, the classification criteria are not met.

Hazardous substances	Result / Value	Route of	Exposure time /	Species	Method
CAS-No.		application	Frequency of		
			treatment		
3,3'-	NOAEL < 100 mg/kg	oral: gavage	59 days	rat	OECD Guideline 422
Oxybis(ethyleneoxy)bis(p			daily		(Combined Repeated
ropylamine)			_		Dose Toxicity Study with
4246-51-9					the Reproduction /
					Developmental Toxicity
					Screening Test)
2,2'-[(1-	NOAEL 50 mg/kg	oral: gavage	14 w	rat	OECD Guideline 408
methylethylidene)bis(4,1-			daily		(Repeated Dose 90-Day
phenyleneoxymethylene)]			_		Oral Toxicity in Rodents)
bisoxirane					
1675-54-3					

SDS No.: 205861 LOCTITE EA 3430 B Page 16 of 24

V014.0

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SDS No.: 205861 LOCTITE EA 3430 B Page 17 of 24

V014.0

SECTION 12: Ecological information

General ecological information:

Do not empty into drains / surface water / ground water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2,2'-[1,2-	LC50	5,7 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
ethanediylbis(oxy)]bis(ethanet					Acute Toxicity Test)
hiol)					
14970-87-7					
3,3'-	LC50	> 215 - 464 mg/l	96 h	Leuciscus idus	DIN 38412-15
Oxybis(ethyleneoxy)bis(propy					
lamine)					
4246-51-9					
N'-(3-Aminopropyl)-N,N-	LC50	> 100 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish,
dimethylpropane-1,3-diamine					Acute Toxicity Test)
10563-29-8					
2,2'-[(1-	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish,
methylethylidene)bis(4,1-					Acute Toxicity Test)
phenyleneoxymethylene)]biso					
xirane					
1675-54-3					
Benzyldimethylamine	LC50	37,8 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish,
103-83-3					Acute Toxicity Test)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2,2'-[1,2- ethanediylbis(oxy)]bis(ethanet hiol) 14970-87-7	EC50	0,76 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC50	218 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	EC50	9,22 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Benzyldimethylamine 103-83-3	EC50	> 100 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type		_		

SDS No.: 205861 LOCTITE EA 3430 B Page 18 of 24

V014.0

2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	NOEC	0,3 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)
Benzyldimethylamine 103-83-3	NOEC	0,789 mg/l	21 d	1 0	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

SDS No.: 205861 LOCTITE EA 3430 B Page 19 of 24

V014.0

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2,2'-[1,2- ethanediylbis(oxy)]bis(ethanet	EC50	3,11 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
hiol) 14970-87-7					
2,2'-[1,2- ethanediylbis(oxy)]bis(ethanet hiol) 14970-87-7	EC10	0,51 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC50	666 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	NOEC	15,6 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	DIN 38412-09
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	EC50	21 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	EC10	5,7 mg/l	72 h	Raphidocelis subcapitata (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Benzyldimethylamine 103-83-3	EC50	1,34 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)
Benzyldimethylamine 103-83-3	NOEC	0,24 mg/l	72 h	Desmodesmus subspicatus (reported as Scenedesmus subspicatus)	EU Method C.3 (Algal Inhibition test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
2,2'-[1,2- ethanediylbis(oxy)]bis(ethanet hiol) 14970-87-7	EC50	772,1 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	EC10	152,5 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Benzyldimethylamine 103-83-3	EC10	534 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm- Test)

SDS No.: 205861 LOCTITE EA 3430 B Page 20 of 24

V014.0

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Result	Test type	Degradability	Exposure	Method
CAS-No.				time	
2,2'-[1,2-	not readily biodegradable.	aerobic	< 10 %	28 d	OECD Guideline 301 A (new
ethanediylbis(oxy)]bis(ethanet					version) (Ready Biodegradability:
hiol)					DOC Die Away Test)
14970-87-7					
3,3'-	not inherently	aerobic	< 20 %	28 d	OECD Guideline 302 B (Inherent
Oxybis(ethyleneoxy)bis(propy	biodegradable				biodegradability: Zahn-
lamine)	_				Wellens/EMPA Test)
4246-51-9					·
3,3'-	not readily biodegradable.	aerobic	0 %	60 d	OECD Guideline 301 B (Ready
Oxybis(ethyleneoxy)bis(propy					Biodegradability: CO2 Evolution
lamine)					Test)
4246-51-9					
N'-(3-Aminopropyl)-N,N-	readily biodegradable		100 %	28 d	OECD Guideline 301 A (new
dimethylpropane-1,3-diamine					version) (Ready Biodegradability:
10563-29-8					DOC Die Away Test)
2,2'-[(1-	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready
methylethylidene)bis(4,1-					Biodegradability: Manometric
phenyleneoxymethylene)]biso					Respirometry Test)
xirane					1 ,
1675-54-3					
Benzyldimethylamine	not readily biodegradable.	aerobic	0 - 2 %	28 d	OECD Guideline 301 C (Ready
103-83-3					Biodegradability: Modified MITI
					Test (I))

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentratio n factor (BCF)	Exposure time	Temperature	Species	Method
Benzyldimethylamine 103-83-3	> 2,1 - 22	42 d		Cyprinus carpio	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

SDS No.: 205861 LOCTITE EA 3430 B Page 21 of 24

V014.0

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	LogPow	Temperature	Method
CAS-No.	Logi 0 W	Temperature	Method
2,2'-[1,2- ethanediylbis(oxy)]bis(ethanet hiol) 14970-87-7	1,66	55 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
3,3'- Oxybis(ethyleneoxy)bis(propy lamine) 4246-51-9	-1,25	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	-0,56	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2,2'-[(1- methylethylidene)bis(4,1- phenyleneoxymethylene)]biso xirane 1675-54-3	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Benzyldimethylamine 103-83-3	1,98		EU Method A.8 (Partition Coefficient)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
2,2'-[1,2-ethanediylbis(oxy)]bis(ethanethiol) 14970-87-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3,3'-Oxybis(ethyleneoxy)bis(propylamine) 4246-51-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
N'-(3-Aminopropyl)-N,N-dimethylpropane-1,3-diamine 10563-29-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Benzyldimethylamine 103-83-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

SDS No.: 205861 LOCTITE EA 3430 B Page 22 of 24

V014.0

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes
for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We
will be happy to advise you.

SECTION 14: Transport information

14.1. UN number or ID number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

14.2. UN proper shipping name

ADR .	AMINES, LIQUID,	CORROSIVE, N.O.S.	(N,N'-Dimethyldipro	pyltriamine,3,3'-
-------	-----------------	-------------------	---------------------	-------------------

oxybis(ethyleneoxy)bis(propylamine))

RID AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-

oxybis(ethyleneoxy)bis(propylamine))

ADN AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-

oxybis(ethyleneoxy)bis(propylamine))

IMDG AMINES, LIQUID, CORROSIVE, N.O.S. (N,N'-Dimethyldipropyltriamine,3,3'-

oxybis (ethyleneoxy) bis (propylamine), 2, 2'-[1, 2-Ethane diylbis (oxy)] bis (ethanethiol))

IATA Amines, liquid, corrosive, n.o.s. (N,N'-Dimethyldipropyltriamine,3,3'-

oxybis(ethyleneoxy)bis(propylamine))

14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
ΙΛΤΛ	Q

14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

SDS No.: 205861 LOCTITE EA 3430 B Page 23 of 24

V014.0

ADN Environmentally Hazardous

IMDG Marine Pollutant IATA not applicable

14.6. Special precautions for user

RID

ADN

IMDG

IATA

ADR not applicable

Tunnelcode: (E) not applicable not applicable not applicable not applicable

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 2024/590):

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):

Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):

Not applicable

VOC content <3 %

(2010/75/EC)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SDS No.: 205861 LOCTITE EA 3430 B Page 24 of 24

V014.0

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL:

EU EXPLD 1:

Substance with a Union workplace exposure limit

EU EXPLD 1:

Substance listed in Annex I, Reg (EC) No. 2019/1148

EU EXPLD 2

Substance listed in Annex II, Reg (EC) No. 2019/1148

SVHC:

Substance of very high concern (REACH Candidate List)

PBT:

Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic criteria

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.