



Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: K2 PRO TAR MAX
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Tar remover
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Melle Sp. z o. o. Stary Staw 9

63-400 OSTRÓW WLKP.

POLAND

· Further information obtainable from:

Product safety department. zakupy@inter-global.com.pl

• 1.4 Emergency telephone number: During normal opening times: 0048/62 735 16 00

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



GHS08 health hazard

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms







GHS02

GHS07

GHS08

· Signal word Danger

(Contd. on page 2)



Page 2/9

Safety data sheet according to 1907/2006/EC and 2015/830/EC

Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 1)

· Hazard-determining components of labelling:

m-xylene

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

p-xylene

ethylbenzene

· Hazard statements

H226 Flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H304 May be fatal if swallowed and enters airways.

· Precautionary statements

P102 Keep out of reach of children.P280 Wear protective clothing.

P271 Use only outdoors or in a well-ventilated area. P301+P310 IF SWALLOWED: Immediately call a doctor.

P331 Do NOT induce vomiting.

P302+P352 IF ON SKIN: Wash with plenty of water.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container to a waste container.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Chemical characterisation: Mixtures
- · Description: Mixture: consisting of the following components.

· Dangerous compone	ents:	
918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	25-50%
	♦ Asp. Tox. 1, H304	
CAS: 108-38-3	m-xylene	25-50%
EINECS: 203-576-3	Flam. Liq. 3, H226; • Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 106-42-3	p-xylene	10-<25%
EINECS: 203-396-5	Flam. Liq. 3, H226; • Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 100-41-4	ethylbenzene	10-<25%
EINECS: 202-849-4	🚸 Flam. Liq. 2, H225; 🕚 Acute Tox. 4, H332	
CAS: 95-47-6	o-xylene	2.5-<10%
EINECS: 202-422-2	♦ Flam. Liq. 3, H226; ♦ Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

- GB



Page 3/9

Safety data sheet according to 1907/2006/EC and 2015/830/EC

Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 2)

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · General information: Take affected persons out into the fresh air.
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: If symptoms persist consult doctor.
- 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures Not required.
- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- $\cdot \textit{6.3 Methods and material for containment and cleaning up:} \\$

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- \cdot 7.3 *Specific end use*(s) *No further relevant information available.*

GB





Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 3)

SECTION 8: Exposure controls/personal protection

· Addit	ional information about design of technical facilities: No further data; see item 7.
	ontrol parameters
	dients with limit values that require monitoring at the workplace:
108-3	8-3 m-xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
106-4	2-3 p-xylene
	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
100-4	1-4 ethylbenzene
WEL	Short-term value: 552 mg/m³, 125 ppm Long-term value: 441 mg/m³, 100 ppm Sk
95-47	-6 o-xylene
WEL	Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV
· Ingre	dients with biological limit values:
108-3	8-3 m-xylene
BMG	V 650 mmol/mol creatinine urine post shift methyl hippuric acid
106-4	12-3 p-xylene
BMG	V 650 mmol/mol creatinine urine post shift methyl hippuric acid
95-47	7-6 o-xylene
BMG	V 650 mmol/mol creatinine urine post shift methyl hippuric acid

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures: Wash hands before breaks and at the end of work.
- · Respiratory protection: Not required.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)





Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling

0.1 Information on basis physical	and abouting I muon outing
9.1 Information on basic physical a General Information	ina cnemicai properties
Appearance:	
Form:	Liquid
Colour:	Light brown
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
Flash point:	Not applicable.
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Self-igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapon mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
Vapour pressure:	Not determined.
Density:	Not determined.
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.

(Contd. on page 6)





Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 5)

· Solubility in / Miscibility with

Soluble. water:

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic: Not determined. Kinematic: Not determined.

9.2 Other information No further relevant information available.

SECTION 10: Stability and reactivity


- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity

Harmful in contact with skin or if inhaled.

· LD/LC50 1	values rele	vant for classification:
ATE (Acut	te Toxicity	Estimates)
Dermal	LD50	5238 mg/kg
Inhalative	LC50/4 h	17.5 mg/l
108-38-3 n	n-xylene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	14100 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
106-42-3 р	-xylene	
Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	1100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)
100-41-4 е	thylbenzer	100
Oral	LD50	3500 mg/kg (rat)
Dermal	LD50	17800 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)
95-47-6 o-	xylene	
Dermal	LD50	1100 mg/kg (ATE)
Inhalative	LC50/4 h	11 mg/l (ATE)
		(Contd. on page



Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 6)

Page 7/9

- · Primary irritant effect:
- · Skin corrosion/irritation

Causes skin irritation.

- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- · Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- · STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

 $Water\ hazard\ class\ 2\ (German\ Regulation)\ (Self-assessment):\ hazardous\ for\ water$

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- · 12.5 Results of PBT and vPvB assessment
- · **PBT**: Not applicable.
- · vPvB: Not applicable.
- $\cdot \ \textbf{12.6 Other adverse effects} \ \textit{No further relevant information available}.$

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- $\cdot \textit{Recommendation:} \ Disposal \ must \ be \ made \ according \ to \ of ficial \ regulations.$

SE)N 14	: Trans	port in	formation	l

· 14.1 UN-Number

· ADR, IMDG, IATA UN1307

· 14.2 UN proper shipping name

· ADR 1307 XYLENES XYLENES XYLENES

(Contd. on page 8)





Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

	(Contd. of pa
· 14.3 Transport hazard class(es)	•
· ADR, IMDG, IATA	
, , , , , , , , , , , , , , , , , , ,	
3	
	2.51 11.11 11
· Class · Label	3 Flammable liquids. 3
	3
· 14.4 Packing group	III
· ADR, IMDG, IATA	III
· 14.5 Environmental hazards:	Not applicable.
· 14.6 Special precautions for user	Warning: Flammable liquids.
· Danger code (Kemler):	33
· EMS Number:	F- E , S - D
· Stowage Category	В
· 14.7 Transport in bulk according to Anna	
Marpol and the IBC Code	Not applicable.
Transport/Additional information:	
· ADR	
· Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E1
	Maximum net quantity per inner packaging: 30 ml
T	Maximum net quantity per outer packaging: 1000 ml
· Transport category · Tunnel restriction code	3 D/E
	<i>D/</i> Ε
· IMDG	17
Limited quantities (LQ)	1L Code: E2
Excepted quantities (EQ)	Coae: E2 Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per inner packaging: 50 ml Maximum net quantity per outer packaging: 500 ml
· UN ''Model Regulation'':	UN 1307 XYLENES, 3, III

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- · National regulations:
- 1. Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation,

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC and 2015/830/EC

Printing date 13.10.2016 Version number 1 Revision: 13.10.2016

Trade name: K2 PRO TAR MAX

(Contd. of page 8

Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

2. REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H332 Harmful if inhaled.

- · Department issuing SDS: Product safety department.
- · Contact: Mrs. Wozniak
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

GB