



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : SynPower™ SAE 5W-30
Synthetic Motor Oil

Product code : 872377

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Engine, gear & lubricating oil.

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local
CSR contact person

E-mail address : SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number
at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Not a hazardous substance or mixture.

Additional Labelling

EUH208 Contains C14-16-18 Alkyl phenol, Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes.

May produce an allergic reaction.

EUH210 Safety data sheet available on request.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED	72623-87-1 276-738-4 649-483-00-5 01-2119474889-13-xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27-xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM)	64742-70-7 265-174-4 649-477-00-2	Asp. Tox. 1; H304	>= 1 - < 2.5
Reaction products of Benzeneamine, N-phenyl- with nonene (branched)	36878-20-3 253-249-4	Aquatic Chronic 4; H413	>= 1 - < 2.5



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

	01-2119488911-28-xxxx		
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25-xxxx	Asp. Tox. 1; H304	>= 1 - < 2.5
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified	64742-56-9 265-159-2 649-469-00-9	Asp. Tox. 1; H304	>= 1 - < 2.5
C14-16-18 Alkyl phenol	Not Assigned 01-2119498288-19-xxxx	Skin Sens. 1B; H317 STOT RE 2; H373 (Liver)	>= 1 - < 2.5
DITHIOPHOSPHORIC ACID, O,O'-DIISOCTYL ESTER, ZINC SALT	28629-66-5 249-109-7 01-2119953278-28-xxxx	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 2; H411	>= 1 - < 2.5
Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes	252312-98-4	Skin Irrit. 2; H315 Skin Sens. 1B; H317 Aquatic Chronic 3; H412	>= 0.1 - < 0.25

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

If eye irritation persists, consult a specialist.

If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : carbon dioxide and carbon monoxide
Nitrogen oxides (NOx)

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Use personal protective equipment.



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

6.2 Environmental precautions

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not breathe vapours/dust.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Contains no substances with occupational exposure limit values.

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
DITHIOPHOSPHORIC ACID, O,O'-DIISOCTYL ESTER, ZINC SALT	Sewage treatment plant	3 mg/l
	Fresh water sediment	0.21 mg/kg
	Marine sediment	0.021 mg/kg
	Soil	0.04 mg/kg

8.2 Exposure controls

Personal protective equipment

Eye protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : No personal respiratory protective equipment normally required.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : amber

Odour : oily



SAFETY DATA SHEET
SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Odour Threshold	:	No data available
pH	:	Not applicable
Pour point	:	< -39 °C
Boiling point/boiling range	:	> 225 °C
Flash point	:	210 °C Method: Pensky-Martens closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	No data available
Relative vapour density	:	No data available
Relative density	:	0.857
Density	:	ca. 0.85 g/cm ³ (15.6 °C)
Solubility(ies)		
Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 12 mm ² /s (100 °C) 73.1 mm ² /s (40 °C)
Oxidizing properties	:	No data available



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

9.2 Other information

Self-ignition : No data available

No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Test atmosphere: **dust/mist**
Assessment: **The substance or mixture has no acute inhalation toxicity**
Remarks: **No mortality observed at this dose.**

Acute dermal toxicity : **LD50 (Rabbit): > 5,000 mg/kg**
Remarks: **No mortality observed at this dose.**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Acute oral toxicity : **LD50 (Rat): > 5,000 mg/kg**
Acute dermal toxicity : **LD50 (Rabbit): > 5,000 mg/kg**

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Acute oral toxicity : **LD50 (Rat): > 2,000 mg/kg**
Assessment: **The substance or mixture has no acute oral toxicity**
Remarks: **The toxicological data has been taken from products of similar composition.**

Acute dermal toxicity : **LD50 (Rabbit): > 2,000 mg/kg**
Assessment: **The substance or mixture has no acute dermal toxicity**
Remarks: **The toxicological data has been taken from products of similar composition.**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Acute oral toxicity : **LD50 (Rat): > 5,000 mg/kg**
Remarks: **No mortality observed at this dose.**

Acute dermal toxicity : **LD50 (Rat): > 2,000 mg/kg**
Assessment: **The substance or mixture has no acute dermal toxicity**
Remarks: **The toxicological data has been taken from products of similar composition.**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Acute oral toxicity : **LD50 (Rat): > 15 g/kg**
Acute dermal toxicity : **LD50 (Rabbit): > 5 g/kg**

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Acute oral toxicity : **LD50 (Rat): > 5,000 mg/kg**



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

C14-16-18 Alkyl phenol:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity
Remarks: No mortality observed at this dose.

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg
Assessment: The substance or mixture has no acute dermal toxicity

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks : May cause skin irritation and/or dermatitis.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No skin irritation

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Result : Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit
Result : Mild skin irritation
Remarks : The toxicological data has been taken from products of similar composition.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Species : Rabbit
Result : Slight, transient irritation

C14-16-18 Alkyl phenol:

Method : OECD Test Guideline 431
Result : No skin irritation

DITHIOPHOSPHORIC ACID, O,O'-DIISOCTYL ESTER, ZINC SALT:

Result : Skin irritation

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Species : Rabbit
Result : Irritating to skin.

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Result : No eye irritation

Remarks : Vapours may cause irritation to the eyes, respiratory system and the skin.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Species : Rabbit
Result : No eye irritation



SAFETY DATA SHEET
SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Assessment : Slight, transient irritation
Result : Slight, transient irritation

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Result : Slight, transient irritation

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Rabbit
Result : Slight, transient irritation
Remarks : The toxicological data has been taken from products of similar composition.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Assessment : No eye irritation
Result : No eye irritation

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Species : Rabbit
Result : Slight, transient irritation

C14-16-18 Alkyl phenol:

Species : Rabbit
Result : Slight, transient irritation

DITHIOPHOSPHORIC ACID, O,O'-DIISOCTYL ESTER, ZINC SALT:

Result : Corrosive

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Species : Rabbit
Result : Slight, transient irritation

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.

Respiratory sensitisation

Not classified based on available information.



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Product:

Assessment : Does not cause skin sensitisation.
Remarks : Based on similar product.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Remarks : The toxicological data has been taken from products of similar composition.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Test Type : Buehler Test
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406

C14-16-18 Alkyl phenol:

Test Type : Local lymph node assay
Species : Mouse
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OECD Test Guideline 429

DITHIOPHOSPHORIC ACID, O,O'-DIISOCTYL ESTER, ZINC SALT:

Assessment : Does not cause skin sensitisation.

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : The product is a skin sensitiser, sub-category 1B.
Method : OPPTS 870.2600

Germ cell mutagenicity

Not classified based on available information.



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

C14-16-18 Alkyl phenol:

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Genotoxicity in vitro : Test Type: **Ames test**
Test system: **Salmonella typhimurium**
Metabolic activation: **with and without metabolic activation**
Result: **negative**

Carcinogenicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Carcinogenicity - Assessment : **Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)**



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Carcinogenicity - Assessment : Classified based on DMSO extract content < 3% (Regulation (EC) 1272/2008, Annex VI, Part 3, Note L)

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Components:

C14-16-18 Alkyl phenol:

Target Organs Assessment : Liver
: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

May be fatal if swallowed and enters airways.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

May be fatal if swallowed and enters airways.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

Further information

Product:



SAFETY DATA SHEET
SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	: NOELR: >= 1,000 mg/l Exposure time: 14 d Species: Oncorhynchus mykiss (rainbow trout)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEL: 10 mg/l Exposure time: 21 d Species: Daphnia (water flea)



SAFETY DATA SHEET
SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Test substance: **WAF**
Method: **OECD Test Guideline 211**

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Not classified based on available information.**

DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC:

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Not classified based on available information.**

CATALYTIC DE WAXED HEAVY PARAFFINIC OIL (PETROLEUM):

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Not classified based on available information.**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Toxicity to fish : **LC50 (Danio rerio (zebra fish)): > 100 mg/l**
Exposure time: **96 h**
Test Type: **static test**
Remarks: **The toxicological data has been taken from products of similar composition.**

Toxicity to daphnia and other aquatic invertebrates : **EC50 (Daphnia magna (Water flea)): > 100 mg/l**
Exposure time: **48 h**
Test Type: **static test**
Test substance: **WAF**

Toxicity to algae/aquatic plants : **EC50 (Pseudokirchneriella subcapitata (algae)): 600 mg/l**
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**

Ecotoxicology Assessment

Acute aquatic toxicity : **Not classified based on available information.**
Chronic aquatic toxicity : **Chronic aquatic toxicity Category 4; May cause long lasting harmful effects to aquatic life.**



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC:

Toxicity to fish	: LL50 (Fish): > 100 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Aquatic invertebrates): > 10,000 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	: EL50 (Algae, algal mat (Algae)): > 100 mg/l Exposure time: 72 h
Toxicity to fish (Chronic toxicity)	: NOEC: 10 mg/l Species: Fish
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 10 mg/l Species: Aquatic invertebrates

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Toxicity to fish	: LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l Exposure time: 96 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l Exposure time: 48 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l End point: Growth inhibition Exposure time: 72 h Test Type: static test Test substance: WAF Method: OECD Test Guideline 201
Toxicity to daphnia and other	: NOEL: 10 mg/l



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

aquatic invertebrates
(Chronic toxicity) Exposure time: 21 d
Species: *Daphnia magna* (Water flea)
Test Type: semi-static test
Test substance: WAF
Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.
Chronic aquatic toxicity : Not classified based on available information.

C14-16-18 Alkyl phenol:

Toxicity to fish : LC50 (*Cyprinus carpio* (Carp)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Test substance: WAF
Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): > 100 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (algae)): > 100 mg/l
End point: Growth inhibition
Exposure time: 72 h
Test Type: static test
Test substance: WAF

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.
Chronic aquatic toxicity : Not classified based on available information.

DITHIOPHOSPHORIC ACID, O,O'-DIISOCTYL ESTER, ZINC SALT:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 3.8 mg/l
Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 510 mg/l
Exposure time: 48 h
Toxicity to algae/aquatic plants : EC50 (*Scenedesmus quadricauda* (Green algae)): 410 mg/l
Exposure time: 72 h
Toxicity to daphnia and other aquatic invertebrates : NOEC: 0.4 mg/l
Exposure time: 21 d



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

(Chronic toxicity) Species: **Daphnia magna (Water flea)**

Ecotoxicology Assessment

Acute aquatic toxicity : **Acute aquatic toxicity Category 2; Toxic to aquatic life.**

Chronic aquatic toxicity : **Chronic aquatic toxicity Category 2; Toxic to aquatic life with long lasting effects.**

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Toxicity to fish : **LL50 (Oncorhynchus mykiss (rainbow trout)): > 94.8 mg/l**
Exposure time: **96 h**
Test Type: **semi-static test**
Test substance: **WAF**
Method: **OECD Test Guideline 203**
Remarks: **No toxicity at the limit of solubility**
The toxicological data has been taken from products of similar composition.

Toxicity to daphnia and other aquatic invertebrates : **EL50 (Daphnia magna (Water flea)): 50 mg/l**
Exposure time: **48 h**
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 202**

Toxicity to algae/aquatic plants : **EL50 (Pseudokirchneriella subcapitata (green algae)): 14 mg/l**
End point: **Growth inhibition**
Exposure time: **72 h**
Test Type: **static test**
Test substance: **WAF**
Method: **OECD Test Guideline 201**
Remarks: **The toxicological data has been taken from products of similar composition.**

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : **NOELR: 100 mg/l**
Exposure time: **21 d**
Species: **Daphnia magna (Water flea)**
Test Type: **semi-static test**
Test substance: **WAF**
Method: **OECD Test Guideline 211**

Ecotoxicology Assessment

Acute aquatic toxicity : **Acute aquatic toxicity Category 3; Harmful to aquatic life.**

Chronic aquatic toxicity : **Chronic aquatic toxicity Category 3; Harmful to aquatic life**



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

with long lasting effects.

12.2 Persistence and degradability

Components:

LUBRICATING OILS, PETROLEUM, C20-50, HYDROTREATED:

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **2 - 4 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **0 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil - unspecified:

Biodegradability : Result: **Inherently biodegradable.**
Biodegradation: **31 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**

C14-16-18 Alkyl phenol:

Biodegradability : Result: **Readily biodegradable.**
Remarks: **Expert judgement**

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Biodegradability : Result: **Not readily biodegradable.**
Biodegradation: **23 %**
Exposure time: **28 d**
Method: **OECD Test Guideline 301B**
Remarks: **The toxicological data has been taken from products of similar composition.**

12.3 Bioaccumulative potential

Components:

Reaction products of Benzeneamine, N-phenyl- with nonene (branched):

Partition coefficient: n-octanol/water : log Pow: **> 7.5**



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

C14-16-18 Alkyl phenol:

Partition coefficient: n-octanol/water : log Pow: > 7.2

Magnesium carbonate fumarate hydroxide, monoalkyl(C10-13) benzene sulfonate, monopolybutenylbenzene sulfonate complexes:

Partition coefficient: n-octanol/water : log Pow: > 5.1 (20 °C)
Method: OECD Test Guideline 107

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

14.1 UN number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

UK REACH List of substances subject to authorisation (Annex XIV) : Not applicable



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

Control of Major Accident Hazards Regulations 2015 (COMAH) : Not applicable

Seveso III Directive (2012/18/EU) implemented by Control of Major Accident Hazards Regulations 2015 (COMAH) : Directive 96/82/EC does not apply

Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 6.36 %

The components of this product are reported in the following inventories:

TCSI : On the inventory, or in compliance with the inventory

TSCA : All substances listed as active on the TSCA inventory

AIIC : Not in compliance with the inventory

DSL : All components of this product are on the Canadian DSL

ENCS : On the inventory, or in compliance with the inventory

ISHL : Not in compliance with the inventory

KECI : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

IECSC : Not in compliance with the inventory

NZIoC : On the inventory, or in compliance with the inventory

TECI : Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

SECTION 16: Other information

Full text of H-Statements

H304	:	May be fatal if swallowed and enters airways.
H315	:	Causes skin irritation.
H317	:	May cause an allergic skin reaction.
H318	:	Causes serious eye damage.
H373	:	May cause damage to organs through prolonged or repeated exposure.
H411	:	Toxic to aquatic life with long lasting effects.
H412	:	Harmful to aquatic life with long lasting effects.
H413	:	May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Dam.	:	Serious eye damage
Skin Irrit.	:	Skin irritation
Skin Sens.	:	Skin sensitisation
STOT RE	:	Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the



SAFETY DATA SHEET

SynPower™ SAE 5W-30 Synthetic Motor Oil

Version: 5.0

Revision Date: 19.09.2022

Print Date: 19/09/2022

International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Internal information : R0517878

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN