	Page: 1
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Conforms to EU Regulation 1907/2006/EC as amended. - SDSGHS_GB

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ PTFE DRY

™ Trademark, Valvoline or its subsidiaries, registered in various countries

1.2 Relevant identified uses of the substance or mixture and uses advised against

Recommended use : Preparation

1.3 Details of the supplier of the safety data sheet Ellis Enterprises B.V., an affiliate of Valvoline Wieldrechtseweg 39 3316 BG Dordrecht Netherlands +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person SDS@valvoline.com	1.4 Emergency telephone number 00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112 Product Information +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person
--	---

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Eye irritation, Category 2


H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

Long-term (chronic) aquatic hazard, Category 2

H411: Toxic to aquatic life with long lasting effects.

	Page: 2
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P102 Keep out of reach of children.
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Dispose of contents/container in accordance with regional regulations.

Hazardous components which must be listed on the label:

Pentane
propan-2-ol


2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Additional advice

No information available.

SECTION 3: Composition/information on ingredients

	Page: 3
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

3.2 Mixtures

Hazardous components


Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (%)
Pentane	109-66-0 203-692-4 01-2119459286-30-xxxx	Flam. Liq.1; H224 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 40,00 - < 50,00
propan-2-ol	67-63-0 200-661-7 01-2119457558-25-xxxx	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336	>= 10,00 - < 15,00
Substances with a workplace exposure limit :			
Butane	106-97-8 203-448-7 01-2119474691-32-xxxx	Flam. Gas1; H220 Press. GasLiquefied gas; H280	>= 15,00 - < 25,00

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice	: Move out of dangerous area. Call a POISON CENTRE or doctor/physician if exposed or you feel unwell. Show this safety data sheet to the doctor in attendance. Do not leave the victim unattended.
If inhaled	: Move to fresh air. If unconscious, place in recovery position and seek medical advice. Consult a physician after significant exposure.
In case of skin contact	: First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
In case of eye contact	: Immediately flush eye(s) with plenty of water.

	Page: 4
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Remove contact lenses.
Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : No symptoms known or expected.

Risks : Causes serious eye irritation.
May cause drowsiness or dizziness.
Repeated exposure may cause skin dryness or cracking.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

SECTION 5: Firefighting measures

5.1 Extinguishing media


Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

	Page: 5
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
- Specific extinguishing methods : Product is compatible with standard fire-fighting agents.
- Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Use a water spray to cool fully closed containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas.
Remove all sources of ignition.
Ensure adequate ventilation.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.
Comply with all applicable federal, state, and local regulations.

6.2 Environmental precautions

- Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

6.4 Reference to other sections

For further information see Section 8 and Section 13 of the safety data sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Open drum carefully as content may be under pressure.
Provide sufficient air exchange and/or exhaust in work rooms.
Do not breathe vapours/dust.
Do not smoke.
Container hazardous when empty.

**SAFETY DATA SHEET**

Revision Date: 17.10.2018

Print Date: 20.10.2020

SDS Number: 000000274751

Version: 1.0

Valvoline™ PTFE DRY

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887045

Take precautionary measures against static discharges.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 Smoking, eating and drinking should be prohibited in the application area.
 For personal protection see section 8.
 Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Keep away from open flames, hot surfaces and sources of ignition. Use only explosion-proof equipment.

Hygiene measures : Wash hands before breaks and at the end of workday. When using do not eat or drink. When using do not smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. No smoking.

Other data : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection**8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m ³	2006/15/EC
		TWA	600 ppm 1.800 mg/m ³	GB EH40
Butane	106-97-8	STEL	750 ppm 1.810 mg/m ³	GB EH40



SAFETY DATA SHEET

Revision Date: 17.10.2018

Print Date: 20.10.2020

SDS Number: 000000274751

Version: 1.0

Valvoline™ PTFE DRY

™ Trademark, Valvoline or its subsidiaries, registered in various countries

887045

		TWA	600 ppm 1.450 mg/m ³	GB EH40
propan-2-ol	67-63-0	TWA	400 ppm 999 mg/m ³	GB EH40
		STEL	500 ppm 1.250 mg/m ³	GB EH40

8.2 Exposure controls

Engineering measures

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Eye protection : Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes
Flame-resistant clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Respiratory protection : In the case of vapour formation use a respirator with an approved filter.
In the case of dust or aerosol formation use respirator with an approved filter.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white, translucent

Odour : solvent-like

Odour Threshold : No data available

pH : No data available

**SAFETY DATA SHEET**

Revision Date: 17.10.2018

Print Date: 20.10.2020

SDS Number: 000000274751

Version: 1.0

Valvoline™ PTFE DRY
 ™ Trademark, Valvoline or its subsidiaries, registered in various countries
 887045

Melting point/freezing point : No data available

Initial boiling point and boiling range : Not applicable

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit / Upper flammability limit : 10,9 %(V)

Lower explosion limit / Lower flammability limit : 1,4 %(V)

Vapour pressure : 8 hPa (20 °C)

Relative vapour density : No data available

Relative density : No data available

Density : 0,6 g/cm³ (20 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Ignition temperature : 285 °C

Decomposition temperature : No data available

Viscosity


Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : not auto-flammable

	Page: 9
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid : None known.

Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Acids
Aldehydes
Alkali metals
alkalis
Amines
Ethylene oxide
halogenated hydrocarbons
halogens
isocyanates
Oxidizing agents
strong bases
strong reducing agents
Do not use with aluminum equipment at temperatures above 49C or 120 degrees F.


10.6 Hazardous decomposition products

Hazardous decomposition products : No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation
Skin contact

	Page: 10
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:

PENTANE NORMAL:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg
Assessment: Not classified as acutely toxic by ingestion under GHS.
Remarks: No mortality observed at this dose.

Acute inhalation toxicity : LC50 (Rat): > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: No adverse effect has been observed in acute inhalation toxicity tests.

Components:

ISOPROPANOL:

Acute oral toxicity : LD50 (Rat): 5,84 g/kg

Acute inhalation toxicity : LC50 (Rat): 16000 ppm
Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 12.800 mg/kg

Components:

BUTANE NORMAL:

Acute inhalation toxicity : LC50 (Mouse): 680 mg/l
Exposure time: 2 h

LC50 (Rat): > 50000 ppm
Exposure time: 2 h
Test atmosphere: gas


Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

Remarks: May cause skin irritation in susceptible persons.

	Page: 11
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Components:

PENTANE NORMAL:

Result: Slight, transient irritation

Result: Repeated exposure may cause skin dryness or cracking.

ISOPROPANOL:

Result: Slight, transient irritation

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin., Causes serious eye irritation.

Components:

PENTANE NORMAL:

Result: Slight, transient irritation

ISOPROPANOL:

Result: Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Germ cell mutagenicity

Not classified based on available information.

Components:

BUTANE NORMAL:

Genotoxicity in vitro : Test Type: Ames test
Test species: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Result: negative

Carcinogenicity

Not classified based on available information.


Reproductive toxicity

Not classified based on available information.

STOT - single exposure

May cause drowsiness or dizziness.

Components:

	Page: 12
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

PENTANE NORMAL:

Assessment: May cause drowsiness or dizziness.

ISOPROPANOL:

Assessment: May cause drowsiness or dizziness.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

PENTANE NORMAL:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting., Concentrations substantially above the TLV value may cause narcotic effects., Solvents may degrease the skin.

Components:

ISOPROPANOL:

Remarks: Central nervous system

SECTION 12: Ecological information

12.1 Toxicity

Components:


Pentane

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,26 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 10,7 mg/l
Exposure time: 72 h

propan-2-ol

	Page: 13
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 5.770 - 7.450 mg/l
Exposure time: 96 h
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates : LC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 24 h
Test Type: static test

Butane
Toxicity to fish : Remarks: No toxicity at the limit of solubility
QSAR

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): Expected > 10 - < 100 mg/l
Exposure time: 48 h
Remarks: QSAR

Toxicity to algae : EC50 (green algae): Expected 7,7 mg/l
Exposure time: 96 h
Remarks: QSAR

12.2 Persistence and degradability

Components:

Pentane
Biodegradability : Result: Readily biodegradable.
Biodegradation: 87 %
Exposure time: 28 d
Method: OECD Test Guideline 301F


Butane
Biodegradability : Result: Readily biodegradable.
Remarks: Information given is based on data obtained from similar substances.

12.3 Bioaccumulative potential

Components:

Pentane
Partition coefficient: n-octanol/water : log Pow: 3,39

propan-2-ol
Partition coefficient: n-octanol/water : log Pow: 0,05

	Page: 14
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Butane
Partition coefficient: n-octanol/water : log Pow: 2,89

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods


Product : The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Empty containers should be taken to an approved waste handling site for recycling or disposal.
Do not re-use empty containers.
Do not burn, or use a cutting torch on, the empty drum.

SECTION 14: Transport information

14.1 UN number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950

	Page: 15
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

IMDG : UN 1950

IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS

ADR : AEROSOLS

RID : AEROSOLS

IMDG : AEROSOLS

IATA : AEROSOLS

14.3 Transport hazard class(es)

ADN : 2

ADR : 2

RID : 2

IMDG : 2.1

IATA : 2.1

14.4 Packing group


ADN
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23
Labels : 2.1

IMDG
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)
Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203

	Page: 16
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Packing group : Not assigned by regulation
Labels : Flammable gas

IATA (Passenger)

Packing instruction : 203
(passenger aircraft)
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.


SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No 1005/2009 on substances that : Not applicable
deplete the ozone layer

Regulation (EC) No 850/2004 on persistent organic : Not applicable
pollutants

REACH - List of substances subject to authorisation : Not applicable
(Annex XIV)

	Page: 17
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 57). : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t

Other regulations : Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work.

The components of this product are reported in the following inventories:

DSL : This product contains one or several components that are not on the Canadian DSL and have annual quantity limits.

AICS Not in compliance with the inventory

ENCS Not in compliance with the inventory


KECI Not in compliance with the inventory

PICCS Not in compliance with the inventory

IECSC Not in compliance with the inventory

TCSI Not in compliance with the inventory

TSCA Not On TSCA Inventory

	Page: 18
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

15.2 Chemical safety assessment

No data available

SECTION 16: Other information

Further information

Revision Date: 17.10.2018

Full text of H-Statements

H220	Extremely flammable gas.
H224	Extremely flammable liquid and vapour.
H225	Highly flammable liquid and vapour.
H280	Contains gas under pressure; may explode if heated.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Other information : The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department ('+31 (0)78 654 3500).

Sources of key data used to compile the Safety Data Sheet


Valvoline internal data including own and sponsored test reports

The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :


ACGIH : American Conference of Industrial Hygienists

BEI : Biological Exposure Index

	Page: 19
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0

CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

ABM : Water Hazard Class for the Netherlands
ADR : Agreement concerning the International Carriage of Dangerous Goods by Road.
ADNR: Regulation for the Carriage of Dangerous Substances on the Rhine
CLP : Classification, Labelling and Packaging
CSA : Chemical Safety Assessment
CSR : Chemical Safety Report
DNEL : Derived No Effect Level.
EINECS : European Inventory of Existing Commercial Chemical Substances.
ELINCS : European List of Notified Chemical Substances
PEC : Predicted Effect Concentration
PEL : Permissible Exposure Limits
PNEC : Predicted No Effect Concentration
R-phrased : Risk phrase
REACH : Registration, Evaluation, Authorisation and Restriction of Chemicals
RID : Regulation Concerning the International Transport of Dangerous Goods by Rail
S-phrased : Safety phrase
WGK : German Water Hazard Class

	Page: 20
SAFETY DATA SHEET	Revision Date: 17.10.2018
	Print Date: 20.10.2020
	SDS Number: 000000274751
Valvoline™ PTFE DRY ™ Trademark, Valvoline or its subsidiaries, registered in various countries 887045	Version: 1.0