

according to Regulation (EC) No 1907/2006

Revision date: BIZOL Protect ATF D-VI

16.02.2021 Page 1 of 9

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**BIZOL Protect ATF D-VI** 

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

### Use of the substance/mixture

Lubricant

### 1.3. Details of the supplier of the safety data sheet

Company name: BIZOL BITA Trading GmbH Street: Martin-Buber-Str. 12
Place: D-14163 Berlin

Telephone: +49 (30) 804 869-0 Telefax: +49 (30) 804 869-2860

e-mail: support@bizol.de Internet: www.bizol.com

**1.4. Emergency telephone** Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)

number: In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454

24 24 24 In Republic of Ireland: 01 809 2166

### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Regulation (EC) No. 1272/2008

Hazard categories:

Hazardous to the aquatic environment: Aquatic Chronic 3

Hazard Statements:

Harmful to aquatic life with long lasting effects.

## 2.2. Label elements

## Regulation (EC) No. 1272/2008

### **Hazard statements**

H412 Harmful to aquatic life with long lasting effects.

## **Precautionary statements**

P273 Avoid release to the environment.

## 2.3. Other hazards

Results of PBT and vPvB assessment: not applicable.

## **SECTION 3: Composition/information on ingredients**

# 3.2. Mixtures

### **Chemical characterization**

Mineral oil-based mixture. Mineral oil with DMSO extract < 3 % as measured by IP 346.



16.02.2021

## **Safety Data Sheet**

according to Regulation (EC) No 1907/2006

Revision date: BIZOL Protect ATF D-VI

Page 2 of 9

Print date: 17.03.2021

### **Hazardous components**

CAS No	Chemical name	Quantity		
	EC No	Index No	REACH No	
	GHS Classification	,		
64742-54-7	distillates (petroleum), hy	ydrotreated heavy paraffinic		25 - <= 100 %
	265-157-1	649-467-00-8	01-2119484627-25	
	Asp. Tox. 1; H304	•		
72623-87-1	lubricating oils (petroleur	m), C20-50, hydrotreated neutral oil-	based	10 - < 20 %
	276-738-4	649-483-00-5	01-2119474889-13	
	Asp. Tox. 1; H304	-		
72623-86-0	lubricating oils (petroleur	1 - < 2.5 %		
	276-737-9	649-482-00-X	01-2119474878-16	
	Asp. Tox. 1; H304	·		
36878-20-3	bis(nonylphenyl)amine	1 - < 2.5 %		
	253-249-4		01-2119488911-28	
	Aquatic Chronic 4; H413			
125643-61-0	reaction mass of isomers	1 - < 2.5 %		
	406-040-9	607-530-00-7	01-0000015551-76	
	Aquatic Chronic 4; H413			
	phosphonic acid, dibutyl	0.1 - < 0.3 %		
	424-820-7		01-0000017126-75	
	Acute Tox. 4, Skin Corr. H400 H410			

Full text of H and EUH statements: see section 16.

### Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity				
	Specific Conc.	Specific Conc. Limits, M-factors and ATE					
64742-54-7	265-157-1	distillates (petroleum), hydrotreated heavy paraffinic	25 - <= 100 %				
	dermal: LD50 :	= > 5000,0 mg/kg; oral: LD50 = > 5000,0 mg/kg					
72623-87-1	276-738-4	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	10 - < 20 %				
	dermal: LD50 :	= > 2000,0 mg/kg; oral: LD50 = > 2000,0 mg/kg					
	424-820-7	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	0.1 - < 0.3 %				
	dermal: ATE =	1100 mg/kg M akut; H400: M=10					
	M chron.; H410	: M=10					

### **SECTION 4: First aid measures**

## 4.1. Description of first aid measures

### **General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

## After inhalation

Remove casualty to fresh air and keep warm and at rest.

### After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

#### After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

#### After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunken in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.



according to Regulation (EC) No 1907/2006

Revision date: 16.02.2021

# **BIZOL Protect ATF D-VI**

Page 3 of 9

### 4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

### 4.3. Indication of any immediate medical attention and special treatment needed

No information available.

### **SECTION 5: Firefighting measures**

### 5.1. Extinguishing media

#### Suitable extinguishing media

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO2).

#### Unsuitable extinguishing media

Full water jet.

#### 5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO2). Do not inhale explosion and combustion gases.

### 5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

#### Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### **General measures**

Protective measures: see section 7 + 8.

## 6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

## 6.3. Methods and material for containment and cleaning up

## Other information

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

#### 6.4. Reference to other sections

Protective measures: see section 7 + 8.

# **SECTION 7: Handling and storage**

## 7.1. Precautions for safe handling

## Advice on safe handling

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

### Advice on protection against fire and explosion

No special measures are necessary.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

#### 7.3. Specific end use(s)

Observe technical data sheet.

## **SECTION 8: Exposure controls/personal protection**

### 8.1. Control parameters



according to Regulation (EC) No 1907/2006

Revision date: 16.02.2021

# **BIZOL Protect ATF D-VI**

Page 4 of 9

Print date: 17.03.2021

## **DNEL/DMEL values**

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic			
Consumer DNE	EL, long-term	inhalation	local	1,2 mg/m³
Worker DNEL,	long-term	inhalation	local	5,4
36878-20-3	bis(nonylphenyl)amine			
Worker DNEL,	long-term	dermal	systemic	0,62 mg/kg bw/day
Worker DNEL,	long-term	inhalation	systemic	4,37 mg/m³
Consumer DNE	EL, long-term	oral	systemic	0,31 mg/kg bw/day
Consumer DNE	EL, long-term	dermal	systemic	0,31 mg/kg bw/day
Consumer DNE	EL, long-term	inhalation	systemic	1,09 mg/m³
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4	4-hydroxyphenyl)propio	nate	
Worker DNEL,	acute	dermal	systemic	20 mg/kg bw/day
Worker DNEL,	acute	dermal	local	1 mg/cm²
Worker DNEL,	long-term	dermal	systemic	0,22 mg/kg bw/day
Worker DNEL,	long-term	dermal	local	0,006 mg/cm²

## PNEC values

CAS No	Substance	
Environmenta	compartment	Value
64742-54-7	distillates (petroleum), hydrotreated heavy paraffinic	
Secondary po	soning	9,33 mg/kg
36878-20-3	bis(nonylphenyl)amine	
Freshwater		0,1 mg/l
Marine water		0,01 mg/l
Freshwater se	diment	132000 mg/kg
Marine sedime	ent	13200 mg/kg
125643-61-0	reaction mass of isomers of: C7-9-alkyl 3-(3,5-di-tert-butyl-4-hydroxyphenyl)propionate	
Freshwater		0,0043 mg/l
Marine water		0,0043 mg/l
Freshwater se	diment	233 mg/kg
Marine sedime	ent	23,3 mg/kg
Soil		189 mg/kg
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol	
Freshwater		0,036 mg/l
Freshwater se	diment	0,128 mg/kg
Soil	Soil	

## 8.2. Exposure controls

## Appropriate engineering controls

See section 7. No additional measures necessary.

## Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

# Eye/face protection

Eye glasses with side protection.



according to Regulation (EC) No 1907/2006

Revision date: BIZOL Protect ATF D-VI

16.02.2021 Page 5 of 9

## **Hand protection**

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time:: > 480 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Skin protection

Protective clothing.

## **Respiratory protection**

With correct and proper use, and under normal conditions, breathing protection is not required. When splashes or fine mist form, a permitted breathing apparatus suitable for these purposes must be used. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / FFP3.

#### **Environmental exposure controls**

Do not allow to enter into surface water or drains.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Physical state: Liquid Colour: red

Odour: characteristic

Test method

pH-Value: not applicable

Changes in the physical state

Melting point: not determined

Boiling point or initial boiling point and not determined

boiling range:

Pour point:  $<= -39 \, ^{\circ}\text{C} \, \text{ASTM D 7346}$  Flash point:  $>= 200 \, ^{\circ}\text{C} \, \text{EN ISO 2592}$ 

Lower explosion limits: 0,4 vol. %
Upper explosion limits: 4,5 vol. %
Auto-ignition temperature: not determined
Decomposition temperature: No information available.
Vapour pressure: < 0,1 hPa

(at 20 °C)

Density (at 15 °C): 0,85 g/cm³ DIN EN ISO 12185

Water solubility: insoluble
Partition coefficient n-octanol/water: not determined
Viscosity / dynamic: not determined

Viscosity / kinematic: 34 mm²/s ASTM D 7042

(at 40 °C)

Flow time: not determined
Relative vapour density: not determined
Evaporation rate: not determined

## 9.2. Other information

No information available.

### **SECTION 10: Stability and reactivity**

### 10.1. Reactivity

No information available.



according to Regulation (EC) No 1907/2006

Revision date:

# **BIZOL Protect ATF D-VI**

16.02.2021 Page 6 of 9

## 10.2. Chemical stability

No information available.

## 10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

## 10.4. Conditions to avoid

Heat.

#### 10.5. Incompatible materials

No information available.

### 10.6. Hazardous decomposition products

No information available.

# **SECTION 11: Toxicological information**

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
64742-54-7	distillates (petroleum), hyd	drotreated heavy paraffi	nic			
	oral	LD50 > 5000,0 mg/kg	Rat			
	dermal	LD50 > 5000,0 mg/kg	Rabbit			
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based					
	oral	LD50 > 2000,0 mg/kg	Rat			
	dermal	LD50 > 2000,0 mg/kg	Rabbit			
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol					
	dermal	ATE 1100 mg/kg				

### Irritation and corrosivity

Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

## STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

## **Aspiration hazard**

Based on available data, the classification criteria are not met.

### 11.2. Information on other hazards

### Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel.

## **SECTION 12: Ecological information**

#### 12.1. Toxicity

There are no data available on the mixture itself.



according to Regulation (EC) No 1907/2006

Revision date: BIZOL Protect ATF D-VI 16.02.2021

Page 7 of 9

CAS No	Chemical name							
	Aquatic toxicity	Dose		[h]   [d]	Species	Source	Method	
	phosphonic acid, dibutyl ester, reaction products with 2-(octylthio)- ethanol							
	Acute fish toxicity	LC50	1,5 mg/l		Oncorhynchus mykiss (Rainbow trout)	ECHA		
	Acute algae toxicity	ErC50 mg/l	0,31		Pseudokirchneriella subcapitata	ECHA		
	Acute crustacea toxicity	EC50 mg/l	0,09		Daphnia magna (Big water flea)	ECHA		
	Crustacea toxicity	NOEC mg/l	0,14	21 d	ECHA			

## 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name				
	Method	Value	d	Source	
	Evaluation				
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based				
	Biodegradation	49,0 %			
36878-20-3	bis(nonylphenyl)amine				
	OECD 301B	1 %	28	ECHA	
	Not readily biodegradable (according to OECD criteria)				

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

# Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
72623-87-1	lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	>4,00
36878-20-3	bis(nonylphenyl)amine	3,60

## 12.4. Mobility in soil

No data available

# 12.5. Results of PBT and vPvB assessment

No data available

### 12.7. Other adverse effects

No data available

## **SECTION 13: Disposal considerations**

## 13.1. Waste treatment methods

### **Disposal recommendations**

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

### List of Wastes Code - residues/unused products

130205 OIL WASTES AND WASTES OF LIQUID FUELS (EXCEPT EDIBLE OILS, AND THOSE IN

CHAPTERS 05, 12 AND 19); waste engine, gear and lubricating oils; mineral-based non-chlorinated

engine, gear and lubricating oils; hazardous waste

### Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

### **SECTION 14: Transport information**

### Land transport (ADR/RID)



according to Regulation (EC) No 1907/2006

**BIZOL Protect ATF D-VI** Revision date: 16.02.2021 Page 8 of 9

14.1. UN number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group:

Marine transport (IMDG)

14.1. UN number: No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.4. Packing group:

NO Marine pollutant:

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: No dangerous good in sense of this transport regulation. 14.2. UN proper shipping name: No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. 14.4. Packing group:

14.5. Environmental hazards

**ENVIRONMENTALLY HAZARDOUS:** No

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

### **EU** regulatory information

Restrictions on use (REACH, annex XVII):

Entry 3

2010/75/EU (VOC): 0 %

Information according to 2012/18/EU Not subject to 2012/18/EU (SEVESO III)

(SEVESO III):

**National regulatory information** 

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

# **SECTION 16: Other information**

#### Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,4,5,6,7,8,9,10,11,12,13,14,15,16.

### Abbreviations and acronyms

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration WEL (UK): Workplace Exposure Limits



according to Regulation (EC) No 1907/2006

**BIZOL Protect ATF D-VI** Revision date:

16.02.2021 Page 9 of 9

TWA (EC): Time-Weighted Average STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

## Classification for mixtures and used evaluation method according to Regulation (EC) No. 1272/2008 [CLP]

Classification	Classification procedure
Aquatic Chronic 3; H412	Calculation method

#### R

Relevant H and E	UH statements (number and full text)	
H304	May be fatal if swallowed and enters airways.	
H312	Harmful in contact with skin.	
H314	Causes severe skin burns and eye damage.	
H318	Causes serious eye damage.	

H400 Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects. H410 H412 Harmful to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

#### **Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)