



**Bizol AC Clean+ c30**

 Revision date:  
11.02.2021

Page 2 of 9

**SECTION 3: Composition/information on ingredients**
**3.2. Mixtures**
**Chemical characterization**

Blend of the following materials with non-hazardous additives.

**Hazardous components**

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
67-63-0	propan-2-ol			10 - < 12,5 %
	200-661-7	603-117-00-0	01-2119457558-25	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
74-98-6	propane			5 - < 10 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
106-97-8	butane			2,5 - < 5,0 %
	203-448-7	601-004-00-0	01-2119474691-32	
	Flam. Gas 1, Compressed gas; H220 H280			
75-28-5	isobutane			2,5 - < 5,0 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
107-98-2	1-methoxy-2-propanol			< 2,5 %
	203-539-1	603-064-00-3	01-2119457435-3	
	Flam. Liq. 3, STOT SE 3; H226 H336			
1336-21-6	ammonia			<= 0,5 %
	215-647-6	007-001-01-2	01-2119982985-14	
	Skin Corr. 1B, Eye Dam. 1, STOT SE 3, Aquatic Acute 1; H314 H318 H335 H400			

Full text of H and EUH statements: see section 16.

**Specific Conc. Limits, M-factors and ATE**

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-63-0	200-661-7	propan-2-ol	10 - < 12,5 %
	inhalation: LC50 = 72,6 mg/l (vapours); dermal: LD50 = 12800,0 mg/kg; oral: LD50 = 5280,0 mg/kg		
106-97-8	203-448-7	butane	2,5 - < 5,0 %
	inhalation: LC50 = 658 ppm (gases)		
107-98-2	203-539-1	1-methoxy-2-propanol	< 2,5 %
	dermal: LD50 = 11000 mg/kg; oral: LD50 = > 5000 mg/kg		
1336-21-6	215-647-6	ammonia	<= 0,5 %
	STOT SE 3; H335: >= 5 - 100		

**Labelling for contents according to Regulation (EC) No 648/2004**

15 % - &lt; 30 % aliphatic hydrocarbons, &lt; 5 % non-ionic surfactants, perfumes (Linalool, Limonene, Geraniol).

**SECTION 4: First aid measures**
**4.1. Description of first aid measures**
**General information**

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

Revision date:  
11.02.2021**Bizol AC Clean+ c30**

Page 3 of 9

**After inhalation**

Remove casualty to fresh air and keep warm and at rest.

**After contact with skin**

After contact with skin, wash immediately with plenty of water and soap.

**After contact with eyes**

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

**After ingestion**

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunk in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

**4.2. Most important symptoms and effects, both acute and delayed**

When in doubt or if symptoms are observed, get medical advice.

**4.3. Indication of any immediate medical attention and special treatment needed**

No information available.

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media**

Full water jet.

**5.2. Special hazards arising from the substance or mixture**

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO<sub>2</sub>). Do not inhale explosion and combustion gases.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Protective measures: see section 7 + 8.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

**6.3. Methods and material for containment and cleaning up****Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

**6.4. Reference to other sections**

Protective measures: see section 7 + 8.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

**Advice on protection against fire and explosion**

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit

## Bizol AC Clean+ c30

Revision date:  
11.02.2021

Page 4 of 9

values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Recommendation: Wear anti-static footwear and clothing

### 7.2. Conditions for safe storage, including any incompatibilities

#### Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

### 7.3. Specific end use(s)

Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
107-98-2	1-Methoxypropan-2-ol	100	375		TWA (8 h)	WEL
		150	560		STEL (15 min)	WEL
7664-41-7	Ammonia, anhydrous	25	18		TWA (8 h)	WEL
		35	25		STEL (15 min)	WEL
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

### 8.2. Exposure controls

#### Appropriate engineering controls

See section 7. No additional measures necessary.

#### Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

#### Eye/face protection

Eye glasses with side protection.

#### Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time: > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

#### Skin protection

Protective clothing.

#### Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / Full-/half-/quarter-face masks (DIN EN 136/140) + Combination filtering device, e.g. A P.

#### Environmental exposure controls

Do not allow to enter into surface water or drains.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state: Aerosol

**Bizol AC Clean+ c30**Revision date:  
11.02.2021

Page 5 of 9

Colour: colourless  
Odour: characteristic  
pH-Value: not determined

**Changes in the physical state**

Melting point: not determined  
Boiling point or initial boiling point and boiling range: not applicable  
Pour point: not applicable  
Flash point: < 0 °C

**Explosive properties**

The product is: not explosive. In use may form flammable/explosive vapour-air mixture.

Lower explosion limits: 2,0 vol. %  
Upper explosion limits: 12,0 vol. %  
Auto-ignition temperature: 425 °C  
Decomposition temperature: No information available.  
Vapour pressure: 43 hPa  
(at 20 °C)  
Density (at 20 °C): 0,87 g/cm<sup>3</sup>  
Water solubility: completely miscible  
Partition coefficient n-octanol/water: not determined  
Viscosity / dynamic: not determined  
Viscosity / kinematic: not determined  
Flow time: not determined  
Relative vapour density: not determined  
Evaporation rate: not determined

**9.2. Other information**

No information available.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No information available.

**10.2. Chemical stability**

No information available.

**10.3. Possibility of hazardous reactions**

No hazardous reaction when handled and stored according to provisions.

**10.4. Conditions to avoid**

Heat.

**10.5. Incompatible materials**

No information available.

**10.6. Hazardous decomposition products**

No information available.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

**ATEmix calculated**

ATE (inhalation gas) 13428,6 ppm

## Bizol AC Clean+ c30

Revision date:  
11.02.2021

Page 6 of 9

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-63-0	propan-2-ol				
	oral	LD50 mg/kg	5280,0	Rat	
	dermal	LD50 mg/kg	12800,0	Rabbit	
	inhalation (4 h) vapour	LC50	72,6 mg/l	Rat	
106-97-8	butane				
	inhalation (4 h) gas	LC50	658 ppm	Rat	GESTIS
107-98-2	1-methoxy-2-propanol				
	oral	LD50 mg/kg	> 5000	Rat	IUCLID
	dermal	LD50 mg/kg	11000	Rabbit	

### Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

### Sensitising effects

Based on available data, the classification criteria are not met.

### Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

### STOT-single exposure

Based on available data, the classification criteria are not met.

### STOT-repeated exposure

Based on available data, the classification criteria are not met.

### Aspiration hazard

Based on available data, the classification criteria are not met.

## 11.2. Information on other hazards

### Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

## SECTION 12: Ecological information

### 12.1. Toxicity

There are no data available on the mixture itself.

### 12.2. Persistence and degradability

There are no data available on the mixture itself.

CAS No	Chemical name			
	Method	Value	d	Source
	Evaluation			
67-63-0	propan-2-ol			
	DOC reduction	95,0 %	21	
	Readily biodegradable (according to OECD criteria).			

### 12.3. Bioaccumulative potential

There are no data available on the mixture itself.

## Bizol AC Clean+ c30

Revision date:  
11.02.2021

Page 7 of 9

### Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-63-0	propan-2-ol	0,05
74-98-6	propane	2,36
106-97-8	butane	2,89
75-28-5	isobutane	2,8
107-98-2	1-methoxy-2-propanol	-0,437
1336-21-6	ammonia	-1,38

### 12.4. Mobility in soil

No data available

### 12.5. Results of PBT and vPvB assessment

No data available

### 12.7. Other adverse effects

No data available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

#### Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

#### List of Wastes Code - residues/unused products

200113 MUNICIPAL WASTES (HOUSEHOLD WASTE AND SIMILAR COMMERCIAL, INDUSTRIAL AND INSTITUTIONAL WASTES) INCLUDING SEPARATELY COLLECTED FRACTIONS; separately collected fractions (except 15 01); Solvents; hazardous waste

#### List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

#### Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

## SECTION 14: Transport information

### Land transport (ADR/RID)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
 Hazard label: 2.1



Classification code: 5F  
 Special Provisions: 190 327 344 625  
 Limited quantity: 1 L  
 Excepted quantity: E0  
 Transport category: 2  
 Tunnel restriction code: D

### Marine transport (IMDG)

**14.1. UN number:** UN 1950

## Bizol AC Clean+ c30

Revision date:  
11.02.2021

Page 8 of 9

**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Marine pollutant: NO  
 Special Provisions: 63, 190, 277, 327, 344, 959  
 Limited quantity: 1000 mL  
 Excepted quantity: E0  
 EmS: F-D, S-U

### Air transport (ICAO-TI/IATA-DGR)

**14.1. UN number:** UN 1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable  
**14.3. Transport hazard class(es):** 2.1  
**14.4. Packing group:** -  
 Hazard label: 2.1



Special Provisions: A145 A167 A802  
 Limited quantity Passenger: 30 kg G  
 Passenger LQ: Y203  
 Excepted quantity: E0  
 IATA-packing instructions - Passenger: 203  
 IATA-max. quantity - Passenger: 75 kg  
 IATA-packing instructions - Cargo: 203  
 IATA-max. quantity - Cargo: 150 kg

### 14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

### 14.6. Special precautions for user

No data available

### 14.7. Maritime transport in bulk according to IMO instruments

No data available

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulatory information

Restrictions on use (REACH, annex XVII):  
Entry 28

2010/75/EU (VOC): 27,02 % (622,9 g/l)

#### National regulatory information

Water hazard class (D): 1 - slightly hazardous to water

### 15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

## SECTION 16: Other information

### Changes

This data sheet contains changes from the previous version in section(s): 1,2,3,7,8,9,11,13,14,15.



Revision date:  
11.02.2021**Bizol AC Clean+ c30**

Page 9 of 9

**Abbreviations and acronyms**

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)  
RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)  
IMDG: International Maritime Code for Dangerous Goods  
IATA: International Air Transport Association  
ICAO: International Civil Aviation Organization  
CAS: Chemical Abstracts Service (a division of the American Chemical Society)  
DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level  
PNEC: Predicted No Effect Concentration  
WEL (UK): Workplace Exposure Limits  
TWA (EC): Time-Weighted Average  
STEL (EC): Short Term Exposure Limit  
ATE: Acute Toxicity Estimate  
LD50: Lethal Dose, 50% (median lethal dose)  
LC50: Lethal Concentration, 50% (median lethal concentration)  
EC50: half maximal Effective Concentration  
ErC50: EC50 in terms of reduction of growth rate  
AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

**Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.

**Further Information**

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

-----  
The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*