

Revision date:
11.02.2021**Bizol Unblock+ f21**

Page 1 of 10

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Bizol Unblock+ f21

1.2. Relevant identified uses of the substance or mixture and uses advised against**Use of the substance/mixture**

Lubricant

1.3. Details of the supplier of the safety data sheet

Company name:	BIZOL BITA Trading GmbH	
Street:	Martin-Buber-Str. 12	
Place:	D-14163 Berlin	
Telephone:	+49 (30) 804 869-0	Telefax: +49 (30) 804 869-2860
e-mail:	support@bizol.de	
Internet:	www.bizol.com	

1.4. Emergency telephone number:

Germany: +49 (30) 804 869-0 (08.00-17.00, Mo-Fr)
In England and Wales: NHS Direct: 0845 4647 or 111 In Scotland: NHS 24 - 08454 24 24 24 In Republic of Ireland: 01 809 2166

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Skin corrosion/irritation: Skin Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazardous to the aquatic environment: Aquatic Chronic 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes skin irritation.

May cause drowsiness or dizziness.

Toxic to aquatic life with long lasting effects.

2.2. Label elements**Regulation (EC) No. 1272/2008****Hazard components for labelling**

kerosine (petroleum), hydrodesulfurized

Signal word: Danger**Pictograms:****Hazard statements**

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Precautionary statements

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Bizol Unblock+ f21

Revision date:
11.02.2021

Page 2 of 10

P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P302+P352	IF ON SKIN: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501	Dispose of waste according to applicable legislation.

2.3. Other hazards

Results of PBT and vPvB assessment: not applicable.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Chemical characterization

Blend of the following materials with non-hazardous additives.

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
64742-81-0	kerosine (petroleum), hydrodesulfurized			25 - 50 %
	265-184-9	649-423-00-8	01-2119462828-25	
	Skin Irrit. 2, STOT SE 3, Asp. Tox. 1, Aquatic Chronic 2; H315 H336 H304 H411			
75-28-5	isobutane			25 - 50 %
	200-857-2	601-004-00-0	01-2119485395-27	
	Flam. Gas 1, Compressed gas; H220 H280			
74-98-6	propane			10 - 25 %
	200-827-9	601-003-00-5	01-2119486944-21	
	Flam. Gas 1, Compressed gas; H220 H280			
64742-53-6	distillates (petroleum), hydrotreated light naphthenic			10 - 25 %
	265-156-6	649-466-00-2	01-2119480375-34	
	Asp. Tox. 1; H304			
111-76-2	2-butoxyethanol			< 2,5 %
	203-905-0	603-014-00-0	01-2119475108-36	
	Acute Tox. 4, Acute Tox. 4, Acute Tox. 4, Skin Irrit. 2, Eye Irrit. 2; H332 H312 H302 H315 H319			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
		Specific Conc. Limits, M-factors and ATE	
111-76-2	203-905-0	2-butoxyethanol	< 2,5 %
		inhalation: ATE = 11 mg/l (vapours); inhalation: ATE = 1,5 mg/l (dusts or mists); dermal: ATE = 1100 mg/kg; oral: LD50 = 470 mg/kg	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. If unconscious but breathing normally, place in recovery position and seek medical advice. Remove contaminated, saturated clothing immediately.

After inhalation

Remove casualty to fresh air and keep warm and at rest.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap.

Revision date:
11.02.2021**Bizol Unblock+ f21**

Page 3 of 10

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

After ingestion

If swallowed, rinse mouth with water (only if the person is conscious). Let water be drunk in little sips (dilution effect). Call a physician immediately. Do NOT induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

When in doubt or if symptoms are observed, get medical advice.

4.3. Indication of any immediate medical attention and special treatment needed

No information available.

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**

alcohol resistant foam, Extinguishing powder, Carbon dioxide (CO₂).

Unsuitable extinguishing media

Full water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products: Carbon monoxide Carbon dioxide (CO₂). Do not inhale explosion and combustion gases.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water. Do not allow to enter into soil/subsoil.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures****General measures**

Protective measures: see section 7 + 8.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Clean contaminated articles and floor according to the environmental legislation.

6.3. Methods and material for containment and cleaning up**Other information**

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

6.4. Reference to other sections

Protective measures: see section 7 + 8.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

Use personal protection equipment. Do not eat, drink or smoke when using this product. Provide fresh air. Handle and open container with care. Conditions to avoid: generation/formation of aerosols.

Advice on protection against fire and explosion

Avoid formation of flammable and explosive vapour concentrations in the air and exceeding the exposure limit values. Only use the material in places where open light, fire and other flammable sources can be kept away. Vapours of flammable solvents can accumulate in the gas phase of closed container, especially during heat treatment. Therefore keep away from fire and sources of ignition. Provide earthing of containers, equipment, pumps and ventilation facilities. Use non-sparking tools. Recommendation: Wear anti-static footwear and clothing

Bizol Unblock+ f21

Revision date:
11.02.2021

Page 4 of 10

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Protect against: Frost. Keep away from heat. Protect from direct sunlight. Keep container tightly closed in a cool, well-ventilated place.

7.3. Specific end use(s)

Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m ³	fibres/ml	Category	Origin
111-76-2	2-Butoxyethanol	25	123		TWA (8 h)	WEL
		50	246		STEL (15 min)	WEL

Biological Monitoring Guidance Values (EH40)

CAS No	Substance	Parameter	Value	Test material	Sampling time
111-76-2	2-Butoxyethanol	butoxyacetic acid (creatinine)	240 mmol/mol	urine	Post shift

DNEL/DMEL values

CAS No	Substance	Exposure route	Effect	Value
111-76-2	2-butoxyethanol			
	Consumer DNEL, long-term	oral	systemic	3,2 mg/kg bw/day
	Consumer DNEL, acute	dermal	systemic	44,5 mg/kg bw/day
	Worker DNEL, acute	dermal	systemic	89 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	38 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	75 mg/kg bw/day
	Consumer DNEL, acute	inhalation	local	123 mg/m ³
	Worker DNEL, acute	inhalation	local	246 mg/m ³
	Consumer DNEL, acute	inhalation	systemic	426 mg/m ³
	Worker DNEL, acute	inhalation	systemic	663 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	49 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	98 mg/m ³

PNEC values

CAS No	Substance	Value
111-76-2	2-butoxyethanol	
	Freshwater	8,8 mg/l
	Marine water	0,88 mg/l
	Freshwater sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Micro-organisms in sewage treatment plants (STP)	463 mg/kg
	Soil	3,13 mg/kg

8.2. Exposure controls

Revision date:
11.02.2021**Bizol Unblock+ f21**

Page 5 of 10

Appropriate engineering controls

See section 7. No additional measures necessary.

Protective and hygiene measures

When using do not eat, drink, smoke, sniff.

Eye/face protection

Eye glasses with side protection.

Hand protection

Wear suitable gloves. Recommended glove articles: EN ISO 374. Suitable material: NBR (Nitrile rubber). Breakthrough time:: > 120 min (Thickness of the glove material: 0.4 mm). Breakthrough times and swelling properties of the material must be taken into consideration. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Barrier creams can help protecting exposed skin areas. In no case should they be used after contact.

Skin protection

Protective clothing.

Respiratory protection

If technical exhaust or ventilation measures are not possible or insufficient, respiratory protection must be worn. Suitable respiratory protection apparatus: Filtering Half-face mask (DIN EN 149), e.g. FFA P / Full-/half-/quarter-face masks (DIN EN 136/140) + Combination filtering device, e.g. A P.

Environmental exposure controls

Do not allow to enter into surface water or drains.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Aerosol	
Colour:	black	
Odour:	characteristic	
pH-Value:		not determined

Changes in the physical state

Melting point:		not determined
Boiling point or initial boiling point and boiling range:		not applicable
Pour point:		not determined
Flash point:		ca. -80 °C

Explosive properties

The product is: not explosive. Heating causes rise in pressure with risk of bursting. In use may form flammable/explosive vapour-air mixture.

Lower explosion limits:		0,6 vol. %
Upper explosion limits:		10,8 vol. %
Auto-ignition temperature:		not determined
Decomposition temperature:		not determined
Vapour pressure:		not determined
Density (at 20 °C):		0,814 g/cm ³
Water solubility:		Immiscible
Partition coefficient n-octanol/water:		not determined
Viscosity / dynamic:		not determined
Viscosity / kinematic:		not determined
Flow time:		not determined
Relative vapour density:		not determined
Evaporation rate:		not determined

Revision date:
11.02.2021

Bizol Unblock+ f21

Page 6 of 10

9.2. Other information

Solid content: 0,4 %
No information available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No information available.

10.2. Chemical stability

No information available.

10.3. Possibility of hazardous reactions

No hazardous reaction when handled and stored according to provisions.

10.4. Conditions to avoid

Heat.

10.5. Incompatible materials

No information available.

10.6. Hazardous decomposition products

No information available.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Based on available data, the classification criteria are not met.

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
111-76-2	2-butoxyethanol				
	oral	LD50 mg/kg 470	Rat		
	dermal	ATE mg/kg 1100			
	inhalation vapour	ATE 11 mg/l			
	inhalation aerosol	ATE 1,5 mg/l			

Irritation and corrosivity

Causes skin irritation.

Serious eye damage/eye irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (kerosine (petroleum), hydrodesulfurized)

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

11.2. Information on other hazards

Other information

Keeping to the general worker's protection rules and the industrial hygienics, there is no risk in handling this product through the personnel. Prolonged or repeated skin contact may cause removal of natural fat from the skin resulting in dermatitis (skin inflammation).

Revision date:
11.02.2021

Bizol Unblock+ f21

Page 7 of 10

SECTION 12: Ecological information

12.1. Toxicity

There are no data available on the mixture itself.

CAS No	Chemical name					
	Aquatic toxicity	Dose	[h] [d]	Species	Source	Method
111-76-2	2-butoxyethanol					
	Acute fish toxicity	LC50 mg/l	1474	96 h	Oncorhynchus mykiss (Rainbow trout)	
	Acute algae toxicity	ErC50	623 mg/l	72 h	Pseudokirchneriella subcapitata	
	Acute crustacea toxicity	EC50 mg/l	1550	48 h	Daphnia magna (Big water flea)	
	Algae toxicity	NOEC mg/l	62,5	3 d	Pseudokirchneriella subcapitata	

12.2. Persistence and degradability

There are no data available on the mixture itself.

12.3. Bioaccumulative potential

There are no data available on the mixture itself.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36
111-76-2	2-butoxyethanol	0,81

12.4. Mobility in soil

No data available

12.5. Results of PBT and vPvB assessment

No data available

12.7. Other adverse effects

No data available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. This material and its container must be disposed of in a safe way. Waste disposal according to EC directives 75/442/EEC and 91/689/EEC in the corresponding versions, covering waste and dangerous waste.

List of Wastes Code - residues/unused products

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

List of Wastes Code - contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Consult the appropriate local waste disposal expert about waste disposal.

SECTION 14: Transport information


Bizol Unblock+ f21

Revision date:
11.02.2021

Page 8 of 10

Land transport (ADR/RID)


14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
 Hazard label: 2.1



Classification code: 5F
 Special Provisions: 190 327 344 625
 Limited quantity: 1 L
 Excepted quantity: E0
 Transport category: 2
 Tunnel restriction code: D

Marine transport (IMDG)


14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Marine pollutant: YES
 Special Provisions: 63, 190, 277, 327, 344, 959
 Limited quantity: 1000 mL
 Excepted quantity: E0
 EmS: F-D, S-U

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN 1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
 Hazard label: 2.1



Special Provisions: A145 A167 A802
 Limited quantity Passenger: 30 kg G
 Passenger LQ: Y203
 Excepted quantity: E0
 IATA-packing instructions - Passenger: 203
 IATA-max. quantity - Passenger: 75 kg
 IATA-packing instructions - Cargo: 203
 IATA-max. quantity - Cargo: 150 kg

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: Yes



Danger releasing substance: kerosine (petroleum), hydrodesulfurized

Revision date:
11.02.2021**Bizol Unblock+ f21**

Page 9 of 10

14.6. Special precautions for user

No data available

14.7. Maritime transport in bulk according to IMO instruments

No data available

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 28

2010/75/EU (VOC): 85 % (691,9 g/l)

National regulatory information

Water hazard class (D): 2 - obviously hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Changes**

This data sheet contains changes from the previous version in section(s): 1,2,3,7,8,9,11,13,14,15.

Abbreviations and acronyms

ADR: Accord relatif au transport international des marchandises dangereuses par route (Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement concernant le transport international ferroviaire des marchandises dangereuses (Regulations concerning the International Carriage of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

CAS: Chemical Abstracts Service (a division of the American Chemical Society)

DNEL/DMEL: Derived No-Effect Level / Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

WEL (UK): Workplace Exposure Limits

TWA (EC): Time-Weighted Average

STEL (EC): Short Term Exposure Limit

ATE: Acute Toxicity Estimate

LD50: Lethal Dose, 50% (median lethal dose)

LC50: Lethal Concentration, 50% (median lethal concentration)

EC50: half maximal Effective Concentration

ErC50: EC50 in terms of reduction of growth rate

AwSV: Verordnung über Anlagen zum Umgang mit wassergefährdenden Stoffen

Relevant H and EUH statements (number and full text)

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H280	Contains gas under pressure; may explode if heated.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.

Revision date:
11.02.2021

Bizol Unblock+ f21

Page 10 of 10

Further Information

Safety Data Sheet according to COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)