

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

1 Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: PROTECTON® ACTION 5 400 ML
- · Article number: SER751
- · 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Lubricant
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

MOTIP DUPLI B.V.

Wolfraamweg 2

NL-8471 XC Wolvega

The Netherlands

Tel: +31 (0)561 694400

Fax: +31 (0)561 694411 e-mail info@nl.motipdupli.com

- · Further information obtainable from: QHSE Department
- 1.4 Emergency telephone number: +31 629058130 (24 h/d, 7 d/wk)

2 Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC



F+; Extremely flammable

R12: Extremely flammable.

R66: Repeated exposure may cause skin dryness or cracking.

· Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Warning! Pressurized container.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms



· Signal word Danger

(Contd. on page 2)

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

(Contd. of page 1)

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

· Precautionary statements

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

- · 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

3 Composition/information on ingredients

- · 3.2 Chemical characterization: Mixtures
- · Description: Mixture of substances listed below with nonhazardous additions.

· Dangerous components:		
CAS: 64742-48-9 EC number: 918-481-9 Index number: 649-327-00-6 Reg.nr.: 01-2119457273-39-xxxx	Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2) Xn R65 R66 ♣ Asp. Tox. 1, H304	25-50%
CAS: 74-98-6 EINECS: 200-827-9 Index number: 601-003-00-5 Reg.nr.: 01-2119486944-21-xxxx	propane	12.5-20%
CAS: 106-97-8 EINECS: 203-448-7 Index number: 601-004-00-0 Reg.nr.: 01-2119474691-32-xxxx	butane F+ R12 Flam. Gas 1, H220 Press. Gas, H280	10-12.5%
CAS: 75-28-5 EINECS: 200-857-2 Index number: 601-004-00-0 Reg.nr.: 01-2119485395-27-xxxx	isobutane F+ R12 Flam. Gas 1, H220 Press. Gas, H280	5-10%
EC number: 939-603-7	Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts Xi R43 ♦ Skin Sens. 1B, H317	0.1-1%

[·] Additional information: For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- · After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 3)

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

(Contd. of page 2)

· 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- · For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

· 6.2 Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/surface or ground water.

- 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation.
- · 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· 7.1 Precautions for safe handling

No special measures required.

Ensure good ventilation/exhaustion at the workplace.

· Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Protect from heat and direct sunlight.
- · 7.3 Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical facilities: No further data; see item 7.

(Contd. on page 4)

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

(Contd. of page 3)

· 8.1 Control parameters

Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

WEL () Short-term value: 1810 mg/m³, 750 ppm Long-term value: 1450 mg/m³, 600 ppm Carc (if more than 0.1% of buta-1.3-diene)

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

- · Respiratory protection: Not required.
- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- · Material of gloves Not required.
- · Penetration time of glove material Not required.
- · Eye protection: Not required.

0 DI	1 1	1		۔۔ ف
9 Physical	ana ci	namuam	properi	ues

· 9.1 Information on basic physical and chemical properties · General Information		
· Appearance: Form:	Aerosol	
Colour:	According to product specification	
· Odour:	Characteristic	
· Odour threshold:	Not determined.	
· pH-value:	Not determined.	
· Change in condition Melting point/Melting range: Boiling point/Boiling range:	Undetermined. Not applicable, as aerosol.	
· Flash point:	< 0 °C (< 32 °F) Not applicable, as aerosol.	
· Flammability (solid, gaseous):	Not applicable.	
· Ignition temperature:	240 °C (464 °F)	
· Decomposition temperature:	Not determined.	
· Self-igniting:	Product is not selfigniting.	
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.	
· Explosion limits:		
Lower:	0.6 Vol %	
Upper:	10.9 Vol %	
· Vapour pressure at 20 °C (68 °F):	3500 hPa (2625 mm Hg)	
· Density at 20 °C (68 °F):	0.695 g/cm³ (5.8 lbs/gal)	

____ G

(Contd. on page 5)

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

		(Contd. of page
· Relative density	Not determined.	
· Vapour density	Not determined.	
· Evaporation rate	Not applicable.	
· Solubility in / Miscibility with		
water:	Not miscible or difficult to mix.	
· Partition coefficient (n-octanol/wa	iter): Not determined.	
· Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
· Solvent content:		
Organic solvents:	82.4 %	
Solids content:	17.6 %	
· 9.2 Other information	No further relevant information available.	

10 Stability and reactivity

- · 10.1 Reactivity
- · 10.2 Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · 11.1 Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values relevant for classification:			
64742-48-	64742-48-9 Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2)		
Oral	LD50	>15000 mg/kg (rat)	
Dermal	LD50	>3000 mg/kg (rab)	
Inhalative	LC50 / 4 h	>4951 mg/m3 (rat)	
106-97-8 butane			
Inhalative	LC50 / 4 h	658000 mg/m3 (rat)	
Benzenesulfonic acid, di-C10-14-alkyl derivs., calcium salts			
Dermal	LD50	>2000 mg/kg (rat)	
Dain and inside at affects			

- · Primary irritant effect:
- · on the skin: No irritant effect.
- · on the eye: No irritating effect.
- · Sensitization: No sensitizing effects known.

LC50 / 96 h | >100 mg/l (crustacean (amphipod))

12 Ecological information

· 12.1 Toxicity

· Aquatic toxicity:	
64742-48-9 Naphtha (petroleum), hydrotreated heavy (< 0,1 % benzol CAS nr. 71-43-2)	

(Contd. on page 6)

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

- · 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · 12.6 Other adverse effects No further relevant information available.

13 Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

	· European waste catalogue		
I	20 01 13*	solvents	
	15 01 04	metallic packaging	

- · Uncleaned packaging:
- · Recommendation: Non contaminated packagings may be recycled.

14 Transport information

· 14.1 UN-Number	
· ADR, IMDG, IATA	UN1950

· 14.2 UN proper shipping name

· ADR 1950 AEROSOLS
· IMDG AEROSOLS

· IATA AEROSOLS, flammable

- · 14.3 Transport hazard class(es)
- $\cdot ADR$



· Class 2 5F Gases.

· Label

(Contd. on page 7)

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

(Contd. of page 6) · IMDG, IATA · Class 2.1 · Label 2.1 · 14.4 Packing group · ADR, IMDG, IATA Void · 14.5 Environmental hazards: · Marine pollutant: No · 14.6 Special precautions for user Warning: Gases. · Danger code (Kemler): · EMS Number: F-D,S-U· 14.7 Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable. · Transport/Additional information: · Limited quantities (LQ) 1L· Transport category 2 D· Tunnel restriction code · UN "Model Regulation": UN1950, AEROSOLS, 2.1

15 Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture No further relevant information available.
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction.

R12 Extremely flammable.

R43 May cause sensitisation by skin contact.

R65 Harmful: may cause lung damage if swallowed.

R66 Repeated exposure may cause skin dryness or cracking.

- · Department issuing MSDS: QHSE Department
- · Contact: Mr. K. Smedeman
- · Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 8)

Page 8/8

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 25.06.2014 Version number 88 Revision: 19.06.2014

Trade name: PROTECTON® ACTION 5 400 ML

(Contd. of page 7)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Gas 1: Flammable gases, Hazard Category 1 Flam. Aerosol 1: Flammable aerosols, Hazard Category 1 Press. Gas: Gases under pressure: Compressed gas Skin Sens. 1B: Sensitisation - Skin, Hazard Category 1B Asp. Tox. 1: Aspiration hazard, Hazard Category 1

* Data compared to the previous version altered.

GB