

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- **1.1 Product identifier**
- **Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776**
- **1.2 Relevant identified uses of the substance or mixture and uses advised against**
No further relevant information available.
- **Application of the substance / the mixture** Detergent
- **1.3 Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**

Alfred Kärcher SE & Co. KG
Alfred-Kärcher-Str. 28-40
D - 71364 Winnenden
Tel.: +49-7195-14-0

Kärcher (UK) Ltd.
Kärcher House
Brookhill Way
Banbury
Oxon OX16 3ED
Great Britain
Tel.: +44-1295-752-000

Internet: www.karcher.com
- **Further information obtainable from:**

Department CSD-D
Tel.: +49-7195-14-0
productsafety.management@de.kaercher.com
- **1.4 Emergency telephone number:**

For Hazardous Materials [or Dangerous Goods] Incidents
Spill, Leak, Fire, Exposure, or Accident
Call CHEMTREC Day or Night
Within USA and Canada: 1-800-424-9300
Outside USA and Canada: +1 703-741-5970 (collect calls accepted)

SECTION 2: Hazards identification

- **2.1 Classification of the substance or mixture**
- **Classification according to Regulation (EC) No 1272/2008**
Met. Corr. 1 H290 May be corrosive to metals.
Skin Corr. 1 H314 Causes severe skin burns and eye damage.
Eye Dam. 1 H318 Causes serious eye damage.
- **2.2 Label elements**
- **Labelling according to Regulation (EC) No 1272/2008**
The product is classified and labelled according to the GB CLP regulation.

(Contd. on page 2)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 1)

· Hazard pictograms



GHS05

· Signal word Danger

· Hazard-determining components of labelling:

sodium hydroxide

· Hazard statements

H290 May be corrosive to metals.

H314 Causes severe skin burns and eye damage.

· Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· 2.3 Other hazards

The product does not contain any organic halogen compounds (AOX), nitrates, heavy metal compounds.

· Results of PBT and vPvB assessment

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with non-hazardous additions.

· Dangerous components:

CAS: 112-34-5 EINECS: 203-961-6 Index number: 603-096-00-8 Reg.nr.: 01-2119475104-44-xxxx	2-(2-butoxyethoxy)ethanol ⚠ Eye Irrit. 2, H319	10%
CAS: 15763-76-5 EINECS: 239-854-6 Reg.nr.: 01-2119489411-37-xxxx	sodium p-cumenesulphonate ⚠ Eye Irrit. 2, H319	1-5%

(Contd. on page 3)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 2)

CAS: 111-76-2 EINECS: 203-905-0 Index number: 603-014-00-0 Reg.nr.: 01-2119475108-36-XXXX	2-butoxyethanol ⚠ Acute Tox. 4, H302; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319 ATE: LD50 oral: 1,200 mg/kg	1-5%
CAS: 1310-73-2 EINECS: 215-185-5 Index number: 011-002-00-6 Reg.nr.: 01-2119457892-27-xxxx	sodium hydroxide ⚠ Met. Corr. 1, H290; Skin Corr. 1A, H314 Specific concentration limits: Skin Corr. 1A; H314: $C \geq 5\%$ Skin Corr. 1B; H314: $2\% \leq C < 5\%$ Skin Irrit. 2; H315: $0.5\% \leq C < 2\%$ Eye Irrit. 2; H319: $0.5\% \leq C < 2\%$	$\geq 0.5\%$ -<2%
CAS: 31726-34-8	hexane-1-ol, ethoxylated (polymer) ⚠ Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302 Specific concentration limits: Eye Dam. 1; H318: $C \geq 15\%$ Eye Irrit. 2; H319: $99\% \leq C < 15\%$	1-5%

Regulation (EC) No 648/2004 on detergents / Labelling for contents

non-ionic surfactants	<5%
perfumes	

Additional information For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

General information

Involve doctor immediately.

Immediately remove any clothing soiled by the product.

After inhalation

In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

After skin contact

Immediately wash with water and soap and rinse thoroughly.

After eye contact

Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing

Rinse out mouth and then drink plenty of water.

Do not induce vomiting; call for medical help immediately.

Drink plenty of water and provide fresh air. Call for a doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

Corneal damage

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

GB

(Contd. on page 4)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776*(Contd. of page 3)***SECTION 5: Firefighting measures**

- **5.1 Extinguishing media**
- **Suitable extinguishing agents**
CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **5.2 Special hazards arising from the substance or mixture** No further relevant information available.
- **5.3 Advice for firefighters**
- **Protective equipment:** Wear fully protective suit.
- **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
Do not allow to penetrate the ground/soil.
- **6.3 Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders).
Use neutralising agent.
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **6.4 Reference to other sections**
See Section 7 for information on safe handling
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
Avoid contact with eyes and skin.
- **Information about fire - and explosion protection:** No special measures required.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage**
- **Requirements to be met by storerooms and receptacles:** Store only in the original receptacle.
- **Information about storage in one common storage facility:**
Do not store together with acids.

(Contd. on page 5)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 4)

Keep away from food, beverages and feed.

· **Further information about storage conditions:** Keep receptacle tightly sealed.

· **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

· 8.1 Control parameters

· Ingredients with limit values that require monitoring at the workplace:

112-34-5 2-(2-butoxyethoxy)ethanol

WEL	Short-term value: 101.2 mg/m ³ , 15 ppm
	Long-term value: 67.5 mg/m ³ , 10 ppm

111-76-2 2-butoxyethanol

WEL	Short-term value: 246 mg/m ³ , 50 ppm
	Long-term value: 123 mg/m ³ , 25 ppm
	Sk, BMGV

1310-73-2 sodium hydroxide

WEL	Short-term value: 2 mg/m ³
-----	---------------------------------------

· DNELs

15763-76-5 sodium p-cumenesulphonate

Oral	DNEL	3.8 mg/kg*d (consumer)
Dermal	DNEL	136.25 mg/kg*d (employee)
		68.1 mg/kg*d (consumer)
Inhalative	DNEL	26.9 mg/m ³ (employee)
		6.6 mg/m ³ (consumer)

1310-73-2 sodium hydroxide

Inhalative	DNEL	1 mg/m ³ (employee)
		1 mg/m ³ (consumer)

· PNECs

15763-76-5 sodium p-cumenesulphonate

PNEC	0.23 mg/l (freshwater)
	0.023 mg/l (marine water)
	100 mg/l (STP)
PNEC sediment	0.862 mg/kg (freshwater)
	0.086 mg/kg (marine water)
PNEC soil	0.037 mg/kg (soil)

· Ingredients with biological limit values:

111-76-2 2-butoxyethanol

BMGV	240 mmol/mol creatinine
	Medium: urine
	Sampling time: post shift
	Parameter: butoxyacetic acid

(Contd. on page 6)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 5)

- **8.2 Exposure controls**
- **Appropriate engineering controls** No further data; see item 7.
- **Individual protection measures, such as personal protective equipment**
- **General protective and hygienic measures**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
Filter A/P2.
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Not necessary if room is well-ventilated.
- **Hand protection**



Protective gloves.

- **Material of gloves** Butyl rubber, BR
- **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **For the permanent contact gloves made of the following materials are suitable:**
* butyl rubber 0,7 mm, 480 min (EN 374)
- **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**
Nitrile rubber, NBR
- **Eye/face protection**



Tightly sealed goggles (EN 166)

- **Body protection:**
Apron
Boots

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
- **General Information**
- **Physical state** Fluid
- **Colour:** Light yellow
- **Odour:** fresh
- **Odour threshold:** Not determined.

(Contd. on page 7)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 6)

· Melting point/freezing point:	-7 °C
· Boiling point or initial boiling point and boiling range	100 °C
· Flammability	Not applicable.
· Lower and upper explosion limit	
· Lower:	Not determined.
· Upper:	Not determined.
· Flash point:	Not applicable
· Ignition temperature:	not applicable
· Decomposition temperature:	Not determined.
· pH at 20 °C	13.2
· pH-value 1 %:	10-11
· Viscosity:	
· Kinematic viscosity	Not determined.
· dynamic at 20 °C:	3 mPas
· Solubility	
· Water:	Fully miscible
· Partition coefficient n-octanol/water (log value)	Not determined.
· Vapour pressure:	Not determined.
· Density and/or relative density	
· Density at 20 °C:	1.063 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.

· 9.2 Other information

· Appearance:	
· Form:	Fluid
· Important information on protection of health and environment, and on safety.	
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Product does not present an explosion hazard.
· Solvent content:	
· Solids content:	19.6 %
· Change in condition	
· Evaporation rate	Not determined.

· Information with regard to physical hazard classes

· Explosives	Void
· Flammable gases	Void
· Aerosols	Void
· Oxidising gases	Void
· Gases under pressure	Void
· Flammable liquids	Void
· Flammable solids	Void
· Self-reactive substances and mixtures	Void
· Pyrophoric liquids	Void
· Pyrophoric solids	Void

(Contd. on page 8)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 7)

- | | |
|---|-----------------------------|
| · Self-heating substances and mixtures | Void |
| · Substances and mixtures, which emit flammable gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | May be corrosive to metals. |
| · Desensitised explosives | Void |

SECTION 10: Stability and reactivity

- **10.1 Reactivity** corresponds to 10.3
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions**
Corrosive action on metals
Reacts with strong acids
Strong exothermic reaction with acids
Reacts with light alloys to form hydrogen
Corrodes aluminium
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** Not compatible with alkali-sensitive substances like Sn, Zn, Al and paintings.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known

SECTION 11: Toxicological information

- **11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**
- **Acute toxicity** Based on available data, the classification criteria are not met.

· LD/LC50 values relevant for classification:

112-34-5 2-(2-butoxyethoxy)ethanol

Dermal	LD50	2,764 mg/kg (Rabbit)
--------	------	----------------------

15763-76-5 sodium p-cumenesulphonate

Oral	LD50	>5,000 mg/kg (Rat) (OECD 401)
------	------	-------------------------------

Dermal	LD50	>2,000 mg/kg (Rabbit)
--------	------	-----------------------

111-76-2 2-butoxyethanol

Oral	LD50	1,200 mg/kg (ATE)
------	------	-------------------

Inhalative	LCLo	>3.1 ppm (consumer)
------------	------	---------------------

(Contd. on page 9)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 8)

31726-34-8 hexane-1-ol, ethoxylated (polymer)

Oral	LD50	>300-2,000 mg/kg (Rat)
------	------	------------------------

- **Skin corrosion/irritation** Causes severe skin burns and eye damage.
- **Serious eye damage/irritation** Causes serious eye damage.
- **Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity** Based on available data, the classification criteria are not met.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure** Based on available data, the classification criteria are not met.
- **STOT-repeated exposure** Based on available data, the classification criteria are not met.
- **Aspiration hazard** Based on available data, the classification criteria are not met.
- **11.2 Information on other hazards**

• Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

• 12.1 Toxicity

• Aquatic toxicity:

112-34-5 2-(2-butoxyethoxy)ethanol

LC50/96 h	1,300 mg/l (Lepomis macrochirus)
EC10/16 h	1,170 mg/l (Pseudomonas putida)
EC50/24 h	2,850 mg/l (Daphnia magna) (DIN 38412)
NOEC	>100 mg/l (Desmodesmus subspicatus)

15763-76-5 sodium p-cumenesulphonate

LC50/96 h (static)	>100 mg/l (Oncorhynchus mykiss)
EC50/48 h (static)	>100 mg/l (Daphnia magna)
EC50/96 h (static)	>100 mg/l (Pseudokirchneriella subcapitata)

111-76-2 2-butoxyethanol

LC50/96 h	1,474 mg/l (Oncorhynchus mykiss) (OECD 203)
EC50/48 h	1,550 mg/l (Daphnia magna) (OECD 202)
EC50/72 h	1,840 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC0 (16 h)	700 mg/l (Pseudomonas putida)
NOEL (21 d)	100 mg/l (Daphnia magna) (OECD 211)
NOEC (static)	286 mg/l /72 h (Pseudokirchneriella subcapitata)

1310-73-2 sodium hydroxide

LC50/96 h	125 mg/l (Gambusia affinis)
EC50/48 h	76 mg/l (Daphnia magna)
	40.4 mg/l (Ceriodaphnia dubia)
EC50/15 min	22 mg/l (Photobacterium phosphoreum)

(Contd. on page 10)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 9)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Endocrine disrupting properties**
The product does not contain substances with endocrine disrupting properties.
- **12.7 Other adverse effects**
- **Additional ecological information:**
- **COD-value:** 468.000 mg/l

· General notes:

The contained organic complexing agents reach a DOC-elimination grade of 80% (corresponding to No. 406 of Annex "Analytic and measuring methods") and with this meet the tightened demands of Annex 49 of the revised Directive on liquid waste.

The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

The product does not contain organically bounded halogens (AOX-free).

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Rinse off of bigger amounts into drains or the aquatic environment may lead to increased pH-values. A high pH-value harms aquatic organisms. In the dilution of the use-level the pH-value is considerably reduced, so that after the use of the product the aqueous waste, emptied into drains, is only low water-dangerous.

SECTION 13: Disposal considerations

· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.
Must be specially treated adhering to official regulations.

· European waste catalogue

20 01 29*	detergents containing hazardous substances
-----------	--

(Contd. on page 11)

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 10)

- **Uncleaned packaging:**
- **Recommendation:**
Packagings that may not be cleansed are to be disposed of in the same manner as the product.
Non contaminated packagings may be recycled.
- **Recommended cleansing agents:** Water, if necessary together with cleaning agents.

SECTION 14: Transport information

· 14.1 UN number or ID number

· ADR, IMDG, IATA UN1824

· 14.2 UN proper shipping name

· ADR 1824 SODIUM HYDROXIDE SOLUTION
· IMDG, IATA SODIUM HYDROXIDE SOLUTION

· 14.3 Transport hazard class(es)

· ADR


· Class 8 (C5) Corrosive substances.
· Label 8

· IMDG, IATA


· Class 8 Corrosive substances.
· Label 8

· 14.4 Packing group

· ADR, IMDG, IATA III

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

· Hazard identification number (Kemler code): 80
· EMS Number: F-A,S-B
· Segregation groups Alkalies
· Stowage Category A
· Segregation Code SG35 Stow "separated from" SGG1-acids

(Contd. on page 12)

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776

(Contd. of page 11)

- | | |
|---|--|
| · 14.7 Maritime transport in bulk according to IMO instruments | Not applicable. |
| · Transport/Additional information: | |
| · ADR | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| · Transport category | 3 |
| · Tunnel restriction code | E |
| · IMDG | |
| · Limited quantities (LQ) | 5L |
| · Excepted quantities (EQ) | Code: E1
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 1000 ml |
| · UN "Model Regulation": | UN 1824 SODIUM HYDROXIDE SOLUTION, 8, III |

SECTION 15: Regulatory information

- **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Directive 2012/18/EU**
- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **National regulations**
- **Information about limitation of use:** Employment restrictions concerning juveniles must be observed.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.
A product information sheet can be provided if requested.

- **Relevant phrases**
- H290 May be corrosive to metals.
- H302 Harmful if swallowed.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.

(Contd. on page 13)

Safety data sheet
according to 1907/2006/EC, Article 31

Printing date 10.06.2022

Version number 7 (replaces version 6)

Revision: 02.11.2021

Trade name: FloorPro Tyre and Abrasion Marks Remover RM 776*(Contd. of page 12)*

H332 Harmful if inhaled.

· **Department issuing SDS:** CSD-D· **Contact:**

Department CSD-D

Tel.: +49-7195-14-0

productsafety.management@de.kaercher.com

· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (GB REACH)

PNEC: Predicted No-Effect Concentration (GB REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Met. Corr. 1: Corrosive to metals – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1: Skin corrosion/irritation – Category 1

Skin Corr. 1A: Skin corrosion/irritation – Category 1A

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

· **Sources**· *** Data compared to the previous version altered.**

· 0-011-343-0

RM776/4

2-462