

according to 1907/2006/EC, Article 31

Page 1/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: CERAMIC SERIES Ceramic Coating
- · UFI: 55N2-J09X-J00S-V3V6
- 1.2 Relevant identified uses of the substance or mixture and uses advised against
- · Sector of Use

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

- · Application of the substance / the mixture Surface active agent
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

Dursol-Fabrik Otto Durst GmbH & Co. KG

Martinstr. 22 42655 SOLINGEN

Germany

Tel.: +49 (0)212 - 2718-0 Fax: +49 (0)212 - 208795

www.autosol.de

· Further information obtainable from:

Department Product Safety

labor@autosol.de

· 1.4 Emergency telephone number:

+49 (0) 212 - 2718-0

Only available during the following office hours: Mo-Fr; 08:00 -16:00 h (MEZ/MESZ)

Languages of the phone service: German & English

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008



Flam. Liq. 3 H226 Flammable liquid and vapour.



Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

(Contd. on page 2)



according to 1907/2006/EC, Article 31

Page 2/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 1)



Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms









GHS02 GHS05 GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

organic polysilazane compound

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics 3-aminopropyltriethoxysilane

Hazard statements

H226 Flammable liquid and vapour.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P321 Specific treatment (see on this label).

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water [or shower].

IF IN EYES: Rinse cautiously with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P362+P364 Take off contaminated clothing and wash it before reuse.

· Additional information:

Keep out of reach of children.

EUH066 Repeated exposure may cause skin dryness or cracking.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

(Contd. on page 3)



according to 1907/2006/EC, Article 31

Page 3/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 2)

· vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

· 3.2 Mixtures

· **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|--|--|---------|
| EC number: 918-481-9 Reg.nr.: 01-2119457273-39-xxxx | Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% | 25-<50% |
| C | aromatics | - |
| | 🕸 Asp. Tox. 1, H304, EUH066 | |
| CAS: 123-86-4 | n-butyl acetate | 25-<50% |
| EINECS: 204-658-1 | ♦ Flam. Liq. 3, H226; ♦ STOT SE 3, H336, EUH066 | - |
| EC number: 927-241-2 | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% | 25-<50% |
| Reg.nr.: 01-2119471843-32-xxxx | aromatics | |
| • | ♦ Flam. Liq. 3, H226; ♦ Asp. Tox. 1, H304; ♦ STOT SE 3, H336; Aquatic Chronic 3, H412, EUH066 | |
| CAS: 475645-84-2 | organic polysilazane compound | 10-<25% |
| | ♦ Flam. Liq. 2, H225; ♦ Skin Corr. 1B, H314; ♦ Acute Tox. 4, H302; Aquatic Chronic 3, H412 | |
| CAS: 919-30-2 | 3-aminopropyltriethoxysilane | 1-<10% |
| EINECS: 213-048-4 | ♦ Skin Corr. 1B, H314; Eye Dam. 1, H318; ♦ Acute Tox. 4, H302; Skin Sens. 1, H317 | |
| Regulation (EC) No 648/2004 on detergents / Labelling for contents | | |
| aliphatic hydrocarbons | | ≥30% |

· Additional information: For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- General information: Immediately remove any clothing soiled by the product.
- · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

· 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

– GB —



according to 1907/2006/EC, Article 31

Page 4/11

Printing date 12.01.2023

Revision: 12.01.2023 Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 3)

SECTION 5: Firefighting measures

- 5.1 Extinguishing media
- Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.
- · Additional information Cool endangered receptacles with water spray.

SECTION 6: Accidental release measures

· 6.1 Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Prevent seepage into sewage system, workpits and cellars.

Inform respective authorities in case of seepage into water course or sewage system.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep container tightly sealed.
- · Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

- GB -



according to 1907/2006/EC, Article 31

Page 5/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 4)

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

123-86-4 n-butyl acetate

WEL Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Appropriate engineering controls No further data; see item 7.
- Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Hand protection



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.5 \text{ mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 16523-1:2015: Level 6).

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)



according to 1907/2006/EC, Article 31

Page 6/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 5)

· Eye/face protection



Tightly sealed goggles

SECTION 9: Physical and chemical properties

· 9.1 Information on basic physical and chemical properties

· General Information

Colour:
 Odour:
 Odour threshold:
 Melting point/freezing point:
 Colourless

 Characteristic
 Not determined.

 Undetermined.

· Boiling point or initial boiling point and boiling

range Undetermined. • Flammability Not applicable.

· Lower and upper explosion limit

Lower: Not determined.Upper: Not determined.

Flash point: 27 °C

Decomposition temperature: Not determined.pH Not determined.

· Viscosity:

Kinematic viscosityDynamic:Not determined.Not determined.

· Solubility

· water: Not miscible or difficult to mix.

Partition coefficient n-octanol/water (log value)
 Vapour pressure:
 Not determined.

Density and/or relative density

Density: Not determined.
Relative density Not determined.
Vapour density Not determined.

· 9.2 Other information

· Appearance:

Form: Fluid

Important information on protection of health and environment, and on safety.

• Auto-ignition temperature: Product is not selfigniting.

• Explosive properties: Product is not explosive. However, formation of

explosive air/vapour mixtures are possible.

· Change in condition

• Evaporation rate Not determined.

(Contd. on page 7)



according to 1907/2006/EC, Article 31

Page 7/11

Printing date 12.01.2023

Revision: 12.01.2023 Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 6)

| | | (Oonta. or page o |
|--|-------|-------------------|
| Information with regard to physical hazard classes | | |
| Explosives | Void | |
| · Flammable gases | Void | |
| · Aerosols | Void | |
| · Oxidising gases | Void | |
| · Gases under pressure | Void | |
| Flammable liquids | | |
| Flammable liquid and vapour. | | |
| Flammable solids | Void | |
| · Self-reactive substances and mixtures | Void | |
| · Pyrophoric liquids | Void | |
| Pyrophoric solids | Void | |
| Self-heating substances and mixtures | Void | |
| Substances and mixtures, which emit flammer | nable | |
| gases in contact with water | Void | |
| · Oxidising liquids | Void | |
| Oxidising solids | Void | |
| Organic peroxides | Void | |
| Corrosive to metals | Void | |
| · Desensitised explosives | Void | |

SECTION 10: Stability and reactivity

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC50 values relevant for classification: | | | | |
|---|---|-----------------------|--|--|
| Hydrocar | Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics | | | |
| Oral | LD50 | >5,000 mg/kg (rat) | | |
| Dermal | LD50 | >5,000 mg/kg (rabbit) | | |
| Inhalative | LC50 (4 h) | >4,951 mg/l (rat) | | |

(Contd. on page 8)



according to 1907/2006/EC, Article 31

Page 8/11

Printing date 12.01.2023

Revision: 12.01.2023 Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 7)

| | | Conta. or page 7 | |
|--------------------------------|---------------------------------------|----------------------|--|
| 123-86-4 ו | 123-86-4 n-butyl acetate | | |
| Oral LD50 13,100 mg/kg (rat) | | 13,100 mg/kg (rat) | |
| Dermal | Dermal LD50 >5,000 mg/kg (rabbit) | | |
| Inhalative | Inhalative LC50 (4 h) >21 mg/l (rat) | | |
| 919-30-2 | 919-30-2 3-aminopropyltriethoxysilane | | |
| Oral | LD50 | 1,780 mg/kg (rat) | |
| Dermal | LD50 | 4,000 mg/kg (rabbit) | |

· Skin corrosion/irritation

Causes severe skin burns and eye damage.

· Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

May cause an allergic skin reaction.

- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure

May cause drowsiness or dizziness.

- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- Aspiration hazard

May be fatal if swallowed and enters airways.

· 11.2 Information on other hazards

| • | Endocrine | disrupting | properties |
|---|-------------|-------------|------------|
| | None of the | ingradiants | ie lietad |

None of the ingredients is listed.

SECTION 12: Ecological information

- · 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Endocrine disrupting properties For information on endocrine disrupting properties see section 11.
- 12.7 Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Harmful to aquatic organisms

– GB –



according to 1907/2006/EC, Article 31

Page 9/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 8)

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

| SECTION 14: Transport informa | tion |
|--|--|
| · 14.1 UN number or ID number · ADR, IMDG, IATA | UN2920 |
| · 14.2 UN proper shipping name · ADR | 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (organic polysilazane compound, BUTYL ACETATES) |
| · IMDG, IATA | CORROSIVE LIQUID, FLAMMABLE, N.O.S. (organic polysilazane compound, BUTYL ACETATES) |
| · 14.3 Transport hazard class(es) | |
| · ADR | |
| | |
| · Class · Label | 8 Corrosive substances. 8+3 |
| · IMDG | 0+3 |
| INDG | |
| · Class | 8 Corrosive substances. |
| Label | 8/3 |
| ·IATA | |
| · Class · Label | 8 Corrosive substances. 8 (3) |

(Contd. on page 10)



according to 1907/2006/EC, Article 31

Page 10/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 9)

| | (Contd. of page 9 |
|---|---|
| · 14.4 Packing group · ADR, IMDG, IATA | II |
| · 14.5 Environmental hazards: | Not applicable. |
| · 14.6 Special precautions for user · Hazard identification number (Kemler code): · EMS Number: · Stowage Category · Stowage Code | Warning: Corrosive substances. 883 F-E,S-C E SW1 Protected from sources of heat. SW2 Clear of living quarters. |
| · 14.7 Maritime transport in bulk according to IM instruments | O Not applicable. |
| · Transport/Additional information: | |
| · ADR · Limited quantities (LQ) · Excepted quantities (EQ) | 1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml |
| Transport category Tunnel restriction code | 2 D/E |
| · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) | 0 Code: E0 Not permitted as Excepted Quantity |
| · UN "Model Regulation": | UN 2920 CORROSIVE LIQUID, FLAMMABLE, N.O.S. (ORGANIC POLYSILAZANE COMPOUND, BUTYL ACETATES), 8 (3), II |

SECTION 15: Regulatory information

- · 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5.000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50.000 t
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

(Contd. on page 11)



according to 1907/2006/EC, Article 31

Page 11/11

Printing date 12.01.2023

Revision: 12.01.2023

Version number 4 (replaces version 3)

Trade name: CERAMIC SERIES - Ceramic Coating

(Contd. of page 10)

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

Harmful if swallowed. H302

H304 May be fatal if swallowed and enters airways.

Causes severe skin burns and eye damage. H314

May cause an allergic skin reaction. H317

Causes serious eye damage. H318

May cause drowsiness or dizziness. H336

H412 Harmful to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Department issuing SDS:

Dursol-Fabrik Otto Durst GmbH & Co. KG

Martinstraße 22

42655 Solingen

Germany

Abteilung F&E / Produktsicherheit

Contact: labor@autosol.de

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.