



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Valvoline™ COOLING SYSTEM STOP LEAK

Product code : 890603

Unique Formula Identifier (UFI) : 90SC-4S9H-K00X-JRTW

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Additive

1.3 Details of the supplier of the safety data sheet

Company : Ellis Enterprises B.V., an affiliate of Valvoline
Wieldrechtseweg 39
3316 BG Dordrecht
Netherlands

Telephone : +31 (0)78 654 3500 (in the Netherlands), or contact your local CSR contact person

E-mail address of person responsible for the SDS : SDS@valvoline.com

1.4 Emergency telephone number

00-800-825-8654 / 001-859-202-3865, or contact your local emergency telephone number at 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Acute toxicity, Category 4 H302: Harmful if swallowed.

Specific target organ toxicity - repeated H373: May cause damage to organs through



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

exposure, Category 2, Kidney, Liver

prolonged or repeated exposure if swallowed.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms

:



Signal word

:

Warning

Hazard statements

:

H302 Harmful if swallowed.
H373 May cause damage to organs (Kidney, Liver) through prolonged or repeated exposure if swallowed.

Precautionary statements

:

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.

Prevention:

P260 Do not breathe mist or vapours.
P264 Wash skin thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Hazardous components which must be listed on the label:

ETHYLENE GLYCOL

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No.	Classification	Concentration (% w/w)
---------------	-------------------	----------------	--------------------------



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

	Index-No. Registration number		
ETHYLENE GLYCOL	107-21-1 203-473-3 603-027-00-1 01-2119456816-28- xxxx	Acute Tox. 4; H302 STOT RE 2; H373 (Kidney)	>= 15 - < 25
MORPHOLINE	110-91-8 203-815-1 613-028-00-9 01-2119496057-30- xxxx	Flam. Liq. 3; H226 Acute Tox. 4; H302 Acute Tox. 3; H331 Acute Tox. 3; H311 Skin Corr. 1B; H314 Eye Dam. 1; H318	>= 0.5 - < 1

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- General advice : Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
- Induce vomiting immediately and call a physician.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : No symptoms known or expected.
- Risks : May cause damage to organs through prolonged or repeated exposure if swallowed.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : No hazards which require special first aid measures.

Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products : carbon dioxide and carbon monoxide

5.3 Advice for firefighters

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

Further information : Standard procedure for chemical fires.
Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Refer to protective measures listed in sections 7 and 8.
Use personal protective equipment.

6.2 Environmental precautions

Environmental precautions : Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Wipe up with absorbent material (e.g. cloth, fleece).
Keep in suitable, closed containers for disposal.

6.4 Reference to other sections

See sections: 7, 8, 11, 12 and 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Hygiene measures : When using do not eat or drink. When using do not smoke.
Wash hands before breaks and at the end of workday.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep container tightly closed in a dry and well-ventilated place. Electrical installations / working materials must comply with the technological safety standards.

Further information on storage stability : No decomposition if stored and applied as directed.

7.3 Specific end use(s)

Specific use(s) : No data available

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
ETHYLENE	107-21-1	TWA (Vapour)	20 ppm	GB EH40



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

GLYCOL			52 mg/m3	
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA (particles)	10 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL (Vapour)	40 ppm 104 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	20 ppm 52 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	40 ppm 104 mg/m3	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
MORPHOLINE	110-91-8	TWA	10 ppm 36 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	20 ppm 72 mg/m3	GB EH40
	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	10 ppm 36 mg/m3	2006/15/EC
	Further information: Indicative			
		STEL	20 ppm 72 mg/m3	2006/15/EC
	Further information: Indicative			

8.2 Exposure controls

Personal protective equipment

Eye/face protection : Eye wash bottle with pure water
Tightly fitting safety goggles

Hand protection

Remarks : The suitability for a specific workplace should be discussed



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

with the producers of the protective gloves.

- | | | |
|--------------------------|---|---------------------------------------------------------------------------------------------------------------------------------------|
| Skin and body protection | : | Impervious clothing
Choose body protection according to the amount and concentration of the dangerous substance at the work place. |
| Respiratory protection | : | No personal respiratory protective equipment normally required. |

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | | |
|--------------------------------------------------|---|-------------------|
| Appearance | : | liquid |
| Colour | : | green |
| Odour | : | citrus |
| Odour Threshold | : | No data available |
| pH | : | 9.5 (20 °C) |
| Melting point/freezing point | : | No data available |
| Initial boiling point and boiling range | : | 100 °C |
| Flash point | : | > 100 °C |
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | No data available |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

Density : 1.02 g/cm³ (20 °C)

Solubility(ies)

Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : No data available

Oxidizing properties : No data available

9.2 Other information

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No decomposition if stored and applied as directed.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Hazardous reactions : No decomposition if stored and applied as directed.

10.4 Conditions to avoid

Conditions to avoid : excessive heat

10.5 Incompatible materials

Materials to avoid : Aldehydes
Alkali metals
Alkaline earth metals
Strong acids
strong alkalis
Strong oxidizing agents



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

Sulphur compounds

10.6 Hazardous decomposition products

No hazardous decomposition products are known.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity	:	Acute toxicity estimate: 500 mg/kg Method: Calculation method
Acute inhalation toxicity	:	Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method
Acute dermal toxicity	:	Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method

Components:

ETHYLENE GLYCOL:

Acute oral toxicity	:	LD ₀ (Human): estimated 1.56 g/kg Assessment: The component/mixture is moderately toxic after single ingestion.
Acute inhalation toxicity	:	LC ₅₀ (Rat): 10.9 mg/l Exposure time: 1 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acute dermal toxicity	:	LD ₅₀ (Rabbit): 9,530 mg/kg
Acute toxicity (other routes of administration)	:	LD ₅₀ (Rat): 5,010 mg/kg Application Route: Intraperitoneal LD ₅₀ (Rat): 3,260 mg/kg Application Route: Intravenous



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

MORPHOLINE:

Acute oral toxicity	:	LD50 (Rat): ca. 1,900 mg/kg Method: OECD Test Guideline 401
Acute inhalation toxicity	:	Test atmosphere: vapour Assessment: The component/mixture is toxic after short term inhalation.
Acute dermal toxicity	:	LD50 (Rabbit): ca. 500 mg/kg

Skin corrosion/irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Species	:	Rabbit
Result	:	No skin irritation

MORPHOLINE:

Species	:	Rabbit
Method	:	OECD Test Guideline 404
Result	:	Corrosive after 3 minutes or less of exposure

Serious eye damage/eye irritation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Result	:	Slight, transient irritation
--------	---	------------------------------

MORPHOLINE:

Species	:	Rabbit
Method	:	OECD Test Guideline 405
Result	:	Corrosive

Respiratory or skin sensitisation

Skin sensitisation

Not classified based on available information.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

Respiratory sensitisation

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Test Type	:	Maximisation Test
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Genotoxicity in vitro	:	Test Type: Ames test
		Test system: Salmonella typhimurium
		Metabolic activation: with and without metabolic activation
		Result: negative

MORPHOLINE:

Genotoxicity in vitro	:	Test Type: unscheduled DNA synthesis assay
		Test system: rat hepatocytes
		Metabolic activation: without metabolic activation
		Method: OECD Test Guideline 482
		Result: negative
		Test Type: In vitro mammalian cell gene mutation test
		Test system: mouse lymphoma cells
		Metabolic activation: without metabolic activation
		Method: OECD Test Guideline 476
		Result: positive

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

May cause damage to organs (Kidney) through prolonged or repeated exposure if swallowed.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

Components:

ETHYLENE GLYCOL:

Exposure routes	:	Ingestion
Target Organs	:	Kidney, Liver
Assessment	:	May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Not classified based on available information.

Experience with human exposure

Components:

ETHYLENE GLYCOL:

Ingestion	:	Target Organs: Kidney
-----------	---	-----------------------

Further information

Product:

Remarks : No data available

SECTION 12: Ecological information

12.1 Toxicity

Product:

Ecotoxicology Assessment

Acute aquatic toxicity : Not classified based on available information.

Chronic aquatic toxicity : Not classified based on available information.

Components:

ETHYLENE GLYCOL:

Toxicity to fish	:	LC50 (<i>Lepomis macrochirus</i> (Bluegill sunfish)): 27,540 mg/l Exposure time: 96 h Test Type: static test LC50 (<i>Pimephales promelas</i> (fathead minnow)): 8,050 mg/l Exposure time: 96 h
Toxicity to daphnia and other	:	LC50 (<i>Daphnia magna</i> (Water flea)): > 10,000 mg/l



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

aquatic invertebrates	Exposure time: 48 h Test Type: static test
Toxicity to algae/aquatic plants	: EC50 (Pseudokirchneriella subcapitata (green algae)): 6,500 - 13,000 mg/l End point: Growth inhibition Exposure time: 7 Days
Toxicity to fish (Chronic toxicity)	: NOEC: 32,000 mg/l Exposure time: 7 d Species: Pimephales promelas (fathead minnow)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 24,000 mg/l Exposure time: 7 d Species: Daphnia magna (Water flea)

Ecotoxicology Assessment

Acute aquatic toxicity	: Not classified based on available information.
Chronic aquatic toxicity	: Not classified based on available information.

MORPHOLINE:

Toxicity to fish	: LC50 (Oncorhynchus mykiss (rainbow trout)): 380 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	: EC50 (Daphnia magna (Water flea)): 45 mg/l Exposure time: 48 h Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	: ErC50 (Pseudokirchneriella subcapitata (green algae)): 28 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	: NOEC: 5 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: semi-static test Method: OECD Test Guideline 211

Ecotoxicology Assessment

Acute aquatic toxicity	: Acute aquatic toxicity Category 3; Harmful to aquatic life.
Chronic aquatic toxicity	: Not classified based on available information.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

12.2 Persistence and degradability

Components:

ETHYLENE GLYCOL:

Biodegradability : Result: **Readily biodegradable.**
Biodegradation: **90 - 100 %**
Exposure time: **10 d**
Method: **OECD Test Guideline 301**

MORPHOLINE:

Biodegradability : Result: **Readily biodegradable.**
Biodegradation: **92.6 %**
Exposure time: **22 d**
Method: **OECD Test Guideline 301E**

12.3 Bioaccumulative potential

Components:

ETHYLENE GLYCOL:

Bioaccumulation : Species: **Crayfish (Procambarus)**
Exposure time: **61 d**
Concentration: **1000 mg/l**
Bioconcentration factor (BCF): **0.27**
Method: **Flow through**

Partition coefficient: n-octanol/water : log Pow: **-1.36**

MORPHOLINE:

Partition coefficient: n-octanol/water : log Pow: **-0.86**

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

12.6 Other adverse effects

Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No data available

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of waste into sewer.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14: Transport information

14.1 UN number

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good

14.2 UN proper shipping name

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

14.3 Transport hazard class(es)

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA_P	:	Not regulated as a dangerous good

14.4 Packing group

ADR	:	Not regulated as a dangerous good
RID	:	Not regulated as a dangerous good
IMDG	:	Not regulated as a dangerous good
IATA (Cargo)	:	Not regulated as a dangerous good
IATA_P (Passenger)	:	Not regulated as a dangerous good

14.5 Environmental hazards

Not regulated as a dangerous good

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable for product as supplied.

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation	:	Not applicable
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain)	:	Not applicable
Regulation (EC) No 1005/2009 on substances that	:	Not applicable



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

deplete the ozone layer

UK REACH List of substances subject to authorisation : Not applicable
(Annex XIV)

Control of Major Accident Hazards Regulations : Not applicable
2015 (COMAH)

Other regulations:

The components of this product are reported in the following inventories:

TCSI	: Not in compliance with the inventory
TSCA	: Product contains substance(s) not listed on TSCA inventory.
AIIC	: Not in compliance with the inventory
DSL	: This product contains the following components that are not on the Canadian DSL nor NDSL. Proprietary of COOLING SYSTEM STOP LEAK (000000272892)
ENCS	: Not in compliance with the inventory
KECI	: Not in compliance with the inventory
PICCS	: Not in compliance with the inventory
IECSC	: Not in compliance with the inventory
NZIoC	: Not in compliance with the inventory

15.2 Chemical safety assessment

No data available

Inventories

AIIC (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TECI (Thailand), TSCA (USA)

SECTION 16: Other information

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

- H314 : Causes severe skin burns and eye damage.
- H318 : Causes serious eye damage.
- H331 : Toxic if inhaled.
- H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.

Full text of other abbreviations

- Acute Tox. : Acute toxicity
- Eye Dam. : Serious eye damage
- Flam. Liq. : Flammable liquids
- Skin Corr. : Skin corrosion
- STOT RE : Specific target organ toxicity - repeated exposure
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- 2006/15/EC : Europe. Indicative occupational exposure limit values
- GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- 2006/15/EC / TWA : Limit Value - eight hours
- 2006/15/EC / STEL : Short term exposure limit
- GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
- GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration,



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006
Valvoline™ COOLING SYSTEM STOP LEAK

Version: 2.0

Revision Date: 13.02.2023

Print Date: 23/06/2023

Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Internal information : 000000272892

Classification of the mixture:

STOT RE 2

H373

Classification procedure:

Calculation method

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

GB / EN