



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

TEROSON MS 9320SF GY

SDS No. : 634030
V007.0

Revision: 02.11.2022

printing date: 24.10.2023

Replaces version from: 14.06.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON MS 9320SF GY

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:
MS Sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd
Adhesives
Wood Lane End
HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

ua-productsafety.uk@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Supplemental information

Contains: Trimethoxyvinylsilane May produce an allergic reaction.
Safety data sheet available on request.
Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

2.3. Other hazards

None if used properly.

Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

Following substances are present in a concentration $\geq 0,1\%$ and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in concentration $\geq$ the concentration limit that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Titanium dioxide < 1% particles with diameter $\leq 10 \mu\text{m}$ 13463-67-7 236-675-5 01-2119489379-17	1- < 3 %			
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9 258-207-9 01-2119537297-32	0,1- < 1 %	Repr. 2, H361f Eye Dam. 1, H318 Aquatic Chronic 2, H411 Aquatic Acute 1, H400	M acute = 1	
Trimethoxyvinylsilane 2768-02-7 220-449-8 01-2119513215-52	0,1- < 1 %	Flam. Liq. 3, H226 Acute Tox. 4, Inhalation, H332 STOT RE 2, H373 Skin Sens. 1B, H317		

For full text of the H - statements and other abbreviations see section 16 "Other information".

Substances without classification may have community workplace exposure limits available.

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing. If necessary, see a dermatologist.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

An allergic reaction cannot be excluded after repeated skin contact.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media:**

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Temperatures between + 10 °C and + 25 °C

7.3. Specific end use(s)

MS Sealant

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for
Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [Dust, inhalable dust]		10	Time Weighted Average (TWA):		EH40 WEL
Calcium carbonate 471-34-1 [Dust, respirable dust]		4	Time Weighted Average (TWA):		EH40 WEL
Di-"isononyl" phthalate 28553-12-0 [Diisononyl phthalate]		5	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [Titanium dioxide, total inhalable]		10	Time Weighted Average (TWA):		EH40 WEL
Titanium dioxide 13463-67-7 [Titanium dioxide, respirable]		4	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate		4	Time Weighted Average		IR_OEL

471-34-1 [CALCIUM CARBONATE]			(TWA):		
Calcium carbonate 471-34-1 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]		4	Time Weighted Average (TWA):		IR_OEL
Calcium carbonate 471-34-1 [DUSTS NON-SPECIFIC]		10	Time Weighted Average (TWA):		IR_OEL
Di-"isononyl" phthalate 28553-12-0 [Diisononyl phthalate]		5	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [Titanium dioxide]		4	Time Weighted Average (TWA):		IR_OEL
Titanium dioxide 13463-67-7 [Titanium dioxide]		10	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	aqua (freshwater)		0,004 mg/l				
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	aqua (marine water)		0,00038 mg/l				
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	Freshwater - intermittent		0,007 mg/l				
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	sediment (freshwater)				5,9 mg/kg		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	sediment (marine water)				0,59 mg/kg		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	Soil				1,18 mg/kg		
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	sewage treatment plant (STP)		1 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (freshwater)		0,4 mg/l				
Trimethoxyvinylsilane 2768-02-7	aqua (marine water)		0,04 mg/l				
Trimethoxyvinylsilane 2768-02-7	Freshwater - intermittent		1,21 mg/l				
Trimethoxyvinylsilane 2768-02-7	sediment (freshwater)				1,5 mg/kg		
Trimethoxyvinylsilane 2768-02-7	sediment (marine water)				0,15 mg/kg		
Trimethoxyvinylsilane 2768-02-7	Soil				0,06 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	Workers	dermal	Long term exposure - systemic effects		1,8 mg/kg	
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	Workers	Inhalation	Long term exposure - systemic effects		1,27 mg/m3	
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	General population	Inhalation	Long term exposure - systemic effects		0,31 mg/m3	
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	General population	dermal	Long term exposure - systemic effects		0,9 mg/kg	
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	General population	oral	Long term exposure - systemic effects		0,18 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	dermal	Long term exposure - systemic effects		0,91 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	inhalation	Long term exposure - systemic effects		27,6 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	dermal	Long term exposure - systemic effects		0,63 mg/kg	
Trimethoxyvinylsilane 2768-02-7	General population	inhalation	Long term exposure - systemic effects		6,8 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	oral	Long term exposure - systemic effects		0,63 mg/kg	
Trimethoxyvinylsilane 2768-02-7	Workers	inhalation	Acute/short term exposure - systemic effects		73,6 mg/m3	
Trimethoxyvinylsilane 2768-02-7	General population	inhalation	Acute/short term exposure - systemic effects		54,4 mg/m3	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

The product should only be used at workplaces with intensive ventilation/extraction.

Hand protection:

Chemical-resistant protective gloves (EN 374). Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >=1 mm thickness) Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374): Polychloroprene (CR; >= 1 mm thickness) or natural rubber (NR; >=1 mm thickness) This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	solid
Delivery form	paste
Colour	grey
Odor	alcohol-like
Melting point	Not applicable, Determination technically not possible
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	> 300 °C (> 572 °F)
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	Not applicable, Product is a solid.
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product reacts with water.
Viscosity (kinematic)	Not applicable, Product is a solid.
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	Reacts with water.
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure (20 °C (68 °F))	Mixture < 0,1 hPa
Density (20 °C (68 °F))	1,54 g/cm3 no method
Bulk density	1,54 g/cm3
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information**General toxicological information:**

An allergic reaction cannot be excluded after repeated skin contact.

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute oral toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LD50	> 5.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	LD50	3.700 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Trimethoxyvinylsilane 2768-02-7	LD50	7.120 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LD50	≥ 10.000 mg/kg	hamster	not specified
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	LD50	> 3.170 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Trimethoxyvinylsilane 2768-02-7	LD50	3.200 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LC50	> 6,82 mg/l	dust	4 h	rat	not specified
Trimethoxyvinylsilane 2768-02-7	LC50	16,8 mg/l	vapour	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	not irritating	24 h	rabbit	EPA OPP 81-5 (Acute Dermal Irritation)
Trimethoxyvinylsilane 2768-02-7	not irritating		rabbit	other guideline:

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	corrosive	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Trimethoxyvinylsilane 2768-02-7	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not sensitising	Mouse local lymphnode assay (LLNA)	mouse	equivalent or similar to OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Trimethoxyvinylsilane 2768-02-7	sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Trimethoxyvinylsilane 2768-02-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Trimethoxyvinylsilane 2768-02-7	positive	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
Trimethoxyvinylsilane 2768-02-7	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Trimethoxyvinylsilane 2768-02-7	negative	intraperitoneal		mouse	other guideline:

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	not carcinogenic	inhalation	24 m 6 h/d; 5 d/w	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOAEL P > 1.000 mg/kg NOAEL F1 > 1.000 mg/kg		oral: gavage	rat	OECD Guideline 421 (Reproduction / Developmental Toxicity Screening Test)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	NOAEL P 109 mg/kg NOAEL F1 121 mg/kg	two- generation study	oral: feed	rat	OECD Guideline 443 (Extended One-Generation Reproductive Toxicity Study)
Trimethoxyvinylsilane 2768-02-7	NOAEL P 250 mg/kg	one- generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Trimethoxyvinylsilane 2768-02-7	NOAEL P 1.000 mg/kg	one- generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)
Trimethoxyvinylsilane 2768-02-7	NOAEL F1 1.000 mg/kg	one- generation study	oral: gavage	rat	OECD Combined Repeated Dose and Reproductive / Developmental Toxicity Screening Test (Precursor Protocol of GL 422)

STOT-single exposure:

No data available.

STOT-repeated exposure::

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOAEL 1.000 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	NOAEL 36 mg/kg	oral: feed	daily	rat	other guideline:
Trimethoxyvinylsilane 2768-02-7	NOAEL < 62,5 mg/kg	oral: gavage	42d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Trimethoxyvinylsilane 2768-02-7	NOAEL 0,605 mg/l	inhalation: vapour	5 days/week for 14 weeks 6 hours/day	rat	not specified

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	LC50	Toxicity > Water solubility	48 h	Danio rerio	other guideline:
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOEC	Toxicity > Water solubility	8 d	Danio rerio	OECD Guideline 212 (Fish, Short-term Toxicity Test on Embryo and Sac-Fry Stages)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	LC50	4,4 mg/l	96 h	Lepomis macrochirus	OECD Guideline 203 (Fish, Acute Toxicity Test)
Trimethoxyvinylsilane 2768-02-7	LC50	191 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

Toxicity (Daphnia):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	EC50	Toxicity > Water solubility	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	EC50	8,58 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Trimethoxyvinylsilane 2768-02-7	EC50	168,7 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)

Chronic toxicity to aquatic invertebrates

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	NOEC	0,23 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Trimethoxyvinylsilane 2768-02-7	NOEC	28,1 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	EC50	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	NOEC	Toxicity > Water solubility	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	EC50	0,705 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	EC10	0,188 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Trimethoxyvinylsilane 2768-02-7	EC50	> 957 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)
Trimethoxyvinylsilane 2768-02-7	NOEC	957 mg/l	72 h	Desmodesmus subspicatus	EU Method C.3 (Algal Inhibition test)

Toxicity to microorganisms

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	EC50	Toxicity > Water solubility	3 h	activated sludge	ISO 8192 (Test for Inhibition of Oxygen Consumption by Activated Sludge)
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	EC50	> 100 mg/l	3 h	activated sludge, domestic	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
Trimethoxyvinylsilane 2768-02-7	EC50	> 100 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

12.2. Persistence and degradability

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Bis(2,2,6,6-tetramethyl-4- piperidyl) sebacate 52829-07-9	not readily biodegradable.	aerobic	24 %	28 d	OECD Guideline 301 B (Ready Biodegradability: CO2 Evolution Test)
Trimethoxyvinylsilane 2768-02-7	not readily biodegradable.	aerobic	51 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

Hazardous substances CAS-No.	LogPow	Temperature	Method
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	0,35	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

Hazardous substances CAS-No.	PBT / vPvB
Titanium dioxide < 1% particles with diameter ≤ 10 µm 13463-67-7	According to Annex XIII of regulation (EC) 1907/2006 a PBT and vPvB assessment shall not be conducted for inorganic substances.
Bis(2,2,6,6-tetramethyl-4-piperidyl) sebacate 52829-07-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Trimethoxyvinylsilane 2768-02-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

SECTION 14: Transport information**14.1. UN number or ID number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content 5,9 %
(2010/75/EU)

15.2. Chemical safety assessment

A chemical safety assessment has been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H332 Harmful if inhaled.
H361f Suspected of damaging fertility.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.