

Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

SDS No.: 647007

V003.1 Revision: 22.06.2023

printing date: 15.01.2024

Replaces version from: 13.06.2023

TEROSON EP 5020 TR KOMP. A

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON EP 5020 TR KOMP. A

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

2-Component epoxy adhesive

1.3. Details of the supplier of the safety data sheet

Henkel Ltd Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

For Safety Data Sheet updates please visit our website https://mysds.henkel.com/index.html#/appSelection or www.henkel-adhesives.com.

SDSinfo.Adhesive@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

Skin irritation Category 2

H315 Causes skin irritation.

Serious eye irritation Category 2

H319 Causes serious eye irritation.

Skin sensitizer Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment Category 2

H411 Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements (CLP):

Hazard pictogram:



Contains Bisphenol A Diglycidyl Ether

oxirane, mono[(C12-14-alkyloxy)methyl] derivs.

Signal word: Warning

Hazard statement: H315 Causes skin irritation.

H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statement: P273 Avoid release to the environment. **Prevention** P280 Wear protective gloves/eye protection.

2.3. Other hazards

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M- factors and ATEs	Add. Information
Bisphenol A Diglycidyl Ether 1675-54-3 216-823-5 01-2119456619-26	40- 60 %	Eye Irrit. 2, H319 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411	Eye Irrit. 2; H319; C >= 5 % Skin Irrit. 2; H315; C >= 5 %	
oxirane, mono[(C12-14- alkyloxy)methyl] derivs. 68609-97-2 271-846-8 01-2119485289-22	5- < 10 %	Skin Irrit. 2, H315 Skin Sens. 1, H317		
Oxirane, 2-[[3- (trimethoxysilyl)propoxy]methyl]-, homopolymer 56325-93-0	1- < 3 %	Eye Dam. 1, H318 Aquatic Chronic 3, H412	inhalation:ATE = 12,5 mg/l;dust/mist	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11. For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures

4.1. Description of first aid measures

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

IF ON SKIN: Wash with plenty of soap and water. In case of adverse health effects seek medical advice.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear self-contained breathing apparatus.

Wear protective equipment.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

Avoid contact with skin and eyes.

Keep unprotected persons away.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

Inform authorities in the event of product spillage to water courses or sewage systems.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Take off contaminated clothing and wash before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

7.3. Specific end use(s)

2-Component epoxy adhesive

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational Exposure Limits

Valid for

Great Britain

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Limestone 1317-65-3 [CALCIUM CARBONATE, INHALABLE DUST]		10	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [CALCIUM CARBONATE, RESPIRABLE DUST]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, RESPIRABLE MARBLE, RESPIRABLE]		4	Time Weighted Average (TWA):		EH40 WEL
Limestone 1317-65-3 [LIMESTONE, TOTAL INHALABLE MARBLE, TOTAL INHALABLE]		10	Time Weighted Average (TWA):		EH40 WEL

Occupational Exposure Limits

Valid for

Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit	Regulatory list
				category / Remarks	
Limestone 1317-65-3 [CALCIUM CARBONATE]		4	Time Weighted Average (TWA):		IR_OEL
Limestone 1317-65-3 [CALCIUM CARBONATE]		10	Time Weighted Average (TWA):		IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value		Remarks		
			mg/l	ppm	mg/kg	others	
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	aqua (freshwater)		0,006 mg/l				
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	Freshwater - intermittent		0,018 mg/l				
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	aqua (marine water)		0,001 mg/l				
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	Marine water - intermittent		0,002 mg/l				
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	sewage treatment plant (STP)		10 mg/l				
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	sediment (freshwater)				0,341 mg/kg		
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	sediment (marine water)				0,034 mg/kg		
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	Air						no hazard identified
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	Soil				0,065 mg/kg		
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	oral				11 mg/kg		
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	aqua (freshwater)		0,106 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	aqua (intermittent releases)		0,072 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	aqua (marine water)		0,011 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sewage treatment plant (STP)		10 mg/l				
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sediment (freshwater)				307,16 mg/kg		
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sediment (marine water)				30,72 mg/kg		
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Soil				1,234 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m3	no hazard identified
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m3	no hazard identified
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
bis-[4-(2,3-epoxipropoxi)phenyl]propane 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Workers	Inhalation	Long term exposure - systemic effects		3,6 mg/m3	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	Workers	dermal	Long term exposure - systemic effects		1 mg/kg	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	General population	Inhalation	Long term exposure - systemic effects		0,87 mg/m3	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	General population	dermal	Long term exposure - systemic effects		0,5 mg/kg	
Oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; >= 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Goggles which can be tightly sealed.

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing that covers arms and legs.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions. Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form paste
Colour grey
Odor Epoxy
Physical state solid

Melting point Not applicable, Determination technically not possible

Solidification temperature Not applicable, Product is a solid.

Initial boiling point Not applicable, Decomposes before boiling point is reached

Flammability
The product is not flammable.
Explosive limits
Not applicable, Product is a solid.
Flash point
Not applicable, Product is a solid.
Auto-ignition temperature
Not applicable, Product is a solid.

Decomposition temperature Not applicable, Substance/mixture is not self-reactive, no organic

peroxide and does not decompose under foreseen conditions of use

pH Not applicable, Product is non-soluble (in water).

Viscosity (kinematic) Not applicable, Product is a solid.

Viscosity, dynamic 100.000 - 120.000 mPa.s Certificate of Supplier

(Physica Rheolab; 23 °C (73.4 °F))

Solubility (qualitative) Insoluble

(20 °C (68 °F); Solvent: Water)

Partition coefficient: n-octanol/water Not applicable

Mixture

Vapour pressure < 1 hPa

(20 °C (68 °F))

Density 0,88 g/cm³

(20 °C (68 °F))

Relative vapour density: Not applicable, Product is a solid.

Particle characteristics Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Species	Method
CAS-No.	type			
Bisphenol A Diglycidyl	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Ether				
1675-54-3				
oxirane, mono[(C12-14-	LD50	26.800 mg/kg	rat	not specified
alkyloxy)methyl] derivs.				
68609-97-2				
Oxirane, 2-[[3-	LD50	8.025 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral
(trimethoxysilyl)propoxy]				Toxicity)
methyl]-, homopolymer				
56325-93-0				

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LD50	> 4.000 mg/kg	rabbit	not specified
Oxirane, 2-[[3- (trimethoxysilyl)propoxy] methyl]-, homopolymer 56325-93-0	LD50	4.248 mg/kg	rabbit	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Value	Value	Test atmosphere	Exposure	Species	Method
CAS-No.	type			time		
Oxirane, 2-[[3- (trimethoxysilyl)propoxy] methyl]-, homopolymer 56325-93-0	LC50	> 5,3 mg/l	dust/mist	4 h	rat	equivalent or similar to OECD Guideline 403 (Acute Inhalation Toxicity)
Oxirane, 2-[[3- (trimethoxysilyl)propoxy] methyl]-, homopolymer 56325-93-0	Acute toxicity estimate (ATE)	12,5 mg/l	dust/mist	4 h		Expert judgement

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Bisphenol A Diglycidyl Ether 1675-54-3	moderately irritating	24 h	rabbit	Draize Test
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	moderately irritating	24 h	rabbit	EPA OTS 798.4470 (Acute Dermal Irritation)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances	Result	Exposure	Species	Method
CAS-No.		time		
Bisphenol A Diglycidyl	slightly		rabbit	Draize Test
Ether	irritating			
1675-54-3	_			
oxirane, mono[(C12-14-	slightly		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
alkyloxy)methyl] derivs.	irritating			
68609-97-2				
Oxirane, 2-[[3-	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
(trimethoxysilyl)propoxy]				•
methyl]-, homopolymer				
56325-93-0				

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	sensitising	Buehler test	guinea pig	EPA OPPTS 870.2600 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances	Result	Type of study /	Metabolic	Species	Method
CAS-No.		Route of	activation /		
		administration	Exposure time		
Bisphenol A Diglycidyl	negative	bacterial reverse	with and without		EU Method B.13/14
Ether		mutation assay (e.g			(Mutagenicity)
1675-54-3		Ames test)			
Bisphenol A Diglycidyl	negative with	mammalian cell	with and without		not specified
Ether	metabolic	gene mutation assay			
1675-54-3	activation				
oxirane, mono[(C12-14-	negative	mammalian cell	with and without		OECD Guideline 476 (In vitro
alkyloxy)methyl] derivs.		gene mutation assay			Mammalian Cell Gene
68609-97-2					Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
Bisphenol A Diglycidyl Ether 1675-54-3	not carcinogenic	oral: gavage	24 m daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
Bisphenol A Diglycidyl Ether 1675-54-3	not carcinogenic	dermal	2 y 3 times/w	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	NOAEL P >= 50 mg/kg NOAEL F1 >= 750 mg/kg NOAEL F2 >= 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Bisphenol A Diglycidyl Ether 1675-54-3	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol A Diglycidyl Ether 1675-54-3	NOAEL 100 mg/kg	dermal	13 w 3 times/w	mouse	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	NOAEL >= 1 mg/kg	oral: gavage	13 w 5 d/w	rat	OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.		Value	Exposure time	Species	Method
	LC50	1,2 mg/l	96 h		EPA-660 (Methods for Acute Toxicity Tests with Fish, Macroinvertebrates and Amphibians)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	LC50	> 1 - 10 mg/l	96 h		OECD Guideline 203 (Fish, Acute Toxicity Test)
Oxirane, 2-[[3- (trimethoxysilyl)propoxy]met hyl]-, homopolymer 56325-93-0	LC50	55 mg/l	96 h	31 1	EU Method C.1 (Acute Toxicity for Fish)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances		Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	2,7 mg/l	48 h	Daphnia magna	other guideline:
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	EC50	> 1 - 10 mg/l	48 h		OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Oxirane, 2-[[3- (trimethoxysilyl)propoxy]met hyl]-, homopolymer 56325-93-0	EC50	324 mg/l	48 h	<u>F</u>	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
1675-54-3					magna, Reproduction Test)
Oxirane, 2-[[3-	NOEC	100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia
(trimethoxysilyl)propoxy]met					magna, Reproduction Test)
hyl]-, homopolymer					
56325-93-0					

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	other guideline:
Bisphenol A Diglycidyl Ether 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	other guideline:
Oxirane, 2-[[3- (trimethoxysilyl)propoxy]met hyl]-, homopolymer 56325-93-0	EC50	350 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Oxirane, 2-[[3- (trimethoxysilyl)propoxy]met hyl]-, homopolymer 56325-93-0	NOEC	130 mg/l	96 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	Value	Value	Exposure time	Species	Method
CAS-No.	type				
Bisphenol A Diglycidyl Ether	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
1675-54-3					
Oxirane, 2-[[3-	EC50	> 100 mg/l	3 h	activated sludge of a	OECD Guideline 209
(trimethoxysilyl)propoxy]met				predominantly domestic sewage	(Activated Sludge,
hyl]-, homopolymer					Respiration Inhibition Test)
56325-93-0					

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Bisphenol A Diglycidyl Ether 1675-54-3	not inherently biodegradable	not specified	12 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn- Wellens/EMPA Test)
Bisphenol A Diglycidyl Ether 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
oxirane, mono[(C12-14-alkyloxy)methyl] derivs. 68609-97-2	readily biodegradable	aerobic	87 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Oxirane, 2-[[3- (trimethoxysilyl)propoxy]met hyl]-, homopolymer 56325-93-0	not readily biodegradable.		< 60 %	28 d	OECD 301 A - F

12.3. Bioaccumulative potential

No data available.

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Bisphenol A Diglycidyl Ether	> 2,64 - 3,78	25 °C	OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC
1675-54-3			Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances	PBT / vPvB
CAS-No.	
Bisphenol A Diglycidyl Ether	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
1675-54-3	Bioaccumulative (vPvB) criteria.
oxirane, mono[(C12-14-alkyloxy)methyl]	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very
derivs.	Bioaccumulative (vPvB) criteria.
68609-97-2	

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you. 080409

SECTION 14: Transport information

14.1. UN number or ID number

ADR	3077
RID	3077
ADN	3077
IMDG	3077
IATA	3077

14.2. UN proper shipping name

ADR ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy

resin)

RID ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy

resin)

ADN ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy

resin)

IMDG ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy

resin)

IATA Environmentally hazardous substance, solid, n.o.s. (Epoxy resin)

14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous

IMDG Marine Pollutant

IATA Environmentally Hazardous

14.6. Special precautions for user

ADR	not applicable
	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content 0 %

(2010/75/EU)

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text

of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

H412 Harmful to aquatic life with long lasting effects.

ED: Substance identified as having endocrine disrupting properties

EU OEL: Substance with a Union workplace exposure limit
EU EXPLD 1: Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2 Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC: Substance of very high concern (REACH Candidate List)
PBT: Substance fulfilling persistent, bioaccumulative and toxic criteria

PBT/vPvB: Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very

bioaccumulative criteria

vPvB: Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.