



Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 16

TEROSON SI 9150

SDS No. : 145330

V008.1

Revision: 07.06.2023

printing date: 27.10.2023

Replaces version from: 28.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

TEROSON SI 9150

1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

1-Component sealant

1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or www.henkel-adhesives.com.

SDSinfo.Adhesive@henkel.com

1.4. Emergency telephone number

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

2.2. Label elements

Label elements (CLP):

The substance or mixture is not hazardous according to Regulation (EC) No 1272/2008 (CLP).

Based on experimental data, the actual labelling differs from the one which may be received by the calculation method.

Supplemental information

Contains: Methyltris(methyl ethyl ketoxime)silane; Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime; 2-butanone oxime; 3-aminopropyltriethoxysilane May produce an allergic reaction.

Safety data sheet available on request.

2.3. Other hazards

None if used properly.

Following substances are present in a concentration \geq the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration \geq the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

SECTION 3: Composition/information on ingredients**3.2. Mixtures****Declaration of the ingredients according to CLP (EC) No 1272/2008:**

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
Methyltris(methyl ethyl ketoxime)silane 22984-54-9 245-366-4 01-2119970560-38 01-2119987100-43	3- < 5 %	Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT RE 2, H373		
3-Aminopropyl-methylsilsesquioxanes ethoxy-terminated 128446-60-6	1- < 2,5 %	Eye Dam. 1, H318 Flam. Liq. 3, H226 Skin Irrit. 2, H315		
2-butanone oxime 96-29-7 202-496-6 01-2119539477-28	0,1- < 1 %	STOT SE 3, H336 STOT RE 2, H373 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 1, H370 Skin Sens. 1, H317 Carc. 1B, H350 Acute Tox. 3, Oral, H301 Acute Tox. 4, Dermal, H312	dermal:ATE = 1.100 mg/kg oral:ATE = 100 mg/kg	
3-aminopropyltriethoxysilane 919-30-2 213-048-4 01-2119480479-24	0,1- < 1 %	Skin Sens. 1B, H317 Skin Corr. 1B, H314 Acute Tox. 4, Oral, H302		
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1 251-882-0 01-2119982966-14	0,1- < 1 %	Flam. Sol. 1, H228 Skin Sens. 1, H317 Eye Irrit. 2, H319 STOT RE 2, H373		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

SECTION 4: First aid measures**4.1. Description of first aid measures**

Inhalation:

Move to fresh air, consult doctor if complaint persists.

Skin contact:

Rinse with running water and soap. Apply replenishing cream. Change all contaminated clothing.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes). Seek medical attention if necessary.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

See section: Description of first aid measures

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media:

All common extinguishing agents are suitable.

Extinguishing media which must not be used for safety reasons:

High pressure waterjet

5.2. Special hazards arising from the substance or mixture

In case of fire toxic gases can be released.

5.3. Advice for firefighters

Wear protective equipment.

Wear self-contained breathing apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Wear protective equipment.

6.2. Environmental precautions

Do not empty into drains / surface water / ground water.

6.3. Methods and material for containment and cleaning up

Remove mechanically.

Dispose of contaminated material as waste according to Section 13.

6.4. Reference to other sections

See advice in section 8

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Hygiene measures:

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

7.2. Conditions for safe storage, including any incompatibilities

Ensure good ventilation/extraction.

Store in a cool, dry place.

Keep away from heat and direct sunlight.

Storage at 15 to 25°C is recommended.

7.3. Specific end use(s)

1-Component sealant

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational Exposure Limits**

Valid for
Great Britain

None

Occupational Exposure Limits

Valid for
Ireland

Ingredient [Regulated substance]	ppm	mg/m ³	Value type	Short term exposure limit category / Remarks	Regulatory list
Butanone oxime 96-29-7 [METHYL ETHYL KETOXIME]	3	10	Time Weighted Average (TWA):		IR_OEL
Butanone oxime 96-29-7 [METHYL ETHYL KETOXIME]	10	33	Short Term Exposure Limit (STEL):	15 minutes	IR_OEL

Predicted No-Effect Concentration (PNEC):

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	aqua (freshwater)		0,26 mg/l				
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	aqua (marine water)		0,026 mg/l				
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	aqua (intermittent releases)		0,12 mg/l				
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	sewage treatment plant (STP)		10 mg/l				
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	sediment (freshwater)				1,02 mg/kg		
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	sediment (marine water)				0,102 mg/kg		
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	Soil				0,05 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	aqua (marine water)		0,05 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	sediment (marine water)				0,18 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	Soil				0,069 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	sewage treatment plant (STP)		0,81 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	aqua (freshwater)		0,5 mg/l				
3-Aminopropyltriethoxysilane 919-30-2	sediment (freshwater)				1,8 mg/kg		
3-Aminopropyltriethoxysilane 919-30-2	aqua (intermittent releases)		2,05 mg/l				
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	aqua (freshwater)		0,0171 mg/l				
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	aqua (marine water)		0,00171 mg/l				
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	sewage treatment plant (STP)		4,825 mg/l				
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	sediment (freshwater)				9835,3 mg/kg		
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	sediment (marine water)				983,5 mg/kg		
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	Soil				1157,9 mg/kg		
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	oral				2,97 mg/kg		

Derived No-Effect Level (DNEL):

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	Workers	inhalation	Long term exposure - systemic effects		0,988 mg/m3	
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	Workers	dermal	Long term exposure - systemic effects		0,14 mg/kg	
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	General population	inhalation	Long term exposure - systemic effects		0,174 mg/m3	
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	General population	dermal	Long term exposure - systemic effects		0,05 mg/kg	
Butan-2-one O,O',O''-(methylsilylidyne)trioxime 22984-54-9	General population	oral	Long term exposure - systemic effects		0,05 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	oral	Long term exposure - systemic effects		1 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	General population	inhalation	Long term exposure - systemic effects		3,5 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	General population	dermal	Long term exposure - systemic effects		1 mg/kg	
3-Aminopropyltriethoxysilane 919-30-2	Workers	inhalation	Long term exposure - systemic effects		14 mg/m3	
3-Aminopropyltriethoxysilane 919-30-2	Workers	dermal	Long term exposure - systemic effects		2 mg/kg	
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	Workers	inhalation	Long term exposure - systemic effects		0,942 mg/m3	
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	Workers	dermal	Long term exposure - systemic effects		0,134 mg/kg	
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	General population	inhalation	Long term exposure - systemic effects		0,232 mg/m3	
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	General population	dermal	Long term exposure - systemic effects		0,067 mg/kg	
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	General population	oral	Long term exposure - systemic effects		0,067 mg/kg	

Biological Exposure Indices:

None

8.2. Exposure controls:

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

In case of dust formation, we recommend wearing of appropriate respiratory protection equipment with particle filter P (EN 14387).

This recommendation should be matched to local conditions.

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR; ≥ 0.4 mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Protective goggles

Protective eye equipment should conform to EN166.

Skin protection:

Wear protective equipment.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

Use only personal protection that's CE-labelled according to Directive 89/686/EEC (Europe) or to Regulation No. 819 of 19 August 1994 (Norway), or equivalent.

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Delivery form	paste
Colour	varied, according to coloration
Odor	characteristic
Physical state	solid
Solidification temperature	Not applicable, Product is a solid.
Initial boiling point	Not available.
Flammability	The product is not flammable.
Explosive limits	Not applicable, Product is a solid.
Flash point	Not applicable, Product is a solid.
Auto-ignition temperature	Not applicable, Product is a solid.
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic)	Not applicable, Product is a solid.
Solubility (qualitative)	Insoluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	< 0,1 hPa
(20 °C (68 °F))	
Density	1,15 g/cm ³ Supplier's method
(20 °C (68 °F))	
Relative vapour density:	Not applicable, Product is a solid.
Particle characteristics	Not applicable, mixture is a paste.

9.2. Other information

Other information not applicable for this product

SECTION 10: Stability and reactivity

10.1. Reactivity

None if used for intended purpose.

10.2. Chemical stability

Stable under recommended storage conditions.

10.3. Possibility of hazardous reactions

See section reactivity

10.4. Conditions to avoid

None if used for intended purpose.

10.5. Incompatible materials

None if used properly.

10.6. Hazardous decomposition products

No decomposition if used according to specifications.

SECTION 11: Toxicological information

General toxicological information:

An allergic reaction cannot be excluded after repeated skin contact.

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	LD50	2.463 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
2-butanone oxime 96-29-7	Acute toxicity estimate (ATE)	100 mg/kg		Expert judgement
3- aminopropyltriethoxysilan e 919-30-2	LD50	1.457 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	LD50	2.463 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)

Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
2-butanone oxime 96-29-7	Acute toxicity estimate (ATE)	1.100 mg/kg		Expert judgement
3- aminopropyltriethoxysilan e 919-30-2	LD50	4.076 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

Acute inhalative toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
2-butanone oxime 96-29-7	LC50	> 20 mg/l	not specified	4 h	not specified	not specified
3-aminopropyltriethoxysilane 919-30-2	LC50	> 7,35 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)

Skin corrosion/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
3-aminopropyltriethoxysilane 919-30-2	corrosive	1 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)

Serious eye damage/irritation:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
2-butanone oxime 96-29-7	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
3-aminopropyltriethoxysilane 919-30-2	highly irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	irritating	1 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

Respiratory or skin sensitization:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	Sensitizing	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2-butanone oxime 96-29-7	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
3-aminopropyltriethoxysilane 919-30-2	Sub-Category 1B (sensitising)	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)

Germ cell mutagenicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2-butanone oxime 96-29-7	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		EPA OPPTS 870.5265 (The Salmonella typhimurium Bacterial Reverse Mutation Test)
2-butanone oxime 96-29-7	negative	mammalian cell gene mutation assay	with		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
2-butanone oxime 96-29-7	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro			OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
3- aminopropyltriethoxysilan e 919-30-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
3- aminopropyltriethoxysilan e 919-30-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
3- aminopropyltriethoxysilan e 919-30-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)

Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2-butanone oxime 96-29-7	carcinogenic	inhalation: vapour	3 - 18 m 6 h/d, 5 d/w	mouse	male	EPA OTS 798.3300 (Carcinogenicity)

Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2-butanone oxime 96-29-7	NOAEL F1 >= 200 mg/kg NOAEL F2 >= 200 mg/kg	Two generation study	oral: gavage	rat	not specified

STOT-single exposure:

No data available.

STOT-repeated exposure:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	LOAEL 40 mg/kg	oral: gavage	13 w 5 d/week	rat	EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
2-butanone oxime 96-29-7	LOAEL 40 mg/kg	oral: gavage	13 w 5 d/week	rat	EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
3-aminopropyltriethoxysilan e 919-30-2	NOAEL 200 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	NOAEL 25 mg/kg	oral: drinking water	90 d daily: ad libitum	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

Aspiration hazard:

No data available.

11.2 Information on other hazards

not applicable

SECTION 12: Ecological information

General ecological information:

Do not empty into drains, soil or bodies of water.

12.1. Toxicity

Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	LC50	> 560 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
2-butanone oxime 96-29-7	LC50	320 - 1.000 mg/l	96 h	Leuciscus idus	DIN 38412-15
2-butanone oxime 96-29-7	NOEC	50 mg/l	14 d	Oryzias latipes	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)
3-aminopropyltriethoxysilane 919-30-2	LC50	> 934 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	LC50	843 mg/l	96 h	Pimephales promelas	OECD Guideline 203 (Fish, Acute Toxicity Test)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	NOEC	50 mg/l	14 d	Oryzias latipes	OECD Guideline 204 (Fish, Prolonged Toxicity Test: 14-day Study)

Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	EC50	> 750 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-butanone oxime 96-29-7	EC50	> 500 mg/l	48 h	Daphnia magna	EU Method C.2 (Acute Toxicity for Daphnia)
3-aminopropyltriethoxysilane 919-30-2	EC50	331 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	EC50	201 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	NOEC	> 100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
2-butanone oxime 96-29-7	NOEC	> 100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Butan-2-one O,O',O'',O'''- silanetetrayltetraoxime 34206-40-1	NOEC	> 100 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	EC50	94 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	NOEC	30 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	EC50	11,8 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-butanone oxime 96-29-7	NOEC	2,56 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
3-aminopropyltriethoxysilane 919-30-2	EC50	> 1.000 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3-aminopropyltriethoxysilane 919-30-2	NOEC	1,3 mg/l	72 h	Scenedesmus subspicatus (new name: Desmodesmus subspicatus)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	EC50	16 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	NOEC	2,6 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)

Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
2-butanone oxime 96-29-7	EC10	177 mg/l	17 h		DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
3-aminopropyltriethoxysilane 919-30-2	EC10	13 mg/l	5 h	not specified	other guideline:

12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	not readily biodegradable.	aerobic	26 %	28 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2-butanone oxime 96-29-7	inherently biodegradable	aerobic	70 %	14 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
3-aminopropyltriethoxysilane 919-30-2	not readily biodegradable.	aerobic	67 %	28 d	EU Method C.4-A (Determination of the "Ready" Biodegradability/Dissolved Organic Carbon (DOC) Die-Away Test)
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	not readily biodegradable.	aerobic	28 %	28 day	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))

12.3. Bioaccumulative potential

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Bioconcentration factor (BCF)	Exposure time	Temperature	Species	Method
2-butanone oxime 96-29-7	0,5 - 0,6	42 d	25 °C	Oryzias latipes	OECD Guideline 305 C (Bioaccumulation: Test for the Degree of Bioconcentration in Fish)

12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
2-butanone oxime 96-29-7	0,65	25 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Methyltris(methyl ethyl ketoxime)silane 22984-54-9	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-butanone oxime 96-29-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3-aminopropyltriethoxysilane 919-30-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Butan-2-one O,O',O'',O'''-silanetetrayltetraoxime 34206-40-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

12.6. Endocrine disrupting properties

not applicable

12.7. Other adverse effects

No data available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product disposal:

In consultation with the responsible local authority, must be subjected to special treatment.

Waste code

08 04 10 Waste adhesives and sealants other than those mentioned in 08 04 09.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

SECTION 14: Transport information**14.1. UN number or ID number**

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.2. UN proper shipping name

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.3. Transport hazard class(es)

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.4. Packing group

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.5. Environmental hazards

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.6. Special precautions for user

Not hazardous according to RID, ADR, ADN, IMDG, IATA-DGR.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009): Not applicable

Prior Informed Consent (PIC) (Regulation (EU) No 649/2012): Not applicable

Persistent organic pollutants (Regulation (EU) 2019/1021): Not applicable

VOC content 0 %
(2010/75/EU)

VOC Paints and Varnishes (EU):

Product (sub)category: This product is not a subject of the Directive 2004/42/EC

15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

SECTION 16: Other information

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H226 Flammable liquid and vapour.
H228 Flammable solid.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
H350 May cause cancer.
H370 Causes damage to organs.
H373 May cause damage to organs through prolonged or repeated exposure.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

Further information:

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your_company.com).

Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.