

SECTION 1: Identification of the substance/mixture and of the company/ undertaking

1.1 Product identifier

Product name : QUARTZ INEO C3 5W-40
Product code : 089245
Product description : Not available.
Product type : Liquid.
Other means of identification : Not available.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses

Engine oil

Uses advised against

Not applicable.

1.3 Details of the supplier of the safety data sheet

TotalEnergies Lubrifiants
562 Avenue du Parc de L'île
92029 Nanterre Cedex FRANCE
Tél: +33 (0)1 41 35 40 00
Fax: +33 (0)1 41 35 84 71
rm.msds-lubs@totalenergies.com

TotalEnergies Marketing UK Limited
10 Upper Bank Street (19th floor)
Canary Wharf,
London E14 5BF
UNITED KINGDOM
Tel: +44 (0)20 7339 8000
Fax: +44 (0)20 7339 8033
rm.gb-msds@totalenergies.com

H.S.E

1.4 Emergency telephone number

National advisory body/Poison Centre

Telephone number : National Poisons Information Service (NPIS): 111

Supplier

Telephone number : Emergency telephone: +44 1235 239670

**SECTION 2: Hazards identification****2.1 Classification of the substance or mixture****Product definition** : Mixture**Classification according to Regulation (EC) No. 1272/2008 [CLP/GHS]**

Not classified.

The product is not classified as hazardous according to UK CLP Regulation SI 2019/720 as amended.

Ingredients of unknown ecotoxicity : Contains 2.6% of components with unknown hazards to the aquatic environment

See Section 11 for more detailed information on health effects and symptoms.

2.2 Label elements**Signal word** : No signal word.**Hazard statements** : No hazard statement.**Precautionary statements****Prevention** : Not applicable.**Response** : Not applicable.**Storage** : Not applicable.**Disposal** : Not applicable.**Supplemental label elements** : Contains C14-16-18 Alkyl phenol. May produce an allergic reaction. Safety data sheet available on request.**Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles** : Not applicable.**2.3 Other hazards****Product meets the criteria for PBT or vPvB according to Regulation (EC) No. 1907/2006, Annex XIII**This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

Other hazards which do not result in classification : Hazard of slipping on spilt product.**SECTION 3: Composition/information on ingredients****3.2 Mixtures** : Mixture

**SECTION 3: Composition/information on ingredients**

Product/ingredient name	Identifiers	%	Classification	Type
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	REACH #: 01-2119474889-13 EC: 276-738-4 CAS: 72623-87-1 Index: 649-483-00-5	≥25 - ≤50	Asp. Tox. 1, H304	[1]
Distillates (petroleum), hydrotreated heavy paraffinic	REACH #: 01-2119484627-25 EC: 265-157-1 CAS: 64742-54-7 Index: 649-467-00-8	≥10 - ≤25	Asp. Tox. 1, H304	[1]
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	REACH #: 01-2119474878-16 EC: 276-737-9 CAS: 72623-86-0 Index: 649-482-00-X	≤3	Asp. Tox. 1, H304	[1]
Distillates (petroleum), solvent-dewaxed heavy paraffinic	REACH #: 01-2119471299-27 EC: 265-169-7 CAS: 64742-65-0 Index: 649-474-00-6	≤3	Asp. Tox. 1, H304	[1]
Distillates (petroleum), solvent-dewaxed light paraffinic	REACH #: 01-2119480132-48 EC: 265-159-2 CAS: 64742-56-9 Index: 649-469-00-9	≤3	Asp. Tox. 1, H304	[1]
C14-16-18 Alkyl phenol	REACH #: 01-2119498288-19 EC: 931-468-2	≤3	Skin Sens. 1B, H317 STOT RE 2, H373	[1]
Paraffin oils (petroleum), catalytic dewaxed heavy	REACH #: 01-2119487080-42 EC: 265-174-4 CAS: 64742-70-7	≤3	Asp. Tox. 1, H304	[1]
			See Section 16 for the full text of the H statements declared above.	

Annex VIIA - Labelling for Contents : Not applicable.

Additional information : Mineral oil of petroleum origin Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs, vPvBs or Substances of equivalent concern, or have been assigned a workplace exposure limit and hence require reporting in this section.

Type

[1] Substance classified with a health or environmental hazard

Occupational exposure limits, if available, are listed in Section 8.



**SECTION 4: First aid measures****4.1 Description of first aid measures**

- Eye contact** : Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention if irritation occurs.
- Inhalation** : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical attention if symptoms occur.
- Skin contact** : Wash skin thoroughly with soap and water or use recognised skin cleanser. Remove contaminated clothing and shoes. Get medical attention if symptoms occur.
- Ingestion** : Wash out mouth with water. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention if symptoms occur.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training.

4.2 Most important symptoms and effects, both acute and delayed**Over-exposure signs/symptoms**

- Eye contact** : No specific data.
- Inhalation** : No specific data.
- Skin contact** : Adverse symptoms may include the following:
irritation
dryness
cracking
- Ingestion** : No specific data.

4.3 Indication of any immediate medical attention and special treatment needed

- Notes to physician** : Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.
- Specific treatments** : No specific treatment.

SECTION 5: Firefighting measures**5.1 Extinguishing media**

- Suitable extinguishing media** : Use dry chemical, CO₂, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.

5.2 Special hazards arising from the substance or mixture

- Hazards from the substance or mixture** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Hazardous combustion products** : carbon monoxide
carbon dioxide
phosphorus oxides
sulfur oxides
Hydrogen sulfide
Mercaptans
Zinc oxides

5.3 Advice for firefighters

SECTION 5: Firefighting measures

- Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Clothing for fire-fighters (including helmets, protective boots and gloves) conforming to British standard BS EN 469 will provide a basic level of protection for chemical incidents.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
- For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

6.2 Environmental precautions

- : Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

6.3 Methods and material for containment and cleaning up

- Small spill** : Stop leak if without risk. Move containers from spill area. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.
- Large spill** : Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations. Dispose of via a licensed waste disposal contractor.

6.4 Reference to other sections

- : See Section 1 for emergency contact information.
See Section 8 for information on appropriate personal protective equipment.
See Section 13 for additional waste treatment information.

SECTION 7: Handling and storage

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

7.1 Precautions for safe handling

- Protective measures** : Put on appropriate personal protective equipment (see Section 8).
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

7.2 Conditions for safe storage, including any incompatibilities



SECTION 7: Handling and storage

Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

7.3 Specific end use(s)

Recommendations : Not available.

Industrial sector specific solutions : Not available.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

No exposure limit value known.

Biological Limit Values (BLV)

No exposure indices known.

Recommended monitoring procedures : Reference should be made to monitoring standards, such as the following: British Standard BS EN 689 (Workplace atmospheres - Guidance for the assessment of exposure by inhalation to chemical agents for comparison with limit values and measurement strategy) British Standard BS EN 14042 (Workplace atmospheres - Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents) British Standard BS EN 482 (Workplace atmospheres - General requirements for the performance of procedures for the measurement of chemical agents) Reference to national guidance documents for methods for the determination of hazardous substances will also be required.

Advisory OEL : Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m³, NIOSH (REL) TWA 5 mg/m³, STEL 10 mg/m³, ACGIH (TLV) TWA 5 mg/m³ (highly refined)

DNELs/DMELs

Product/substance	Type	Exposure	Value	Population	Effects
<input checked="" type="checkbox"/> Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Local
	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), hydrotreated heavy paraffinic	DNEL	Long term Oral	0.74 mg/kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local



SECTION 8: Exposure controls/personal protection

Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	DNEL	Inhalation Long term	5.4 mg/m ³	Workers	Local
	DNEL	Inhalation Long term	1.2 mg/m ³	General population	Local
	DNEL	Inhalation Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), solvent-dewaxed heavy paraffinic	DNEL	Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
Distillates (petroleum), solvent-dewaxed light paraffinic	DNEL	Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
C14-16-18 Alkyl phenol	DNEL	Long term Inhalation	1.17 mg/m ³	Workers	Systemic
	DNEL	Long term Dermal	0.3 mg/kg bw/day	Workers	Systemic
	DNEL	Long term Oral	0.74 mg/ kg bw/day	General population	Systemic
Paraffin oils (petroleum), catalytic dewaxed heavy	DNEL	Long term Dermal	0.97 mg/ kg bw/day	Workers	Systemic
	DNEL	Long term Inhalation	1.19 mg/m ³	General population	Local
	DNEL	Long term Inhalation	2.73 mg/m ³	Workers	Systemic
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local
	DNEL	Long term Inhalation	5.58 mg/m ³	Workers	Local

PNECs

**SECTION 8: Exposure controls/personal protection**

Product/substance	Compartment Detail	Value	Method Detail
Distillates (petroleum), hydrotreated heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
Distillates (petroleum), solvent-dewaxed heavy paraffinic	Secondary Poisoning	9.33 mg/kg	-
C14-16-18 Alkyl phenol	Fresh water	0.1 mg/l	-
	Marine water	0.01 mg/l	-
	Fresh water sediment	4266.16 mg/kg	-
	dwt		
	Marine water sediment	426.62 mg/kg dwt	-
	Soil	852.58 mg/kg dwt	-
	Sewage Treatment Plant	100 mg/l	-

8.2 Exposure controls

Appropriate engineering controls : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: safety glasses with side-shields. EN 166

Skin protection

Hand protection : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Hydrocarbon-proof gloves
nitrile rubber
Fluorinated rubber

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

In case of prolonged contact with the product, it is recommended to wear gloves complying with ISO 21420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency

Body protection : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Respiratory protection : None under normal use conditions. If these are not sufficient to maintain exposure below the OEL, suitable respiratory protection must be worn (Type A/P1).

**SECTION 8: Exposure controls/personal protection**

Environmental exposure controls : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

The conditions of measurement of all properties are at standard temperature (20°C / 68°F) and pressure (1013 hPa) unless otherwise indicated

9.1 Information on basic physical and chemical propertiesAppearance

Physical state : Liquid. [Clear]
Colour : Yellow.
Odour : Characteristic.
Melting point/freezing point : Technically not possible to measure
Initial boiling point and boiling range : >316°C (>600.8°F) [ISO 3405]
Flammability (solid, gas) : Not applicable.
Upper/lower flammability or explosive limits : Lower: 0.9%
Upper: 7%
Flash point : Open cup: 240°C (464°F) [ASTM D 92]
Auto-ignition temperature : >240°C (>464°F) [ASTM E 659]
Decomposition temperature : Not applicable.
pH : Not applicable. Product is non-soluble (in water).
Viscosity : Dynamic (room temperature): Not available.
Kinematic (room temperature): Not available.
Kinematic (40°C): 83.9 mm²/s [ISO 3104]

Solubility(ies) :

Media	Result
water	Not soluble

Miscible with water : No.
Partition coefficient: n-octanol/ water : Not applicable.
Vapour pressure : <0.013 kPa (<0.1 mm Hg) [room temperature]
Not applicable. [50°C (122°F)]
Relative density : 0.838 to 0.858 [ISO 12185]
Density : 0.838 to 0.858 g/cm³ [15°C (59°F)] [ISO 12185]
Vapour density : >2 [Air = 1]
Particle characteristics
Median particle size : Not applicable.

9.2 Other information

No other relevant physical and chemical parameters for the safe use of the product

**SECTION 10: Stability and reactivity**

- 10.1 Reactivity** : No specific test data related to reactivity available for this product or its ingredients.
- 10.2 Chemical stability** : Stable under recommended storage and handling conditions (see Section 7).
- 10.3 Possibility of hazardous reactions** : Under normal conditions of storage and use, hazardous reactions will not occur.
- 10.4 Conditions to avoid** : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.
No smoking.
- 10.5 Incompatible materials** : Strong oxidising agents
- 10.6 Hazardous decomposition products** : carbon monoxide
carbon dioxide
phosphorus oxides
sulfur oxides
Hydrogen sulfide
Mercaptans
Zinc oxides

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Product/substance	Result	Species	Dose	Exposure	Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
Distillates (petroleum), hydrotreated heavy paraffinic	LC50 Inhalation Dusts and mists	Rat - Male, Female	>5 mg/l	4 hours	Read across OECD 403
	LD50 Dermal	Rabbit - Male, Female	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat - Male, Female	>5000 mg/kg	-	Read across OECD 401
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	LC50 Inhalation Dusts and mists	Rat	5.53 mg/l	4 hours	Read across OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
Distillates (petroleum), solvent-dewaxed heavy paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402
	LD50 Oral	Rat	>5000 mg/kg	-	OECD 420
Distillates (petroleum), solvent-dewaxed light paraffinic	LC50 Inhalation Dusts and mists	Rat	>5 mg/l	4 hours	OECD 403
	LD50 Dermal	Rabbit	>5000 mg/kg	-	OECD 402

**SECTION 11: Toxicological information**

C14-16-18 Alkyl phenol Paraffin oils (petroleum), catalytic dewaxed heavy	LD50 Oral	Rat	>5000 mg/kg	-	OECD 401
	LD50 Dermal	Rat	2000 mg/kg	-	-
	LD50 Oral	Rat	2000 mg/kg	-	-
	LC50 Inhalation Dusts and mists	Rat	5.1 mg/l	4 hours	-
	LC50 Inhalation Vapour	Rat	80.4 mg/l	1 hours	-
	LC50 Inhalation Vapour	Rat	20.1 mg/l	4 hours	-
	LD50 Dermal	Rabbit	>5000 mg/kg	-	-
	LD50 Oral	Rat	>5000 mg/kg	-	-

Acute toxicity estimates

Product/substance	Oral (mg/kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	N/A	N/A	N/A	N/A	5.53
Paraffin oils (petroleum), catalytic dewaxed heavy	N/A	N/A	N/A	20.1	5.1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Irritation/Corrosion**Conclusion/Summary**

Skin : Based on available data, the classification criteria are not met.

Eyes : Based on available data, the classification criteria are not met.

Respiratory : Based on available data, the classification criteria are not met.

Sensitisation**Conclusion/Summary**

Skin : Based on available data, the classification criteria are not met. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required. Contains sensitizer. May produce an allergic reaction.

Respiratory : Based on available data, the classification criteria are not met.

Mutagenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Carcinogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Reproductive toxicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Teratogenicity

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (single exposure)

Not available.

Conclusion/Summary : Based on available data, the classification criteria are not met.

Specific target organ toxicity (repeated exposure)

**SECTION 11: Toxicological information**

Product/substance	Category	Route of exposure	Target organs
C14-16-18 Alkyl phenol	Category 2	-	-

Conclusion/Summary : Based on available data, the classification criteria are not met.

Aspiration hazard

Product/substance	Result
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), hydrotreated heavy paraffinic	ASPIRATION HAZARD - Category 1
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed heavy paraffinic	ASPIRATION HAZARD - Category 1
Distillates (petroleum), solvent-dewaxed light paraffinic	ASPIRATION HAZARD - Category 1
Paraffin oils (petroleum), catalytic dewaxed heavy	ASPIRATION HAZARD - Category 1

Conclusion/Summary : Based on available data, the classification criteria are not met.

Information on likely routes of exposure : Not available.

Potential acute health effects

Eye contact : No known significant effects or critical hazards.
Inhalation : No known significant effects or critical hazards.
Skin contact : Defatting to the skin. May cause skin dryness and irritation.
Ingestion : No known significant effects or critical hazards.

Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : Adverse symptoms may include the following:
irritation
dryness
cracking
Ingestion : No specific data.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Short term exposure**

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Long term exposure

Potential immediate effects : Not available.

Potential delayed effects : Not available.

Potential chronic health effects

Not available.

Conclusion/Summary : Not available.

**SECTION 11: Toxicological information**

General	: No known significant effects or critical hazards.
Carcinogenicity	: <input checked="" type="checkbox"/> No known significant effects or critical hazards.
Mutagenicity	: No known significant effects or critical hazards.
Reproductive toxicity	: No known significant effects or critical hazards.

11.2 Information on other hazards**11.2.1 Endocrine disrupting properties**

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

11.2.2 Other information

Not available.

SECTION 12: Ecological information**12.1 Toxicity**

Product/substance	Result	Species	Exposure	Test
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	48 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Distillates (petroleum), hydrotreated heavy paraffinic	Acute EC50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EC50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	-
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute LL50 >1000 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
Distillates (petroleum), solvent-dewaxed heavy	Acute EL50 >10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202



SECTION 12: Ecological information

paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic	Acute LL50 >1000 mg/l	Fish - <i>Oncorhynchus mykiss</i>	96 hours	OECD 203
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
	Acute EL50 >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Acute EL50 10000 mg/l	Crustaceans - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute EL50 ≥100 mg/l	Fish - <i>Pimephales promelas</i>	96 hours	OECD 203
	Chronic NOEL >100 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	OECD 201
	Chronic NOEL >1000 mg/l	Crustaceans - <i>Daphnia magna</i>	21 days	OECD 211
C14-16-18 Alkyl phenol Paraffin oils (petroleum), catalytic dewaxed heavy	Acute EC50 >100 mg/l	Daphnia - <i>Daphnia magna</i>	48 hours	OECD 202
	Acute EC50 10000 mg/l	Daphnia	48 hours	-
	Acute NOEL 101 mg/l	Algae - <i>Pseudokirchneriella subcapitata</i>	72 hours	-

Conclusion/Summary : Not available.

12.2 Persistence and degradability

Product/substance	Test	Result	Dose	Inoculum
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), hydrotreated heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed heavy paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge
Distillates (petroleum), solvent-dewaxed light paraffinic	OECD 301F	31 % - Not readily - 28 days	-	Activated sludge

Conclusion/Summary : Not available.

Product/substance	Aquatic half-life	Photolysis	Biodegradability
Lubricating oils (petroleum), C20-50, hydrotreated neutral oil-based	-	-	Not readily
Distillates (petroleum), hydrotreated heavy paraffinic	-	-	Not readily
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	-	-	Not readily
Distillates (petroleum), solvent-dewaxed heavy	-	-	Not readily

**SECTION 12: Ecological information**

paraffinic Distillates (petroleum), solvent-dewaxed light paraffinic	-	-	Not readily
Paraffin oils (petroleum), catalytic dewaxed heavy	-	-	Not readily

12.3 Bioaccumulative potential

Product/substance	LogP _{ow}	BCF	Potential
Distillates (petroleum), hydrotreated heavy paraffinic	>4	-	High
Lubricating oils (petroleum), C15-30, hydrotreated neutral oil-based	6.1	-	High
Distillates (petroleum), solvent-dewaxed heavy paraffinic	9.2	260	Low
Distillates (petroleum), solvent-dewaxed light paraffinic	3.1	-	Low

12.4 Mobility in soil

Soil/water partition coefficient (K_{oc}) : Not available.

Mobility : Not available.

Mobility in soil : Given its physical and chemical characteristics, the product generally shows low soil mobility. The product is insoluble and floats on water. Loss by evaporation is limited.

12.5 Results of PBT and vPvB assessment

This mixture does not contain any substances that are assessed to be a PBT or a vPvB in a concentration $\geq 0,1$ %.

12.6 Endocrine disrupting properties

This product does not contain any substance present at a concentration equal to or greater than 0.1% by mass, included in the list drawn up in accordance with article 59, paragraph 1 of the REACH Regulation, due to its endocrine disrupting properties, or a substance known to have endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation 2018/605.

12.7 Other adverse effects

No known significant effects or critical hazards.

SECTION 13: Disposal considerations

The information in this section contains generic advice and guidance. The list of Identified Uses in Section 1 should be consulted for any available use-specific information provided in the Exposure Scenario(s).

13.1 Waste treatment methods**Product**



SECTION 13: Disposal considerations

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction.

Hazardous waste : Yes.
According to the European Waste Catalogue, Waste Codes are not product specific, but application specific. Waste codes should be assigned by the user based on the application for which the product was used. The following Waste Codes are only suggestions: 13 02 05*

Packaging

Methods of disposal : The generation of waste should be avoided or minimised wherever possible. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible.

Special precautions : This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

	ADR/RID	ADN	IMDG	ICAO/IATA
14.1 UN number or ID number	Not regulated.	Not regulated.	Not regulated.	Not regulated.
14.2 UN proper shipping name	-	-	-	-
14.3 Transport hazard class(es)	-	-	-	-
14.4 Packing group	-	-	-	-
14.5 Environmental hazards	No.	No.	No.	No.

14.6 Special precautions for user : **Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.7 Maritime transport in bulk according to IMO instruments : Not available.

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****UK (GB)/REACH****Annex XIV - List of substances subject to authorisation****Annex XIV**

None of the components are listed.

Substances of very high concern

None of the components are listed.

Ozone depleting substances

Not listed.

Prior Informed Consent (PIC)

Not listed.

Persistent Organic Pollutants

Not listed.

Annex XVII - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles**Seveso Directive**

This product is not controlled under the Seveso Directive.

EU regulations

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work.

Industrial emissions (integrated pollution prevention and control) - Air : Not listed

Industrial emissions (integrated pollution prevention and control) - Water : Not listed

International regulations**Chemical Weapon Convention List Schedules I, II & III Chemicals**

Not listed.

Montreal Protocol

Not listed.

Stockholm Convention on Persistent Organic Pollutants

Not listed.

Rotterdam Convention on Prior Informed Consent (PIC)

Not listed.

UNECE Aarhus Protocol on POPs and Heavy Metals

Not listed.

Inventory list**Australia inventory (AIC)**

: All components are listed or exempted.

**SECTION 15: Regulatory information**

Canada inventory	: All components are listed or exempted.
China inventory (IECSC)	: All components are listed or exempted.
Europe inventory	: All components are listed or exempted.
Japan inventory	: Japan inventory (CSCL) : All components are listed or exempted. Japan inventory (ISHL) : All components are listed or exempted.
New Zealand Inventory of Chemicals (NZIoC)	: All components are listed or exempted.
Philippines inventory (PICCS)	: All components are listed or exempted.
Korea inventory (KECI)	: All components are listed or exempted.
Taiwan Chemical Substances Inventory (TCSI)	: All components are listed or exempted.
Thailand inventory	: Not determined.
Turkey inventory	: <input checked="" type="checkbox"/> Not determined.
United States inventory (TSCA 8b)	: All components are listed or exempted.
Vietnam inventory	: Not determined.

The information stated in this section relates solely to the conformity of the chemical product with the countries inventories. The information used to confirm the inventory status of this product may be based on additional data to the chemical composition shown in Section 3. Other regulations may apply for importation or marketing authorizations.

15.2 Chemical safety assessment : This product contains substances for which Chemical Safety Assessments are still required.

SECTION 16: Other information

Indicates information that has changed from previously issued version.

Abbreviations and acronyms :

- ATE = Acute Toxicity Estimate
- CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]
- DNEL = Derived No Effect Level
- DMEL = Derived Minimal Effect Level
- EUH statement = CLP-specific Hazard statement
- N/A = Not available
- PBT = Persistent, Bioaccumulative and Toxic
- vPvB = Very Persistent and Very Bioaccumulative
- PNEC = Predicted No Effect Concentration
- LC50 = Median lethal concentration
- LD50 = Median lethal dose
- OEL = Occupational Exposure Limit
- VOC = Volatile Organic Compound
- UVCB Substance of unknown or Variable composition, Complex reaction products or Biological material
- NOEC No Observed Effect Concentration
- QSAR = Quantitative Structure–Activity Relationship

Procedure used to derive the classification

Not classified.

Full text of abbreviated H statements

**SECTION 16: Other information**

H304	May be fatal if swallowed and enters airways.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated exposure.

Full text of classifications

Asp. Tox. 1	ASPIRATION HAZARD - Category 1
Skin Sens. 1B	SKIN SENSITISATION - Category 1B
STOT RE 2	SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - Category 2

Date of printing : 2024/08/23**Date of issue/ Date of revision** : 2024/08/23**Date of previous issue** : 2023/02/24**Version** : 2.01**Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.