



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 1

LOCTITE EA 3421 DC50ML DE

SDS No. : 178258  
V005.0

Revision: 10.01.2024

printing date: 12.01.2024

Replaces version from: 20.02.2023

---

### Kit/Multi-component Product

1. SDS No.293497 - LOCTITE EA 3421 A
2. SDS No.152796 - LOCTITE EA 3421 B



## Safety Data Sheet according to (EC) No 1907/2006 as amended

Page 1 of 19

LOCTITE EA 3421 A

SDS No. : 293497

V005.0

Revision: 10.01.2024

printing date: 12.01.2024

Replaces version from: 09.01.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 3421 A

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy resin

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin irritation

Category 2

H315 Causes skin irritation.

Serious eye irritation

Category 2

H319 Causes serious eye irritation.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Chronic hazards to the aquatic environment

Category 2

H411 Toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

##### Hazard pictogram:



##### Contains

2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane

p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether  
Bisphenol-F epichlorhydrin resin; MW<700

<b>Signal word:</b>	Warning
<b>Hazard statement:</b>	H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H411 Toxic to aquatic life with long lasting effects.
<b>Precautionary statement:</b>	P273 Avoid release to the environment.
<b>Prevention</b>	P280 Wear protective gloves.
<b>Precautionary statement:</b>	P302+P352 IF ON SKIN: Wash with plenty of soap and water.
<b>Response</b>	P333+P313 If skin irritation or rash occurs: Get medical advice/attention. P337+P313 If eye irritation persists: Get medical advice/attention.

### 2.3. Other hazards

None if used properly.

Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Declaration of the ingredients according to CLP (EC) No 1272/2008:

Hazardous components CAS-No. EC Number REACH-Reg No.	Concentration	Classification	Specific Conc. Limits, M-factors and ATEs	Add. Information
2,2'-(1-methylethylidene)bis(4,1-phenyleneoxymethylene)bisoxyirane 1675-54-3 01-2119456619-26	25- 50 %	Eye Irrit. 2, H319 Aquatic Chronic 2, H411 Skin Sens. 1, H317 Skin Irrit. 2, H315	Eye Irrit. 2; H319; C $\geq$ 5 % Skin Irrit. 2; H315; C $\geq$ 5 %	
Bisphenol-F epichlorhydrin resin; MW<700 ----- 01-2119454392-40	25- 50 %	Skin Irrit. 2, Dermal, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8 221-453-2 01-2119959496-20	1- < 5 %	Skin Sens. 1A, H317 Aquatic Chronic 2, H411	oral:ATE = 2.500 mg/kg	

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

Inhalation:

Move to fresh air. If symptoms persist, seek medical advice.

Skin contact:

Rinse with running water and soap.

Obtain medical attention if irritation persists.

Eye contact:

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

Ingestion:

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

#### **4.2. Most important symptoms and effects, both acute and delayed**

EYE: Irritation, conjunctivitis.

SKIN: Redness, inflammation.

SKIN: Rash, Urticaria.

#### **4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

### **SECTION 5: Firefighting measures**

#### **5.1. Extinguishing media**

**Suitable extinguishing media:**

water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

#### **5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

#### **5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

#### **Additional information:**

In case of fire, keep containers cool with water spray.

### **SECTION 6: Accidental release measures**

#### **6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

#### **6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

#### **6.3. Methods and material for containment and cleaning up**

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

#### **6.4. Reference to other sections**

See advice in section 8

### **SECTION 7: Handling and storage**

#### **7.1. Precautions for safe handling**

Avoid skin and eye contact.

See advice in section 8

**Hygiene measures:**

Wash hands before work breaks and after finishing work.

Do not eat, drink or smoke while working.

Good industrial hygiene practices should be observed.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.

Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Epoxy resin

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**

Valid for

Great Britain

None

**Occupational Exposure Limits**

Valid for

Ireland

None

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (freshwater)		0,006 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Freshwater - intermittent		0,018 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	aqua (marine water)		0,001 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Marine water - intermittent		0,002 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sewage treatment plant (STP)		10 mg/l				
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (freshwater)				0,341 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	sediment (marine water)				0,034 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Soil				0,065 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	oral				11 mg/kg		
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight ≤ 700 1675-54-3	Air						no hazard identified
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) -----	aqua (freshwater)		0,003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) -----	aqua (marine water)		0,0003 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) -----	sewage treatment plant (STP)		10 mg/l				
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) -----	sediment (freshwater)				0,294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) -----	sediment (marine water)				0,0294 mg/kg		
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) -----	Soil				0,237		

(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----					mg/kg		
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	aqua (intermittent releases)		0,0254 mg/l				
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Air						no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Predator						no potential for bioaccumulation
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	aqua (freshwater)		0,0075 mg/l				
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	aqua (marine water)		0,00075 mg/l				
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sewage treatment plant (STP)		100 mg/l				
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sediment (freshwater)				33,54 mg/kg		
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sediment (marine water)				3,354 mg/kg		
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Soil				11,4 mg/kg		
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	aqua (intermittent releases)		0,075 mg/l				

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	Workers	inhalation	Long term exposure - systemic effects		4,93 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	Workers	dermal	Long term exposure - systemic effects		0,75 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	inhalation	Long term exposure - systemic effects		0,87 mg/m <sup>3</sup>	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	dermal	Long term exposure - systemic effects		0,0893 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	oral	Long term exposure - systemic effects		0,5 mg/kg	no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	Workers	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	Workers	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	Workers	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	Workers	dermal	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	inhalation	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	inhalation	Acute/short term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	dermal	Long term exposure - local effects			no hazard identified
4,4'-Isopropylidenediphenol, oligomeric reaction products with 1-chloro-2,3-epoxypropane, number average molecular weight $\leq 700$ 1675-54-3	General population	dermal	Acute/short term exposure - local effects			no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Workers	Inhalation	Long term exposure - systemic effects		29,39 mg/m <sup>3</sup>	no hazard identified
Reaction product: bisphenol-F-(epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ )	Workers	dermal	Long term exposure - systemic effects		104,15 mg/kg	no hazard identified



----- Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	Workers	dermal	Acute/short term exposure - local effects		0,0083 mg/cm <sup>2</sup>	no hazard identified
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	General population	Inhalation	Long term exposure - systemic effects		8,7 mg/m <sup>3</sup>	no hazard identified
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	General population	dermal	Long term exposure - systemic effects		62,5 mg/kg	no hazard identified
Reaction product: bisphenol-F- (epichlorhydrin); epoxy resin (number average molecular weight $\leq 700$ ) -----	General population	oral	Long term exposure - systemic effects		6,25 mg/kg	no hazard identified
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Long term exposure - systemic effects		19,6 mg/m <sup>3</sup>	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Acute/short term exposure - systemic effects		19,6 mg/m <sup>3</sup>	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Acute/short term exposure - local effects		19,6 mg/m <sup>3</sup>	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	inhalation	Long term exposure - local effects		19,6 mg/m <sup>3</sup>	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	dermal	Long term exposure - systemic effects		5,6 mg/kg	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	dermal	Acute/short term exposure - systemic effects		5,6 mg/kg	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	dermal	Long term exposure - local effects		0,0016 mg/cm <sup>2</sup> 1,6 µg/cm <sup>2</sup> /day	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Workers	dermal	Acute/short term exposure - local effects		0,0016 mg/cm <sup>2</sup> 1,6 µg/cm <sup>2</sup> /day	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	General population	inhalation	Long term exposure - systemic effects		11,7 mg/m <sup>3</sup>	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	General population	inhalation	Long term exposure - local effects		11,7 mg/m <sup>3</sup>	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	General population	dermal	Long term exposure - systemic effects		3,3 mg/kg	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	General population	dermal	Acute/short term exposure - systemic effects		3,3 mg/kg	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	General population	dermal	Long term exposure - local effects		0,00095 mg/cm <sup>2</sup> 0,95 µg/cm <sup>2</sup> /day	
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	General population	dermal	Acute/short term exposure - local effects		0,00095 mg/cm <sup>2</sup> 0,95 µg/cm <sup>2</sup> /day	

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

**Hand protection:**

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to > 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to > 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

**Eye protection:**

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

**Skin protection:**

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

**Advices to personal protection equipment:**

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Delivery form	paste
Colour	white
Odor	odourless
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	$< 5^{\circ}\text{C}$ ( $< 41^{\circ}\text{F}$ )
Initial boiling point	$> 190^{\circ}\text{C}$ ( $> 374^{\circ}\text{F}$ )
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	$> 100^{\circ}\text{C}$ ( $> 212^{\circ}\text{F}$ )
Auto-ignition temperature	$> 300^{\circ}\text{C}$ ( $> 572^{\circ}\text{F}$ )
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	Not applicable, Product is non-soluble (in water).
Viscosity (kinematic) ( $25^{\circ}\text{C}$ ( $77^{\circ}\text{F}$ ); )	52.000 mm <sup>2</sup> /s
Viscosity, dynamic (Brookfield; Instrument: RVT; $25^{\circ}\text{C}$ ( $77^{\circ}\text{F}$ ); speed of rotation: 2,5 min <sup>-1</sup> ; Spindle No: 6)	40.000 - 80.000 mPa.s LCT STM 10; Viscosity Brookfield
Solubility (qualitative) ( $20^{\circ}\text{C}$ ( $68^{\circ}\text{F}$ ); Solvent: Water)	Not soluble
Partition coefficient: n-octanol/water	Not applicable
Vapour pressure ( $50^{\circ}\text{C}$ ( $122^{\circ}\text{F}$ ))	Mixture 0,001 mbar
Vapour pressure ( $21,1^{\circ}\text{C}$ ( $70^{\circ}\text{F}$ ))	$< 6,78$ hPa
Density ( $25^{\circ}\text{C}$ ( $77^{\circ}\text{F}$ ))	1,13 - 1,17 g/cm <sup>3</sup> None
Relative vapour density: ( $20^{\circ}\text{C}$ )	$> 1$
Particle characteristics	Not applicable Product is a liquid

**9.2. Other information**

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with strong oxidants.

Reaction with strong acids.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.

## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 420 (Acute Oral Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 -----	LD50	> 5.000 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 425 (Acute Oral Toxicity: Up-and-Down Procedure)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement

#### Acute dermal toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Bisphenol-F epichlorhydrin resin; MW<700 -----	LD50	> 2.000 mg/kg	rat	equivalent or similar to OECD Guideline 402 (Acute Dermal Toxicity)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)

**Acute inhalative toxicity:**

No data available.

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	not irritating	4 h	rabbit	not specified
Bisphenol-F epichlorhydrin resin; MW<700 -----	irritating	4 h	rabbit	equivalent or similar to OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	not irritating	24 h	rat	other guideline:

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	not irritating		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Bisphenol-F epichlorhydrin resin; MW<700 -----	not irritating		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	not irritating	72 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Bisphenol-F epichlorhydrin resin; MW<700 -----	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Type of study / Route of administration	Metabolic activation / Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 472 (Genetic Toxicology: Escherichia coli, Reverse Mutation Assay)
Bisphenol-F epichlorhydrin resin; MW<700 -----	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	positive without metabolic activation	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	positive without metabolic activation	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	positive	sister chromatid exchange assay in mammalian cells	without		OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	negative	oral: gavage		mouse	not specified
Bisphenol-F epichlorhydrin resin; MW<700 -----	negative	oral: gavage		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	negative	oral: gavage		rat	OECD Guideline 486 (Unscheduled DNA Synthesis (UDS) Test with Mammalian Liver Cells in vivo)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	negative	oral: gavage		rat	OECD Guideline 489 (In Vivo Mammalian Alkaline Comet Assay)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	negative	oral: gavage		rat	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

**Carcinogenicity**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	dermal	2 y daily	mouse	male	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)] bisoxirane 1675-54-3	not carcinogenic	oral: gavage	2 y daily	rat	male/female	OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

**Reproductive toxicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOAEL P $\geq$ 50 mg/kg NOAEL F1 $\geq$ 750 mg/kg NOAEL F2 $\geq$ 750 mg/kg	Two generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOAEL P > 750 mg/kg NOAEL F1 750 mg/kg NOAEL F2 750 mg/kg	two-generation study	oral: gavage	rat	OECD Guideline 416 (Two-Generation Reproduction Toxicity Study)

**STOT-single exposure:**

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOAEL 50 mg/kg	oral: gavage	14 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOAEL 250 mg/kg	oral: gavage	13 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	NOAEL 100 mg/kg	oral: gavage	90 d daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable

## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	LC50	1,75 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	LC50	5,7 mg/l	96 h	Leuciscus idus	OECD Guideline 203 (Fish, Acute Toxicity Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	LC50	7,5 mg/l	96 h	Oncorhynchus mykiss	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	EC50	1,7 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	EC50	2,55 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	EC50	67,9 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

#### Chronic toxicity (aquatic invertebrates):

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	NOEC	0,3 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)

#### Toxicity (Algae):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	EC50	> 11 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	NOEC	4,2 mg/l	72 h	Scenedesmus capricornutum	OECD Guideline 201 (Alga, Growth Inhibition Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	EC50	1,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	EC50	9 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
Bisphenol-F epichlorhydrin resin; MW<700 -----	IC50	> 100 mg/l	3 h	activated sludge, industrial	other guideline:
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	EC50	> 1.000 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

#### 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	not readily biodegradable.	aerobic	5 %	28 d	OECD Guideline 301 F (Ready Biodegradability: Manometric Respirometry Test)
Bisphenol-F epichlorhydrin resin; MW<700 -----	not readily biodegradable.	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	not readily biodegradable.	aerobic	1,1 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)

#### 12.3. Bioaccumulative potential

No data available.



**12.4. Mobility in soil**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	3,242	25 °C	EU Method A.8 (Partition Coefficient)
Bisphenol-F epichlorhydrin resin; MW<700 -----	2,7 - 3,6		OECD Guideline 117 (Partition Coefficient (n-octanol / water), HPLC Method)
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	3,59	20 °C	OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)

**12.5. Results of PBT and vPvB assessment**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
2,2'-[(1-methylethylidene)bis(4,1-phenyleneoxymethylene)]bisoxirane 1675-54-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Bisphenol-F epichlorhydrin resin; MW<700 -----	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
p-tert-Butylphenyl 1-(2,3-epoxy)propyl ether 3101-60-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

**12.6. Endocrine disrupting properties**

not applicable

**12.7. Other adverse effects**

No data available.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods**

Product disposal:

Dispose of in accordance with local and national regulations.

Do not empty into drains / surface water / ground water.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

## SECTION 14: Transport information

### 14.1. UN number or ID number

ADR	3082
RID	3082
ADN	3082
IMDG	3082
IATA	3082

### 14.2. UN proper shipping name

ADR	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
RID	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)
IATA	Environmentally hazardous substance, liquid, n.o.s. (Bisphenol-F Epichlorhydrin resin,Bisphenol-A Epichlorhydrin resin)

### 14.3. Transport hazard class(es)

ADR	9
RID	9
ADN	9
IMDG	9
IATA	9

### 14.4. Packing group

ADR	III
RID	III
ADN	III
IMDG	III
IATA	III

### 14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous
ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	Environmentally Hazardous

### 14.6. Special precautions for user

ADR	not applicable
-----	----------------

	Tunnelcode:
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

The transport classifications in this section apply generally to packed and bulk goods alike. For containers with a net volume of no more than 5 L for liquid substances or a net mass of no more than 5 kg for solid substances per individual or inner package, the exemptions SP 375 (ADR), A197 (IATA), 2.10.2.7 (IMDG) may be applied, which can result in a deviation from the transport classification for packed goods.

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

## SECTION 15: Regulatory information

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3,00 %

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.

**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**



## Safety Data Sheet according to (EC) No 1907/2006 as amended

SDS No. : 152796

V005.0

LOCTITE EA 3421 B

Revision: 10.01.2024

printing date: 12.01.2024

Replaces version from: 09.01.2024

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

LOCTITE EA 3421 B

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Intended use:

Epoxy Hardener

#### 1.3. Details of the supplier of the safety data sheet

Henkel Ltd

Adhesives

Wood Lane End

HP2 4RQ Hemel Hempstead

Great Britain

Phone: +44 (1442) 278000

SDSinfo.Adhesive@henkel.com

For Safety Data Sheet updates please visit our website <https://mysds.henkel.com/index.html#/appSelection> or [www.henkel-adhesives.com](http://www.henkel-adhesives.com).

#### 1.4. Emergency telephone number

24 Hours Emergency Tel: +44 (0)1442 278497

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (CLP):

Skin corrosion

Sub-category 1B

H314 Causes severe skin burns and eye damage.

Serious eye damage

Category 1

H318 Causes serious eye damage.

Skin sensitizer

Category 1

H317 May cause an allergic skin reaction.

Acute hazards to the aquatic environment

Category 1

H400 Very toxic to aquatic life.

Chronic hazards to the aquatic environment

Category 1

H410 Very toxic to aquatic life with long lasting effects.

#### 2.2. Label elements

##### Label elements (CLP):

**Hazard pictogram:****Contains**

Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine

Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine

Amines, polyethylenepoly-, triethylenetetramine fraction

2-piperazin-1-ylethylamine

3,6-diazaoctanethylenediamine

Amines, polyethylenepoly-, tetraethylenepentamine fraction

**Signal word:**

Danger

**Hazard statement:**

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H410 Very toxic to aquatic life with long lasting effects.

**Precautionary statement:  
Prevention**

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement:  
Response**

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER or doctor.

**2.3. Other hazards**

None if used properly.

**Following substances are present in a concentration  $\geq$  the concentration limit for depiction in Section 3 and fulfill the criteria for PBT/vPvB, or were identified as endocrine disruptor (ED):**

This mixture does not contain any substances in a concentration  $\geq$  the concentration limit for depiction in Section 3 that are assessed to be a PBT, vPvB or ED.

## SECTION 3: Composition/information on ingredients

**3.2. Mixtures**

**Declaration of the ingredients according to CLP (EC) No 1272/2008:**

<b>Hazardous components CAS-No. EC Number REACH-Reg No.</b>	<b>Concentration</b>	<b>Classification</b>	<b>Specific Conc. Limits, M-factors and ATEs</b>	<b>Add. Information</b>
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1 500-191-5 500-191-5 01-2119972320-44	25- 50 %	Aquatic Chronic 2, H411 Eye Dam. 1, H318 Skin Irrit. 2, H315 Skin Sens. 1, H317		
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	20- 40 %	Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Chronic 2, H411		
Polyamide adduct 106906-26-7 500-296-6	2,5- < 25 %	Aquatic Acute 1, H400 Aquatic Chronic 1, H410	M acute = 10 M chronic = 10	
benzyl alcohol 100-51-6 202-859-9 01-2119492630-38	5- < 10 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Inhalation, H332 Eye Irrit. 2, H319	dermal:ATE = 2.500 mg/kg inhalation:ATE = 4,17 mg/l;dust/mist	
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2 202-013-9 01-2119560597-27	1- < 5 %	Acute Tox. 4, Oral, H302 Skin Irrit. 2, H315 Eye Irrit. 2, H319		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8 292-588-2 01-2119487919-13	1- < 3 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Eye Dam. 1, H318 Aquatic Chronic 3, H412		
2-piperazin-1-ylethylamine 140-31-8 205-411-0 01-2119471486-30	1- < 3 %	Acute Tox. 3, Dermal, H311 Acute Tox. 4, Oral, H302 Skin Corr. 1B, H314 Aquatic Chronic 3, H412 Skin Sens. 1, H317 Repr. 2, H361	inhalation:ATE = > 10 mg/l;dust/mist	
3,6-diazaoctanethylenediamine 112-24-3 203-950-6 01-2119487919-13	0,1- < 1 %	Acute Tox. 4, Oral, H302 Acute Tox. 4, Dermal, H312 Skin Sens. 1, H317 Skin Corr. 1B, H314 Aquatic Chronic 3, H412		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7 292-587-7, 292-587-7 01-2119487290-37	0,1- < 1 %	Acute Tox. 4, Dermal, H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 2, H411 Eye Dam. 1, H318		

If no ATE values are displayed, please refer to LD/LC50 values in Section 11.

For full text of the H - statements and other abbreviations see section 16 "Other information".

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**Inhalation:**

Move to fresh air. If symptoms persist, seek medical advice.

**Skin contact:**

Rinse with running water and soap.

Obtain medical attention if irritation persists.

**Eye contact:**

Rinse immediately with plenty of running water (for 10 minutes), seek medical attention from a specialist.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**4.2. Most important symptoms and effects, both acute and delayed**

SKIN: Rash, Urticaria.

Causes burns.

**4.3. Indication of any immediate medical attention and special treatment needed**

See section: Description of first aid measures

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media:**

water, carbon dioxide, foam, powder

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**5.2. Special hazards arising from the substance or mixture**

In the event of a fire, carbon monoxide (CO), carbon dioxide (CO<sub>2</sub>) and nitrogen oxides (NO<sub>x</sub>) can be released.

**5.3. Advice for firefighters**

Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

**Additional information:**

In case of fire, keep containers cool with water spray.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Avoid contact with skin and eyes.

Wear protective equipment.

Ensure adequate ventilation.

Keep away from sources of ignition.

**6.2. Environmental precautions**

Do not empty into drains / surface water / ground water.

**6.3. Methods and material for containment and cleaning up**

Dispose of contaminated material as waste according to Section 13.

For small spills wipe up with paper towel and place in container for disposal.

For large spills absorb onto inert absorbent material and place in sealed container for disposal.

**6.4. Reference to other sections**

See advice in section 8

**SECTION 7: Handling and storage**



**7.1. Precautions for safe handling**

Avoid skin and eye contact.  
See advice in section 8

## Hygiene measures:

Good industrial hygiene practices should be observed.  
Wash hands before work breaks and after finishing work.  
Do not eat, drink or smoke while working.

**7.2. Conditions for safe storage, including any incompatibilities**

Store in a cool, well-ventilated place.  
Refer to Technical Data Sheet

**7.3. Specific end use(s)**

Epoxy Hardener

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters****Occupational Exposure Limits**

Valid for  
Great Britain

None

**Occupational Exposure Limits**

Valid for  
Ireland

None

**Predicted No-Effect Concentration (PNEC):**

Name on list	Environmental Compartment	Exposure period	Value				Remarks
			mg/l	ppm	mg/kg	others	
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	aqua (freshwater)		0,004 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	Freshwater - intermittent		0,042 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	aqua (marine water)		0 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	sewage treatment plant (STP)		3,84 mg/l				
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	sediment (freshwater)				434,02 mg/kg		
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	sediment (marine water)				43,4 mg/kg		
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	Soil				86,78 mg/kg		
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	Predator						no potential for bioaccumulation
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	aqua (freshwater)		0,00434 mg/l				
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	aqua (marine water)		0,00043 mg/l				
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	aqua (intermittent releases)		0,0434 mg/l				
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sewage treatment plant (STP)		3,84 mg/l				
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sediment (freshwater)				434,02 mg/kg		
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sediment (marine water)				43,4 mg/kg		
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Soil				86,78 mg/kg		
Benzyl alcohol 100-51-6	Soil				0,456 mg/kg		
Benzyl alcohol 100-51-6	sewage treatment plant (STP)		39 mg/l				
Benzyl alcohol 100-51-6	sediment (freshwater)				5,27 mg/kg		
Benzyl alcohol 100-51-6	sediment (marine water)				0,527 mg/kg		

Benzyl alcohol 100-51-6	aqua (marine water)		0,1 mg/l				
Benzyl alcohol 100-51-6	aqua (intermittent releases)		2,3 mg/l				
Benzyl alcohol 100-51-6	aqua (freshwater)		1 mg/l				
Benzyl alcohol 100-51-6	Predator						no potential for bioaccumulation
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	aqua (freshwater)		0,046 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	aqua (marine water)		0,005 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Freshwater - intermittent		0,46 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Marine water - intermittent		0,046 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sewage treatment plant (STP)		0,2 mg/l				
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sediment (freshwater)				0,262 mg/kg		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	sediment (marine water)				0,026 mg/kg		
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Soil				0,025 mg/kg		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	aqua (intermittent releases)		0,2 mg/l				
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	aqua (freshwater)		0,027 mg/l				
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	aqua (marine water)		0,003 mg/l				
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	sediment (freshwater)				8,572 mg/kg		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	sediment (marine water)				0,857 mg/kg		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Soil				1,25 mg/kg		
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	sewage treatment plant (STP)		0,13 mg/l				
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	oral						no potential for bioaccumulation
2-Piperazin-1-ylethylamine 140-31-8	aqua (freshwater)		0,058 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	aqua (marine water)		0,006 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	sediment (freshwater)				215 mg/kg		
2-Piperazin-1-ylethylamine 140-31-8	sediment (marine water)				21,5 mg/kg		
2-Piperazin-1-ylethylamine 140-31-8	sewage treatment plant (STP)		250 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	Freshwater - intermittent		0,58 mg/l				
2-Piperazin-1-ylethylamine 140-31-8	Soil				1 mg/kg		
3,6-diazaoctanethylenediamine 112-24-3	aqua (freshwater)		0,027 mg/l				
3,6-diazaoctanethylenediamine 112-24-3	aqua (marine water)		0,003 mg/l				
3,6-diazaoctanethylenediamine 112-24-3	Sewage treatment plant		0,13 mg/l				
3,6-diazaoctanethylenediamine 112-24-3	sediment (freshwater)				8,572 mg/kg		
3,6-diazaoctanethylenediamine	sediment				0,857		

112-24-3	(marine water)				mg/kg		
3,6-diazaoctanethylenediamine 112-24-3	Soil				1,25 mg/kg		
3,6-diazaoctanethylenediamine 112-24-3	Freshwater - intermittent		0,2 mg/l				
3,6-diazaoctanethylenediamine 112-24-3	Marine water - intermittent		0,02 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	aqua (freshwater)		0,01 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	aqua (marine water)		0,001 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	aqua (intermittent releases)		0,068 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	sediment (freshwater)				3,198 mg/kg		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	sediment (marine water)				0,32 mg/kg		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Soil				2,5 mg/kg		
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	sewage treatment plant (STP)		4,6 mg/l				
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Air						no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Predator						no potential for bioaccumulation

**Derived No-Effect Level (DNEL):**

Name on list	Application Area	Route of Exposure	Health Effect	Exposure Time	Value	Remarks
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Workers	inhalation	Long term exposure - systemic effects		3,9 mg/m <sup>3</sup>	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Workers	dermal	Long term exposure - systemic effects		1,1 mg/kg	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	General population	inhalation	Long term exposure - systemic effects		0,97 mg/m <sup>3</sup>	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	General population	dermal	Long term exposure - systemic effects		0,56 mg/kg	
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	General population	oral	Long term exposure - systemic effects		0,56 mg/kg	
Benzyl alcohol 100-51-6	General population	oral	Acute/short term exposure - systemic effects		20 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	oral	Long term exposure - systemic effects		4 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	inhalation	Acute/short term exposure - systemic effects		110 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	inhalation	Long term exposure - systemic effects		22 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	inhalation	Acute/short term exposure - systemic effects		27 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	inhalation	Long term exposure - systemic effects		5,4 mg/m <sup>3</sup>	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	dermal	Acute/short term exposure - systemic effects		40 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	Workers	dermal	Long term exposure - systemic effects		8 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	dermal	Acute/short term exposure - systemic effects		20 mg/kg	no potential for bioaccumulation
Benzyl alcohol 100-51-6	General population	dermal	Long term exposure - systemic effects		4 mg/kg	no potential for bioaccumulation
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	inhalation	Long term exposure - systemic effects		0,53 mg/m <sup>3</sup>	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	inhalation	Acute/short term exposure - systemic effects		2,1 mg/m <sup>3</sup>	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	dermal	Long term exposure - systemic effects		0,15 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	Workers	dermal	Acute/short term exposure - systemic effects		0,6 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	inhalation	Long term exposure - systemic effects		0,13 mg/m <sup>3</sup>	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	inhalation	Acute/short term exposure - systemic effects		0,13 mg/m <sup>3</sup>	
2,4,6-Tris(dimethylaminomethyl)phenol	General	dermal	Long term		0,075 mg/kg	

90-72-2	population		exposure - systemic effects			
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	dermal	Acute/short term exposure - systemic effects		0,075 mg/kg	
2,4,6-Tris(dimethylaminomethyl)phenol 90-72-2	General population	oral	Long term exposure - systemic effects		0,075 mg/kg	
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Workers	Inhalation	Long term exposure - systemic effects		0,54 mg/m3	no potential for bioaccumulation
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	General population	Inhalation	Long term exposure - systemic effects		0,096 mg/m3	no potential for bioaccumulation
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	General population	oral	Long term exposure - systemic effects		0,14 mg/kg	no potential for bioaccumulation
2-Piperazin-1-ylethylamine 140-31-8	Workers	inhalation	Acute/short term exposure - local effects		0,08 mg/m3	
2-Piperazin-1-ylethylamine 140-31-8	Workers	inhalation	Long term exposure - local effects		0,015 mg/m3	
2-Piperazin-1-ylethylamine 140-31-8	Workers	inhalation	Acute/short term exposure - systemic effects		10,6 mg/m3	
2-Piperazin-1-ylethylamine 140-31-8	Workers	dermal	Long term exposure - systemic effects		3,33 mg/kg	
2-Piperazin-1-ylethylamine 140-31-8	Workers	inhalation	Long term exposure - systemic effects		10,6 mg/m3	
3,6-diazaoctanethylenediamine 112-24-3	Workers	inhalation	Long term exposure - systemic effects		0,54 mg/m3	
3,6-diazaoctanethylenediamine 112-24-3	General population	inhalation	Long term exposure - systemic effects		0,096 mg/m3	
3,6-diazaoctanethylenediamine 112-24-3	General population	oral	Long term exposure - systemic effects		0,14 mg/kg	
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Workers	inhalation	Long term exposure - systemic effects		1,29 mg/m3	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Workers	inhalation	Acute/short term exposure - systemic effects		6940 mg/m3	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Workers	dermal	Long term exposure - systemic effects		0,74 mg/kg	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Workers	dermal	Long term exposure - local effects		0,036 mg/cm2	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	inhalation	Long term exposure - systemic effects		0,38 mg/m3	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	inhalation	Acute/short term exposure - systemic effects		2071 mg/m3	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	dermal	Long term exposure - systemic effects		0,32 mg/kg	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	dermal	Acute/short term exposure - systemic effects		10 mg/kg	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	dermal	Long term exposure - local effects		0,56 mg/cm2	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	dermal	Acute/short term exposure - local effects		1,29 mg/cm2	no hazard identified
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	General population	oral	Long term exposure - systemic effects		0,53 mg/kg	no hazard identified
Amines, polyethylenepoly-,	General	oral	Acute/short term		26 mg/kg	no hazard identified

tetraethylenepentamine fraction 90640-66-7	population	exposure - systemic effects			
---	------------	--------------------------------	--	--	--

**Biological Exposure Indices:**

None

**8.2. Exposure controls:**

Engineering controls:

Ensure good ventilation/extraction.

Respiratory protection:

Ensure adequate ventilation.

An approved mask or respirator fitted with an organic vapour cartridge should be worn if the product is used in a poorly ventilated area

Filter type: A (EN 14387)

Hand protection:

Chemical-resistant protective gloves (EN 374).

Suitable materials for short-term contact or splashes (recommended: at least protection index 2, corresponding to &gt; 30 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

Suitable materials for longer, direct contact (recommended: protection index 6, corresponding to &gt; 480 minutes permeation time as per EN 374):

nitrile rubber (NBR;  $\geq 0.4$  mm thickness)

This information is based on literature references and on information provided by glove manufacturers, or is derived by analogy with similar substances. Please note that in practice the working life of chemical-resistant protective gloves may be considerably shorter than the permeation time determined in accordance with EN 374 as a result of the many influencing factors (e.g. temperature). If signs of wear and tear are noticed then the gloves should be replaced.

Eye protection:

Safety glasses with sideshields or chemical safety goggles should be worn if there is a risk of splashing.

Protective eye equipment should conform to EN166.

Skin protection:

Wear suitable protective clothing.

Protective clothing should conform to EN 14605 for liquid splashes or to EN 13982 for dusts.

Advices to personal protection equipment:

The information provided on personal protective equipment is for guidance purposes only. A full risk assessment should be conducted prior to using this product to determine the appropriate personal protective equipment to suit local conditions.

Personal protective equipment should conform to the relevant EN standard.

## SECTION 9: Physical and chemical properties

**9.1. Information on basic physical and chemical properties**

Delivery form	liquid
Colour	Amber, Clear
Odor	Of amine
Physical state	liquid
Melting point	Not applicable, Product is a liquid
Solidification temperature	< 5 °C (< 41 °F)
Initial boiling point	> 180 °C (> 356 °F)no method / method unknown
Flammability	The product is not flammable.
Explosive limits	Not applicable, The product is not flammable.
Flash point	110 °C (230 °F)
Auto-ignition temperature	> 200 °C (> 392 °F)
Decomposition temperature	Not applicable, Substance/mixture is not self-reactive, no organic peroxide and does not decompose under foreseen conditions of use
pH	11,1

(25 °C (77 °F); Conc.: 100 g/l; Solvent: Water)	
Viscosity (kinematic)	15.000 mm <sup>2</sup> /s
(25 °C (77 °F); )	
Viscosity, dynamic	11.000,00 - 19.000,00 mPa.s LCT STM 10; Viscosity Brookfield
(Brookfield; Instrument: RVT; 25 °C (77 °F);	
speed of rotation: 10 min <sup>-1</sup> ; Spindle No: 6)	
Solubility (qualitative)	Partially soluble
(20 °C (68 °F); Solvent: Water)	
Partition coefficient: n-octanol/water	Not applicable
	Mixture
Vapour pressure	0,04 mbar
(21 °C (69,8 °F))	
Density	1,1 g/cm <sup>3</sup> None
(25 °C (77 °F))	
Relative vapour density:	> 1
(20 °C)	
Particle characteristics	Not applicable
	Product is a liquid

## 9.2. Other information

Other information not applicable for this product

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Reacts with strong oxidants.

Acids.

Reaction with strong acids.

Strong bases.

### 10.2. Chemical stability

Stable under recommended storage conditions.

### 10.3. Possibility of hazardous reactions

See section reactivity

### 10.4. Conditions to avoid

Stable under normal conditions of storage and use.

### 10.5. Incompatible materials

See section reactivity.

### 10.6. Hazardous decomposition products

carbon oxides.

Rapid polymerisation may generate excessive heat and pressure.

May produce fumes when heated to decomposition. Fumes may contain carbon monoxide and other toxic fumes.



## SECTION 11: Toxicological information

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute oral toxicity:

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 423 (Acute Oral toxicity)
Polyamide adduct 106906-26-7	LD50	> 2.000 mg/kg	rat	not specified
benzyl alcohol 100-51-6	LD50	1.620 mg/kg	rat	not specified
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	LD50	1.200 mg/kg	rat	not specified
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LD50	1.716 mg/kg	rat	equivalent or similar to OECD Guideline 401 (Acute Oral Toxicity)
3,6-diazaoctanethylenediamine 112-24-3	LD50	1.591 mg/kg	rat	OECD Guideline 401 (Acute Oral Toxicity)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LD50	3.221 mg/kg	rat	not specified

**Acute dermal toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	LD50	> 2.000 mg/kg	rat	OECD Guideline 402 (Acute Dermal Toxicity)
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	2.500 mg/kg		Expert judgement
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LD50	1.465 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
2-piperazin-1-ylethylamine 140-31-8	LD50	866 mg/kg	rabbit	Draize Test
3,6-diazaoctanethylenediamine 112-24-3	LD50	1.465 mg/kg	rabbit	OECD Guideline 402 (Acute Dermal Toxicity)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LD50	1.260 mg/kg	rabbit	not specified

**Acute inhalative toxicity:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Test atmosphere	Exposure time	Species	Method
benzyl alcohol 100-51-6	Acute toxicity estimate (ATE)	4,17 mg/l	dust/mist			Expert judgement
benzyl alcohol 100-51-6	LC50	> 4,178 mg/l	dust/mist	4 h	rat	OECD Guideline 403 (Acute Inhalation Toxicity)
2-piperazin-1- ylethylamine 140-31-8	Acute toxicity estimate (ATE)	> 10 mg/l	dust/mist	4 h		Expert judgement

**Skin corrosion/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	irritating or corrosive		Human, EpiDerm™ SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	not corrosive		Human, in vitro skin model	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	irritating or corrosive		Human, EpiDerm™ SIT (EPI-200), Reconstructed Human Epidermis (RHE)	OECD Guideline 439 (In Vitro Skin Irritation: Reconstructed Human Epidermis (RHE) Test Method)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	not corrosive		Human, in vitro skin model	OECD Guideline 431 (In Vitro Skin Corrosion: Reconstructed Human Epidermis (RHE) Test Method)
benzyl alcohol 100-51-6	not irritating	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,4,6- tris(dimethylaminomethyl) phenol 90-72-2	corrosive	4 h	rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2,4,6- tris(dimethylaminomethyl) phenol 90-72-2	Sub-Category 1C (corrosive)		Corrositex Biobarrier Membrane (reconstituted collagen matrix)	OECD Guideline 435 (In Vitro Membrane Barrier Test Method for Skin Corrosion)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
2-piperazin-1- ylethylamine 140-31-8	corrosive	20 min	rabbit	not specified
3,6- diazaoctanethylenediamin e 112-24-3	corrosive		rabbit	OECD Guideline 404 (Acute Dermal Irritation / Corrosion)
Amines, polyethylenepoly-,	corrosive		Corrositex Biobarrier	OECD Guideline 435 (In Vitro Membrane Barrier Test Method for Skin Corrosion)

tetraethylenepentamine fraction 90640-66-7			Membrane (reconstituted collagen matrix)	
--	--	--	--	--

**Serious eye damage/irritation:**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	corrosive		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Category 1 (irreversible effects on the eye)		rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
benzyl alcohol 100-51-6	irritating	24 h	rabbit	OECD Guideline 405 (Acute Eye Irritation / Corrosion)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Category 1 (irreversible effects on the eye)		rabbit	equivalent or similar to OECD Guideline 405 (Acute Eye Irritation / Corrosion)

**Respiratory or skin sensitization:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Test type</b>	<b>Species</b>	<b>Method</b>
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sensitising	Mouse local lymphnode assay (LLNA)	mouse	OECD Guideline 429 (Skin Sensitisation: Local Lymph Node Assay)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	not sensitising	Buehler test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	not sensitising	Guinea pig maximisation test	guinea pig	OECD Guideline 406 (Skin Sensitisation)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Sensitizing	Buehler test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
2-piperazin-1-ylethylamine 140-31-8	sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
3,6-diazaoctanethylenediamine 112-24-3	sensitising	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Sensitizing	Guinea pig maximisation test	guinea pig	equivalent or similar to OECD Guideline 406 (Skin Sensitisation)

**Germ cell mutagenicity:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

<b>Hazardous substances CAS-No.</b>	<b>Result</b>	<b>Type of study / Route of administration</b>	<b>Metabolic activation / Exposure time</b>	<b>Species</b>	<b>Method</b>
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
benzyl alcohol 100-51-6	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		equivalent or similar to OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	negative	in vitro mammalian chromosome aberration test	with and without		OECD Guideline 473 (In vitro Mammalian Chromosome Aberration Test)
2,4,6- tris(dimethylaminomethyl )phenol 90-72-2	negative	mammalian cell gene mutation assay	with and without		OECD Guideline 476 (In vitro Mammalian Cell Gene Mutation Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
2-piperazin-1- ylethylamine 140-31-8	negative	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
2-piperazin-1- ylethylamine 140-31-8	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		not specified
2-piperazin-1- ylethylamine 140-31-8	negative	mammalian cell gene mutation assay	with and without		not specified
3,6- diazaoctanethylenediamin e 112-24-3	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
3,6- diazaoctanethylenediamin e 112-24-3	negative	DNA damage and repair assay, unscheduled DNA synthesis in mammalian cells in vitro	with and without		OECD Guideline 482 (Genetic Toxicology: DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	positive	bacterial reverse mutation assay (e.g Ames test)	with and without		OECD Guideline 471 (Bacterial Reverse Mutation Assay)
Amines, polyethylenepoly-, tetraethylenepentamine	positive	mammalian cell gene mutation assay	with and without		equivalent or similar to OECD Guideline 476 (In vitro Mammalian Cell Gene

fraction 90640-66-7					Mutation Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	positive	sister chromatid exchange assay in mammalian cells	with and without		equivalent or similar to OECD Guideline 479 (Genetic Toxicology: In Vitro Sister Chromatid Exchange Assay in Mammalian Cells)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	negative	in vitro mammalian cell micronucleus test	with and without		OECD Guideline 487 (In vitro Mammalian Cell Micronucleus Test)
benzyl alcohol 100-51-6	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
2-piperazin-1-ylethylamine 140-31-8	negative	intraperitoneal		mouse	not specified
3,6-diazaoctanethylenediamine 112-24-3	negative	intraperitoneal		mouse	OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	negative	intraperitoneal		mouse	equivalent or similar to OECD Guideline 474 (Mammalian Erythrocyte Micronucleus Test)

### Carcinogenicity

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous components CAS-No.	Result	Route of application	Exposure time / Frequency of treatment	Species	Sex	Method
benzyl alcohol 100-51-6	not carcinogenic	oral: gavage	104 weeks once daily, 5 days/week	rat	male/female	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	not carcinogenic	dermal	lifetime three times/w	mouse	male	equivalent or similar OECD Guideline 451 (Carcinogenicity Studies)

### Reproductive toxicity:

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Test type	Route of application	Species	Method
benzyl alcohol 100-51-6	NOAEL P 200 mg/kg	screening	oral: gavage	mouse	not specified
2-piperazin-1-ylethylamine 140-31-8	NOAEL P 8000 ppm NOAEL F1 8000 ppm	screening	oral: drinking water	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)

### STOT-single exposure:

No data available.

**STOT-repeated exposure:**

The mixture is classified based on threshold limits referring to the classified substances present in the mixture.

Hazardous substances CAS-No.	Result / Value	Route of application	Exposure time / Frequency of treatment	Species	Method
benzyl alcohol 100-51-6	NOAEL 400 mg/kg	oral: gavage	13 weeks once daily, 5 days/week	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
2-piperazin-1- ylethylamine 140-31-8	NOAEL 2000 ppm	oral: drinking water	>= 28 d daily	rat	OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
3,6- diazaoctanethylenediamin e 112-24-3	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
3,6- diazaoctanethylenediamin e 112-24-3	NOAEL 50 mg/kg	oral: gavage	26 w daily	rat	OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LOAEL 50 mg/kg	oral: gavage	26 w daily	rat	equivalent or similar to OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity in Rodents)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	NOAEL 200 mg/kg	dermal	20 d 6 h/d, 5 d/w	rabbit	OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)

**Aspiration hazard:**

No data available.

**11.2 Information on other hazards**

not applicable



## SECTION 12: Ecological information

### General ecological information:

Do not empty into drains / surface water / ground water.

### 12.1. Toxicity

#### Toxicity (Fish):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	LC50	7,07 mg/l	96 h	Danio rerio	OECD Guideline 203 (Fish, Acute Toxicity Test)
benzyl alcohol 100-51-6	LC50	460 mg/l	96 h	Pimephales promelas	EPA OPP 72-1 (Fish Acute Toxicity Test)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	LC50	153 mg/l	96 h	Brachydanio rerio (new name: Danio rerio)	ISO 7346-1 (Determination of the Acute Lethal Toxicity of Substances to a Freshwater Fish [Brachydanio rerio Hamilton-Buchanan (Teleostei, Cyprinidae)])
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	LC50	330 mg/l	96 h	Pimephales promelas	other guideline:
2-piperazin-1-ylethylamine 140-31-8	LC50	> 100 mg/l	96 h	Salmo gairdneri (new name: Oncorhynchus mykiss)	OECD Guideline 203 (Fish, Acute Toxicity Test)
3,6-diazaoctanethylenediamine 112-24-3	LC50	570 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	LC50	420 mg/l	96 h	Poecilia reticulata	OECD Guideline 203 (Fish, Acute Toxicity Test)

#### Toxicity (aquatic invertebrates):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	EC50	7,07 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Polyamide adduct 106906-26-7	EC50	0,048 mg/l	48 h	Daphnia magna	not specified
benzyl alcohol 100-51-6	EC50	230 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2,4,6-	EC50	> 100 mg/l	48 h	Daphnia magna	OECD Guideline 202

tris(dimethylaminomethyl)phenol 90-72-2					(Daphnia sp. Acute Immobilisation Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	EC50	31 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
2-piperazin-1-ylethylamine 140-31-8	EC50	32 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
3,6-diazaoctanethylenediamine 112-24-3	EC50	31 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC50	24,1 mg/l	48 h	Daphnia magna	OECD Guideline 202 (Daphnia sp. Acute Immobilisation Test)

**Chronic toxicity (aquatic invertebrates):**

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
benzyl alcohol 100-51-6	NOEC	51 mg/l	21 d	Daphnia magna	OECD 211 (Daphnia magna, Reproduction Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	EC10	1,9 mg/l	21 day	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC10	1,9 mg/l	21 d	Daphnia magna	OECD Guideline 202 (Daphnia sp. Chronic Immobilisation Test)

**Toxicity (Algae):**

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	EC50	4,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	EC50	4,34 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	EC50	770 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
benzyl alcohol 100-51-6	NOEC	310 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6-tris(dimethylaminomethyl)phe nol 90-72-2	EC50	46,7 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
2,4,6-tris(dimethylaminomethyl)phe nol 90-72-2	NOEC	6,44 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	EC50	20 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	EC10	1,34 mg/l	72 h	Pseudokirchneriella subcapitata (reported as Raphidocelis subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-piperazin-1-ylethylamine 140-31-8	NOEC	31 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
2-piperazin-1-ylethylamine 140-31-8	EC50	495 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
3,6-diazaoctanethylenediamine 112-24-3	EC50	20 mg/l	72 h	Selenastrum capricornutum (new name: Pseudokirchneriella subcapitata)	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC50	6,8 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	NOEC	0,5 mg/l	72 h	Pseudokirchneriella subcapitata	OECD Guideline 201 (Alga, Growth Inhibition Test)

#### Toxicity (microorganisms):

The mixture is classified based on calculation method referring to the classified substances present in the mixture.

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Value type	Value	Exposure time	Species	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine	EC10	130 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)

68082-29-1					
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	EC10	130 mg/l	3 h	activated sludge of a predominantly domestic sewage	OECD Guideline 209 (Activated Sludge, Respiration Inhibition Test)
benzyl alcohol 100-51-6	EC10	658 mg/l	17 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	EC0	27 mg/l	16 h	Pseudomonas putida	DIN 38412, part 8 (Pseudomonas Zellvermehrungshemm-Test)
2-piperazin-1-ylethylamine 140-31-8	EC10	100 mg/l	17 h		not specified
3,6-diazaoctanethylenediamine 112-24-3	EC0	137 mg/l	30 min	Pseudomonas putida	DIN 38412, part 27 (Bacterial oxygen consumption test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	EC50	97,3 mg/l	2 h	other:	other guideline:

## 12.2. Persistence and degradability

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	Result	Test type	Degradability	Exposure time	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	not readily biodegradable.	no data	> 0 - < 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	not readily biodegradable.	no data	0 - 60 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
benzyl alcohol 100-51-6	readily biodegradable	aerobic	92 - 96 %	14 d	OECD Guideline 301 C (Ready Biodegradability: Modified MITI Test (I))
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	not readily biodegradable.	aerobic	4 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	not inherently biodegradable	aerobic	20 %	84 d	OECD Guideline 302 A (Inherent Biodegradability: Modified SCAS Test)
2-piperazin-1-ylethylamine 140-31-8	under test conditions no biodegradation observed	aerobic	0 %	28 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
3,6-diazaoctanethylenediamine 112-24-3	not inherently biodegradable	aerobic	0 %	28 d	OECD Guideline 302 B (Inherent biodegradability: Zahn-Wellens/EMPA Test)
3,6-diazaoctanethylenediamine 112-24-3	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	not readily biodegradable.	aerobic	0 %	162 d	OECD Guideline 301 D (Ready Biodegradability: Closed Bottle Test)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	not inherently biodegradable	aerobic	17 %	84 d	OECD Guideline 302 A (Inherent Biodegradability: Modified SCAS Test)

**12.3. Bioaccumulative potential**

No data available.

#### 12.4. Mobility in soil

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	LogPow	Temperature	Method
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	10,34		QSAR (Quantitative Structure Activity Relationship)
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	10,34		QSAR (Quantitative Structure Activity Relationship)
benzyl alcohol 100-51-6	1,05	20 °C	EU Method A.8 (Partition Coefficient)
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	-0,66	21,5 °C	EPA OPPTS 830.7550 (Partition Coefficient, n-octanol / H <sub>2</sub> O, Shake Flask Method)
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	-2,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
2-piperazin-1-ylethylamine 140-31-8	-1,48		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
3,6-diazaoctanethylenediamine 112-24-3	-2,65		OECD Guideline 107 (Partition Coefficient (n-octanol / water), Shake Flask Method)
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	-3,16		QSAR (Quantitative Structure Activity Relationship)

#### 12.5. Results of PBT and vPvB assessment

The table below presents the data of the classified substances present in the mixture.

Hazardous substances CAS-No.	PBT / vPvB
Fatty acids, C18-unsatd., dimers, oligomeric reaction products with tall-oil fatty acids and triethylenetetramine 68082-29-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Fatty acids, C18 unsaturated, dimers, polymers with tall oil fatty acids and triethylenetetramine 68082-29-1	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Polyamide adduct 106906-26-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
benzyl alcohol 100-51-6	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2,4,6-tris(dimethylaminomethyl)phenol 90-72-2	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, polyethylenepoly-, triethylenetetramine fraction 90640-67-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
2-piperazin-1-ylethylamine 140-31-8	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
3,6-diazaoctanethylenediamine 112-24-3	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.
Amines, polyethylenepoly-, tetraethylenepentamine fraction 90640-66-7	Not fulfilling Persistent, Bioaccumulative and Toxic (PBT), very Persistent and very Bioaccumulative (vPvB) criteria.

#### 12.6. Endocrine disrupting properties

not applicable

#### 12.7. Other adverse effects

No data available.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Product disposal:

Do not empty into drains / surface water / ground water.

Dispose of in accordance with local and national regulations.

Disposal of uncleaned packages:

After use, tubes, cartons and bottles containing residual product should be disposed of as chemically contaminated waste in an authorised legal land fill site or incinerated.

Waste code

The valid EWC waste code numbers are source-related. The manufacturer is therefore unable to specify EWC waste codes for the articles or products used in the various sectors. The EWC codes listed are intended as a recommendation for users. We will be happy to advise you.

08 04 09\* waste adhesives and sealants containing organic solvents and other dangerous substances

### SECTION 14: Transport information

#### 14.1. UN number or ID number

ADR	2735
RID	2735
ADN	2735
IMDG	2735
IATA	2735

#### 14.2. UN proper shipping name

ADR	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethyl amino methyl) phenole,Amines, polyethylenepoly-, triethylenetetramine fraction)
RID	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethyl amino methyl) phenole,Amines, polyethylenepoly-, triethylenetetramine fraction)
ADN	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethyl amino methyl) phenole,Amines, polyethylenepoly-, triethylenetetramine fraction)
IMDG	AMINES, LIQUID, CORROSIVE, N.O.S. (2,4,6-Tris(dimethyl amino methyl) phenole,Amines, polyethylenepoly-, triethylenetetramine fraction,Polyamide/epoxy adduct)
IATA	Amines, liquid, corrosive, n.o.s. (2,4,6-Tris(dimethyl amino methyl) phenole,Amines, polyethylenepoly-, triethylenetetramine fraction)

#### 14.3. Transport hazard class(es)

ADR	8
RID	8
ADN	8
IMDG	8
IATA	8

#### 14.4. Packing group

ADR	II
RID	II
ADN	II
IMDG	II
IATA	II

#### 14.5. Environmental hazards

ADR	Environmentally Hazardous
RID	Environmentally Hazardous

ADN	Environmentally Hazardous
IMDG	Marine Pollutant
IATA	not applicable

**14.6. Special precautions for user**

ADR	not applicable
	Tunnelcode: (E)
RID	not applicable
ADN	not applicable
IMDG	not applicable
IATA	not applicable

**14.7. Maritime transport in bulk according to IMO instruments**

not applicable

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

Ozone Depleting Substance (ODS) (Regulation (EC) No 1005/2009):	Not applicable
Prior Informed Consent (PIC) (Regulation (EU) No 649/2012):	Not applicable
Persistent organic pollutants (Regulation (EU) 2019/1021):	Not applicable
VOC content (2010/75/EC)	< 3,00 % Combined A/B

**15.2. Chemical safety assessment**

A chemical safety assessment has not been carried out.



**SECTION 16: Other information**

The labelling of the product is indicated in Section 2. The full text of all abbreviations indicated by codes in this safety data sheet are as follows:

H302 Harmful if swallowed.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H332 Harmful if inhaled.  
H361 Suspected of damaging fertility or the unborn child.  
H400 Very toxic to aquatic life.  
H410 Very toxic to aquatic life with long lasting effects.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.

ED:	Substance identified as having endocrine disrupting properties
EU OEL:	Substance with a Union workplace exposure limit
EU EXPLD 1:	Substance listed in Annex I, Reg (EC) No. 2019/1148
EU EXPLD 2	Substance listed in Annex II, Reg (EC) No. 2019/1148
SVHC:	Substance of very high concern (REACH Candidate List)
PBT:	Substance fulfilling persistent, bioaccumulative and toxic criteria
PBT/vPvB:	Substance fulfilling persistent, bioaccumulative and toxic plus very persistent and very bioaccumulative criteria
vPvB:	Substance fulfilling very persistent and very bioaccumulative criteria

**Further information:**

This Safety Data Sheet has been produced for sales from Henkel to parties purchasing from Henkel, is based on Regulation (EC) No 1907/2006 and provides information in accordance with applicable regulations of the European Union only. In that respect, no statement, warranty or representation of any kind is given as to compliance with any statutory laws or regulations of any other jurisdiction or territory other than the European Union. When exporting to territories other than the European Union, please consult with the respective Safety Data Sheet of the concerned territory to ensure compliance or liaise with Henkel's Product Safety and Regulatory Affairs Department (SDSinfo.Adhesive@henkel.com) prior to export to other territories than the European Union.

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

Dear Customer,

Henkel is committed to creating a sustainable future by promoting opportunities along the entire value chain. If you would like to contribute by switching from a paper to the electronic version of SDS, please contact the local Customer Service representative. We recommend to use a non-personal email address (e.g. SDS@your\_company.com).

**Relevant changes in this safety data sheet are indicated by vertical lines at the left margin in the body of this document. Corresponding text is displayed in a different color on shadowed fields.**