

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1. Product identifier**  
Substance / mixture MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS mixture  
Number M-03082023  
UFI E960-W098-J009-35ND
- 1.2. Relevant identified uses of the substance or mixture and uses advised against**  
**Mixture's intended use**  
Varnish.  
**Main intended use**  
PC-PNT-1 Aerosol paints and coatings  
**Mixture uses advised against**  
The product should not be used in ways other than those referred in Section 1.
- 1.3. Details of the supplier of the safety data sheet**  
**Manufacturer**  
Name or trade name AMTRA Sp. z o. o.  
Address Schonów 3, Sosnowiec, 41-200  
Poland  
VAT Reg No PL6250009241  
Phone +48 32 294 41 00  
E-mail amtra@amtra.pl  
**Competent person responsible for the safety data sheet**  
Name AMTRA Sp. z o. o.  
E-mail amtra@amtra.pl
- 1.4. Emergency telephone number**  
European emergency number: 112

### SECTION 2: Hazards identification

- 2.1. Classification of the substance or mixture**  
**Classification of the mixture in accordance with Regulation (EC) No 1272/2008**

The mixture is classified as dangerous.

Aerosol 1, H222, H229  
Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
STOT SE 3, H336

#### Most serious adverse physico-chemical effects

Pressurised container: May burst if heated. Extremely flammable aerosol.

#### Most serious adverse effects on human health and the environment

Causes serious eye irritation. Causes skin irritation. May cause drowsiness or dizziness.

- 2.2. Label elements**

#### Hazard pictogram



#### Signal word

Danger

#### Hazardous substances

acetone  
n-butyl acetate

#### Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date 03rd August 2023  
Revision date 20th March 2025 Version 2.0

H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

### Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P271 Use only outdoors or in a well-ventilated area.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

### 2.3. Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended. Does not contain any PMT or vPvM components.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
Index: 603-019-00-8 CAS: 115-10-6 EC: 204-065-8	dimethyl ether	>60-<70	Press. Gas, Flam. Gas 1, H220	2, 3
Index: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2	acetone	>10-<20	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	3, 4, 5
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7	xylene	6-12	Flam. Liq. 3, H226 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315	1, 3
Index: 607-025-00-1 CAS: 123-86-4 EC: 204-658-1	n-butyl acetate	1-6	Flam. Liq. 3, H226 STOT SE 3, H336 EUH066	3

### Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note U (Table 3): When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned:

Press. Gas (Comp.)  
Press. Gas (Liq.)  
Press. Gas (Ref. Liq.)  
Press. Gas (Diss.)

Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

- A substance for which exposure limits are set.
- Explosive precursor
- Drug precursor

Full text of all classifications and hazard statements is given in the section 16.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet.

##### **If inhaled**

Terminate the exposure immediately; move the affected person to fresh air. Protect the person against growing cold. Provide medical treatment if irritation, dyspnoea or other symptoms persist.

##### **If on skin**

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible.

##### **If in eyes**

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. Rinsing should continue at least for 10 minutes. Provide medical treatment, specialized if possible.

##### **If swallowed**

Unlikely.

#### 4.2. Most important symptoms and effects, both acute and delayed

##### **If inhaled**

May cause drowsiness or dizziness.

##### **If on skin**

Causes skin irritation.

##### **If in eyes**

Causes serious eye irritation.

##### **If swallowed**

Irritation, nausea.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

##### **Suitable extinguishing media**

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

##### **Unsuitable extinguishing media**

Water - full jet.

#### 5.2. Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

#### 5.3. Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

### SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Pressurised container: May burst if heated. Extremely flammable aerosol. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale aerosols. Prevent contact with skin and eyes.

#### 6.2. Environmental precautions

Prevent contamination of the soil and entering surface or ground water.

#### 6.3. Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date 03rd August 2023  
Revision date 20th March 2025 Version 2.0

### 6.4. Reference to other sections

See the Section 7, 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale aerosols. Prevent contact with skin and eyes. No smoking. Protect against direct sunlight. Do not pierce or burn, even after use. Wash hands and exposed parts of the body thoroughly after handling. Do not spray on an open flame or other ignition source. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection.

### 7.2. Conditions for safe storage, including any incompatibilities

Recommended storage temperature is from +5 °C to +30 °C. Protect against frost. Protect from sunlight. Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Store locked up. Keep container tightly closed. Do not expose to temperatures exceeding 50 °C.

### 7.3. Specific end use(s)

not available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

The mixture contains substances for which occupational exposure limits are set.

#### European Union

#### Commission Directive (EU) 2019/1831

Substance name (component)	Type	Value
n-butyl acetate (CAS: 123-86-4)	OEL 8 hours	241 mg/m <sup>3</sup>
	OEL 8 hours	50 ppm
	OEL 15 minutes	723 mg/m <sup>3</sup>
	OEL 15 minutes	150 ppm

#### European Union

#### Commission Directive 2000/39/EC

Substance name (component)	Type	Value
dimethyl ether (CAS: 115-10-6)	OEL 8 hours	1920 mg/m <sup>3</sup>
	OEL 8 hours	1000 ppm
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m <sup>3</sup>
	OEL 8 hours	500 ppm

#### European Union

#### Commission Directive 2000/39/EC

Substance name (component)	Type	Value
xylene (CAS: 1330-20-7)	OEL 8 hours	221 mg/m <sup>3</sup>
	OEL 8 hours	50 ppm
	OEL 15 minutes	442 mg/m <sup>3</sup>
	OEL 15 minutes	100 ppm

Notes

Skin.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### 8.2. Exposure controls

Take off contaminated clothing and wash before reuse. Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

#### Eye/face protection

Protective goggles.

#### Skin protection

Hand protection:

Chemical resistant gloves should be worn whenever working with chemical products when a risk assessment indicates this is necessary.

The selected protective gloves must meet the requirements of the EN 374-1 standard. Recommended for long-term contact:

Material for protective gloves: nitrile rubber. Thickness: 0.11 mm

Breakthrough time: > 480 min.

Efficiency class: 6

Recommended for momentary contact:

Material for protective gloves: nitrile rubber

Thickness: 0.11 mm

Breakthrough time: > 480 min.

Efficiency class: 6

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

#### Respiratory protection

Halfmask with a filter against organic vapours or a self-contained breathing apparatus as appropriate if exposure limit values of substances are exceeded or in a poorly ventilated environment.

#### Thermal hazard

Not available.

#### Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	liquid
Colour	black
Odour	characteristic
Melting point/freezing point	not determined
Boiling point or initial boiling point and boiling range	not determined
Flammability	flammable
Lower and upper explosion limit	not determined
Flash point	not determined
Auto-ignition temperature	not determined
Decomposition temperature	not determined
pH	non-soluble (in water)
Kinematic viscosity	not determined
Solubility in water	insoluble
Partition coefficient n-octanol/water (log value)	not determined
Vapour pressure	not determined
Density and/or relative density	not determined
Relative vapour density	not determined
Particle characteristics	not determined

### 9.2. Other information

none

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

not available

#### 10.2. Chemical stability

The product is stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

Unknown.

#### 10.4. Conditions to avoid

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost. Pressurised container: May burst if heated.

#### 10.5. Incompatible materials

Protect against strong acids, bases and oxidizing agents.

#### 10.6. Hazardous decomposition products

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

##### Acute toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

##### Skin corrosion/irritation

Causes skin irritation. Data for the components of the mixture are not available.

##### Serious eye damage/irritation

Causes serious eye irritation. Data for the components of the mixture are not available.

##### Respiratory or skin sensitisation

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

##### Germ cell mutagenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

##### Carcinogenicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

##### Reproductive toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

##### Toxicity for specific target organ - single exposure

May cause drowsiness or dizziness. Data for the components of the mixture are not available.

##### Toxicity for specific target organ - repeated exposure

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### Aspiration hazard

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

### 11.2. Information on other hazards

#### Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption for humans.

#### Other information

not available

## SECTION 12: Ecological information

### 12.1. Toxicity

No data are available for either the mixture or the components. Based on the available data, the criteria for classification of the mixture are not met.

### 12.2. Persistence and degradability

No data are available for either the mixture or the components.

### 12.3. Bioaccumulative potential

No data are available for either the mixture or the components.

### 12.4. Mobility in soil

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PMT or vPvM components.

### 12.5. Results of PBT and vPvB assessment

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any PBT or vPvB components.

### 12.6. Endocrine disrupting properties

Based on the available data, the criteria for classification of the mixture are not met. Does not contain any components that may cause endocrine disruption in the environment.

### 12.7. Other adverse effects

Data not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

#### Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

## SECTION 14: Transport information

### 14.1. UN number or ID number

UN 1950

### 14.2. UN proper shipping name

AEROSOLS

### 14.3. Transport hazard class(es)

2 Gases

### 14.4. Packing group

not relevant

### 14.5. Environmental hazards

not relevant

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### 14.6. Special precautions for user

Reference in the Sections 4 to 8.

### 14.7. Maritime transport in bulk according to IMO instruments

not relevant


#### Additional information

Hazard identification No.

UN number

Classification code

Safety signs



5F

2.1



#### Road transport - ADR

Special provisions 190, 327, 344, 625

Limited quantities 1 L

Excepted quantities E0

#### Packaging

Packing instructions P207, LP200

Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9

Transport category 2

Tunnel restriction code (D)

#### Special provision for

packages V14

loading, unloading and handling CV9, CV12

operation S2

#### Railway transport - RID

Special provisions 190, 327, 344, 625

Excepted quantities E0

#### Packaging

Packing instructions P207, LP200

Special packing provisions PP87, RR6, L2

Mixed packing provisions MP9

Transport category 0

#### Special provision for

packages W14

loading, unloading and handling CW9, CW12

#### Air transport - ICAO/IATA

Packaging instructions for limited amount Y203

Packaging instructions passenger 203

Cargo packaging instructions 203

#### Marine transport - IMDG

EmS (emergency plan) F-D, S-U

MFAG 620



# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9. Commission Regulation (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH).

#### 15.2. Chemical safety assessment

A chemical safety assessment has not been carried out.

### SECTION 16: Other information

#### A list of standard risk phrases used in the safety data sheet

EUH066	Repeated exposure may cause skin dryness or cracking.
H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H226	Flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H312+H332	Harmful in contact with skin or if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

#### Guidelines for safe handling used in the safety data sheet

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P271	Use only outdoors or in a well-ventilated area.
P405	Store locked up.
P410+P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

#### Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1. The user is responsible for adherence to all related health protection regulations.

#### Key to abbreviations and acronyms used in the safety data sheet

Acute Tox.	Acute toxicity
ADR	European agreement concerning the international carriage of dangerous goods by road
Aerosol	Aerosol
BCF	Bioconcentration Factor
CAS	Chemical Abstracts Service
CLP	Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures
EC	Identification code for each substance listed in EINECS
EINECS	European Inventory of Existing Commercial Chemical Substances
EmS	Emergency plan
EU	European Union
EuPCS	European Product Categorisation System
Eye Irrit.	Eye irritation
Flam. Gas	Flammable gas
Flam. Liq.	Flammable liquid
IATA	International Air Transport Association

# SAFETY DATA SHEET

according to Commission Regulation (EU) 2020/878 as amended

## MA PROFESSIONAL ACRYLIC SPRAY PAINT BLACK GLOSS

Creation date	03rd August 2023	Version	2.0
Revision date	20th March 2025		

IBC	International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals
ICAO	International Civil Aviation Organization
IMDG	International Maritime Dangerous Goods
IMO	International Maritime Organization
INCI	International Nomenclature of Cosmetic Ingredients
ISO	International Organization for Standardization
IUPAC	International Union of Pure and Applied Chemistry
log Kow	Octanol-water partition coefficient
OEL	Occupational Exposure Limits
PBT	Persistent, bioaccumulative and toxic
PMT	Persistent, mobile and toxic
ppm	Parts per million
Press. Gas (Comp.)	Gas under pressure: compressed gas
Press. Gas (Diss.)	Gas under pressure: dissolved gas
Press. Gas (Liq.)	Gas under pressure: liquefied gas
Press. Gas (Ref. Liq.)	Gas under pressure: refrigerated liquefied gas
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals
RID	Agreement on the transport of dangerous goods by rail
Skin Irrit.	Skin irritation
STOT SE	Specific target organ toxicity - single exposure
UN	Four-figure identification number of the substance or article taken from the UN Model Regulations
UVCB	Substances of unknown or variable composition, complex reaction products or biological materials
VOC	Volatile organic compounds
vPvB	Very persistent and very bioaccumulative
vPvM	Very persistent and very mobile

### Training guidelines

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

### Recommended restrictions of use

not available

### Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended.  
REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data from the manufacturer of the substance / mixture, if available - information from registration dossiers.

### The changes (which information has been added, deleted or modified)

The version 2.0 replaces the SDS version from Thursday, 3 August 2023. Changes were made in sections 2, 11, 12, 13, 15 and 16.

### More information

Classification procedure - calculation method.

## Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.