

XF PREMIUM ENGINE OIL C5 0W20 VW

Compilation date: 26/01/2018 Revision date: 04/04/2022

Revision No: 1c

Page: 1

# Section 1: Identification of the substance/mixture and of the company/undertaking

# 1.1. Product identifier

Product name: XF PREMIUM ENGINE OIL C5 0W20 VW

Product code: 8049

1.2. Relevant identified uses of the substance or mixture and uses advised against

# 1.3. Details of the supplier of the safety data sheet

Company name:	Millers Oils Ltd	
	Hillside Oilworks	
	Rastrick Common	
	Brighouse	
	West Yorkshire	
	HD6 3DP	
	United Kingdom	
Tel:	+44 (0)1484 713201	
Fax:	+44 (0)1484 721263	
Email:	h.s@millersoils.co.uk	

**1.4. Emergency telephone number** 

Emergency tel: NHS Direct +44 111

# Section 2: Hazards identification

## 2.1. Classification of the substance or mixture

Classification under CLP: This product has no classification under CLP.

2.2. Label elements

Label elements: This product has no label elements.

2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# Section 3: Composition/information on ingredients

3.2. Mixtures

# XF PREMIUM ENGINE OIL C5 0W20 VW

#### Hazardous ingredients:

# DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC - REACH registered number(s): 01-2119484627-25-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
265-157-1	64742-54-7	-	Asp. Tox. 1: H304	50-70%

REACTION MASS OF ISOMERS OF: C7-9-ALKYL 3-(3,5-DI-TRANS-BUTYL-4-HYDROXYPHENYL)PROPIONATE -REACH registered number(s): 01-0000015551-76-XXXX

406-040-9	-	-	Aquatic Chronic 4: H413	1-10%
BENZOIC ACID, 2-HYDROXY-, MONO-C14-18-ALKYL DERIVS., CALCIUM SALTS				
601-337-1	114959-46-5	-	Skin Sens. 1B: H317	<1%
ALKYL (C18-C28) TOLUENESULFONIC ACID, CALCIUM SALTS, BORATED				
953-650-0	-	-	Skin Sens. 1B: H317; Repr. 2: H361d	<1%

# Section 4: First aid measures

# 4.1. Description of first aid measures

**Skin contact:** Wash immediately with plenty of soap and water. Remove all contaminated clothes and footwear immediately unless stuck to skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

#### 4.2. Most important symptoms and effects, both acute and delayed

**Skin contact:** There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

**Ingestion:** There may be irritation of the throat.

Inhalation: No symptoms.

### 4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Eye bathing equipment should be available on the premises.

### Section 5: Fire-fighting measures

#### 5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray

to cool containers. Carbon dioxide. Alcohol resistant foam. Dry chemical powder.

### 5.2. Special hazards arising from the substance or mixture

**Exposure hazards:** In combustion emits toxic fumes.

### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

# XF PREMIUM ENGINE OIL C5 0W20 VW

#### Section 6: Accidental release measures

# 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions:** Refer to section 8 of SDS for personal protection details. Turn leaking containers leakside up to prevent the escape of liquid.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

### 6.3. Methods and material for containment and cleaning up

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

## 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

## Section 7: Handling and storage

#### 7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

#### 7.3. Specific end use(s)

Specific end use(s): No data available.

#### Section 8: Exposure controls/personal protection

#### 8.1. Control parameters

Workplace exposure limits: No data available.

### **DNEL/PNEC** Values

#### Hazardous ingredients:

#### **DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC**

Туре	Exposure	Value	Population	Effect
DNEL	Inhalation	5.4 mg/m3	Workers	Local
DNEL	Inhalation	1.2 mg/m3	Consumers	Local

#### 8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.
Respiratory protection: Respiratory protection not required.
Hand protection: Protective gloves.
Eye protection: Safety glasses. Ensure eye bath is to hand.
Skin protection: Protective clothing.

# XF PREMIUM ENGINE OIL C5 0W20 VW

Page: 4

#### Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties			
State:	Liquid		
Odour:	Barely perceptible odour		
Evaporation rate:	Negligible		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Insoluble		
Kinematic viscosity:	45 cSt @40		
Boiling point/range°C:	No data available.	Melting point/range°C:	No data available.
Flammability limits %: lower:	No data available.	upper:	No data available.
Flash point°C:	>200	Part.coeff. n-octanol/water:	No data available.
Autoflammability°C:	No data available.	Vapour pressure:	No data available.
Relative density:	0.844	pH:	No data available.
VOC g/I:	No data available.		

9.2. Other information

Other information: No data available.

# Section 10: Stability and reactivity

# 10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

# 10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

## **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

11.1. Information on toxicological effects

Toxicity values: No data available.

# XF PREMIUM ENGINE OIL C5 0W20 VW

**Page:** 5

### Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

#### Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

### 12.2. Persistence and degradability

Persistence and degradability: No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: No data available.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

### 12.6. Other adverse effects

Other adverse effects: No data available.

# Section 13: Disposal considerations

#### 13.1. Waste treatment methods

 Disposal operations:
 Transfer to a suitable container and arrange for collection by specialised disposal company.

 Disposal of packaging:
 Arrange for collection by specialised disposal company.

 NB:
 The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

#### Section 14: Transport information

Transport class: This product does not require a classification for transport.

#### Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

#### 15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

# XF PREMIUM ENGINE OIL C5 0W20 VW

# Section 16: Other information

Other information	
Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	2015/830.
Phrases used in s.2 and s.3:	H304: May be fatal if swallowed and enters airways.
	H317: May cause an allergic skin reaction.
	H361d: Suspected of damaging the unborn child.
	H413: May cause long lasting harmful effects to aquatic life.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.