

#### 3 SILICON

# SECTION 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

# 1.1. Product Identifier

Trade name: 3 SILICON

# 1.2. Relevant identified uses of the substance/mixture and uses advised against

Preserve and protect plastic and rubber.

#### 1.3. Details of the supplier of the safety data sheet

**Company:** Entertrade Spółka z ograniczoną odpowiedzialnością – Sp.K.

ul. Wenecka 12, 03-244 Warszawa

**POLAND** 

# 1.4. Emergency telephone number:

+48 22 762 97 57

**Date of issue:** 2020-03-26

#### SECTION 2. HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008









#### Danger

H222 Extremely flammable aerosol

H229 Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters airways

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

EUH066 Repeated exposure may cause skin dryness or cracking.

# 2.2. Label elements

#### **Contains:**

C7-C9 hydrocarbons, n-alkanes, isoalkanes, cyclic

# Signal word:

Danger

# Pictogram:







Hazard statement(s)

# KAMOKA

# **Material Safety Data Sheet**

#### 3 SILICON

H222 Extremely flammable aerosol

H229 Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

EUH066 Repeated exposure may cause skin dryness or cracking.

# **Precautionary statement(s)**

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open fl ame or other ignition source.

P251 Do not pierce or burn, even after use.

P410+ P412 Protect from sunlight. Do no expose to temperatures exceeding 50 °C/122 °F.

P260 Do not breathe vapours/spray.

P405 Store locked up.

P501 Dispose of contents/container to an authorised waste collection point.

# 2.3 Other hazards

Does not fulfil criteria of PBT and vPvB according to annex XIII 1907/2006 UN 1950

# SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

N.A.

3.2. Mixtures

Hazardous components within the meaning of CLP regulation and related classification:

Substance name	Conc.	CAS No	Index No	EC No	Classification
C7-C9 hydrocarbons, n- alkanes, cycloalkanes, isoalkanes Reach Reg. No 01-2119475515-33	<55%	-	-	920-750-0	GHS02; GHS07; GHS08, GHS09 Dgr FlamLiq2: H225 AspTox1: H304 STOT SE3: H336 AquaticChronic2: H411 EUH066
Butane Propane	<42 %	106-97-8 74-98-6	601-004-00-0 601-003-00-5	203-448-7 200-827-9	GHS02; GHS04 Dgr FlamGas1: H220 PressGas: H280

Full text of H-Phrases can be found under heading 16

#### **SECTION 4. FIRST AID MEASURES**

#### 4.1. Description of first aid measures

# In case of skin contact:

Immediately take off all contaminated clothing. After contact with skin, wash immediately with soap and plenty of water. In case of irritation, consult a doctor



#### 3 SILICON

#### In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time. In case of irritation, consult an ophthalmologist. Remove Contact Lenses

#### In case of Ingestion:

Do not under any circumstances induce vomiting. Never give anything by mouth to an unconscious person. Consult a doctor immediately and show him label or Safety Data Sheet.

#### In case of Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. In case of respiration problems, consult a doctor immediately and show him label or Safety Data Sheet.

# 4.2. Most important symptoms and effects, both acute and delayed

May be fatal if swallowed and enters Airways.

May cause drowsiness or dizziness

Repeated exposure may cause skin dryness or cracking.

# 4.3. Indication of any immediate medical attention and special treatment needed

In case if ingestion consult a doctor.

#### **Treatment:**

None

#### SECTION 5. FIRE-FIGHTING MEASURES

#### 5.1. Extinguishing media

#### Suitable extinguishing media:

Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.

# Extinguishing media which must not be used for safety reasons:

Water jet.

#### 5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container: May burst if heated. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.. The vapour is heavier than air, spreads along the ground and distant ignition is possible. Toxic fumes may be evolved on burning or exposure to heat. Do not inhale explosion and combustion gases.

#### 5.3. Advice for fire-fighters

Fires in confined spaces should be dealt with by trained personnel warning approved air supplied brething apparatus. Water may be used to cool nearby heat exposed areas/objects/packages. Avoid spraying directly into storage containers because of the danger of boil-over. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Move undamaged containers from immediate hazard area if it can be done safely.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

# 6.1. Personal precautions, protective equipment and emergency procedures

Wear personal protection equipment.

Wear breathing apparatus if exposed to vapours/dusts/aerosols.

Provide adequate ventilation.

Use appropriate respiratory protection.

See protective measures under point 7 and 8.

#### **6.2.** Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.

Retain contaminated washing water and dispose it.

# 6.3. Methods and material for containment and cleaning up

Contain and recover liquid using sand or other suitable inert absorbent material. It is advised that stocks of suitable absorbent material should be held in quantities sufficient to deal with any spillage which may be reasonably anticipated. Recovery of large spillages should be effected by specialist personnel. Protect drains from potential spills to minimise contamination. Do not wash product into drainage system. Large and uncontained spillages should be smothered in foam to reduce the risk of ignition. The foam blanket should be maintained until



#### 3 SILICON

the area is declared safe. Vapour is heavier than air and may travel to remote sources of ignition (e.g. along drainage systems, in basements, etc.). In the case of spillage on water, prevent the spread of product by the use of suitable barrier equipment. Recover product from the surface. Protect environmentally sensitive areas and water supplies. In case of spillage at sea, approved dispersants may be used where authorized by the appropriate regulatory authority. In the event of spillages, contact the appropriate authorities.

#### **6.4.** Reference to other sections

See Section 8 for information on personal protection equipment.

#### SECTION 7. HANDLING AND STORAGE

#### 7.1. Precautions for safe handling

Avoid breathing vapours or contact with material. Only use in well ventilated areas. Wash thoroughly after handling. Air-dry contaminated clothing in a well-ventilated area before laundering. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use local exhaust ventilation if there is risk of inhalation of vapours. Prevent spillages. For comprehensive advice on handling, product transfer, storage and tank cleaning refer to the product supplier. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

# 7.2. Conditions for safe storage, including any incompatibilities

Store and dispense only in well ventilated areas away from heat and sources of ignition. Store and use only in equipment/containers designed for use with the product. Containers must be properly labelled and kept closed when not in use. Do not remove warning labels from containers. Do not re-use container for any other product. Empty packages may retain residual product; retain hazard warning labels on empty packages as a guide to their safe handling, storage and disposal. Do not introduce an ignition source. Heating may cause an explosion. Storage on solid, hydrocarbons-proof floor.

#### 7.3. Specific end use(s)

None.

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

No data.

# 8.2. Exposure controls

Do not eat, drink or smoke while working. Instantly remove any soiled and impregnated garments.

Wash hands during breaks and at the end of the work. Avoid contact with the eyes and skin.

Eye protection:

Protective mask, goggles

Protection for skin/hands:

If skin contact is likely, wear impervious protective clothing and/or gloves.

Respiratory protection:

Respiratory protection is normally unnecessary, provided the concentration of vapour is adequately controlled.

Thermal Hazards:

None

Environmental exposure controls:

None

# SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Appearance and colour: liquid - aerosol

Odour: characteristic Odour threshold: N.D.

pH: N.A.

Melting point / freezing point: N.D.

Initial boiling point and boiling range: N.D.



#### 3 SILICON

Upper/lower flammability or explosive limits: N.D.

Vapour density: N.D. Flash point: <0°C Evaporation rate: N.A. Vapour pressure: N.D.

Density: N.D.

Solubility in water: insoluble

Solubility in organic solvents: soluble in aromatic solvents

Lipid solubility: N.A.

Partition coefficient (n-octanol/water): N.A.

Ignition temperature: N.D. Auto-ignition temperature: N.A. Decomposition temperature: N.A.

Viscosity: N.D.

Explosive properties: can form an explisive mixture in air

Oxidizing properties: not oxidizing

9.2. Other information

\_

# SECTION 10. STABILITY AND REACTIVITY

# 10.1. Reactivity

Mixture is not reactive.

#### 10.2. Chemical stability

Stable under normal conditions of handling and storage.

# 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

- solar radiation
- sparks
- flame
- heat

#### **10.5.** Incompatible materials

- none

#### 10.6. Hazardous decomposition products

- carbon oxides
- toxic gases and smoke

#### SECTION 11. TOXICOLOGICAL INFORMATION

#### 11.1. Information on toxicological effects

Repeated exposure may cause skin dryness or cracking.

- a) acute toxicity: no hazard
- b) skin corrosion/irritation: no hazard
- c) serious eye damage/irritation: no hazard
- d) respiratory or skin sensitization: no hazard
- e) germ cell mutagenicity: no hazard
- f) carcinogenicity: no hazard
- g) reproductive toxicity: no hazard
- h) STOT-single exposure: may cause drowsiness or dizziness
- i) STOT-repeated exposure: no hazard
- j) aspiration hazard: may be fatal if swallowed and enters airways

# SECTION 12. ECOLOGICAL INFORMATION



#### 3 SILICON

#### 12.1. Toxicity

Toxic to aquatic life with long lasting effects

12.2. Persistence and degradability

No data.

12.3. Bioaccumulative potential

No data.

12.4. Mobility in soil

No data

12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

12.6. Other adverse effects

None

#### SECTION 13. DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Dispose of via an authorised person/ licensed waste disposal contractor in accordance with local regulations or if approved allowed to degrade in situ. Dispose of product and container carefully and responsibly. Do not dispose of near ponds, ditches, down drains or onto soil. Empty packages may contain some remaining product. Hazard warning labels are a guide to the safe handling of empty packages and should not be removed.

# **SECTION 14. TRANSPORT INFORMATION**

14.1. UN number

1950

14.2. UN proper shipping name

Aerosols, flammable

14.3. Transport hazard class(es)

2

14.4. Packing Group

No

14.5. Environmental hazards

Yes

14.6. Special Precautions for User

During handling wear personal protection equipment (see Section 8)

Avoid heat and flame.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

N.A.

Label: 2.1

#### **SECTION 15. REGULATORY INFORMATION**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n.1272/2008 (CLP), Regulation (CE) n.790/2009.

# Where applicable, refer to the following regulatory provisions:

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent



# 3 SILICON

amendments.

Regulation (EC) nr 648/2004 (detergents). 1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment

No

#### **SECTION 16. OTHER INFORMATION**

Full text of phrases referred to in Section 3:				
Extremely flammable gas				
Extremely flammable aerosol				
Pressurised container: May burst if heated.				
Contains gas under pressure; may explode if heated				
Highly flammable liquid and vapour				
May be fatal if swallowed and enters airways				
May cause drowsiness or dizziness				
Toxic to aquatic life with long lasting effects				
Repeated exposure may cause skin dryness or cracking				

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.