

Printing date 29.10.2020 Version: 5.01 Revision: 02.10.2019

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Trade name: SONAX PREMIUM CLASS Saphir Power Polish

Article number: 02009410

1.2 Relevant identified uses of the substance or mixture and uses advised against

Sector of Use

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category PC31 Polishes and wax blends

Application of the substance / the mixture Car care product

#### 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0

# Further information obtainable from:

Product safety E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217

1.4 Emergency telephone number: Emergency Phone Munich Tel.: +49 (0)89 19240

# **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

# 2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 Void

Hazard pictograms Void

Signal word Void

Hazard statements Void

**Precautionary statements** P102 Keep out of reach of children.

2.3 Other hazards

Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

# SECTION 3: Composition/information on ingredients

# 3.2 Mixtures

Description: Emulsion of solvents, abrasives and additives

Dangerous components:		
	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics Alternative CAS number: 64742-48-9     Flam. Liq. 3, H226;  Asp. Tox. 1, H304;  STOT SE 3, H336; Aquatic Chronic 3, H412	10 - <15%
EC No 934-956-3 Reg.nr.: 01-2119827000-58-xxxx	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7  \$\infty\$ Asp. Tox. 1, H304	3 - <5%
EC No 934-954-2 Reg.nr.: 01-2119826592-36-xxxx	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics Alternative CAS number: 64742-46-7  \$ Asp. Tox. 1, H304	1 - <3%
EC No 920-107-4 Reg.nr.: 01-2119453414-43-xxxx	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics Alternative CAS number: 64742-47-8  \$\tilde{\Phi}\$ Asp. Tox. 1, H304	1 - <3%

i page i



Printing date 29.10.2020 Version: 5.01 Revision: 02.10.2019

Trade name: SONAX PREMIUM CLASS Saphir Power Polish

(Contd. of page 1)

Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

#### 4.1 Description of first aid measures

General information: No special measures required.

After inhalation: Supply fresh air.

After skin contact:

Generally the product does not irritate the skin.

Wash the areas of skin affected with water and a mild detergent.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Do not induce vomiting; call for medical help immediately.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# SECTION 5: Firefighting measures

# 5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

#### 5.3 Advice for firefighters

#### Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

#### Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

# SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures Not required.

#### 6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

# 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

# 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

**7.1 Precautions for safe handling** No special precautions are necessary if used correctly. **Information about fire - and explosion protection:** No special measures required.

# 7.2 Conditions for safe storage, including any incompatibilities

Requirements to be met by storerooms and receptacles: Provide solvent resistant, sealed floor.

Information about storage in one common storage facility: Store away from foodstuffs.

#### Further information about storage conditions:

Store receptacle in a well ventilated area.

Protect from frost.

Recommended storage temperature: 20 °C.

(Contd. on page 3)



Printing date 29.10.2020 Version: 5.01 Revision: 02.10.2019

Trade name: SONAX PREMIUM CLASS Saphir Power Polish

7.3 Specific end use(s) No further relevant information available.

(Contd. of page 2)

# SECTION 8: Exposure controls/personal protection

8.1 Contro	8.1 Control parameters			
Ingredien	Ingredients with limit values that require monitoring at the workplace:			
Hydrocari	Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics			
GERMAN	RCP-M	ETHOD (EU)	Long-term value: 600 mg/m³ 2 (II) / AGW (German TRGS 900)	
Hydrocari	Hydrocarbons, C13-C16, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics			
GERMAN	RCP-M	ETHOD (EU)	Long-term value: 600 mg/m³ 2 (II) / AGW (German TRGS 900)	
Hydrocari	Hydrocarbons, C12-C15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
GERMAN	GERMAN RCP-METHOD (EU)		Long-term value: 600 mg/m³ 2 (II) / AGW (German TRGS 900)	
DNELs				
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
Oral	DNEL	300 mg/kg bw/day (consumer) (ChronicExposure, SystemicEffects)		
Dermal	Dermal DNEL 300 mg/kg bw/day (consumer) (ChronicExposure, SystemiEffects)			
	300 mg/kg bw/day (worker) (ChronicExposure, SystemicEffects)			
Inhalative	Inhalative DNEL 900 mg/m³ (consumer) (ChronicExposure, SystemicEffects)		onsumer) (ChronicExposure, SystemicEffects)	

Additional information: The lists valid during the making were used as basis.

1,500 mg/m³ (worker) (ChronicExposure, SystemicEffects)

#### 8.2 Exposure controls

# Suitable technical control devices

Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to

# Personal protective equipment:

# General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work.

Respiratory protection:

Not required in normal cases

Ensure good ventilation/exhaustion at the workplace. Protection of hands: Not required in normal cases. Eye protection: Not required in normal cases

# SECTION 9: Physical and chemical properties

# 9.1 Information on basic physical and chemical properties

General Information

Appearance:

Form: **Emulsion** Colour: White Odour: Odourless Odour threshold: Not determined.

pH-value: Not applicable.

Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: 100 - 278 °C

Flash point: Not applicable.

(Contd. on page 4)



Printing date 29.10.2020 Version: 5.01 Revision: 02.10.2019

Trade name: SONAX PREMIUM CLASS Saphir Power Polish

		(Contd. of pag
Flammability (solid, gas):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto-ignition temperature:	Product is not selfigniting.	
Explosive properties:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Explosion limits components:	
	0,6Vol% (Main ingredient data)	
Upper:	Explosion limits components:	
	7,0Vol.% (Main ingredient data)	
Vapour pressure:	Not determined.	
Density at 20 °C:	0.94 - 0.95 g/cm <sup>3</sup>	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
water:	Partly miscible.	
Partition coefficient: n-octanol/water:	Not determined.	
Viscosity:		
Kinematic at 40 °C:	>20.5 mm²/s	
9.2 Other information	No further relevant information available.	

# SECTION 10: Stability and reactivity

- 10.1 Reactivity No dangerous reactions known.
- 10.2 Chemical stability Stable under normal conditions.
- 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid See Section 7 for information on safe handling.
- 10.5 Incompatible materials: strong oxidizing agents
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

# SECTION 11: Toxicological information

**11.1 Information on toxicological effects** There are no toxicological findings on this mixture. **Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50	LD/LC50 values relevant for classification:				
Hydrocari	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
Oral	LD50	>5,000 mg/kg (rat) (OECD 401)			
Dermal	Dermal LD50 >5,000 mg/kg (rabbit) (OECD 402)				
Inhalative	LC50/4d	>4,951 mg/l (rat) (OECD 403)			
Aliphatic	Aliphatic and cyclic-aliphatic hydrocarbon mixture:				
Oral	LD50	>5,000 mg/kg (rat) (structurally similar material[OECD 401 equivalent])			
Dermal	LD50	>3,160 mg/kg (rabbit) (structurally similar material[OECD 402 equivalent])			
Inhalative	LC50 / 4h	>5,266 mg/m³ (rat) (structurally similar material[OECD 403 equivalent])			
Primary in	Primary irritant effect:				

Skin corrosion/irritation Based on available data, the classification criteria are not met.

Serious eye damage/irritation Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

(Contd. on page 5)



Printing date 29.10.2020 Version: 5.01 Revision: 02.10.2019

Trade name: SONAX PREMIUM CLASS Saphir Power Polish

(Contd. of page 4) **Reproductive toxicity** Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard

Viscosity: > 20,5mm²/s (40°C)

On the basis of the available data, the classification criteria are not complied with (Conventional Method).

# SECTION 12: Ecological information

12.1 Toxicity There are no ecotoxicological data available on this mixture.

Aquatic toxi	Aquatic toxicity:				
Hydrocarbo	Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics				
LL50 / 96h	LL50 / 96h   >10-<30 mg/l (Oncorhynchus mykiss)				
EL50 / 48h	EL50 / 48h   >22-<46 mg/l (Daphnia magna)				
EL50 / 72h	>1,000 mg/l (Pseudokirchneriella subcapitata)				
NOELR 72 h	NOELR 72 h <1 mg/l (Pseudokirchneriella subcapitata)				
Aliphatic an	Aliphatic and cyclic-aliphatic hydrocarbon mixture:				
LL50 / 96h	>1,028 mg/l (Scophtalamus maximus) (structurally similar material)				
EL50 / 72h	>10,000 mg/l (Skeletonema costatum) (structurally similar material)				
NOELR 21d	>1,000 mg/l (Oncorhynchus mykiss) (structurally similar material)				
40.00	40.0 B 1-4 1-4 1-1-114				

#### 12.2 Persistence and degradability

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics

Biodegradiation 89 % (28d)

Aliphatic and cyclic-aliphatic hydrocarbon mixture:

Biodegradiation 74 % (28d)

**12.3 Bioaccumulative potential** No further relevant information available.

**12.4 Mobility in soil** No further relevant information available.

Additional ecological information:

General notes: The product may not be released into the environment without control.

12.5 Results of PBT and vPvB assessment

**PBT:** Not applicable. **vPvB:** Not applicable.

12.6 Other adverse effects No further relevant information available.

# SECTION 13: Disposal considerations

#### 13.1 Waste treatment methods

Not classified as hazardous waste according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

### European waste catalogue

- 1) Disposal / product
- 2) Disposal / contaminated packaging

20 01 13*	solvents
15 01 02	plastic packaging

SECTION 14: Transport inform	ation
14.1 UN-Number ADR, IMDG, IATA	Void
14.2 UN proper shipping name ADR, IMDG, IATA	Void

(Contd. on page 6)



Printing date 29.10.2020 Version: 5.01 Revision: 02.10.2019

Trade name: SONAX PREMIUM CLASS Saphir Power Polish

		(Contd. of page
14.3 Transport hazard class(es)		
ADR, ADN, IMDG, IATA Class	Void	
14.4 Packing group ADR, IMDG, IATA	Void	
14.5 Environmental hazards: Marine pollutant:	No	
14.6 Special precautions for user	Not applicable.	
14.7 Transport in bulk according to Annex II of  Marpol and the IBC Code Not applicable.		
UN "Model Regulation":	Void	

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives:

EC/1907/2006 (REACh) EC/1272/2008 (CLP) EC/648/2004

#### National regulations:

#### Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

# SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

# Relevant phrases

H226 Flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

#### Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

LC = letal Concentration

EC50 = half maximal effective concentration log POW = Octanol / water partition coefficient

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ATE: acute toxicity estimate

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage

of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

DNEL: Derived No-Effect Level (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

IOELV = indicative occupational exposure limit values

Flam. Liq. 3: Flammable liquids - Category 3

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

Version history and indication of changes: Replaces version 5.00.

\* Data compared to the previous version altered.