

# Safety data sheet

according to 1907/2006/EC, Article 31 Version: 9.01 (replaces version 9.00)

Printing date 26.06.2023	Version: 9.01 (replaces version 9.00)	Revision: 04.05.2023
SECTION 1: Identificat	ion of the substance/mixture and of t	he company/undertaking
1.1 Product identifier		
Trade name: <u>SONAX Wax</u>		
<b>UFI:</b> MK70-Q0H9-J00S-1EUX <b>1.2 Relevant identified uses</b> <b>Application of the substanc</b> Professional uses Car care product	of the substance or mixture and uses advise	•
<b>1.3 Details of the supplier of</b> <b>Manufacturer/Supplier:</b> SONAX GmbH Münchener Straße 75 D-86633 Neuburg (Donau) Tel.: ++49 (0)8431/53-0	f the safety data sheet	
<i>Further information obtaina</i> Product safety E-mail: erp@sonax.de Phone: + +49 (0) 8431 53 217 <u>United Kingdom:</u> Anglo American Oil Company 58 Holton Road, Holton Heatt Telephone: (+44) 01929 5515 Email: info@aaoil.co.uk	7 Ltd n Trading Park, Poole, Dorset, BH16 6LT	
United Kingdom: 0344 892	<b>19240</b> (Poison Centre Munich) <b>0111</b> (UK NPIS) J. Scotland and Wales can contact NHS 111/NHS	S 24 by dialling 111

# **SECTION 2: Hazards identification**

2.1 Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008 Skin Irrit. 2 H315 Causes skin irritation. Eye Dam. 1 H318 Causes serious eye damage. Additional information: Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2): no self-sustained combustion \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ \_ 2.2 Label elements Labelling according to Regulation (EC) No 1272/2008 The product is classified and labelled according to the GB CLP regulation. Hazard pictograms GHS05 Signal word Danger Hazard-determining components of labelling: Dipalmoylisopropyl Dimonium Methosulfate Hazard statements H315 Causes skin irritation. H318 Causes serious eye damage. Precautionary statements P280 Wear protective gloves/eye protection. (Contd. on page 2)

- GB



### Safety data sheet according to 1907/2006/EC, Article 31

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

		(Contd. of page 1)
P302+P352	IF ON SKIN: Wash with plenty of water.	
P305+P351+P3	38 IF IN EYES: Rinse cautiously with water for several minutes. Remove co	ntact lenses, if
	present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor.	
P332+P313	If skin irritation occurs: Get medical advice/attention.	
P501	Dispose of contents/container in accordance with local/regional/national/	<i>(international</i>
	regulations.	
2.3 Other haza	rds	

### Results of PBT and vPvB assessment

PBT:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as PBT

vPvB:

According to information provided in the supply chain, the mix contains less than 0.1% of any substances classified as vPvB.

### Determination of endocrine-disrupting properties

The substance/mixture does not contain components considered to have endocrine disrupting properties according to UK REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Description: Tensides, care additives, alcohol in aqueous solution.

CAS: 67-63-0	propan-2-ol	10-<15%
EINECS: 200-661-7 Reg.nr.: 01-2119457558-25-xxxx	🚸 Flam. Liq. 2, H225; 🚸 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 1474044-71-7 EC No 939-685-4 Reg.nr.: 01-2119983493-26-xxxx	1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl- , esters withfatty acids, C18 unsatd., Me sulfates (salts) Alternative CAS number: 95009-13-5 Eye Dam. 1, H318; () Skin Irrit. 2, H315; Aquatic Chronic 3, H412	5-<10%
CAS: 9004-78-8 NLP: 500-013-6	Phenol polyethoxilate ① Acute Tox. 4, H302; Eye Irrit. 2, H319	5-<10%
CAS: 5131-66-8 EINECS: 225-878-4 Reg.nr.: 01-2119475527-28-xxxx	3-butoxypropan-2-ol Skin Irrit. 2, H315; Eye Irrit. 2, H319	3-<5%
CAS: 71750-79-3 EC number: 615-336-9	Siloxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di- Me Skin Corr. 1B, H314	1-<3%

Additional information: For the wording of the listed hazard phrases refer to section 16.

# SECTION 4: First aid measures

4.1 Description of first aid measures
General information: Remove soiled clothing
After inhalation: Supply fresh air; consult doctor in case of complaints.
After skin contact:
Wash the areas of skin affected with water and a mild detergent.
If symptoms persist consult doctor.
After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
After swallowing:
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; call for medical help immediately.
4.2 Most important symptoms and effects, both acute and delayed
Eye irritation / Eye damage
Skin irritation

\_\_\_\_ GB



# Safety data sheet according to 1907/2006/EC, Article 31

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

(Contd. of page 2)

4.3 Indication of any immediate medical attention and special treatment needed

Treatment in accordance with the doctor's assessment of the patient's condition. Symptomatic treatment.

# SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

5.2 Special hazards arising from the substance or mixture No further relevant information available.

### 5.3 Advice for firefighters

Protective equipment:

The normal measures for firefighting are to be taken.

Do not enter the hazardous area without a self-contained breathing apparatus.

See Section 8 for information on personal protection equipment.

Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system.

### SECTION 6: Accidental release measures

**6.1 Personal precautions, protective equipment and emergency procedures** Ensure adequate ventilation **For non-emergency personnel** Wear protective clothing. Avoid contact with the eyes and skin.

For emergency responders Wear protective equipment. Keep unprotected persons away.

6.2 Environmental precautions:

Do not allow to penetrate the ground/soil.

Do not allow to enter sewers/ surface or ground water.

6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# SECTION 7: Handling and storage

7.1 Precautions for safe handling Use only in well ventilated areas.

Information about fire - and explosion protection: No special measures required.

7.2 Conditions for safe storage, including any incompatibilities Storage:

Requirements to be met by storerooms and receptacles: Prevent any seepage into the ground. Information about storage in one common storage facility: Store away from foodstuffs. Observe local/state/federal regulations. Further information about storage conditions: Store receptacle in a well ventilated area. Keep container tightly sealed. Protect from frost. Recommended storage temperature: 20 °C.

7.3 Specific end use(s) No further relevant information available.

GB (Contd. on page 4)



# Safety data sheet according to 1907/2006/EC, Article 31

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

(Contd. of page 3)

8.1 Co	ntrol parar	neters
	-	limit values that require monitoring at the workplace:
-	7-63-0 pro	
	-	n) Short-term value: 1250 mg/m³, 500 ppm
,		Long-term value: 999 mg/m³, 400 ppm
OEL (II	reland)	Short-term value: 400 ppm
		Long-term value: 200 ppm Sk
Regula	tory infor	
WĚL (O	Great Britai	n): EH40/2020
,	,	21 CoP for the Safety, Health and Welfare at Work
DNELs		
	7-63-0 pro	•
Oral		26 mg/kg (consumer) (chornic effects (1d))
Derma		319 mg/kg (consumer) (chronic effects (1d))
		888 mg/kg (worker) (chronic effects (1d))
Inhalat	ive DNEL	89 mg/m <sup>3</sup> (consumer) (chronic effects)
040		500 mg/m <sup>3</sup> (worker) (chronic effects)
CAS: 1	4/4044-71	-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty acids, C18 unsatd., Me sulfates (salts)
Oral	DNEL	1.25 mg/kg bw/day (consumer) (longterm systematic effects)
Derma	DNEL	56.25 mg/kg bw/day (consumer) (longterm systematic effects)
		112.5 mg/kg bw/day (worker) (longterm systematic effects)
Inhalat	ive DNEL	2.17 mg/m <sup>3</sup> (consumer) (longterm systematic effects)
		8.72 mg/m³ (worker) (longterm systematic effects)
CAS: 5	131-66-8 3	B-butoxypropan-2-ol
Oral	DNEL	12.5 mg/kg (consumer) (longterm systematic effects)
Derma	DNEL	22 mg/kg (consumer) (longterm systematic effects)
		52 mg/kg (worker) (longterm systematic effects)
Inhalat	ive DNEL	43 mg/m³ (consumer) (longterm systematic effects)
		147 mg/m <sup>3</sup> (worker) (longterm systematic effects)
PNECs		
	7-63-0 pro	•
PNEC	-	(sporadic release)
	2,251 mg/l	
	-	(water (fresh water))
	-	(water (sea water))
PNEC	28 mg/kg (	
CA 0: 4		(sediment)
CAS: 1	4/4044-/1	-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty acids, C18 unsatd., Me sulfates (salts)
PNEC	10 mg/l (S	
		(water (fresh water))
	0.002 mg/l (water (sea water))	
PNEC	-	(sediment (fresh water))
		g (sediment (sea water))
	0.331 mg/kg (soil)	
CAS: 5		-butoxypropan-2-ol
PNEC	10 mg/l (se	ewage plant)
	5.25 mg/l (	(sporadic release)
	0.525 ma/	(water (fresh water))



Printing date 26.06.2023

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

0.0525 mg/l (water (sea water))         2.36 mg/kg (sediment (fresh water))         0.256 mg/kg (sediment (sea water))         0.16 mg/kg (sedi)         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Suitable technical control devices         Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.         Individual protection measures, such as personal protective equipment         General protective and hygienic measures:         The usual precautionary measures are to be adhered to when handling chemicals.         Keep away from foodstuffs, beverages and feed.         Wash hands before breaks and at the end of work.         Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of gloves         Nitrie rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 116]         Section 9 Physical and chemical properties <tr< th=""><th></th><th>(Contd. of page</th></tr<>		(Contd. of page
0.236 mg/kg (sediment (sea water))         0.16 mg/kg (soil)    Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Suitable technical control devices Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn. Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection protective gloves Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eye/ace protection Sectron 9: Physical and chemical properties General Information Physical state Colour: Read Fluid Colour: Waxen Melting point/freezing point: Undetermined. Und	0.0525 mg/l (water (sea water)	
0.16 mg/kg (soil)         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Suitable technical control devices         Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.         Individual protection measures, such as personal protective equipment         General protective and hygienic measures:         The usual precautionary measures are to be adhered to when handling chemicals.         Keep away from foodstuffs, beverages and feed.         Wash hands before breaks and at the end of work.         Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protetive gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         Sectron 9: Physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown <td>PNEC 2.36 mg/kg (sediment (fresh wa</td> <td>ater))</td>	PNEC 2.36 mg/kg (sediment (fresh wa	ater))
0.16 mg/kg (soil)         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Suitable technical control devices         Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.         Individual protection measures, such as personal protective equipment         General protective and hygienic measures:         The usual precautionary measures are to be adhered to when handling chemicals.         Keep away from foodstuffs, beverages and feed.         Wash hands before breaks and at the end of work.         Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protetive gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         Sectron 9: Physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown <td>0.236 ma/kg (sediment (sea wa</td> <td>ater))</td>	0.236 ma/kg (sediment (sea wa	ater))
Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Suitable technical control devices Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn. Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection Protective gloves Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eye/face protection Safety glasses [EN 166] SECTION 9: Physical and chemical properties General Information Physical state Colour: Red-brown Meting point/Treezing point: Undetermined. Boiling point or initial boiling point and boiling range Reader and upper explosion limit Lower: 2 Vol % (CAS: 67-63-0 propan-2-ol)		
8.2 Exposure controls Suitable technical control devices Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn. Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep eway from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection Protective gloves Material of gloves Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eye/face protection SECTION 9: Physical and chemical properties General Information Physical state Fluid Colour: Nater quire is the set of the material is 0.4 mm [EN 374] Physical state Fluid Colour: Red-brown Waxen Waxen Multing point/freezing point: Boiling point or initial boiling point and boiling range S2 - 175 °C Flammability Lower: Lower: 2 Vol % (CAS: 67-63-0 propan-2-0) Upper: 3 Vol % (CAS: 67-63-0 propan-2-0)		during the making were used as basis
Suitable technical control devices         Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn.         Individual protection measures, such as personal protective equipment         General protective and hygienic measures:         The usual precautionary measures are to be adhered to when handling chemicals.         Keep away from foodstuffs, beverages and feed.         Wash hands before breaks and at the end of work.         Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Metting point/freezing point:       Undetermined.         Boiling point or		a duning the making were used as basis.
Ensure good ventilation. This can be achieved by localised extraction or general ventilation. If this is not sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn. Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection protective gloves Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eye/face protection SECTION 9: Physical and chemical properties General Information on basic physical and chemical properties General Information Physical state Colour: Physical state Fluid Colour: Builty Hand protein point: Builty Hand point or initial boiling point and boiling range Builty Colour: Builty Col		
sufficient to keep the concentration below the occupational exposure limit, suitable breathing protection is to be worn. Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection Protective gloves Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eyeface protection Safety glasses [EN 166] SECTION 9: Physical and chemical properties General Information on basic physical and chemical properties General Information Physical state Colour: Waxen Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range Reamability Lower: 2 Vol % (CAS: 67-63-0 propan-2-ol)		phiavad by leadlined attraction or general ventilation. If this is not
be worn. Individual protection measures, such as personal protective equipment General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection Protective gloves Material of gloves Material Value for the permeation: Level 6 (≥ 480 min) Eyeface protection Safety glasses [EN 166]  SECTION 9: Physical and chemical properties General Information Physical state Fluid Colour: Waxen Material point or initial boiling point and boiling range Range Material boiling point and boiling range Cower and upper explosion limit Lower: Varie: V		
Individual protection measures, such as personal protective equipment         General protective and hygienic measures:         The usual precautionary measures are to be adhered to when handling chemicals.         Keep away from foodstuffs, beverages and fed.         Wash hands before breaks and at the end of work.         Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eyeface protection         Safety glasses         [EN 1166]         SECTION 9: Physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       Flammable.         Lower:       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
General protective and hygienic measures:       The usual precautionary measures are to be adhered to when handling chemicals.         Keep away from foodstuffs, beverages and feed.       Wash hands before breaks and at the end of work.         Respiratory protection:       Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.       Hand protection Protective gloves         Material of gloves       Material of gloves         Mitrile rubber, NBR       Recommended thickness of the material: ≥ 0.4 mm         [EN 374]       Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection       Safety glasses         [EN 166]       Sectron y: Physical and chemical properties         General Information       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       Flammable.         Lower:       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		h as personal protective equipment
The usual precautionary measures are to be adhered to when handling chemicals. Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Respiratory protection: Not required in normal cases Ensure good ventilation/exhaustion at the workplace. Hand protection Protective gloves Material of gloves Material of gloves Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eyeface protection SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties General Information Physical state Colour: Physical state Fluid Colour: Red-brown Odour: Waxen Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range Flammability Lower: 2 Vol % (CAS: 67-63-0 propan-2-ol)		
Keep away from foodstuffs, beverages and feed.         Wash hands before breaks and at the end of work.         Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         Section on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       82 - 175 °C         Flammability       Flammable.         Lower:       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
Respiratory protection:         Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of glove material: ≥ 0.4 mm         [EN 374]       Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) <b>Eyeface protection</b> Safety glasses         [EN 166]       Eyeface protection         SECTION 9: Physical and chemical properties         General Information on basic physical and chemical properties         General Information         Physical state         Fluid         Colour:         Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       Flammable.         Lower and upper explosion limit         Lower:       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol) <td>Keep away from foodstuffs, beverages</td> <td>s and feed.</td>	Keep away from foodstuffs, beverages	s and feed.
Not required in normal cases         Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         SECTION 9: Physical and chemical properties         General Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		end of work.
Ensure good ventilation/exhaustion at the workplace.         Hand protection Protective gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         SECTION 9: Physical and chemical properties         9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
Hand protection Protective gloves         Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         SECTION 9: Physical and chemical properties         General Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
Material of gloves         Nitrile rubber, NBR         Recommended thickness of the material: ≥ 0.4 mm         [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         SECTION 9: Physical and chemical properties         General Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       Flammability         range       82 - 175 °C         Flammability       Flammabile.         Lower and upper explosion limit       Z Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		the workplace.
Nitrile rubber, NBR Recommended thickness of the material: ≥ 0.4 mm [EN 374] Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min) Eye/face protection Safety glasses [EN 166] SECTION 9: Physical and chemical properties 9.1 Information on basic physical and chemical properties General Information Physical state Fluid Colour: Red-brown Odour: Waxen Melting point/freezing point: Undetermined. Boiling point or initial boiling point and boiling range 82 - 175 °C Flammability Flammable. Lower and upper explosion limit Lower: 2 Vol % (CAS: 67-63-0 propan-2-ol) Upper: 13 Vol % (CAS: 67-63-0 propan-2-ol)		
Recommended thickness of the material: ≥ 0.4 mm [EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection Safety glasses [EN 166]         SECTION 9: Physical and chemical properties         9.1 Information on basic physical and chemical properties         General Information Physical state         Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling range       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
[EN 374]         Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         SECTION 9: Physical and chemical properties         Section on basic physical and chemical properties         General Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       range         range       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       Lower:         Lower:       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		ial: > 0.4 mm
Penetration time of glove material Value for the permeation: Level 6 (≥ 480 min)         Eye/face protection         Safety glasses         [EN 166]         SECTION 9: Physical and chemical properties         9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       Lower:         Lower:       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
Eye/face protection Safety glasses [EN 166]         SECTION 9: Physical and chemical properties         9.1 Information on basic physical and chemical properties         General Information Physical state         Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling range       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		'alue for the permeation: Level 6 (≥ 480 min)
Safety glasses [EN 166]         SECTION 9: Physical and chemical properties         9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       range         range       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       Z Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
SECTION 9: Physical and chemical properties         9.1 Information on basic physical and chemical properties         General Information       Fluid         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       sea - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       z Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       s2 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)	[EN 166]	
9.1 Information on basic physical and chemical properties         General Information         Physical state       Fluid         Colour:       Red-brown         Odour:       Waxen         Melting point/freezing point:       Undetermined.         Boiling point or initial boiling point and boiling       82 - 175 °C         Flammability       Flammable.         Lower and upper explosion limit       2 Vol % (CAS: 67-63-0 propan-2-ol)         Upper:       13 Vol % (CAS: 67-63-0 propan-2-ol)		
General InformationPhysical stateFluidColour:Red-brownOdour:WaxenMelting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)	SECTION 9: Physical and che	emical properties
Physical stateFluidColour:Red-brownOdour:WaxenMelting point/freezing point:Undetermined.Boiling point or initial boiling point and boilingseanrange82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		nd chemical properties
Colour:Red-brownOdour:WaxenMelting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		
Odour:WaxenMelting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)	•	
Melting point/freezing point:Undetermined.Boiling point or initial boiling point and boiling range82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		
Boiling point or initial boiling point and boiling range82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		
range82 - 175 °CFlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		
FlammabilityFlammable.Lower and upper explosion limit2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		
Lower and upper explosion limitLower:2 Vol % (CAS: 67-63-0 propan-2-ol)Upper:13 Vol % (CAS: 67-63-0 propan-2-ol)		
Lower:         2 Vol % (CAS: 67-63-0 propan-2-ol)           Upper:         13 Vol % (CAS: 67-63-0 propan-2-ol)		
Upper: 13 Vol % (CAS: 67-63-0 propan-2-ol)		2 Vol % (CAS: 67-63-0 proper-2-01)

2 Vol % (CAS: 67-63-0 propan-2-ol) 13 Vol % (CAS: 67-63-0 propan-2-ol) 36 °C (DIN 51755) Not determined. 5.0 - 5.5

<20.5 mm²/s

Partly miscible. Not determined. 43 hPa (CAS: 67-63-0 propan-2-ol)

0.97 - 0.98 g/cm<sup>3</sup> Not determined.

9.2 Other informationAppearance:Form:FluidImportant information on protection of health and<br/>environment, and on safety.Ignition temperature:Not determined.

Decomposition temperature:

Kinematic viscosity at 40 °C

Vapour pressure at 20 °C: Density and/or relative density

Partition coefficient n-octanol/water (log value)

pH at 20 °C

Viscosity:

Solubility water:

Density at 20 °C:

Vapour density

(Contd. on page 6)

- GB



Printing date 26.06.2023

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

	(Contd. of page 5
Explosive properties:	Product does not present an explosion hazard.
Change in condition	
Evaporation rate	Not determined.
Information with regard to physical hazard cl	lasses
Explosives	Void
Flammable gases	Void
Aerosols	Void
Oxidising gases	Void
Gases under pressure	Void
Flammable liquids	Sustained combustibility test ISO 9038/UN manual of
•	tests and criteria (32.5.2):
	no self-sustained combustion
Flammable solids	Void
Self-reactive substances and mixtures	Void
Pyrophoric liquids	Void
Pyrophoric solids	Void
Self-heating substances and mixtures	Void
Substances and mixtures, which emit flamma	able
gases in contact with water	Void
Oxidising liquids	Void
Oxidising solids	Void
Organic peroxides	Void
Corrosive to metals	Void
Desensitised explosives	Void

# SECTION 10: Stability and reactivity

10.1 Reactivity No dangerous reactions known.

10.2 Chemical stability Stable under normal conditions.

10.3 Possibility of hazardous reactions No dangerous reactions known.

- 10.4 Conditions to avoid See Section 7 for information on safe handling.
- 10.5 Incompatible materials: strong oxidizing agents

10.6 Hazardous decomposition products: No dangerous decomposition products known.

### SECTION 11: Toxicological information

**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008 Acute toxicity** Based on available data, the classification criteria are not met.

LD/LC50 values relevant for classification:

CAS: 67-6	63-0 propar	p-2-ol
Oral	LD50	5,840 mg/kg (rat)
Dermal	LD50	13,900 mg/kg (rabbit)
Inhalative	LC50 / 6 h	>25 mg/l (rat) (OECD 403)
CAS: 147		-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty ccids, C18 unsatd., Me sulfates (salts)
Oral	LD50	>2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	>2,000 mg/kg (rat) (OECD TG 402)
CAS: 900	4-78-8 Phe	nol polyethoxilate
Oral	LD50	500-2,000 mg/kg (rat) (OECD 423)
Dermal	LD50	2,140 mg/kg (rabbit)
CAS: 513	1-66-8 3-bu	toxypropan-2-ol
Oral	LD50	3,300 mg/kg (rat) (OECD 401)
Dermal	LD50	>2,000 mg/kg (rat) (OECD 402)
Inhalative	LC50 / 4h	>3.5 mg/l (rat) (OECD 403)
CAS: 717	50-79-3 Sile	oxanes and Silicones, 3-[(2-aminoethyl)amino]propyl Me, di-Me
Oral	LD50	>2,000 mg/kg (rat)
	•	(Contd. on pag

- GB



Printing date 26.06.2023

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

	(Contd. of pag
Skin corrosion/irrit	ation Causes skin irritation.
Serious eye damag	e/irritation Causes serious eye damage.
Respiratory or skin	sensitisation Based on available data, the classification criteria are not met.
Germ cell mutagen	icity Based on available data, the classification criteria are not met.
Carcinogenicity Ba	sed on available data, the classification criteria are not met.
Reproductive toxic	<i>ity</i> Based on available data, the classification criteria are not met.
STOT-single expos	ure Based on available data, the classification criteria are not met.
STOT-repeated exp	<b>posure</b> Based on available data, the classification criteria are not met.
Aspiration hazard	Based on available data, the classification criteria are not met.
Additional toxicolo	gical information:
Repeated dose tox	icity
CAS: 1474044-71-7	1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty acids, C18 unsatd., Me sulfates (salts)
Oral NOAEL	500 mg/kg (rat) (OECD 407)
Dermal NOAEL 28d	500 mg/kg (rat) (OECD 407)
Values relevant for	classification:
CAS: 67-63-0 propa	
Oral NOAEL 400 m	
11.2 Information on	
Endocrine disruptin According to the curr disrupting properties	rent state of scientific knowledge, there is no data for the product regarding endocrine
None of the ingredie	nts is listed.

12.1 Toxicity	Y There are no ecotoxicological data available on this mixture.
Aquatic toxi	city:
CAS: 67-63-	0 propan-2-ol
LC50 / 96h	9,640 mg/l (Pimephales promelas)
LC50 / 24h	9,714 mg/l (daphnia)
EC50	>100 mg/l (bacteria)
EC50 / 72h	>100 mg/l (algae)
LOEC	1,000 mg/l (algae)
CAS: 147404	44-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, esters withfatty acids, C18 unsatd., Me sulfates (salts)
LC50 / 96h	>10 mg/l (Cyprinus carpio) (OECD 203)
EC20 / 6d	10 mg/l (activated sludge)
EC50 / 48h	>8.6 mg/l (Daphnia magna) (OECD 202)
EC50 / 72h	1.2 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
EC50 / 6 d	100 mg/l (activated sludge)
NOEC / 21 d	1 mg/l (Daphnia magna) (EPA OTS 797.1330)
NOEC / 72 h	0.39 mg/l (Pseudokirchneriella subcapitata) (OECD 201)
NOEC / 35 d	0.686 mg/l (Pimephales promelas) (US-EPA)
CAS: 9004-7	8-8 Phenol polyethoxilate
LC50 / 96h	>100 mg/l (fish) (OECD 203)
EC50	>128 mg/kg (Daphnia magna) (OECD 202)
CAS: 5131-6	6-8 3-butoxypropan-2-ol
LC50 / 96h	>560-1,000 mg/l (Poecilla reticulata) (OECD 203)
EC50/3h	>1,000 mg/l (activated sludge) (OECD 209)



Printing date 26.06.2023

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

EC50 / 48h	>1,000 mg/l (Daphnia magna) (OECD 202)	(Contd. of pag
EC50 / 96 h	>1,000 mg/l (Pseudokirchneriella subcapitata)	
	tence and degradability	
	-0 propan-2-ol	
Biodegrada	tion 53 %	
	044-71-7 1-Propanaminium, 2-hydroxy-N-(2-hydroxypropyl)-N,N-dimethyl-, acids, C18 unsatd., Me sulfates (salts)	esters withfatty
Biodegrada	tion >60 % (OECD TG 301 F)	
CAS: 9004	78-8 Phenol polyethoxilate	
Biodegrada	tion >60 % (OECD 311)	
CAS: 5131-	66-8 3-butoxypropan-2-ol	
Biodegrada	tion 90 % (OECD301E/92/69/EWG, C4B)	
classified a. vPvB: According t classified a. 12.6 Endoo According t disrupting p 12.7 Other	o information provided in the supply chain, the mix conatins less than 0.1% of a s vPvB o the current state of scientific knowledge, there is no data for the product rega roperties with effects on the environment. adverse effects ecological information:	any substances
The produc The produc Water haza	t may not be released into the environment without control. t does not contain organically bounded halogens (AOX-free). t does not contain organic complexing agents. rd class 1 (German Regulation) (Self-assessment): slightly hazardous for water v undiluted product or large quantities of it to reach ground water, water course	

# SECTION 13: Disposal considerations

13.1 Waste treatment methods

Waste classified as hazardous according to Annex III to Directive 2008/98/EC.

Recommendation Waste must be disposed of while observing the local, official regulations.

### European waste catalogue

07 06 04\* other organic solvents, washing liquids and mother liquors

HP4 Irritant - skin irritation and eye damage

### Uncleaned packaging:

15 01 10\*: packaging containing residues of or contaminated by dangerous substances **Recommendation**:

Packaging may be reused or recycled after cleaning.

15 01 02: plastic packaging

Recommended cleansing agents: Water

# SECTION 14: Transport information 14.1 UN number or ID number ADR/RID/ADN, IMDG, IATA Void 14.2 UN proper shipping name ADR/RID/ADN, IMDG, IATA Void (Contd. on page 9) GB



Printing date 26.06.2023

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

	(Contd. of page
14.3 Transport hazard class(es)	
ADR/RID/ADN, ADN, IMDG, IATA Class	Void
14.4 Packing group ADR/RID/ADN, IMDG, IATA	Void
14.5 Environmental hazards: Marine pollutant:	No
14.6 Special precautions for user	Not applicable.
14.7 Maritime transport in bulk according instruments	to IMO Not applicable.
Transport/Additional information:	Sustained combustibility test ISO 9038/UN manual of tests and criteria (32.5.2): no self-sustained combustion
UN "Model Regulation":	Void

# **SECTION 15: Regulatory information**

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture European Directives: Directive 2010/75/EU (VOC) 13.40 %

Catégorie SEVESO (DIRECTIVE 2012/18/EU) not subject to

REGULATION (EU) 2019/1148

Annex I - RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

National regulations:

Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed.

15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. This Safety Data Sheets is in compliance with Regulation (EC) No 1907/2006, Article 31 as amended by Regulation (EU) 2020/878.

### Relevant phrases

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

Skin corrosion/irritationThe classification of the mixture is generally based on the calculation methodSerious eye damage/irritationusing substance data according to Regulation (EC) No 1272/2008.

**Date of previous version:** 21.04.2022 **Version number of previous version:** 9.00 **Abbreviations and acronyms:** 

NOEL = No Observed Effect Level

NOEC = No Observed Effect Concentration

(Contd. on page 10)

GB



# Safety data sheet according to 1907/2006/EC, Article 31

Version: 9.01 (replaces version 9.00)

Revision: 04.05.2023

	(Contd. of page 9)
LC = letal Concentration	
EC50 = half maximal effective concentration	
log POW = Octanol / water partition coefficient	
GHS: Globally Harmonized System of Classification and Labelling of Chemicals	
ATE: acute toxicity estimate	
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning	g the International
Carriage of Dangerous Goods by Road)	
IMDG: International Maritime Code for Dangerous Goods	
IATA: International Air Transport Association	
EINECS: European Inventory of Existing Commercial Chemical Substances	
ELINCS: European List of Notified Chemical Substances	
CAS: Chemical Abstracts Service (division of the American Chemical Society)	
DNEL: Derived No-Effect Level (UK REACH)	
PNEC: Predicted No-Effect Concentration (UK REACH)	
LC50: Lethal concentration, 50 percent	
LD50: Lethal dose, 50 percent	
IOELV = indicative occupational exposure limit values	
Flam. Liq. 2: Flammable liquids – Category 2	
Acute Tox. 4: Acute toxicity – Category 4	
Skin Corr. 1B: Skin corrosion/irritation – Category 1B	
Skin Irrit. 2: Skin corrosion/irritation – Category 2	
Eye Dam. 1: Serious eye damage/eye irritation – Category 1	
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2	
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3	
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3	
* Data compared to the previous version altered.	
· · ·	GB