

SAFETY DATA SHEET

(REACH regulation (EC) n° 1907/2006 - n° 2020/878)



SECTION 1 : IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name : FORK OIL FL V L 2.5W

Product code : 31900

1.2. Relevant identified uses of the substance or mixture and uses advised against

Fluid for fork

1.3. Details of the supplier of the safety data sheet

Registered company name : MOTUL

Address : 119, Boulevard Felix Faure. 93300 AUBERVILLIERS CEDEX FRANCE

Telephone : 33.1.48.11.70.00. Fax: 33.1.48.33.28.79. Telex: .

Email : motul_hse@motul.fr

1.4. Emergency telephone number : +44 (0) 1235 239 670.

Association/Organisation : CARECHEM 24/7 NCEC..

Other emergency numbers

UNITED STATES: 001 866 928 0789 / CANADA: 001 800 579 7421 / MEXICO : +52 55 5004 8763 / MIDDLE EAST - AFRICA : +44 1235 239671

BRAZIL : +55 11 3197 5891 / COLOMBIA : +57 601 508 7337 / ARGENTINA : +54 11 5984 3690 / CHILE : +562 2582 9336

Ireland : +353 1 8092566

24 hours a day, 7 days a week

SECTION 2 : HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

In compliance with EC regulation No. 1272/2008 and its amendments.

Aspiration hazard, Category 1 (Asp. Tox. 1, H304).

Hazardous to the aquatic environment - Chronic hazard, Category 3 (Aquatic Chronic 3, H412).

This mixture does not present a physical hazard. Refer to the recommendations regarding the other products present on the site.

2.2. Label elements

In compliance with EC regulation No. 1272/2008 and its amendments.

Hazard pictograms :



GHS08

Signal Word :

DANGER

Product identifiers :

EC 276-738-4 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED

Hazard statements :

H304 May be fatal if swallowed and enters airways.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements - General :

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

Precautionary statements - Prevention :

P273 Avoid release to the environment.

Precautionary statements - Response :

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

Precautionary statements - Disposal :

P501 Dispose of contents / container in accordance with local / regional / national / international regulations



2.3. Other hazards

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) $\geq 0.1\%$ published by the European Chemicals Agency (ECHA) under article 57 of REACH: <http://echa.europa.eu/fr/candidate-list-table>

The mixture fulfils neither the PBT nor the vPvB criteria for mixtures in accordance with annexe XIII of the REACH regulations EC 1907/2006.

The mixture does not contain substances $\geq 0.1\%$ with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

SECTION 3 : COMPOSITION/INFORMATION ON INGREDIENTS

3.2. Mixtures



Composition :

Identification	(EC) 1272/2008	Note	%
CAS: 72623-87-1 EC: 276-738-4 REACH: 01-2119474889-13-XXXX LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	GHS08 Dgr Asp. Tox. 1, H304	L	50 $\leq$ x % < 100
CAS: 72623-87-1 EC: 276-738-4 REACH: 01-2119474889-13 LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED	GHS08 Dgr Asp. Tox. 1, H304	L	25 $\leq$ x % < 50
CAS: 64742-54-7 EC: 265-157-1 REACH: 01-2119484627-25 DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC		L	2.5 $\leq$ x % < 10
CAS: 112-90-3 EC: 204-015-5 REACH: 01-2119473797-19 (Z)-OCTADEC-9-ENYLAMINE	GHS07, GHS05, GHS09, GHS08 Dgr Acute Tox. 4, H302 Asp. Tox. 1, H304 Skin Corr. 1B, H314 STOT SE 3, H335 STOT RE 2, H373 Aquatic Acute 1, H400 M Acute = 10 Aquatic Chronic 1, H410 M Chronic = 10		0 $\leq$ x % < 1
CAS: 128-39-2 EC: 204-884-0 REACH: 01-2119490822-33 2,6-DI-TERT-BUTYLPHENOL	GHS07, GHS09 Wng Skin Irrit. 2, H315 Aquatic Acute 1, H400 M Acute = 1 Aquatic Chronic 1, H410 M Chronic = 1		0 $\leq$ x % < 1
CAS: 34140-91-5 EC: 251-846-4 REACH: 01-2119974119-29-0000 OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3 -DIAMINE	GHS07, GHS09, GHS08 Wng Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT RE 2, H373 Aquatic Chronic 2, H411 Aquatic Acute 1, H400 M Acute = 10		0 $\leq$ x % < 1



Information on ingredients :

(Full text of H-phrases: see section 16)

Note L: The carcinogen classification does not apply because the substance contains less than 3 % w/w of dimethyl sulphoxide (DMSO) measured using the IP 346 method.

SECTION 4 : FIRST AID MEASURES

As a general rule, in case of doubt or if symptoms persist, always call a doctor.

NEVER induce swallowing by an unconscious person.



4.1. description of first aid measures

In the event of exposure by inhalation :

Remove the victim to fresh air. If the symptoms persist, call a physician.

In the event of splashes or contact with eyes :

Wash immediately and abundantly with water, including under the eyelids.

In the event of splashes or contact with skin :

Immediately remove all soiled clothing.

Wash immediately and abundantly with soap and water.

In the event of swallowing :

Do not give the patient anything orally.

Seek medical attention, showing the label.

If swallowed accidentally, do not allow to drink, do not induce vomiting and transfer to hospital immediately by ambulance. Show the label to the doctor.

4.2. Most important symptoms and effects, both acute and delayed

No data available.

4.3. Indication of any immediate medical attention and special treatment needed

No data available.

SECTION 5 : FIREFIGHTING MEASURES

Non-flammable.

5.1. Extinguishing media

Suitable methods of extinction

Dry agent, foam, carbon dioxide.

Unsuitable methods of extinction

High volume water jet

5.2. Special hazards arising from the substance or mixture

A fire will often produce a thick black smoke. Exposure to decomposition products may be hazardous to health.

Do not breathe in smoke.

In the event of a fire, the following may be formed :

- carbon monoxide (CO)
- carbon dioxide (CO₂)

5.3. Advice for firefighters

No data available.

SECTION 6 : ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Consult the safety measures listed under headings 7 and 8.

Spilled product may make surfaces slippery.

For first aid worker

First aid workers will be equipped with suitable personal protective equipment (See section 8).

6.2. Environmental precautions

Contain and control the leaks or spills with non-combustible absorbent materials such as sand, earth, vermiculite, diatomaceous earth in drums for waste disposal.

Prevent any material from entering drains or waterways.

6.3. Methods and material for containment and cleaning up

Clean preferably with a detergent, do not use solvents.

6.4. Reference to other sections

No data available.

SECTION 7 : HANDLING AND STORAGE

Requirements relating to storage premises apply to all facilities where the mixture is handled.

7.1. Precautions for safe handling

Always wash hands after handling.
Remove and wash contaminated clothing before re-using.
Do not swallow
Do not get in eyes, on skin, or on clothing.

Fire prevention :

Never inhale this mixture.
Prevent access by unauthorised personnel.
Take precautionary measures against static discharges by bonding and grounding equipment.
No smoking.

Recommended equipment and procedures :

For personal protection, see section 8.
Observe precautions stated on label and also industrial safety regulations.
Ensure good ventilation at the workplace

Prohibited equipment and procedures :

No smoking, eating or drinking in areas where the mixture is used.
Do not breathe fumes, vapour, spray.

7.2. Conditions for safe storage, including any incompatibilities

Store between 5°C and 40°C in a dry, well ventilated place.
Only use hydrocarbon-resistant containers, joints and pipes.

Storage

Keep out of reach of children.
Keep away from food and drink, including those for animals.

Packaging

Always keep in packaging made of an identical material to the original.

7.3. Specific end use(s)

No data available.

SECTION 8 : EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control parameters

No data available.

Derived no effect level (DNEL) or derived minimum effect level (DMEL):

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Final use:

Exposure method:
Potential health effects:
DNEL :

Workers.

Dermal contact.
Long term systemic effects.
2.77 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
19.6 mg of substance/m3

Final use:

Exposure method:
Potential health effects:
DNEL :

Consumers.

Dermal contact.
Long term systemic effects.
2.77 mg/kg body weight/day

Exposure method:
Potential health effects:
DNEL :

Inhalation.
Long term systemic effects.
19.6 mg of substance/m3

Final use:

Exposure method:
Potential health effects:
DNEL :

Man exposed via the environment.

Inhalation.
Long term systemic effects.
5.8 mg of substance/m3

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Final use:

Workers.

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DMEL : 0.38 mg of substance/m3

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Final use:**Workers.**

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 5.4 mg of substance/m3

Final use:**Consumers.**

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1.2 mg of substance/m3

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Final use:**Workers.**

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 5.4 mg of substance/m3

Final use:**Consumers.**

Exposure method: Inhalation.
Potential health effects: Long term local effects.
DNEL : 1.2 mg of substance/m3

Predicted no effect concentration (PNEC):

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Environmental compartment: Soil.
PNEC : 38.9 µg/kg

Environmental compartment: Fresh water.
PNEC : 0.45 µg/l

Environmental compartment: Sea water.
PNEC : 0.045 µg/l

Environmental compartment: Intermittent waste water.
PNEC : 4.5 µg/l

Environmental compartment: Fresh water sediment.
PNEC : 0.196 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.0196 mg/kg

Environmental compartment: Waste water treatment plant.
PNEC : 10 mg/l

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Environmental compartment: Soil.
PNEC : 10 mg/kg

Environmental compartment: Fresh water.
PNEC : 0.00026 mg/l

Environmental compartment: Sea water.
PNEC : 0.00026 mg/l

Environmental compartment: Intermittent waste water.
PNEC : 0.55 mg/l

Environmental compartment: Fresh water sediment.

PNEC : 0.1794 mg/kg

Environmental compartment: Marine sediment.
PNEC : 0.01794 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, if possible with extractor fans at work posts and appropriate general extraction.
Personnel shall wear regularly laundered overalls.



Personal protection measures, such as personal protective equipment

Use personal protective equipment that is clean and has been properly maintained.
Store personal protective equipment in a clean place, away from the work area.
Never eat, drink or smoke during use. Remove and wash contaminated clothing before re-using. Ensure that there is adequate ventilation, especially in confined areas.

- Eye / face protection

Avoid contact with eyes.
Use eye protectors designed to protect against liquid splashes
Before handling, wear safety goggles in accordance with standard EN166.



- Hand protection

Use suitable protective gloves that are resistant to chemical agents in accordance with standard EN ISO 374-1.
Gloves must be selected according to the application and duration of use at the workstation.
Protective gloves need to be selected according to their suitability for the workstation in question : other chemical products that may be handled, necessary physical protections (cutting, pricking, heat protection), level of dexterity required.
Type of gloves recommended :

Glove thickness:	0.38 mm
Break-through time:	> 480 mn

- Body protection

Work clothing worn by personnel shall be laundered regularly.
After contact with the product, all parts of the body that have been soiled must be washed.

- Respiratory protection

Breathing apparatus only when aerosol or spray are formed.

SECTION 9 : PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties



Physical state

Physical state :	Fluid liquid.
------------------	---------------



Colour

Color:	Amber
--------	-------



Odour

Odour threshold :	Not stated.
-------------------	-------------



Melting point

Melting point/melting range :	Not relevant.
-------------------------------	---------------



Freezing point

Freezing point / Freezing range :	Not stated.
-----------------------------------	-------------



Boiling point or initial boiling point and boiling range

Boiling point/boiling range :	Not relevant.
-------------------------------	---------------



Flammability

Flammability (solid, gas) :	Not stated.
-----------------------------	-------------



Lower and upper explosion limit

Explosive properties, lower explosivity limit (%) :	Not stated.
Explosive properties, upper explosivity limit (%) :	Not stated.



Flash point

Flash Point Interval :	FP > 100°C.
------------------------	-------------



Auto-ignition temperature

Self-ignition temperature :	Not relevant.
-----------------------------	---------------



Decomposition temperature

Decomposition point/decomposition range :

Not relevant.

**pH**

pH (aqueous solution) :

Not stated.

pH :

Not relevant.

**Kinematic viscosity**

Viscosity :

15 mm²/s à 40°C

Viscosity :

14 mm²/s < v ≤ 20,5 mm²/s (40°C)

**Solubility**

Water solubility :

Insoluble.

Fat solubility :

Not stated.

**Partition coefficient n-octanol/water (log value)**

Partition coefficient: n-octanol/water :

Not stated.

**Vapour pressure**

Vapour pressure (50°C) :

Not relevant.

**Density and/or relative density**

Density :

< 1

**Relative vapour density**

Vapour density :

Not stated.

**9.2. Other information**

No data available.

**9.2.1. Information with regard to physical hazard classes**

No data available.

**9.2.2. Other safety characteristics**

No data available.

SECTION 10 : STABILITY AND REACTIVITY**10.1. Reactivity**

No data available.

10.2. Chemical stability

This mixture is stable under the recommended handling and storage conditions in section 7.

10.3. Possibility of hazardous reactions

No data available.

10.4. Conditions to avoid

Keep away from heat and from sources of ignition

Take precautionary measures against static discharges.

10.5. Incompatible materials

Strong oxidants

Acids

10.6. Hazardous decomposition products

The thermal decomposition may release/form :

- carbon monoxide (CO)

- carbon dioxide (CO₂)**SECTION 11 : TOXICOLOGICAL INFORMATION****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

11.1.1. Substances**Acute toxicity :**

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)

Oral route :

LD50 ≥ 2000 mg/kg

Species : Rat

OCDE Ligne directrice 423 (Toxicité aiguë par voie orale - Méthode de la classe de toxicité aiguë)

Dermal route :

LD50 > 2000 mg/kg

Species : Rat

OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Oral route : LD50 > 5000 mg/kg
Species : Rat

Dermal route : LD50 > 5000 mg/kg
Species : Rabbit

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Oral route : 300 < LD50 <= 2000 mg/kg
Species : Rat

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Oral route : LD50 > 5000 mg/kg
Species : Rat
OCDE Ligne directrice 401 (Toxicité aiguë par voie orale)

Dermal route : LD50 > 2000 mg/kg
Species : Rabbit
OCDE Ligne directrice 402 (Toxicité aiguë par voie cutanée)

Inhalation route (Dusts/mist) : LC50 > 5.53 mg/l
Species : Rat
OCDE Ligne directrice 403 (Toxicité aiguë par inhalation)

11.1.2. Mixture**Skin corrosion/skin irritation :**

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in non allergic contact dermatitis and absorption through the skin.

Serious damage to eyes/eye irritation :

Mild eye irritation

Aspiration hazard :

May be fatal if swallowed and enters airways.

Aspiration toxicity includes severe acute effects such as chemical pneumonia, varying degrees of pulmonary injury or death following aspiration.

"Inhalation of vapours may cause irritation of the respiratory system in very susceptible persons."

May cause lung damage if swallowed

**11.2. Information on other hazards****Monograph(s) from the IARC (International Agency for Research on Cancer) :**

CAS 140-88-5 : IARC Group 2B : The agent is possibly carcinogenic to humans.

SECTION 12 : ECOLOGICAL INFORMATION

Harmful to aquatic life with long lasting effects.

The product must not be allowed to run into drains or waterways.

12.1. Toxicity**12.1.1. Substances**

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Fish toxicity : 0.01 < LC50 <= 0.1 mg/l
Factor M = 10
Species : Pimephales promelas
OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)

Crustacean toxicity : 0.01 < EC50 <= 0.1 mg/l
Factor M = 10
Species : Daphnia magna
OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate)

Algae toxicity : 0.01 < ECr50 <= 0.1 mg/l
Factor M = 10
Species : Desmodesmus subspicatus

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Fish toxicity :	LC50 > 100 mg/l Duration of exposure : 96 h OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë) NOEC >= 1000 mg/l Species : Oncorhynchus mykiss Duration of exposure : 14 jours
Crustacean toxicity :	EC50 > 10000 mg/l Duration of exposure : 48 h OCDE Ligne directrice 202 (Daphnia sp., essai d'immobilisation immédiate) NOEC = 10 mg/l Species : Daphnia magna Duration of exposure : 21 jours
Algae toxicity :	ECr50 > 100 mg/l Duration of exposure : 72 h OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)	
Fish toxicity :	LC50 = 0.13 mg/l Factor M = 10 Species : Danio rerio Duration of exposure : 96 h OCDE Ligne directrice 203 (Poisson, essai de toxicité aiguë)
Crustacean toxicity :	EC50 = 0.14 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 0.041 mg/l Species : Pseudokirchnerella subcapitata Duration of exposure : 72 h OCDE Ligne directrice 201 (Algues, Essai d'inhibition de la croissance)
2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)	
Fish toxicity :	LC50 >= 1.4 mg/l Duration of exposure : 96 h NOEC = 0.43 mg/l Duration of exposure : 14 jours
Crustacean toxicity :	EC50 = 0.45 mg/l Species : Daphnia magna Duration of exposure : 48 h
Algae toxicity :	ECr50 = 1.2 mg/l Duration of exposure : 72 h

12.1.2. Mixtures

Fish toxicity :	Harmful. 10 < LC50 <= 100 mg/l
-----------------	-----------------------------------

12.2. Persistence and degradability

12.2.1. Substances

OLEIC ACID, COMPOUND WITH (Z)-N-OCTADEC-9-ENYLPROPANE-1,3-DIAMINE (CAS: 34140-91-5)

Biodegradability : Rapidly degradable.

2,6-DI-TERT-BUTYLPHENOL (CAS: 128-39-2)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Biodegradability : Rapidly degradable.

DISTILLATES (PETROLEUM), HYDROTREATED HEAVY PARAFFINIC (CAS: 64742-54-7)

Biodegradability : no degradability data is available, the substance is considered as not degrading quickly.

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Biodegradability : Non-rapidly degradable.



12.2.2. Mixtures

Biodegradation : No data on decomposition is available, the mixture is not considered to decompose rapidly.

12.3. Bioaccumulative potential



12.3.1. Substances

(Z)-OCTADEC-9-ENYLAMINE (CAS: 112-90-3)

Bioaccumulation : BCF >= 500.

LUBRICATING OILS (PETROLEUM), C20-50, HYDROTREATED NEUTRAL OIL-BASED (CAS: 72623-87-1)

Octanol/water partition coefficient : log K_{ow} > 6

12.4. Mobility in soil

Not very mobile in soil.

The product is insoluble in water and will spread on the surface

12.5. Results of PBT and vPvB assessment

No data available.



12.6. Endocrine disrupting properties

No data available.



12.7. Other adverse effects

Do not dispose of the product in the natural environment, effluents or surface waters.



German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 3 : Extremely hazardous for water.

SECTION 13 : DISPOSAL CONSIDERATIONS

Proper waste management of the mixture and/or its container must be determined in accordance with Directive 2008/98/EC.

13.1. Waste treatment methods

Do not pour into drains or waterways.

Waste :

Waste management is carried out without endangering human health, without harming the environment and, in particular without risk to water, air, soil, plants or animals.

Recycle or dispose of waste in compliance with current legislation, preferably via a certified collector or company.

Do not contaminate the ground or water with waste, do not dispose of waste into the environment.

Soiled packaging :

Empty container completely. Keep label(s) on container.

Give to a certified disposal contractor.

SECTION 14 : TRANSPORT INFORMATION

Exempt from transport classification and labelling.



14.1. UN number or ID number

-

14.2. UN proper shipping name

-

14.3. Transport hazard class(es)

-

14.4. Packing group

-

14.5. Environmental hazards

14.6. Special precautions for user **14.7. Maritime transport in bulk according to IMO instruments** **SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture** **- Classification and labelling information included in section 2:**

The following regulations have been used:

- EU Regulation No. 1272/2008 amended by EU Regulation No. 2022/692 (ATP 18)

 - Container information:

Packaging to be fitted with child-resistant fastenings (see EC Regulation No. 1272/2008, Annex II, Part 3).

Containers to be fitted with a tactile warning of danger (see EC Regulation No. 1272/2008, Annex II, Part 3).

The mixture does not contain any substance restricted under Annex XVII of Regulation (EC) No. 1907/2006 (REACH):

<https://echa.europa.eu/substances-restricted-under-reach>.

 - Particular provisions :

No data available.

 - German regulations concerning the classification of hazards for water (WGK, AwSV Annex I, KBws) :

WGK 3 : Extremely hazardous for water.

15.2. Chemical safety assessment

No data available.

 SECTION 16 : OTHER INFORMATION

Since the user's working conditions are not known by us, the information supplied on this safety data sheet is based on our current level of knowledge and on national and community regulations.

The mixture must not be used for other uses than those specified in section 1 without having first obtained written handling instructions.

It is at all times the responsibility of the user to take all necessary measures to comply with legal requirements and local regulations.

The information in this safety data sheet must be regarded as a description of the safety requirements relating to the mixture and not as a guarantee of the properties thereof.

Wording of the phrases mentioned in section 3 :

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure .
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

 Abbreviations :

LD50 : The dose of a test substance resulting in 50% lethality in a given time period.

LC50 : The concentration of a test substance resulting in 50% lethality in a given period.

EC50 : The effective concentration of substance that causes 50% of the maximum response.

ECr50 : The effective concentration of substance that causes 50% reduction in growth rate.

NOEC : The concentration with no observed effect.

REACH : Registration, Evaluation, Authorization and Restriction of Chemical Substances.

DNEL : Derived No-Effect Level

DMEL : Derived Minimal Effect Level

PNEC : Predicted No-Effect Concentration

STEL : Short-term exposure limit

TWA : Time Weighted Averages

TMP : French Occupational Illness table

TLV : Threshold Limit Value (exposure)

AEV : Average Exposure Value.

ADR : European agreement concerning the international carriage of dangerous goods by Road.

IMDG : International Maritime Dangerous Goods.

IATA : International Air Transport Association.

ICAO : International Civil Aviation Organisation

RID : Regulations concerning the International carriage of Dangerous goods by rail.

WGK : Wassergefährdungsklasse (Water Hazard Class).

GHS08 : Health hazard

PBT: Persistent, bioaccumulable and toxic.

vPvB : Very persistent, very bioaccumulable.

SVHC : Substances of very high concern.